

Compressor coolant , 104L2123,Compresseur Danfoss SC18CL – R404A, R449A, R407A, R452A,R404a/R507, SC18CL, 220-240V 50Hz, LBP/MBP, 5/8HP , CSR,LRA 20A, 3.25A , 715W, 210*85 freezer

Category: compressor

written by Lilianne | 16 June 2020

Mbsm_dot_pro_private_PDF_sc18clTélécharger

Mbsm_dot_pro_private_PDF_sc18cl-1Télécharger



Compressor Danfoss Secop SC18CL, SC18CLX, 104L2123, LBP / HBP – R404A, R507, 220-240V/1/50Hz, discharge 17.69 cm³, motor type CSR, oil type POE, oil charge 600 cm³, 715 W at -25 / 55° C, LRA 20 A, maximum refrigerant charge 1300 g, height: 219 mm, weight 13.7 kg

Refrigerant:	R507a R404A
Power range(W):	701 – 1000 W 1 – 1,5 kW
Performance range (C):	-45 C to -5 C

Working area:	LBP HBP
Design type:	Hermetic
Model series:	SC
Use with:	Expansion/Capillary
Power supply:	230 V
Oil type:	P0E
Engine type:	CSR
Article condition:	New
Info:	Oil filled
Shipping weight:	15,70 Kg
Contents:	1,00 Pieces
Dimensions (height):	21,90 cm
Cooling capacity condition:	T0 -15 C
Manufacturer:	Danfoss Secop
Model:	SC18CL
Modelname:	104L2123
Modellname 3:	SC18CLX
Stroke volume (cm3):	17,69
Performance condition:	-25 / +55 °C
Power (W):	715
Cooling capacity (W):	1154
Max. Starting current (A):	20
Engine type:	CSR
Note:	Maximum refrigerant amount 1300 g
Oil quantity (l):	0,6
Compressor type:	Piston
Power range:	-45 C to -5 C





Private Picture Copyright : WWW.MBSM.PRO

Compressor DANFOSS SC18CL 104L2123



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO