

Mbsm.Pro , Tecumseh Refrigeration Compressor, CAE9460Z ,R404A refrigerant ,3/8 hp, mhbp, 1/2HP ,1PH(phase) , 220V to 240V

Category: Solutions,Tester ok

written by Jamila | 12 October 2018

Mbsm.Pro , Tecumseh Refrigeration Compressor ,R404A refrigerant ,1/2HP ,1PH(phase) , 220V to 240V

- Brand Name:Tecumseh
- Certification:RoHS
- Application:Refrigeration Parts
- Type:Refrigeration Compressor

411445

 
6B88330200
CAE9460Z

R404A LRA 17
220-240V ~ 50Hz I_A 3.40


53 D1510 10 195819 A
COUNTRY OF ORIGIN: FRANCE THERMALLY PROTECTED



THE NEW TWO GENERATION BRAZIL COMPRESSORS

TYPE	COMPRESSOR MODELS	Nominal Power (H.P.)			REFRIGERATION CAPACITY AT 50HZ Rafed @54.5°C Cond Temp (Watts)								VOLTAGE
		τ	Refrigerant		Evaporating Temperature								
			τ	Displacement (cm ³)	-20°C	-15°C	-10°C	-5°C	0°C	+5°C	+10°C	+15°C	
PISTON	AE4425Z-FZ1A	1/5	R404A	4.24	222	228	290	362	446	545	659	792	220-240V/1/50HZ
	AE4430Z-FZ1A	1/4	R404A	5.16	216	293	375	466	568	685	821	977	220-240V/1/50HZ
	AE4440Z-FZ1A	1/3	R404A	6.69	278	377	482	599	730	881	1055	1257	220-240V/1/50HZ
	AE4450Z-FZ1A	7/16	R404A	8.85	369	500	640	795	970	1170	1401	1668	220-240V/1/50HZ
	AE4460Z-FZ1C	1/2	R404A	10.33	460	636	784	959	1160	1380	1630	1920	220-240V/1/50HZ

Tecumseh Compressor

LOW BACK PRESSURE COMPRESSORS

TYPE	COMPRESSOR MODELS	Nominal Power (H.P.)				REFRIGERATION CAPACITY AT 50HZ Rafed @54.5°C Cond Temp (Watts)						VOLTAGE	
		τ	Refrigerant		Displacement (cm ³)	Oil charge (cm ³)	Evaporating Temperature						
			τ	Oil charge (cm ³)			-35°C	-30°C	-25°C	-20°C	-15°C		-10°C
ROTARY	RGA/HGA2426Z	2/3	R404A	9.50	290	375	474	590	726	888	1080	220-240V/1/50HZ	
	RGA/HGA2432Z	4/5	R404A	11.50	290	451	567	707	872	1065	1290	220-240V/1/50HZ	
	RGA/HGA2436Z	1	R404A	12.70	290	508	643	804	994	1219	1483	220-240V/1/50HZ	

PictureS Mbsm Dot Pro : www.mbsm.pro

Tecumseh Compressor

MEDIUM/HIGH BACK PRESSURE COMPRESSORS


TYPE	COMPRESSOR MODELS	Nominal Power (H.P.)				REFRIGERATION CAPACITY AT 50HZ Rafed @54.5°C Cond Temp (Watts)								VOLTAGE	
		τ	Refrigerant		Displacement (cm ³)	Oil charge (cm ³)	Evaporating Temperature								
			τ	Oil charge (cm ³)			-15°C	-10°C	-5°C	0°C	+5°C	+10°C	+15°C		
ROTARY	RGA/HGA4467Z	1/2	R404A	9.50	290	679	847	1047	1283	1557	1872	2231	220-240V/1/50Hz		
	BGA/HGA4480Z	2/3	R404A	11.50	290	825	1017	1252	1530	1851	2212	2613	220-240V/1/50Hz		
	RGA/HGA4492Z	3/4	R404A	12.50	290	905	1133	1398	1706	2080	2468	2932	220-240V/1/50Hz		
	RGA/HGA4512Z	1	R404A	16.10	290	1183	1438	1770	2160	2609	3118	3689	220-240V/1/50Hz		
	RGA/HGA4445Y	1/3	R134a	9.50	290	392	493	618	770	954	1173	1430	220-240V/1/50Hz		
	RGA/HGA4450Y	2/5	R134a	11.50	290	501	625	778	963	1184	1445	1749	220-240V/1/50Hz		
	RGA/HGA4460Y	1/2	R134a	12.70	290	537	677	844	1045	1287	1576	1920	220-240V/1/50Hz		

PictureS Mbsm Dot Pro : www.mbsm.pro

00J22 144422

CAE946

208V 50Hz In 3.30A 77.00



23859902



L'UNITE HERMETIQUE

CAUTION: This refrigeration is not approved by the manufacturer
ATTENTION: Pas de réfrigération du fabricant pour l'utilisation d'autres matériaux
ACHTUNG: Keine Nachbefüllung für Kältemittelstoffe



Infinix SMART 6