Austria ,RECIPROCATING ,COMPRESSOR ,SECOP ,HXD30AA ,0.04 1/25 HP ,R600a , 220v 50Hz

Category: Technologie, Tester ok written by Lilianne | 26 April 2020



PictureS Mbsm Dot Pro : WWW.mbsm.pro

Model	
:Compressor type	Round trip compressor
:Compressor model	HXD30AA
: Manufacturer	Scoop
: Manufacturing Country	Slovakia
Electrical specifications	
:Capacity (Hp)	0.04
:Voltage / phase / hertz	50/1/220
:Consumer amps	
:Number of solenoid valves	(x) \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
:Number of phases	
Technical Specifications	
:Dubai (CFM)	
Activer Windows :Dubai (M ^ 3 / hr) Accédez aux paramètres pour activer Wi	
:Temperature application	

PictureS Mbsm Dot Pro : www.mbsm.pro

				ASHRAE ASHRAE										-			
Compressor	Code number	Application	Capacity [W] Tc=45°C, Tuiq=32.2°C, Tsuc=32.2°C Evaporating temperature [°C]				LBP rating point -23.3°C / 45°C		MBP rating point -6.7°C / 45°C		HBP rating point 7.2°C / 45°C		Displacement	Voltage and frequencies	Compressor		
		Appl	-35	-15	-5	0	10	15	Cooling Copacity	COP	Cooling capacity	COP	Cooling capacity	COP	Disp	(* dual frequency type with 50/60 Hz)	Com
									[W]	[W/W]	[W]	[W/W]	[W]	[W/W]	[cm ³]		
HTD30AA	CD000052	LBP	20	83	127				53	1.84					3.00	187-264 V, 50 Hz	
HTD35AA	CD000053	LBP	28	97	149				63	1.86					3.50	187-264 V, 50 Hz	
HTD40AA	CD000054	LBP	36	114	174				75	1.90					4.00	187-264 V, 50 Hz	
HTD45AA	CD000055	LBP	39	136	201				90	1.89					4.80	187-264 V, 50 Hz	
HTD55AA	CD000056	LBP	56	161	240				109	1.92					5.50	187-264 V, 50 Hz	
HTD60AA	CD000073	LBP	66	182	278				122	1.91					6.20	187-264 V, 50 Hz	
HTD30AG	CD000118	LBP	21	79	124				50	1.71					3.00	198-253 V, 50 Hz *	
HXD30AA	CD000097	LBP	22	80	128				51	1.90					3.00	187-264 V, 50 Hz	
HXD35AA	CD000098	LBP	27	94	148				61	1.97					3.50	187-264 V, 50 Hz	
HXD40AA	CD000099	LBP	34	112	175				73	1.92					4.00	187-264 V, 50 Hz	
HXD45AA	CD000100	LBP	42	131	203				86	1.92					4.80	187-264 V, 50 Hz	
HXD55AA	CD000101	LBP	52	153	229				101	1.96					5.50	187-264 V, 50 Hz	
HXD60AA	CD000102	LBP	59	171	261				115	1.90					6.20	187-264 V, 50 Hz	
HZD30AA	CD000088	LBP	21	79	125				49	1.98					3.00	187-264 V, 50 Hz	
HZD35AA	CD000089	LBP	27	95	149				61	2.03					3.50	187-264 V, 50 Hz	
HZD40AA	CD000090	LBP	33	110	172				72	2.02					4.00	187-264 V, 50 Hz	
HZD45AA	CD000091	LBP	43	132	204				87	2.04					4.80	187-264 V, 50 Hz	
HZDSSAA	CDOUUNGS	I RP	50	15/	23%				103	2.05					5 50	187-264 V 50 Hz	

PictureS Mbsm Dot Pro : WWW.mbsm.pro