

Compresseur, Aspera – Embraco EMT
, EMT2121U, R290 , 1/3 HP , 220-240V 50
Hz , Cylindrée = 5.56 CM3 , Moteur
type: CSIR, 7.7LRA , Oil 180ML

Category: Technologie, Tester ok

written by Lilianne | 9 May 2020

Mbsm_dot_pro_private_PDF_Catalogue_EmbracoTélécharger



Private Picture : www.MBSM.PRO

embraco EMT



R290


LBP

Private Picture : www.MBSM.PRO

50Hz 50-60Hz	R290							
	LBP	VOLT. FREQ.	COOL. CAP. [W]	DISPL. [cc]	M/HBP	VOLT. FREQ.	COOL. CAP. [W]	DISPL. [cc]
EM	EMT1117U	A	123	4,5	EMT6144U	A	343	4,50
	EMT1121U	A	159	5,57	EMT6152U	A	418	5,20
	EMT1125U	A	177	5,96	EMT6165U	A	485	5,96
	EMT1130U	A	198	6,76	EMTE6181U	A	697	2,77
	EMT2117U	A	123	4,5				
	EMT2121U	A	159	5,57				
	EMT2125U	A	177	5,96				
	EMT2130U	A	196	6,76				
	EMTE2134U	A	265	1,31				

Private Picture : www.MBSM.PRO

EM/NE/NT/NJ



Private Picture : www.MBSM.PRO

Electrical components

MOTOR TYPE	OVERLOAD PROTECTOR	STARTING DEVICE			CAPACITORS	
		CURRENT RELAYS	VOLTAGE RELAYS	PTC	START	RUN
RSIR	YES	YES ⁽¹⁾		YES ⁽¹⁾		
CSIR	YES	YES			YES	
RSCR	YES			YES		YES
PSC	YES					YES
CSR	YES		YES		YES	YES
3Ø	YES					

(1) For some RSIR models in the NB series, a PTC starting device can be used as an alternative to the current relay. For the RSIR compressors in the BP and EM series, the PTC starting device is standard. Only some specific HBP models in the BP series can use a current relay.

Private Picture : www.MBSM.PRO