

# Compressor ,ACC Cubigel ,Huayi ,Electrolux ,ZEM ,GP16TG, HMBP,R134a, 200- 220V / 220-230V/1/50/60Hz, 3/8 HP, displacement 16,15 cm<sup>3</sup>

Category: Technologie,Tester ok

written by Lilianne | 23 May 2020

Compressor ACC Cubigel Huayi Electrolux ZEM GP16TG, HMBP – R134a, 200- 220V/220 – 230V/1/50/60Hz, 3/8 HP, discharge 16.15 cm<sup>3</sup>, motor type CSIR, oil type ISO VG 46 ester, oil charge 400 cm<sup>3</sup>, 1205 W at +5 / +55 °, input power, current 662 W, 4.28 A, expansion device: capillar or valve, cooling: fan, weight 12.9 kg , the statutory warranty period shall apply (24 months), Delivery time Info: with “immediately available” and “scarce stock”, usually delivery within 2 days. For “currently not available” delivery time usually 2 weeks or delivery time in urgent cases contact us.

Refrigerant:	R134a
Power range(W):	1 – 1,5 kW
Connecting size:	6,5 mm
Suction:	8,1 mm
Working area:	HMBP
Design type:	Hermetic
Model series:	GP
Use with:	Expansion/Capillary
Power range(HP):	0-2
Power supply:	230 V
Oil type:	ISO VG 22 Ester AB46 ISO VG 46 Ester
Engine type:	CSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	24,90 Kg
Dimensions ( length × width × height ):	23,10 × 16,20 × 21,10 cm
Cooling capacity condition:	+5 / +55 C
Manufacturer:	ACC Cubigel Huayi Electrolux ZEM
Model:	GP16TG
Stroke volume (cm <sup>3</sup> ):	16,15
Cooling capacity (W):	1205
Power (HP):	0,4
Power consumption (W):	662
Max. Starting current (A):	23
Max. Operating current (A):	4,28
Engine type:	CSIR
COP:	1,82
Note:	Fan cooling necessary
Oil quantity (l):	0,4

Compressor type: Piston  
Pressure line (mm): 6,5  
Suction line (mm): 8,1



**GP16TG**  
200-220V~50Hz PH  
230V~60Hz  
**R-134a** CE CCC G **FU** US  
MADE IN SPAIN  
7681174759100838  
2  
93231

WARRANTY  
**3**  
YEAR



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_GP16TG\_danfoss\_GP16TG\_R134a\_230\_60Télécharger