

Compressor, NPT12FSC, CUBIGEL, R290,
12,10ccm, LBP, 3/8HP, 220 V 50/60 Hz

Category: compressor

written by Lilianne | 1 May 2021



Private Picture Copyright : WWW.MBSM.PRO

Technical Data Sheet

Compressor model NPT12FSC

Voltage 220-240V 50/60Hz ~1

Refrigerant R290

APPLICATION COMPRESSOR MOTOR

Application Low Back Pressure Displacement 12,10 cm³ Nominal Power 3/8 hp

Refrigerant R290 Diameter 27,00 mm Voltage/Frequency 220-240V 50/60Hz
Evaporating Temp. -40,0 °C to -10,0 °C Stroke 21,13 mm Voltage range 187-264 V
Expansion Capillar Net Weight 10,18 Kg Type ECM
Comp. Cooling Fan cooled Oil type ISO VG 32 ESTER Phase number 1 PH
Max. ambient temp. 43,0 °C Oil charge 520 cm³ Locked Rotor Amps (LRA) 5,00 A
Max. Cont. Current (MCC) 3,70 A
Main W. resist. at 25°C 6,70 Ω
Start W. resist. at 25°C 6,70 Ω
NOMINAL PERFORMANCE – 3.000 RPM
ASHRAE CECOMAF
Cooling Capacity 585 kCal/h 508 W
COP 1,57 W/W 1,22 W/W
EER 1,35 kCal/Wh 1,06 kCal/Wh
Input Power 433 W 415 W
Current 3,43 A 3,30 A
TEST CYCLE CONDITIONS
ASHRAE CECOMAF
LBP (B) LBP (A)
Evaporating temp. -23,3 °C -25,0 °C
Condensing temp. 55,0 °C 55,0 °C
Liquid temp. 32,0 °C 55,0 °C
Ambient temp. 32,0 °C 32,0 °C
Suction temp. 32,0 °C 32,0 °C
Voltage/Frequency 220 V 50/60 Hz 220 V 50/60 Hz

cubigel

NPT12FSC

220-240V-50Hz PH1
THERMALLY PROTECTED



CE

2

11161

MADE IN
SPAIN





Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Technical-Notes-NPT12FSC-1Télécharger

Mbsm_dot_pro_private_PDF_danfoss_NPT12FSC_R290_220_5060Télécharger