

Compressor, 103U2954, Danfoss, fr10B,
103u, 2954, 1/3 HP, lbp, r12, FR10B
COMPRESSOR 220V, 103U2954FR10B, FR11B
Compressor R-12 3/8 HP 230V, fr21b
Compressor R134a 3/4 HP++/ 1 hp-,
230V, hbp++

Category: compressor

written by Lilianne | 2 May 2021



This article was edited by the director to adjust the horsepower value of the compressor. Thank you for your understanding

Refrigerant	Capacity (kg)	Temp. (°C)	Cond. (°C)	Evap. (°C)	Pressure (bar)	Power (kW)	Power (HP)	Power (HP)	Power (HP)	Power (HP)	Power (HP)	Power (HP)	Power (HP)		
R22 LBP -5/-45 °C	SC10C	10.3	D	1	104L2516	50	155	325	560	700	850		300		
	SC12C	12.9	D	1	104L2674	95	220	415	680	840	1020		380		
	SC15CM	15.3	D	2	104L2848	115	270	510	840	1050	1280		470		
	SC18CM	17.7	E	2	104L2120	130	310	585	980	1230	1500		510		
	SC1010**2x	10.3D		1	104L4076	100	310	650	1120	1400	1700	600			
	SC1212**2x	12.9D		1	104L4077	190	440	830	1360	1680	2040	760			
	SC1515CM*	2x 15.3	D	2	104L4079	230	540	1020	1690	2100	2560		940		
	SC1818CM*	2x 17.7	E	2	104L4081	260	620	1170	1960	2460	3000		1020		
	SC10C	10.3	C	1	104L2516	80	215	365	590	710	870		335		
	SC12C	12.9	C	1	104L2674	110	270	470	770	950	1140		420		
R502 LBP -5/-45 °C	SC15CM	15.3	C	2	104L2848	150	325	590	920	1120	1390		535		
	SC18CM	17.7	C	2	104L2120	180	400	685	1080	1330	1660		580		
	SC1010**	2x 10.3	C	1	104L4076	160	240	240	1160	1420	1740		670		
	SC1212**	2x 12.9	C	1	104L4077	220	540	940	1540	1900	2280		840		
	SC1515CM*	2x 15.3	C	2	104L4079	300	650	1180	1840	2240	2780		1070		
	SC1818CM*	2x 17.7	C	2	104L4081	360	800	1370	2160	2650	3200		1160		
	TL2.5B	2.61	A	C.A	1-6	102U2021		20	45	80	102	126	182	248	117
	TL3B	3.13	A	C.A	1-6	102U2023		27	56	96	120	148	215	296	141
	TL4B	3.86	A	C	1-6	102U2016		39	73	116	145	182	264	364	157
	FR6B	6.24	A	C.A	1-6	103U2654		55	110	190	235	295	438	620	243
R12 HBP 15/-40 °C	FR7.5B	6.93	B.A	C.B	1-6	103U2754		65	127	210	275	340	495	695	280
	FR8.5B	7.95	B.A	C.B	1-6	103U2854		72	146	240	300	375	555	770	326
	FR9B	9.05	B.A	C.B	1-6	103U2954		85	158	268	340	420	620	860	375
	FR11B	11.15	C	C	1	103U2154		110	205	340	420	520	758	1050	485
	SC10B	10.3	C.B	C.B	1-6	104L2510		70	170	310	400	490	760	1080	390
	SC12B	12.9	C.B	C.B	1-6	104L2670		95	230	410	520	630	950	1330	500
	SC15B	15.3	C.B	C.B	1-6	104L2830		130	275	490	615	760	1090	1590	595
	SC18B	17.7	C	C	1-6	104L2110		170	340	575	715	870	1280	1830	720
	SC21B	20.95	C	C	1	104L2310		220	460	670	840	1010	1450	2080	730
	SC1212B*	2x 12.9	C	1	104L4072		190	460	820	1040	1260	1900	2660	1000	
SC1515B*	2x 15.3	C	1	104L4073		260	550	980	1230	1520	2180	3180	1190		
SC1818B*	2x 17.7	C	1	104L4074		340	680	1190	1430	1740	2560	3640	1440		
SC2121B*	2x 20.95	C	1	104L4075		440	800	1340	1680	2020	2900	4160	1660		





TL2.5B 2.61 A C-A 1-6 102U2021 20 45 80 102 126 182 248 112
 TL3B 3.13 A C-A 1-6 102U2023 27 56 96 120 148 215 296 141
 TL4B 3.86 A C 1-6 102U2016 39 73 116 145 182 264 364 157
 FR6B 6.24 A C-A 1-6 103U2654 55 110 190 235 295 438 620 243
 FR7.5B 6.93 B-A C-B 1-6 103U2754 103U2764 65 127 210 275 340 495 695 280
 FR8.5B 7.95 B-A C-B 1-6 103U2854 103U2864 72 146 240 300 375 555 770 326
 FR10B 9.05 B-A C-B 1-6 103U2954 103U2964 85 158 268 340 420 620 860 375
 FR11B 11.15 C C 1 103U2154 110 205 340 420 520 758 1050 485
 SC10B 10.3 C-B C-B 1-6 104L2510 104L2511 70 170 310 400 490 760 1080 390
 SC12B 12.9 C-B C-B 1-6 104L2670 104L2671 95 230 410 520 630 950 1330 500
 SC15B 15.3 C-B C-B 1-6 104L2830 104L2831 130 275 490 615 760 1090 1590 595
 SC18B 17.7 C C 1-6 104L2110 170 340 575 715 870 1280 1820 720
 SC21B 20.95 C C 1 104L2310 220 400 670 840 1010 1450 2080 730
 SC12/12B* 2 x 12.9 C 1 104L4072 190 460 820 1040 1260 1900 2660 1000
 SC15/15B* 2 x 15.3 C 1 104L4073 260 550 980 1230 1520 2180 3180 1190
 SC18/18B* 2 x 17.7 C 1 104L4074 340 680 1150 1430 1740 2560 3640 1440
 SC21/21B* 2 x 20.95 C 1 104L4075 440 800 1340 1680 2020 2900 4160 1460

Mbsm_dot_pro_private_PDF_danfossr12r22r502compressorpdf_compresTélécharger

K1Z / F35b Hoge Druk - Haute Pression

195B0020	102U2023	TL3B	1/8	3,13	27	56	96	120	148	215	296	307,15
195B0018	102U2016	TL4B	1/6	3,86	39	73	116	145	182	264	364	317,75
195B0030	103U2654	FR6B	1/5	6,24	55	110	190	235	295	438	620	336,10
195B0034	103U2754	FR7,5B	1/4	6,93	65	127	210	275	340	495	695	351,70
195B0037	103U2854	FR8,5B	1/4	7,95	72	146	240	300	375	555	770	365,70
195B0040	103U2954	FR10B	1/3	9,05	85	158	268	340	420	620	860	387,75
195B0029	103U2154	FR11B	1/3	11,15	110	205	340	420	520	758	1050	410,95
195B0071	104L2510	SC10B*	1/3	10,3	70	170	310	400	490	760	1080	415,10
195B0078	104L2670	SC12B*	3/8	12,9	95	230	410	520	630	950	1330	458,25
195B0084	104L2830	SC15B*	1/2	15,3	130	275	490	615	760	1090	1590	460,00
195B0063	104L2110	SC18B*	1/2	17,7	170	340	575	715	870	1280	1820	470,35
195B0068	104L2310	SC21B*	3/4	20,95	220	400	670	840	1010	1450	2080	624,20

(*) Ook voor lage temp. toepassing – aussi pour application basse temp.



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_103U2954Télécharger