

Table of characteristics of compressors for refrigerators

Category: Chaud&Froid, compressor
written by Lilianne | 20 December 2021



If it is necessary to replace the compressor in the refrigerator, it is necessary to choose the right analogue.

Compressors are designed for different types of application, namely, they are classified according to the temperature range.

LBP (Low Suction Pressure) indicates a range of low evaporating temperatures, typically -10 ° C to -35 ° C or even -45 ° C, these compressors are designed for use in freezers or fridge freezers.

MBP (Medium Suction Pressure) indicates a range of average evaporating temperatures, typically -20 ° C to 0 ° C. These compressors are used in refrigerated cabinets, milk coolers, ice makers and water dispensers.

HBP (High Suction Pressure) indicates a range of high evaporating temperatures, typically -5 ° C to + 15 ° C, and is used, for example, in dryers and standalone liquid chillers. The additional T indicates a "tropical" compressor design. This means that the compressor is designed for high ambient temperatures and can operate with unstable power supplies.

Also, when repairing refrigerators, it is important to take into account the peculiarities of the length and diameter of the capillary tube.

Capillary tubes play an important role. It is always necessary to correctly select the diameter and length of the capillary; their values cannot be changed arbitrarily.

About capillary tube problems.

One of the most common problems is clogging of the capillary tubes, they must be replaced with the same length and diameter.

If you install a capillary tube with a larger diameter than the one originally installed, the system will work, but the cooling efficiency will be lower.

Typically, capillaries are installed in compressors as follows:

The 73W compressors are fitted with a 0.63 mm (0.025 in) capillary tube.

92W compressors are fitted with a 0.71 mm (0.028 in) capillary tube.

The 122W compressors are fitted with a 0.71 mm (0.028 in) capillary tube.

184W compressors are fitted with a 0.8 mm (0.031 in) capillary tube.

245W compressors are fitted with a 0.1 mm (0.039 in) capillary tube.

The 368W compressors are fitted with a 1.4 mm (0.055 in) capillary tube.

	IN	Displ.CC	R L A	k	CAL/HR	B T U	In -23	W -5	In 7.2+	
D	51C10RAW5	5 , 1		116	461		135		LBP	R 134 a
D	51C90RAW5	5 , 1		116	461		135		LBP	R 134 a
D	57C10RAW5	5 , 7		121	481		141		LBP	R 134 a
D	57C13RAX5	5 , 7		121	481		141		LBP	R 134 a
D	66C13RAW5	6 , 6		138	546		160		LBP	R 134 a
D	66C13RAX5	6 , 6		130	515		151		LBP	R 134 a
D	77C15RAW5	7 , 7		160	635		186		LBP	R 134 a
D	77C18RAX5	7 , 7		160	635		186		LBP	R 134 a
D	91C18RAW5	9 , 1		195	774		227		LBP	R 134 a
D	91C21RAX5	9 , 1		195	774		227		LBP	R 134 a
D	110C21RAX5	11		256	1017		298		LBP	R 134 a
D	110C21RAZ5	11		256	1017		298		LBP	R 134 a
D	110C21RBX5	11		256	1017		298		LBP	R 134 a
D	110C24GAX5	11		256	1017		298		LBP	R 134 a

200 /
MODEL 220 /
50 HZ

compressor
panasonic

COOLING
C

	IN	Displ.CC	R L A	k	CAL/HR	B T U	In -23	W -5	In 7.2+	
DA	57C11RAY5	5 , 7		140	556		163		LBP	R 134 a
DA	66C12RAY5	6 , 6		158	628		184		LBP	R 134 a
DA	77C15RAY5	7 , 7		184	730		214		LBP	R 134 a

DB 66C10RAW5	6 , 6	161	638	187	LBP	R 134 a
DB 66C12RAY5	6 , 6	158	628	184	LBP	R 134 a
DB 66C14RBX5	6 , 6	158	628	184	LBP	R 134 a
DB 73C13RAY5	7 , 3	175	696	204	LBP	R 134 a
DB 77C14RAY5	7 , 7	184	730	214	LBP	R 134 a
DB 77C16RBX5	7 , 7	184	730	214	LBP	R 134 a
DB 86C16RAY5	8 , 6	207	822	241	LBP	R 134 a
DB 91C14RAW5	9 , 1	218	863	253	LBP	R 134 a
DB 91C19RAY5	9 , 1	220	873	256	LBP	R 134 a
DB 91C21RAX5	9 , 1	220	873	256	LBP	R 134 a
DB 110C19RAW5	11	260	1030	302	LBP	R 134 a
DB 110C22RAW5	11	260	1030	302	LBP	R 134 a

MODEL 200 /
 220 /
 50 HZ

Matsushita	IN	Displ.CC	R L A	COOLING				In -23	W -5	In 7.2+	R 134 a
				k	CAL/HR	B	T U				
DD 57C10RAW5	5 , 7			140	556			163		LBP	R 134 a
DD 57C12GAX5	5 , 7			140	556			163		LBP	R 134 a
DD 66C13RAW5	6 , 6			158	628			184		LBP	R 134 a
DD 66C14GAX5	6 , 6			157	624			183		LBP	R 134 a
DD 77C15GAX5	7 , 7			183	727			213		LBP	R 134 a
DD 77C15RAW5	7 , 7			184	730			214		LBP	R 134 a

DD 86C18RAW5	8 , 6	207	822	241	LBP	R 134 a
					LBP	R 134 a
DG					LBP	R 134 a
DG 51C89RAW5	5 , 1	125	495	145	LBP	R 134 a
DG 57C90GCW5	5 , 7	144	573	168	LBP	R 134 a
DG 57C96RAW5	5 , 7	144	573	168	LBP	R 134 a
DG 66C11RAW5	6 , 6	161	638	187	LBP	R 134 a
DG 66C13GAX5	6 , 6	161	638	187	LBP	R 134 a
DG 73C12RAW5	7 , 3	182	723	212	LBP	R 134 a
DG 77C14RAW5	7 , 7	193	768	225	LBP	R 134 a
DG 77C16GAX5	7 , 7	193	768	225	LBP	R 134 a
DG 91C18RAW5	9 , 1	223	884	259	LBP	R 134 a
DG 91C21RAX5	9 , 1	223	884	259	LBP	R 134 a
MODEL						
compressor panasonic	200/2		COOLING C			
	IN	Displ.CC	R L A	k CAL/HR B T U	In -23 W -5 ^{In} _{7.2+}	
DGH 66C13GAX	6 , 6			163 645	189	LBP R 134 a
DGH 66C96RAW	6 , 6			163 648	190	LBP R 134 a
DGH 73C14RAE	7 , 3			185 734	215	LBP R 134 a
DGH 73C15GAX	7 , 3			185 734	215	LBP R 134 a
DGH 73C15RAX	7 , 3			185 734	215	LBP R 134 a
DGH 77C13RAW	7 , 7			191 757	222	LBP R 134 a

DGH 86C16RAW	8 , 6	213	846	248	LBP	R 134 a
DGH 86C19GAX	9 , 6	224	887	260	LBP	R 134 a
					LBP	R 134 a
DGK					LBP	R 134 a
DGK 57C97RLX	5 , 7	145	577	169	LBP	R 134 a
DGK 66C90RPW	6 , 6	165	655	192	LBP	R 134 a
					LBP	R 134 a
D H S					LBP	R 134 a
DHS 51C74RAW	5 , 1	132	525	154	LBP	R 134 a
DHS 57C80RAW	5 , 7	148	587	172	LBP	R 134 a
DHS 66C10RAW	6 , 6	163	648	190	LBP	R 134 a
DHS 66C88RAW	6 , 6	163	648	190	LBP	R 134 a
DHS 73C10RAW	7 , 3	181	716	210	LBP	R 134 a
DHS 73C13RAW	7 , 3	191	757	222	LBP	R 134 a
DHS 86C15RAW	8 , 6	213	846	248	LBP	R 134 a
					LBP	R 134 a
DKK					LBP	R 134 a
DKK 57C11RAE	5 , 7	145	577	169	LBP	R 134 a
DKK 66C13RAE	6 , 6	167	662	194	LBP	R 134 a
MODEL	200 / 220 / 50 HZ					
compressor						
panasonic				C		

	IN	Displ.CC	R L A	k	CAL/HR	B T U	In -23	W -5	In 7.2+	
QA 66C12GAX5	6 , 6			125	495		145		LBP	R 134 a
QA 66C14GAX5	6 , 6			125	495		145		LBP	R 134 a
QA 66C15GAX5	6 , 6			125	495		145		LBP	R 134 a
QA 77C17GAX5	7 , 7			151	600		176		LBP	R 134 a
QA 91C22GAX5	9 , 1			178	706		207		LBP	R 134 a
MODEL										
compressor panasonic	200/2				COOLING C					
	IN	Displ.CC	R L A	k	CAL/HR	B T U	In -23	W -5	In 7.2+	
QB 51C74GAW5	5 , 1			110	437		128		LBP	R 134 a
QB 51C95GPW5	5 , 1			110	437		128		LBP	R 134 a
QB 51C99GAW0	5 , 1			110	437		128		LBP	R 134 a
QB 51C99GLX5	5 , 1			110	437		128		LBP	R 134 a
QB 57C11GAX0	5 , 7			126	498		146		LBP	R 134 a
QB 57C11GLX5	5 , 7			126	498		146		LBP	R 134 a
QB 57C11GPX5	5 , 7			126	498		146		LBP	R 134 a
QB 57C86GAX0	5 , 7			126	498		146		LBP	R 134 a
QB 57C87GAW5	5 , 7			126	498		146		LBP	R 134 a
QB 66C13GAX5	6 , 6			142	563		165		LBP	R 134 a
QB 66C13GLX5	6 , 6			142	563		165		LBP	R 134 a
QB 66C13GPX5	6 , 6			142	563		165		LBP	R 134 a
QB 66C16GAX0	6 , 6			142	563		165		LBP	R 134 a

QB 66C97GAW5	6 , 6	142	563	165	LBP	R 134 a
QB 73C12GAW5	7 , 3	159	631	185	LBP	R 134 a
QB 73C15GAX5	7 , 3	159	631	185	LBP	R 134 a
QB 73C16GAX5	7 , 3	159	631	185	LBP	R 134 a
QB 77C13GAW5	7 , 7	174	689	202	LBP	R 134 a
QB 77C16GAX5	7 , 7	174	689	202	LBP	R 134 a
QB 77C16GLX5	7 , 7	174	689	202	LBP	R 134 a
QB 77C16GPX5	7 , 7	174	689	202	LBP	R 134 a
QB 77C18GAX0	7 , 7	174	689	202	LBP	R 134 a
QB 86C13GAW5	8 , 6	191	757	222	LBP	R 134 a
QB 86C18GAX5	8 , 6	191	757	222	LBP	R 134 a
QB 91C16GAW5	9 , 1	203	805	236	LBP	R 134 a
QB 91C18GAX0	9 , 1	203	805	236	LBP	R 134 a
QB 91C19GAX5	9 , 1	203	805	236	LBP	R 134 a
QB 91C21RPX5	9 , 1	203	805	236	LBP	R 134 a
QB 91C24GAX0	9 , 1	203	805	236	LBP	R 134 a
QB 110C19GAW5	11	235	931	273	LBP	R 134 a
QB 110C25CAX0	11	235	931	273	LBP	R 134 a
QB 110C25GAX5	11	235	931	273	LBP	R 134 a

MODEL

compressor 200/2
panasonic

COOLING
C

IN	Displ.CC	R L A	k CAL/HR B T U	In -23 W -5 $\frac{In}{7.2+}$
----	----------	-------	----------------	-------------------------------

QBH 51C90GLX	5 , 1	122	484	142	LBP	R 134 a
QBH 57C10GLX	5 , 7	139	553	162	LBP	R 134 a
QBH 57C10GPX	5 , 7	139	553	162	LBP	R 134 a
QBH 57C15RLX	5 , 7	139	553	162	LBP	R 134 a
QBH 66C13GPX	6 , 6	153	607	178	LBP	R 134 a
QBH 66C13RLX	6 , 6	153	607	178	LBP	R 134 a
QBH 73C13GAE	7 , 3	174	689	202	LBP	R 134 a
QBH 73C15RLX	7 , 3	174	689	202	LBP	R 134 a
QBH 73C16GPX	7 , 3	174	689	202	LBP	R 134 a
QBH 73C20RLX	7 , 3	174	689	202	LBP	R 134 a
QBH 77C16RLX	7 , 7	189	751	220	LBP	R 134 a
QBH 86C19RLX	8 , 6	206	819	240	LBP	R 134 a
QBH 86C19RPX	8 , 6	206	819	240	LBP	R 134 a

MODEL 200 /
 220 /
 50 HZ

compressor
panasonic

COOLING
C

	IN	Displ.CC	R L A	K CAL/HR B T U	In -23 W -5	In 7.2+	
QA 43K11CAS0	4 , 3				385	HBP	R 134 a
QA 51K13GAW5	5 , 1				450	HBP	R 134 a
QA 77K18CAW5	7 , 7				680	HBP	R 134 a
QA 77K18CAX0	7 , 7				680	HBP	R 134 a
QA 91K21CAW5	9 , 1				800	HBP	R 134 a

QA 110K23CAW5	11		980	HBP	R 134 a
QA 125K26CAW5	12 , 5		1100	HBP	R 134 a
QA 125K29CAX5	12 , 5		1100	HBP	R 134 a

MODEL 200 /
 220 /
 50 HZ

Secop (Danfoss)	IN	Displ.CC	R L A	COOLING					In	-23	W -5	$\frac{In}{7.2+}$	L / MBP	134 a
				K	CAL/HR	B	T	U						
TL 2.5 F	2 , 61			40		157			46		112		L / MBP	134 a
TL 3F	3 , 13			51		201			59		141		L / MBP	134 a
TL 4F	3 , 86			72		287			84				L B P	134 a
TL 5F	5 , 08			97		386			113				L B P	134 a
TL 4G	3 , 86			70		276			81	187	347		L /M /HBP	134 a
TL 5G	5 , 08			94		372			109	234	412		L /M /HBP	134 a
TLS 3FT	3 , 13			59		235			69				L B P	134 a
TLS 4FT	3 , 86			76		300			88				L B P	134 a
TLS 5FT	5 , 08			115		457			134				L B P	134 a
TLS 5F	5 , 08			115		457			134				L B P	134 a
TLS 6F	5 , 70			123		488			143				L B P	134 a
TLS 7F	6 , 49			142		563			165				L B P	134 a
TLES 3F	3 , 13			60		239			70	161			L / MBP	134 a
TLES 4F	3 , 86			83		331			97				LBP	134 a
TLES 5F	5 , 08			115		457			134				LBP	134 a
TLES 6F	5 , 70			123		488			143				LBP	134 a
TLES 5.7 FT.3	5 , 70			140		556			163				LBP	134 a
TLES 6.5 FT.3	6 , 49			157		624			183				LBP	134 a
TLES 7 FT.4	6..49			157		624			183				LBP	134 a
TLY 4F	3 , 86			85		338			99				LBP	134 a
TLY 5FK	5 , 08			115		457			134				LBP	134 a

MODEL	200 / 220 / 50 HZ												
Secop (Danfoss)				C O O L I N G C									
	IN	Displ.CC	R L A	K CAL/HR B T U		In -23	W -5	I n 7.2+					
NL 6 F	6 , 13			131 519		152			LBP		134	a	
NL 7 F	7 , 27			161 638		187			LBP		134	a	
NL 8 F	7 , 95			173 686		201			LBP		134	a	
NL 9 F	8 , 35			183 727		213			LBP		134	a	
NL 11 F	11 , 15			236 935		274			LBP		134	a	
NF 7FX	7 , 27			177 703		206	441 781	L / MBP	134	a			
NF 9FX	8 , 34			197 781		229	485 874	L / MBP	134	a			
NF 10FX	10 , 09			230 911		267	567 1011	L / MBP	134	a			
NF 11FX	11 , 15			253 1003		294	612 1092	L / MBP	134	a			
NL 6F	6 , 13			131 519		152			LBP		134	a	
NL 6FT	6 , 13			135 536		157			LBP		134	a	
NL 6.1FT	6 , 13			135 536		157			LBP		134	a	
NL 6.1MF	6 , 13			0 0			326 597	MBP			134	a	
NL Y6F	6 , 70			162 641		188			LBP		134	a	
NL 7FT	7 , 27			160 635		186			LBP		134	a	
NL 7.3 FT	7 , 27			160 635		186			LBP		134	a	
NL 7.3 MF	7 , 27			0 0			402 731	MBP			134	a	
NL 7 F	7 , 27			161 638		187			LBP		134	a	
NLY 7 F	7 , 27			184 730		214			LBP		134	a	
NL 8 F	7 , 95			173 686		201			LBP		134	a	
NL 8.4 FT	8 , 35			189 751		220			LBP		134	a	
NL 8.4 MF	8 , 35			0 0			465 839	MBP			134	a	
NL 9 F	8 , 35			183 727		213			LBP		134	a	
NL 9 FT	8 , 35			189 751		220			LBP		134	a	

NLY 9 FK	8 , 35	205	812	238	LBP	134 a
NL 10 FT	10 , 09	245	972	285	LBP	134 a
NL 10 MF	10 , 09	0	0	580	1040 MBP	134 a
NLE 10 MF	10 , 09	230	914	268	579	1044 MBP
NLE 10 MF.2	10 , 09	249	989	290	608	1097 L / MBP
NL 11 F	11 , 15	236	935	274	LBP	134 a
NL 11 MF	11 , 15	0	0	638	1144 M/HBP	134 a
NL 11 MF.2	11 , 15	285	1129	331	680	1211 MBP
NLE 12.6 MFT	12 , 55	305	1211	355	738	1341 L / MBP
NLE 12.6 MF.2	12 , 55	305	1211	355	738	1341 L / MBP

MODEL 200 /
 220 /
 50 HZ

Danfoss COOLING C

	IN	Displ.CC	R L A	k CAL/HR B T U	In -23	W -5	In 7.2+	
FR 6G	6 , 23			141	558	121	302	560 L/M/HBP
FR 7GH	6 , 93			141	558	121	341	658 HBP
FR 7.5G	6 , 93			164	651	141	338	626 L/M/HBP
FR 8.5G	7 , 95			200	794	172	397	732 L/M/HBP
FR 10G	9 , 05			220	872	189	429	789 L/M/HBP
FR 11G	11 , 15			274	1089	236	523	L/M/HBP

MODEL 200 /
 220 /
 50 HZ

Secop COOLING C run capacitor

	IN	Displ.CC	R L A	k CAL/HR B T U	In -23	W -5	In 7.2+	
GTK 55 AT	5 , 60			198	785	170	302	560 LBP
GTK 70 AT	6 , 64			238	946	205	341	658 LBP
GTK 80 AT	7 , 70			270	1071	232	338	626 LBP

GS 26 MFX	26 , 30	0	0	1592	MBP	134 a	CR MF 10
GS 26 GHX	26 , 30	0	0	1472	2664 MBP	134 a	CR MF 10

GS 34 MFX	33 , 80			2079 3799 HBP	134 a	CR MF 20
MODEL	200 / 220 / 50 HZ					
Secop		COOLING C				
	IN	Displ.CC	R L A	K CAL/HR B T U	In -23 W -5 In 7.2+	
SC 10G	10 , 29			145 577	169 502 942 L/M/HBP	134 a
SC 10GH	10 , 29			0 0	490 944 HBP	134 a
SC 10GHH	0 , 33			0 0	481 950 HBP	134 a M F 5
SC 12G	12 , 87			214 850	249 626 1194 L/M/HBP	134 a
SC 12GH	12 , 87			0 0	594 1199 HBP	134 a
SC 12FT	12 , 87			277 1099	322 678 LBP	134 a
SC 15F	15 , 28			279 1105	324 759 LBP	134 a
SC 15G	15 , 28			224 890	261 760 1369 L/M/HBP	134 a
SC 15GH	15 , 28			0 0	751 1415 HBP	134 a
SC 15GHH	15 , 28			0 0	753 1410 HBP	134 a M F 10
SC 15FT	15 , 28			332 1317	386 811 LBP	134 a
SC 15MFX	15 , 28			280 1112	326 800 1436 MBP	134 a
SC 18F	17 , 69			334 1327	389 879 LBP	134 a
SC 18G	17 , 69			342 1358	398 910 1645 L/M/HBP	134 a
SC 18GH	17 , 79			0 0	892 1665 HBP	134 a M F 10
SC 18FTX	17 , 69			385 1529	448 942 LBP	134 a
SC 18MFX	17 , 69			373 1481	434 933 1694 MBP	134 a
SC 21F	20 , 95			394 1563	458 1026 LBP	134 a
SC 21FTX	20 , 95			490 1945	570 1178 LBP	134 a
SC 21MFX	20 , 95			458 1819	533 1101 1969 MBP	134 a
SC 21G	20 , 95			397 1576	462 1059 1928 L/M/HBP	134 a M F 10
SC 12/12G	25 , 74			427 1696	four hundred ninety seven 1252 2355 L/M/HBP	134 a
SC 15/15G	30 , 56			449 1781	522 1519 2737 L/M/HBP	134 a
SC 18/18G	35 , 38			673 2671	783 1808 3291 L/M/HBP	134 a

SC 21/21G	41 , 90	0	923	2116 3855 L/M/HBP	¹³⁴ a
MODEL	200 / 220 / 50 HZ				
EMBRACO	COOLING C				
	IN	Displ.CC	R L A	k CAL/HR B T U	In -23 W -5 ^{In} _{7.2+}
IN 20HHR	2 , 27	0 , 5	43	171	50 135 246 L/M/HBP ¹³⁴ a
EMI 28HER	3	0 , 56	62	246	72 LBP ¹³⁴ a
EMI 30HER	3	0 , 56	62	246	72 LBP ¹³⁴ a
IN 30HHR	3	0 , 6	65	259	76 207 343 L/M/HBP ¹³⁴ a
EMU 30HER	3	0 , 55	70	276	81 LBP ¹³⁴ a
EMI 40HNR	3 , 77	0 , 72	77	304	89 LBP ¹³⁴ a
IN 45HNR	3 , 77	0 , 89	83	331	97 LBP ¹³⁴ a
EMI 45HER	3 , 77	0 , 77	86	341	100 LBP ¹³⁴ a
IN 45HHR	3 , 77	0 , 86	88	348	102 256 440 L/M/HBP ¹³⁴ a
EMU 45HEP	3 , 77	1 , 52	89	351	103 LBP ¹³⁴ a
EMU 45HER	3 , 77	0 , 74	92	365	107 LBP ¹³⁴ a
EMY45HSC	3 , 77	0 , 33	94	372	109 LBP ¹³⁴ a
EMU 45HSC	3 , 77	0 , 36	94	372	109 LBP ¹³⁴ a
EMT 45HDR	3 , 97	1 , 08			479 HBP ¹³⁴ a
EM 55HNR	4 , 6	1	106	420	123 LBP ¹³⁴ a
EMI 55HER	4 , 6	0 , 75	106	420	123 LBP ¹³⁴ a
EM 50HNP	4 , 99	0 , 82	107	426	125 LBP ¹³⁴ a
EMI 60HER	4 , 99	1 , 05	119	471	138 LBP ¹³⁴ a
IN 60HNP	5 , 54	0 , 83	122	484	142 LBP ¹³⁴ a CR 2MF
EMY60HSC	4 , 99	0 , 43	124	491	144 LBP ¹³⁴ a C R 5MF
EM 65HNR	5 , 54	1 , 05	131	519	152 LBP ¹³⁴ a
IN 65HHR	5 , 54	1 , 42			639 HBP
EMI 70HER	5 , 89	1 , 08	143	566	166 LBP ¹³⁴ a
EMY 65HLC	5 , 96	0 , 53	159	631	185 LBP ¹³⁴ a C.R 4MF

MODEL		200 / 220 / 50 HZ										
EMBRACO												
				COOLING C								
	IN	Displ.	CC	R A	L k	CAL/HR	B	T	U	In -23	W -5	In 7.2+
EGAS 70HLR		5 , 56		0 96	, 141		560		164			LBP 134 a C.R 4MF
EGZS 70HLC		5 , 56		0 46	, 141		560		164			LBP 134 a
EGAS 80HLR		6 , 36		1 07	, 168		665		195			LBP 134 a C.R 4MF
EGAS 80HLC		6 , 36		0 57	, 168		665		195			LBP 134 a
EGYS 90HLP		7 , 15		0 92	, 194		771		226			134 a C.R 4MF
EGZS 90HLC		7 , 15		0 71	, 194		771		226			134 a
EGAS 100HLR		7 , 95		1 36	, 216		856		251			134 a
EGAS 100HLP		7 , 95		0 99	, 216		856		251			134 a C.R 4MF
EGAS 100HLC		7 , 95		0 79	, 216		856		251			134 a
EG 80HLR		7 , 15		1 24	, 176		699		205			134 a
EG 100HLR		9 , 04		1 5	, 222		880		258			134 a
FG 65HAK		6 , 76		0 88	, 143		566		166			LBP 134 a
FFV 6HAK		6 , 23		1 06	, 144		570		167			LBP 134 a
FFI 6HAK		6 , 23		1 37	, 146		580		170	437	L / MBP	134 a C.R 5MF
FGS 70HA		6 , 36		0 58	, 151		600		176			LBP 134 a
FFU 70HAK		6 , 36		1 07	, 159		631		185	471	L / MBP	134 a
FFI 7.5HAK		6 , 76		1 3	, 163		648		190	470	L / MBP	134 a
FFV 7.5HAK		6 , 76		1 13	, 163		648		190	479	L / MBP	134 a
EG 70HLR		6 , 76		1 11	, 165		655		192			LBP 134 a
FG 75HAK		7 , 95		1 07	, 166		658		193			LBP 134 a C.R 5MF

FF 8.5HBK	7 , 95	$\frac{1}{45}$, 167	662	194	507	844	L / MBP	134 a
FGU 80HA	6 , 76	$\frac{0}{64}$, 170	676	198			LBP	134 a
FFU 80HAK	6 , 76	$\frac{1}{3}$, 171	679	199	499		L / MBP	134 a C.R 5MF
FGS 80HA	7 , 15	$\frac{0}{65}$, 175	696	204			LBP	134 a
FFI 8.5HAK	7 , 15	$\frac{1}{35}$, 176	699	205	508		L / MBP	134 a
FFV 8.5HAK	7 , 15	$\frac{1}{3}$, 176	699	205	493		L / MBP	134 a
FG 8.5HAK	9 , 04	$\frac{1}{2}$, 195	774	227			LBP	134 a C.R 5MF
FGS 90HA	7 , 95	$\frac{0}{78}$, 201	798	234			LBP	134 a
FG 95HAK	10 , 61	$\frac{1}{54}$, 222	880	258			LBP	134 a
100HAK FUEL	7 , 95	$\frac{1}{69}$, 206	815	239	594		L / MBP	134 a
FGS 100HA	9 , 04	$\frac{1}{36}$, 214	850	249			LBP	134 a
FFI 10HAK	9 , 04	$\frac{1}{73}$, 214	850	249	636		L / MBP	134 a
FU 130HAX	10 , 61	$\frac{1}{88}$, 266	1054	309	764		L / MBP	134 a C.R 4MF
FGS 130HA	11 , 14	$\frac{1}{12}$, 273	1082	317			LBP	134 a
FFI 12HBK	11 , 14	$\frac{1}{96}$, 274	1088	319	790	1269	L / MBP	134 a

200
/
220
/
50
HZ

LG	IN	Displ.	CC	COOLING C					W -5	In 7.2+	VS	
				R A	L k	CAL/HR	B T	U				
MA 42 LFJG	4 , 2		92			365	107				LBP	134 a
MA 42 LFJM	4 , 2		92			365	107				LBP	134 a .5 R MF
MA 42 LDJG	4 , 2		88			348	102				LBP	134 a
MA 42 LBHG	4 , 2		95			379	111				LBP	134 a
MA 42 LHJG	4 , 2		92			365	107				LBP	134 a
MA 42 LEJG	4 , 2		92			365	107				LBP	134 a
MA 42 LHJM	4 , 2		92			365	107				LBP	134 a .5 R MF

MA 45 LDJG	4 , 5	99	392	115	LBP	134 a	VS
MA 45 LCJM	4 , 5	99	392	115	LBP	134 a	R
MA 45 LBJM	4 , 5	99	392	115	LBP	134 a	VS
MA 45 LDJM	4 , 5	99	392	115	LBP	134 a	MF
MA 45 LFJM	4 , 5	101	403	118	LBP	134 a	VS
MA 53 NEWS	5 , 3	125	495	145	LBP	134 a	R
MA 53 LBJG	5 , 3	125	495	145	LBP	134 a	VS
MA 53 LBJM	5 , 3	125	495	145	LBP	134 a	MF
MA 53 LATG	5 , 3	124	491	144	LBP	134 a	
MA 57 LBJG	5 , 7	138	546	160	LBP	134 a	VS
MA 57 LCJG	5 , 7	144	573	168	LBP	134 a	R
MA 57 LDJM	5 , 7	144	573	168	LBP	134 a	MF
MA 57 LATG	5 , 7	138	546	160	LBP	134 a	
MA 62 LBJG	6 , 2	150	594	174	LBP	134 a	VS
MA 62 LDJM	6 , 2	150	594	174	LBP	134 a	R
MA 62 LBEG	6 , 2	150	594	174	LBP	134 a	MF
MA 62 LCEG	6 , 2	150	594	174	LBP	134 a	
MA 62 LATG	6 , 2	150	594	174	LBP	134 a	

HAS 69 LAY	6 , 9	172	682	200	LBP	134 a
MA 69 LAEM	6 , 9	172	682	200	LBP	134 a
MA 69 LAEP	6 , 9	169	672	197	LBP	134 a
MA 69 LCJM	6 , 9	172	682	200	LBP	134 a
MA 69 LBJG	6 , 9	172	682	200	LBP	134 a
MA 69 LATG	6 , 9	172	682	200	LBP	134 a

MA 72 LBJG	7 , 2	180	713	209	LBP	134 a
MA 72 LBJM	7 , 2	180	713	209	LBP	134 a
MA 72 LBEG	7 , 2	139	553	162	LBP	134 a
MA 72 LAEP	7 , 2	189	751	220	LBP	134 a

MA 88 LATP	8 , 8	235	931	273	LBP	134 a
MA 88 LAEP	8 , 8	235	931	273	LBP	134 a

MA 42 HAEG	4 , 2				412	HBP	134 a
MA 53 HAEF	5 , 3				510	HBP	134 a
MA 53 HAEG	5 , 3				510	HBP	134 a
MA 62 HAEG	6 , 2				603	HBP	134 a
MA 72 HAEP	7 , 2				731	HBP	134 a
MA 88 HAEP	8 , 8				858	HBP	134 a

200
/
MODEL
220
/
50
HZ

Samsung	COOLING														
	IN	Displ.	CC	R	L	k	CAL/HR	B	T	U	In	W	-5	In	7.2+
CD124H-L1Z2	2 , 4					43		171	50					LBP	134 a
CD130H-L1Z2	3					60		239	70					LBP	134 a
CD137H-L1UB	3 , 7					75		297	87					LBP	134 a

CD143H-L1UA	4 3	98	389	114	LBP	134	a
CD152H-S1UB	5 2	120	478	140	LBP	134	a
CD162H-L1UB	6 2	146	580	170	LBP	134	a
SK170H-L1UB	7	168	665	195	LBP	134	a
SK172H-L1UB	7 2	176	699	205	LBP	134	a
SK182H-L2UB	8 2	203	805	236	LBP	134	a
SK190H-L2UB	9	227	901	264	LBP	134	a
CD 124 Q-L1Z2	2 4	43	171	50	LBP	134	a
CD 130 Q-L1Z2	3	58	229	67	LBP	134	a
CD 130 Q-S1ZA	3	58	229	67	LBP	134	a
CD 137 Q-S1U2	3 7	72	287	84	LBP	134	a
SD 137 Q-L1ZB	3 7	75	297	87	LBP	134	a
SD 137 Q-L1UB	3 7	75	297	87	LBP	134	a
SD 143 Q-L1U2	4 3	1212	4811	1410	LBP	134	a
MSA 143 Q-S1Z	4 3	96	382	112	LBP	134	a
SD 152 Q-L1UB	5 2	120	478	140	LBP	134	a
MD 152 Q-L1U2	5 2	118	467	137	LBP	134	a
SD 162 Q-L1UB	5 2	146	580	170	LBP	134	a
CD 124 H-L1Z2	2 4	43	171	50	LBP	134	a
CD 124 H-L1ZA	2 4	42	167	49	LBP	134	a
CD 130 H-L1Z2	3	58	229	67	LBP	134	a
SD 137 H-L1ZB	3 7	75	297	87	LBP	134	a
SD 137 H-L1UB	3 7	75	297	87	LBP	134	a
SD 143 H-L1UA	4 3	98	389	114	LBP	134	a
SD 152 H-S1UB	5 2	120	478	140	LBP	134	a

SD 162 H-L1UB	6 2	146	580	170	LBP	134	a
SK 170 H-L1UB	7	168	665	195	LBP	134	a
MSA 170 H-L1B	7	173	686	201	LBP	134	a
MSA 170 H-L1G	7	173	686	201	LBP	134	a

MK 172 H-L1U	7 2	176	699	205	LBP	134	a
MK 172 H-L1UB	7 2	176	699	205	LBP	134	a
SK 182 H-L2UA	8 2	203	805	236	LBP	134	a
SK 182 H-L2UB	8 2	203	805	236	LBP	134	a
MK 183 H-L2UB	8 3	203	805	236	LBP	134	a
SK 190 H-S2U	9	227	901	264	LBP	134	a
SK 190 H-L2UA	9	227	901	264	LBP	134	a
SK 190 H-L2UB	9	227	901	264	LBP	134	a
MK 190 H-L2U	9	225	894	262	LBP	134	a

MSS 151 G-L1U	5 1	125	495	145	LBP	134	a
MSA 151 G-L1B	5 1	125	495	145	LBP	134	a
MSA 162 G-L1B	6 2	151	600	176	LBP	134	a
MSS 170 G-L1U	7	153	607	178	LBP	134	a
MK 183 G-L2U	8 3	203	805	236	LBP	134	a
MK 190 G-L2U	9	225	894	262	LBP	134	a

MK 162 Q-L1UA	6 2	145	577	169	LBP	134	a
MSS 162 Q-L1U	6 2	151	600	176	LBP	134	a
MSA 162 Q-L1G	6 2	151	600	176	LBP	134	a
SK 170 Q-L1U	7	168	665	195	LBP	134	a
MSA 170 Q-L1B	7	173	686	201	LBP	134	a
MSA 170 Q-L1G	7	173	686	201	LBP	134	a
MK 172 Q-L2UB	7 2	176	699	205	LBP	134	a
SK 182 Q-L2U	8 2	203	805	236	LBP	134	a

MK 183 Q-L2UB	8 3	203	805	236		LBP	134	a	
SK 190 Q-L2U	9	227	901	264		LBP	134	a	
CD 124 K-S1ZA	2 4	42	167	49		LBP	134	a	
CD 130 K-S1ZA	3	58	229	67		LBP	134	a	
MSA 143 K-S1B	4 3	96	382	112		LBP	134	a	
SK 170 K-T1UA	7	168	665	195		LBP	134	a	
SK 170 K-S1UB	7	168	665	195		LBP	134	a	
MSA 170 K-S1G	7	173	686	201		LBP	134	a	
MK 172 K-S1U	7	176	699	205		LBP	134	a	
SD 643 Q-H2Z2	4 3				430	HBP	134	a	
SD 652 Q-H2Z2	5 2				523	HBP	134	a	
SK 670 Q-H2S	7				698	HBP	134	a	
SK 670 Q-H2Z	7				692	HBP	134	a	
SK 682 Q-H2Z	8 2				814	HBP	134	a	
SK 6A1 Q-S2S	10 68				1047	HBP	134	a	
HK 672 Q2Z	7 2				709	HBP	134	a	
HK 680 Q2Z	8				814	HBP	134	a	
HK 690 Q2Z	9				907	HBP	134	a	
HK 6A1 Q2Z	1 68				1058	HBP	134	a	
HK 6A3 Q2U	12 52				1221	HBP	134	a	
MODEL	200 / 220 / 50 HZ								
Tecumseh			COOLING C						
	IN	Displ.CC A	R L k	CAL/HR B T U	In -23	W -5	In 7.2+		
THD 1330 Y	3 14		72	287	84			LBP	134 a
THD 1335 Y	3 4		79	314	92			LBP	134 a
THG 1340 Y	3 79		89	355	104			LBP	134 a

THB 1346 Y	4 , 23	101	399	117		LBP	134 a
THB 1352 Y	5 , 01	116	461	135		LBP	134 a
THB 1358 Y	5 , 6	132	525	154		LBP	134 a
THD 1365 Y	5 , 9	144	570	167		LBP	134 a
THB 1374 Y	6 , 95	165	655	192		LBP	134 a

TSB 1355 Y	4 , 59	120	478	140		LBP	134 a
TSB 1360 Y	5 , 23	128	508	149		LBP	134 a
TSB 1374 Y	5 , 65	144	570	167		LBP	134 a
TSB 1380 Y	6 , 53	164	652	191		LBP	134 a
TSB 1390 Y	7 , 28	185	734	215		LBP	134 a

TPH 1380 Y	6 , 53	175	696	204		LBP	134 a
TPH 1410 Y	8 , 37	232	921	270		LBP	134 a
TPH 1413 Y	10 , 86	271	1075	315		LBP	134 a
TPH 1415 Y	12 , 52	312	1239	363		LBP	134 a

MODEL
200
/
220
/
50
HZ

Lanhai	COOLING C								
	IN	Displ.	CC R A L k	CAL/HR	B T U	In -23	W -5	In 7.2+	
LAW QD 25 HHP	2 , 50		65	259	76			LBP	134 a
LAW QD 30 HHP	3 , 00		65	259	76			LBP	134 a
LAW QD 35 HHP	3 , 50		77	304	89			LBP	134 a
LAW QD 43 HHP	4 , 30		90	358	105			LBP	134 a
LAW QD 52 HHP	4 , 00		99	392	115			LBP	134 a

LAF	QD	59	HHP	5 , 50		105	416	122		LBP	134	a
LAF	QD	65	HHP	6 , 20		116	461	135		LBP	134	a
LAF	QD	75	HHP	7 , 20		129	512	150		LBP	134	a
LAF	QD	91	HHP	8 , 80		152	604	177		LBP	134	a
MODEL					200 / 220 / 50 HZ							
	Wansheng (China)				COOLING C							
				IN	Displ. CC R L A	k CAL/HR	B T U	In -23	W -5	In 7.2+		
QD 43 H.				4 , 30		95	375	110	320		L / MBP	134 a
QD 52 H				5 , 20		115	457	134	358		L / MBP	134 a
QD 59 H				5 , 90		125	495	145	415		L / MBP	134 a
QD 65H				6 , 50		146	580	170	435		L / MBP	134 a
QD 75 H.				7 , 50		159	631	185	510		L / MBP	134 a
QD 91 H.				9 , 10		189	751	220	625		L / MBP	134 a
QD 110 H				11 , 00		245	972	285	680		L / MBP	134 a
QD 128 H.				12 , 80		310	1228	360	830		L / MBP	134 a
QD 142 H.				14 , 20		340	1348	395	890		L / MBP	134 a
QD 158 H				15 , 80		387	1535	450	980		L / MBP	134 a
MAW QD 30 HHP				3 , 00		71	280	82	89		L / MBP	134 a
MAW QD 35 HHP				3 , 50		77	304	89	111		L / MBP	134 a
MAM QD 43 HHP				4 , 30		100	396	116	134		L / MBP	134 a
MAF QD 52 HHP				5 , 50		101	403	118	174		L / MBP	134 a
MAF QD 59 HHP				6 , 20		122	484	142	194		L / MBP	134 a
MAF QD 65 HHP				6 , 60		135	536	157	193		L / MBP	134 a

MAF QD 75 HHP	7 , 60	150	597	175	241	L / MBP	134 a
MAF QD 91 HHR	8 , 80	163	645	189	252	L / MBP	134 a
MAL QD 75 HHR	7 , 60	132	525	154	235	L / MBP	134 a
MAL QD 91 HHR	8 , 80	154	611	179	250	L / MBP	134 a
MAL QD 91 HGR	9 , 30	164	652	191	270	L / MBP	134 a
MAL QD 110 HHR	11 , 10	201	798	234	337	L / MBP	134 a
MAQ QD 128 HHR	12 , 30	236	938	275	463	L / MBP	134 a
MAQ QD 142 HHM	13 , 50	258	1024	300	500	L / MBP	134 a
MAQ QD 158 HHM	15 , 30	285	1129	331	560	L / MBP	134 a
MAQ QD 168 HHM	16 , 30	304	1208	354	610	L / MBP	134 a

F . N

FN 57 H	5 , 70	114	454	133	360	L / MBP	134 a
FN 66 H	6 , 60	142	563	165	410	L / MBP	134 a
FN 77 H	7 , 70	159	631	185	526	L / MBP	134 a
FN 91 H	9 , 10	176	699	205	570	L / MBP	134 a
FN 110 H	11 , 00	232	921	270	685	L / MBP	134 a
MODEL	200 / 220 / 50 Hz						

Wansheng (China)

	IN	Displ.	CC	R L A	k CAL/HR	B T U	In -23	COOLING C	
								W -5	In 7.2+
HQD 43 H	4 , 30							238	404
HQD 52 H	5 , 20							290	492
HQD 59 H	5 , 90							332	563
HQD 65 H	6 , 50							368	625
HQD 75 H	7 , 50							430	730

HQD 91 H	9 , 10		535	908	M/HBP	130	a	
HQD 110 H	11 , 00		654	1110	M/HBP	131	a	
HQD 128 H	12 , 80		766	1300	M/HBP	132	a	
HQD 142 H	14 , 20		859	1459	M/HBP	133	a	
HAW QD 30 HHP	3 , 00		100	138	M/HBP	134	a	
HAW QD 35 HHP	3 , 50		111	152	M/HBP	134	a	
HAM QD 43 HHP			134	182	M/HBP	134	a	
HAF QD 52 HHP	4 , 90		154	207	M/HBP	134	a	
HAF QD 59 HHP	5 , 50		173	234	M/HBP	134	a	
HAF QD 65 HHR	6 , 20		190	265	M/HBP	134	a	
HAF QD 75 HHR	7 , 20		205	277	M/HBP	134	a	
HAL QD 75 HHR	7 , 20		205	275	M/HBP	134	a	
HAL QD 91 HHR	8 , 80		250	331	M/HBP	134	a	
HAL QD 110 HHM	10 , 60		307	408	M/HBP	134	a	
HAL QD 120 HHM	11 , 60		348	516	M/HBP	134	a	
HAQ QD 128 HHM	12 , 30		411	559	M/HBP	134	a	
HAQ QD 142 HHM	13 , 60		455	618	M/HBP	134	a	
HAQ QD 158 HHM	15 , 30		499	675	M/HBP	134	a	
MODEL	200 / 220 / 50 HZ							
China		COOLING C						
	IN	Displ.CC R A	L k CAL/HR	B T U	In -23	W -5 In 7.2+		
TAW QD 30 HHP	3 , 00		65	259	76	103	145	L/M/HBP 134 a
TAW QD 35 HHP	3 , 50		72	287	84	111	152	L/M/HBP 134 a
TAF QD 43 HHP	4 , 30		84	334	98	134	182	L/M/HBP 134 a

TAF QD 52 HHP	4 , 90	96	382	112	154	207	L/M/HBP 134 a
TAF QD 59 HHP	5 , 50	104	413	121	173	234	L/M/HBP 134 a
TAF QD 65 HHP	6 , 20	120	474	139	190	251	L/M/HBP 134 a
TAF QD 75 HHP	7 , 20	119	471	138	205	278	L/M/HBP 134 a
TAL QD 75 HHR	7 , 20	118	467	137	205	276	L/M/HBP 134 a
TAL QD 91 HHR	8 , 80	141	560	164	259	339	L/M/HBP 134 a
TAL QD 110 HHM	10 , 60	171	679	199	307	420	L/M/HBP 134 a
TAL QD 120 HHM	11 , 60	212	839	246	256	485	L/M/HBP 134 a
TAQ QD 128 HHM	12 , 30	233	925	271	381	515	L/M/HBP 134 a
TAQ QD 142 HHM	13 , 60	249	989	290	413	557	L/M/HBP 134 a
TAQ QD 158 HHM	15 , 30	278	1102	323	458	619	L/M/HBP 134 a

TAX FN 57 HHR	5 , 70	99	392	115	175	236	L/M/HBP 134 a
TAX FN 66 HHR	6 , 60	103	409	120	195	263	L/M/HBP 134 a
TAX FN 77 HHR	7 , 70	114	454	133	209	278	L/M/HBP 134 a
TAX FN 91 HHR	9 , 10	135	536	157	248	333	L/M/HBP 134 a
TAX FN 110 HHR	11 , 00	168	665	195	308	414	L/M/HBP 134 a

MODEL
200 /
220 /
50 Hz

Daewoo	COOLING									
	R	IN	Displ.	CC L	k	CAL/HR	B T U	In -23	W -5	In 7.2+
HSL 11 YE-5	4 , 51		80		317	93			LBP	134 a
HSL 13 YE-5	4 , 62		93		368	108			LBP	134 a
HSL 15 YE-5	5 , 12		107		423	124			LBP	134 a
HSL 17 YE-5	5 , 55		126		498	146			LBP	134 a

HSL 19 YE-5	5 , 84	130	515	151		LBP	134 a
						LBP	134 a
						LBP	134 a
HSL 21 YE-5	149	151	600	176		LBP	134 a
HSL 23 YE-5	161	155	614	180		LBP	134 a
HSL 25 YE-5	176	174	689	202		LBP	134 a
HSL 27 YE-5	196	197	781	229		LBP	134 a
HSL 30 YE-5	253	230	911	267		LBP	134 a
HSL 5 Y-5P	2 , 29	35	140	41		LBP	134 a
HPL 7 Y-5	2 , 65	50	198	58		LBP	134 a
HSL 7 Y-5	2 , 65	48	191	56		LBP	134 a
HSL 9 Y-5	3 , 43	58	229	67		LBP	134 a
HSL 11 Y-5	4 , 51	80	317	93		LBP	134 a
HSL 11Y -5-K	4 , 51	84	334	98		LBP	134 a
HSL 11 Y-5-L	4 , 51	80	317	93		LBP	134 a
HPL 11 Y-5-K	4 , 51	80	317	93		LBP	134 a
HPL 13 JE-5	4 , 62	93	368	108		LBP	134 a
HPL 15 JE-5	5 , 12	107	423	124		LBP	134 a
HSL 15 JE-5	5 , 12	108	430	126		LBP	134 a
HSL 15 JE-5C	5 , 12	108	430	126		LBP	134 a
HSL 17 JE-5	5 , 55	126	502	147		LBP	134 a
HPL 19 JE-5	5 , 84	134	532	156		LBP	134 a
HSL 19 JE-5	5 , 84	130	515	151		LBP	134 a
HSL 19 JE-5A	5 , 84	135	536	157		LBP	134 a
HPL 17 YH-5	5 , 5	129	512	150		LBP	134 a
HPL 19 YH-5	5 , 84	136	539	158		LBP	134 a
HPL 21 YH-5	6 , 73	152	604	177		LBP	134 a

HPL 23 YH-5	7 , 03	166	658	193		LBP	134 a
HPL 25 YH-5	7 , 96	194	771	226		LBP	134 a
HPL 25 YH-5-K	7 , 96	188	747	219		LBP	134 a
HPL 26 YH-5	8 , 25	192	761	223		LBP	134 a
HPL 26 YH-5-K	8 , 25	192	761	223		LBP	134 a
HPL 30 YH-5	9 , 92	229	908	266		LBP	134 a
YX 51 LHS5	5 , 1	122	484	142		LBP	134 a
YX 58 LHP5	5 , 84	141	560	164		LBP	134 a
HPL 25 YG1-5	7 , 68	180	713	209		LBP	134 a
HPL 25 YG2-5	7 , 68	180	713	209		LBP	134 a
HPL 27 YG1-5	8 , 69	206	819	240		LBP	134 a
HPL 30 YG-5	9 , 92	235	931	273		LBP	134 a
HPL 30 YG-5A	9 , 92	228	904	265		LBP	134 a
HPL 21 YE-5-K	6 , 72	148	587	172		LBP	134 a
HPL 21 YE-5-L	6 , 73	152	604	177		LBP	134 a
HSL 21 YE-5	6 , 73	151	600	176		LBP	134 a
HPL 23 YE-5	7 , 03	166	658	193		LBP	134 a
HPL 23 YE-5-K0	7 , 03	162	641	188		LBP	134 a
HSL 23 YE-5	7 , 03	155	614	180		LBP	134 a
HKL 25 YE-5	7 , 68	177	703	206		LBP	134 a
HPL 25 YE-5-K	7 , 68	175	693	203		LBP	134 a
HPL 25 YE-5-L	7 , 68	180	713	209		LBP	134 a
HSL 25 YE-5	7 , 68	174	689	202		LBP	134 a
HKL 27 YE-5	8 , 69	200	795	233		LBP	134 a
HPL 27 YE-5	8 , 69	204	809	237		LBP	134 a
HPL 27 YE-5-K	8 , 69	199	788	231		LBP	134 a

HSL 27 YE-5	8 , 69	197	781	229	LBP	134 a
HSL 27 YE-5A	8 , 69	195	774	227	LBP	134 a
HKL 30 YE-5	9 , 92	236	935	274	LBP	134 a
HPL 30 YE-5	9 , 92	228	904	265	LBP	134 a
HPL 30 YE-5-K	9 , 92	221	877	257	LBP	134 a
HSL 30 YE-5	9 , 92	230	911	267	LBP	134 a
DH 70 LHP5	7 , 03	161	638	187	LBP	134 a
DH 80 LHP5	7 , 89	189	751	220	LBP	134 a
DH 90 LHK5	8 , 93	203	805	236	LBP	134 a
DH 90 LHP5	8 , 93	205	812	238	LBP	134 a
DH 120 LHG5	12	270	1071	314	LBP	134 a
DH 126 LHG5	12 , 6	290	1150	337	LBP	134 a
JX 41 LHP5-K	4 , 09	88	348	102	LBP	134 a
JX 41 LHS5	4 , 09	89	355	104	LBP	134 a
JX 46 LHS5	4 , 6	100	396	116	LBP	134 a
JX 51 LHS5-K	5 , 12	114	454	133	LBP	134 a
JX 51 LHS5	5 , 12	121	481	141	LBP	134 a
JX 51 LHT5	5 , 12	115	457	134	LBP	134 a
JX 55 LHP5-K	5 , 55	128	508	149	LBP	134 a
JX 55 LHS5-K	5 , 55	126	498	146	LBP	134 a
JX 58 LHK5	5 , 84	141	560	164	LBP	134 a
JX 58 Film Festival	5 , 84	140	556	163	LBP	134 a
JX 58 LHP5-K	5 , 84	140	556	163	LBP	134 a
JX 58 LHS5	5 , 84	141	560	164	LBP	134 a
JX 58 LHS5-K	5 , 84	140	556	163	LBP	134 a
JX 58 LHS5A	5 , 84	140	556	163	LBP	134 a

200 /
MODEL
220 /
50 HZ

HUAYI CUBIGEL

COOLING
C

	R	IN	Displ.CC	L	k CAL/HR	B T U	In -23	W -5	In 7.2+	
	A									
HY 69 YG		6 , 9		168		665	195			LBP 134 a
HYE 60 YX		6		159		631	185			LBP 134 a
HYE 69 YS		6 , 7		168		665	195			LBP 134 a
HYE 55 YL63		5 , 5		129		512	150			LBP 134 a
HYE 60 YL63		6		146		580	170			LBP 134 a
HYE 69 YL		6 , 7		168		665	195			LBP 134 a
HYE 60 YKL		6		155		614	180			LBP 134 a
HYE 69 YKL		6		168		665	195			LBP 134 a
HYB 41 YL		4 , 1		95		375	110			LBP 134 a
HY 69 YH		6 , 9		168		665	195			LBP 134 a
HYB 30 YL63		3 , 1		73		290	85			LBP 134 a
HY90Y		9		228		904	265			LBP 134 a
HYE 90 YG		9 , 4		232		921	270			LBP 134 a
HYE 81 YG		8 , 1		202		802	235			LBP 134 a
HY 81 YTL		8 , 1		202		802	235			LBP 134 a
HY 81 YGL		8 , 1		202		802	235			LBP 134 a
HY 69 YGL		6 , 9		168		665	195			LBP 134 a
HY 90 YL		9		228		904	265			LBP 134 a
HY 113 Y		11 , 3		284		1126	330			LBP 134 a
HYB 25 Y63a		2 , 5		56		222	65			LBP 134 a
HYE 52 YK63a		5 , 1		129		512	150			LBP 134 a
HY 69 Y63		6 , 9		168		665	195			LBP 134 a
HYS 45 Y		4 , 5		107		426	125			LBP 134 a
HYB 35 Y		3 , 4		77		307	90			LBP 134 a
HYE 55 YG63		5 , 5		129		512	150			LBP 134 a
HYE 55 Y		5 , 5		129		512	150			LBP 134 a
HYE 60 Y63		6		146		580	170			LBP 134 a
HYE 69 Y		6 , 7		163		648	190			LBP 134 a
HYE 60 YS		6		155		614	180			LBP 134 a
HYE 60 YG63		6		146		580	170			LBP 134 a
HYE 55 YT		5 , 5		133		529	155			LBP 134 a
HYE 55 YT63		5 , 5		155		614	180			LBP 134 a
HYE 69 YG		6 , 7		163		648	190			LBP 134 a

HYE 69 Y63	6 , 7	163	648	190	LBP	134 a
HYE 69 YK	6 , 7	168	665	195	LBP	134 a
HYE 60 YK	6	150	597	175	LBP	134 a
HYE 60 YG	6	146	580	170	LBP	134 a
HYE 60Y	6	146	580	170	LBP	134 a
HYE 81 MSU	8 , 1	122	484	142	LBP	134 a
HYE 90 MSU	8 , 9	131	519	152	LBP	134 a

HY113YZ	11 , 3	860	3412	1000	M/HBP	134 a
HYE 69 YZ63a▲	6 , 9	619	2457	720	M/HBP	134 a
HY 69 YZ	6 , 9	555	2201	645	M/HBP	134 a
HYE 69 YZ	6 , 9	619	2457	720	M/HBP	134 a
HY 94 YZ	9 , 4	739	2934	860	M/HBP	134 a
HY 131 YZ	13 , 1	997	3958	1160	M/HBP	134 a
HY 153 YZ	15 , 3	1118	4435	1300	M/HBP	134 a
HYE 81 YZ	8 , 1	714	2832	830	M/HBP	134 a
HYE 81 YZ63a▲	8 , 1	714	2832	830	M/HBP	134 a
HY81YZ	8 , 1	641	2542	745		134 a

200 /
MODEL 220 /
50 HZ

IN	Displ.	CC L A	COOLING C					W -5 In 7.2+	
			R k	CAL/HR	B	T	U		
AE 123 YES / YP / YT / YC	5 , 75		106		420	123		LBP	134 a
AE 148 YES / YP / YT / YC	6 , 91		127		505	148		LBP	134 a
AE 176 Y / YP / YT / YC	7 , 94		151		600	176		LBP	134 a
AE 196 YD /YP/YT/YC/YK	8 , 99		169		669	196		LBP	134 a
AE 230/YC	14 , 17		198		785	230		LBP	134 a
AE 282 YC	16 , 13		242		962	282		LBP	134 a

TE 150 YP / YT	6 , 36	128	508	149	LBP	134 a
TE 165 YP / YT	6 , 91	142	563	165	LBP	134 a
TE 180 YP / YT	7 , 50	156	618	181	LBP	134 a
TE 195 YP / YT	7 , 94		658	193	LBP	134 a
TE 215 YP / YT	8 , 99	187	740	217	LBP	134 a

MTE 160 YP / YT	6 , 36	138	546	160	LBP	134 a
MTE 175 YP / YT	6 , 91	150	594	174	LBP	134 a

MTE 190 YP / YT	7 , 50	163	645	189	LBP	134 a
MTE 205 YP / YT	7 , 94	176	699	205	LBP	134 a
MTE 225 YP / YT	8 , 99	193	768	225	LBP	134 a
AZ 47 YD / YP / YT	2 , 80	40	160	47	LBP	134 a
AZ 68 YD / YP / YT	3 , 59	58	232	68	LBP	134 a
AZ 82 YD / YP / YT	4 , 00	71	280	82	LBP	134 a
AZ 90 YD / YP / YT	5 , 00	77	307	90	LBP	134 a
AZ 107 YD / YP / YT	5 , 59	92	365	107	LBP	134 a
AZ 121 YD / YP / YT	5 , 90	104	413	121	LBP	134 a
THA 65 YP / YT	3 , 08	56	222	65	LBP	134 a
THA 80 YP / YT	3 , 59	70	276	81	LBP	134 a
THA 90 YP / YT	3 , 80	76	300	88	LBP	134 a
THA 100 YP / YT	4 , 23	85	338	99	LBP	134 a
THA 110 YP / YT	5 , 00	94	372	109	LBP	134 a
THA 125 YP / YT	5 , 59	108	430	126	LBP	134 a
THA 138 YP / YT	5 , 90	119	471	138	LBP	134 a
THB 55 YP / YT	2 , 80	46	184	54	LBP	134 a
THB 75 YP / YT	3 , 59	65	259	76	LBP	134 a
THB 85 YP / YT	3 , 80	73	290	85	LBP	134 a
THB 95 YP / YT	4 , 23	81	321	94	LBP	134 a
THB 105 YP / YT	5 , 00	91	362	106	LBP	134 a
THB 118 YP / YT	5 , 59	101	403	118	LBP	134 a
THB 130 YP / YT	5 , 90	113	447	131	LBP	134 a
		0	0			
MTH 75 YP / YT	3 , 09	63	249	73	LBP	134 a
MTH 85 YP / YT	3 , 59	74	293	86	LBP	134 a
MTH 95 YP / YT	3 , 80	81	321	94	LBP	134 a
MTH 105 YP / YT	4 , 23	90	358	105	LBP	134 a
MTH 115 YP / YT	5 , 00	104	413	121	LBP	134 a
MTH 135 YP / YT	5 , 59	110	437	128	LBP	134 a
MTH 145 YP / YT	5 , 90	128	508	149	LBP	134 a
AE 560 Y / YP / YC	7 , 57		560	HBP	134 a	
AE 666 YC / YK	8 , 84		666	HBP	134 a	
AE 881 YC / YK	12 , 04		881	HBP	134 a	

AE 1024 YC / YK 14 , 17 1024 HBP 134 a

200
/
MODEL 220
/ 50
HZ

				COOLING															
				R	C	L	A	k	CAL/HR	B	T	U	In	-23	W	-5	In	7.2+	
D 30 CZC		3			64				256	75						LBP	134	a	
DK 30 CZ1		3			60				239	70						LBP	134	a	
S 65 CZ1		6 , 5			146				580	170						LBP	134	a	
LK 65 CZ1		6 , 5			150				597	175						LBP	134	a	VS . R MF 4
LM 65 CZ		6 , 5			150				597	175						LBP	134	a	VS . R MF 4
LJ 65 CZ		6 , 5			150				597	175						LBP	134	a	VS . R MF 4
LU 70 CZ		7			163				648	190						LBP	134	a	VS . R MF 5
S 70 CZ1		7 , 2			168				665	195						LBP	134	a	
LK 70 CZ1		7 , 2			168				665	195						LBP	134	a	VS . R MF 4
LM 70 CZ		7 , 2			168				665	195						LBP	134	a	VS . R MF 4
L 76 CZ1		7 , 6			185				734	215						LBP	134	a	
L 83 CZ1		8 , 3			198				785	230						LBP	134	a	
KK 230 CZ1		8 , 3			198				785	230						LBP	134	a	VS . R MF 5
KM 230 CZ		8 , 3			198				785	230						LBP	134	a	VS . R MF 5
K 270 CZ1		9 , 5			232				921	270						LBP	134	a	
KK 270 CZ1		9 , 5			232				921	270						LBP	134	a	VS . R MF 5
K 325 CZ1		11 , 4			279				1109	325						LBP	134	a	
K 375 CZ1		12 , 7			322				1279	375						LBP	134	a	
K 400 CZ1		14 , 3			344				1365	400						LBP	134	a	VS . R MF 6

200
/
MODEL 220
/ 50
HZ

				COOLING															
				R	C	L	A	k	CAL/HR	B	T	U	In	-23	W	-5	In	7.2+	
D 5136 CZ1		4 , 1			361				1433						420	M/HBP	134	a	
S 5 150 CZ1		6			559				2218						650	M/HBP	134	a	

S 6160 CZ`	7 , 2	645	2559	750	M/HBP 134 a	
L 6170 CZ	7 , 9	731	2900	850	M/HBP 134 a	VS . S MF 50
NE 5170 CZ	9 , 8	800	3173	930	M/HBP 134 a	
BN 6188 CZ	12	946	3753	1100	M/HBP 134 a	VS . S MF 75
K 6210 CZ	11 , 4	1032	4094	1200	M/HBP 134 a	VS . S MF 75

200
/
MODEL 220
/
50
HZ

IN	Displ.	CC	R A	L	COOLING				W -5	In 7.2+	R 134 a	
					k	CAL/HR	B	T	U	In -23		
N 1080 Y	5 , 5				82		324		95		LBP	R 134 a
N 1090 Y	6				86		341		100		LBP	R 134 a
N 1110 Y	6 , 7				98		389		114		LBP	R 134 a
N 1111 Y	7 , 2				112		444		130		LBP	R 134 a
N 1112 Y	8 , 1				120		478		140		LBP	R 134 a
N 1113 Y	8 , 9				132		525		154		LBP	R 134 a
N 1114 Y	9 , 6				144		573		168		LBP	R 134 a
NT 1112 Y	8 , 1				120		478		140		LBP	R 134 4
NT 1113 Y	8 , 9				132		525		154		LBP	R 134 4
NT 1114 Y	9 , 6				146		580		170		LBP	R 134 4.0 / a 4.5
NT 1117 Y	11 , 2				170		676		198		LBP	R 134 4
NOW 1080 Y	5 , 5				82		324		95		LBP	R 134 3
NOW 1090 Y	6				88		348		102		LBP	R 134 4
NOW 1110 Y	6 , 7				99		392		115		LBP	R 134 4
NOW 1111 Y	7 , 2				112		444		130		LBP	R 134 3.5 / a 4.0

NOW 1112 Y	8 , 1	120	478	140	LBP	R a	134	4
NOW 1113 Y	8 , 9	132	525	154	LBP	R a	134	4
NU 1114Y	9 , 6	146	580	170	LBP	R a	134	4.0 / 4.5
NOW 1116 Y	10 , 5	160	635	186	LBP	R a	134	4 , 5
NOW 1112 GY	8 , 1	120	478	140	LBP	R a	134	3.5 / 4.0
NOW 1113 GY	8 , 9	132	525	154	LBP	R a	134	4
NS 1060 Y	4 , 2	56	222	65	LBP	R a	134	2
NS 1080 Y	5 , 5	82	324	95	LBP	R a	134	3
NS 1090 Y	6	90	358	105	LBP	R a	134	2.0 / 3.0
NS 1110 Y	6 , 7	100	396	116	LBP	R a	134	3.0 / 4.0
NS 1111 Y	7 , 2	112	444	130	LBP	R a	134	3.5 / 4.0
NS 1112 Y	8 , 1	122	484	142	LBP	R a	134	3.5 / 4.0
NS 1113 Y	8 , 9	133	529	155	LBP	R a	134	4
NS 1114 Y	9 , 6	148	587	172	LBP	R a	134	4
NS 1116 Y	10 , 5	160	635	186	LBP	R a	134	4.0 / 5.0
NS 1117 Y	11 , 2	170	676	198	LBP	R a	134	4
NC 1090 Y	6	90	358	105	LBP	R a	134	2 , 5
NC 1110 Y	6 , 7	100	396	116	LBP	R a	134	3.0 / 4.0
NC 1111 Y	7 , 2	110	437	128	LBP	R a	134	4
NC 1112 Y	8 , 1	122	484	142	LBP	R a	134	4
NC 1113 Y	8 , 9	133	529	155	LBP	R a	134	4
NC 1114 Y	9 , 6	148	587	172	LBP	R a	134	3.0 / 4.0
NC 1116 Y	10 , 5	160	635	186	LBP	R a	134	3
NX 1080 Y	5 , 5	83	328	96	LBP	R a	134	2

NX	1090	Y	6	93	368	108	LBP	R a	134	2	,	5
NX	1110	Y	6 , 7	101	399	117	LBP	R a	134	2	,	5
NX	1111	Y	7 , 2	112	444	130	LBP	R a	134	3		
NX	1112	Y	8 , 1	125	495	145	LBP	R a	134	3		
NX	1113	Y	8 , 9	133	529	155	LBP	R a	134	2	,	5
NX	1114	Y	9 , 6	148	587	172	LBP	R a	134	4		
NB	1080	Y	5 , 5	83	328	96	LBP	R a	134	2		
NB	1090	Y	6	93	368	108	LBP	R a	134	2	,	5
NB	1110	Y	6 , 7	101	399	117	LBP	R a	134	2	,	5
NB	1111	Y	7 , 2	112	444	130	LBP	R a	134	3		
NB	1112	Y	8 , 1	125	495	145	LBP	R a	134	3		
NB	1113	Y	8 , 9	133	529	155	LBP	R a	134	2	,	5
NB	1114	Y	9 , 6	148	587	172	LBP	R a	134	4		
NB	1116	Y	10 , 5	160	635	186	LBP	R a	134	4		
NE	1080	Y	5 , 5	83	328	96	LBP	R a	134	2		
NE	1090	Y	6	93	368	108	LBP	R a	134	2	,	5
NE	1110	Y	6 , 7	101	399	117	LBP	R a	134	2	,	5
NE	1111	Y	7 , 2	112	444	130	LBP	R a	134	3		
NE	1112	Y	8 , 1	125	495	145	LBP	R a	134	3		

MODEL
200
/
220
/
50
Hz

COOLING C

	IN	Displ.	CC	R A	L	k	CAL/HR	B	T	U	In -23	W	-5	In 7.2+
AE 1360 Y		6 , 91	1			136		539		158				

AE 1370 Y	8 , 12	$\frac{1}{2}$,	160	635	186		LBP	134 a
AE 1390 Y	9 , 42	$\frac{1}{3}$,	217	860	252		LBP	134 a
AE 1390 Y-6	9 , 42	$\frac{1}{6}$,	228	904	265		LBP	134 a
AE 1411 Y	14 , 14	2 ,	256	1017	298		LBP	134 a
AE 2340 Y	5 , 11	$\frac{0}{8}$,	95	375	110		LBP	134 a
AE 2360 Y	6 , 91	1 ,	136	539	158		LBP	134 a
AE 2370 Y	8 , 12	$\frac{1}{2}$,	159	631	185		LBP	134 a
AE 2390 Y	9 , 42	$\frac{1}{4}$,	206	819	240		LBP	134 a
AE 2417 Y	18	$\frac{1}{2}$,	344	1365	400		LBP	134 a
AEA 2410 AND	12 , 05	2 ,	232	921	270		LBP	134 a
AEA 2413 AND	14 , 14	2 ,	301	1194	350		LBP	134 a
AEA 2415 AND	18 , 6	$\frac{1}{3}$,	318	1262	370		LBP	134 a C R5 MF 8
AE 6412 Y	5 , 99	$\frac{1}{2}$,	267	1061	311		MBP	134 a
AE 7415 Y	7 , 55	$\frac{1}{8}$,	317	1259	369		MBP	134 a
AE 7423 Y	12 , 05	$\frac{2}{3}$,	494	1958	574		MBP	134 a
AE 7426 Y	14 , 14	$\frac{2}{5}$,	550	2184	640		MBP	134 a
AE 7430 Y	16 , 08	$\frac{2}{2}$,	641	2542	745		MBP	134 a C R5 MF 8
AE 3414 Y	4 , 49	$\frac{1}{3}$,	318	1262		370	HBP	134 a
AE 3417 Y	5 , 68	$\frac{1}{6}$,	430	1706		500	HBP	134 a
AE 3425 Y	7 , 55	202	628	2491		730	HBP	134 a
AE 3430 Y	8 , 86	$\frac{2}{5}$,	731	2900		850	HBP	134 a
AE 3435 Y	9 , 42	$\frac{2}{7}$,	767	3043		892	HBP	134 a
AE 3440 Y	12 , 05	3 ,	916	3634		1065	HBP	134 a
AE 3448 Y	14 , 14	$\frac{3}{5}$,	1032	4094		1200	HBP	134 a
AE 4414 Y	4 , 49	$\frac{1}{3}$,	318	1262		370	HBP	134 a

AE 4425 Y	7 , 55	$\frac{2}{2}$	602	2388	700	HBP	134 a
AE 4430 Y	8 , 86	$\frac{2}{5}$	705	2798	820	HBP	134 a
AE 4430 Y	8 , 86	$\frac{1}{6}$	684	2716	796	HBP	134 a C R5 MF 8
AE 4435 Y	9 , 42	$\frac{2}{7}$	776	3078	902	HBP	134 a
AE 4440 Y	12 , 05	$\frac{3}{1}$	924	3668	1075	HBP	134 a
AE 4440 Y	12 , 05	$\frac{2}{2}$	924	3668	1075	HBP	134 a C R5 MF 8
AE 4448 Y	14 , 14	$\frac{3}{6}$	1023	4060	1190	HBP	134 a
AE 4448 Y	14 , 14	$\frac{2}{4}$	1049	4162	1220	HBP	134 a C R5 MF12
AE 4459 Y	16 , 08	3	1247	4947	1450	HBP	134 a C R5 MF 15

200
/
MODEL 220
/ 50
HZ

IN	Displ.	CC	$\frac{R}{A}$	COOLING C				W -5	In 7.2+	LBP	134 a	C R5 MF 4
				k CAL/HR	B	T	U					
AZ A 1320 UN	2 , 5	$\frac{0}{4}$,	49	194	57				LBP	134 a	C R5 MF 4
AZ A 1327 UN	3 , 28	$\frac{0}{5}$,	63	249	73				LBP	134 a	C R5 MF 4
AZ A 1330 UN	3 , 69	$\frac{0}{5}$,	68	270	79				LBP	134 a	C R5 MF 4
AZ A 1335 UN	3 , 8	$\frac{0}{6}$,	71	280	82				LBP	134 a	C R5 MF 4
AZ A 1340 UN	4	$\frac{0}{7}$,	79	314	92				LBP	134 a	C R5 MF 4
AZ A 1350 UN	5	$\frac{0}{8}$,	94	372	109				LBP	134 a	C R5 MF 4
AZ A 1360 UN	5 , 59	$\frac{0}{5}$,	92	365	107				LBP	134 a	C R5 MF 4
AZ A 1370 UN	6	1		118	467	137				LBP	134 a	C R5 MF 4
AZ A 0413 UN	6	$\frac{1}{5}$,	183	727	213				LBP	134 a	
AZ A 4913 UN	6	$\frac{1}{6}$,	183	727	213				LBP	134 a	

AW 4495 YK	30	$\frac{3}{5}$	585	2320	680	MBP	134 a	C R5 MF20
AW 4513 YK	35 , 6	$\frac{3}{9}$	638	2532	742	MBP	134 a	C R5 MF30
AW 4514 YK	37 , 5	$\frac{3}{9}$	641	2542	745	MBP	134 a	C R5 MF35
AW 4515 YK	39 , 6	$\frac{4}{2}$	728	2890	847	MBP	134 a	C R5 MF35
AW 4517 YK	48 , 4	$\frac{4}{9}$	903	3582	1050	MBP	134 a	C R5 MF20

200
/
MODEL
220
/
50
HZ

COOLING C								
	IN	Displ.	CC R A	k CAL/HR	B T U	In -23	W -5	In 7.2+
L QD 25 HG	52	2 , 5	$\frac{0}{55}$	47	188	55		LBP 134 a
L / QD 30 HG	62	3	$\frac{0}{63}$	56	222	65		LBP 134 a
L / QD 35 HG	71	3 , 5	$\frac{0}{68}$	64	256	75		LBP 134 a
L / ADW 43	100	4 , 3	1	95	375	110		LBP 134 a
L / ADW 57	104	5 , 1	$\frac{1}{1}$	107	426	125		LBP 134 a
L / ADW 57	112	5 , 7	$\frac{1}{15}$	116	461	135		LBP 134 a
MS / ADW 43	100	4 , 3	1	95	375	110		LBP 134 a
MS / ADW 43	104	5 , 1	$\frac{1}{1}$	107	426	125		LBP 134 a
MS / ADW 57	112	5 , 7	$\frac{1}{15}$	116	461	135		LBP 134 a
MS / ADW 66	132	6 , 6	$\frac{1}{2}$	142	563	165		LBP 134 a
MS / ADW 77	148	7 , 7	$\frac{1}{4}$	159	631	185		LBP 134 a
MS / ADW 86	160	8 , 6	$\frac{1}{45}$	172	682	200		LBP 134 a
MS / ADW 91	176	9 , 1	$\frac{1}{65}$	189	751	220		LBP 134 a
MK / ADW 66	132	6 , 6	$\frac{1}{2}$	142	563	165		LBP 134 a
MK / ADW 77	148	7 , 7	$\frac{1}{4}$	159	631	185		LBP 134 a
MK / ADW 86	160	8 , 6	$\frac{1}{45}$	172	682	200		LBP 134 a

MK / ADW	91	176	9 , 1	$\frac{1}{65}$	189	751	220	LBP	134 a
MK ADW	110	215	11	$\frac{2}{05}$	232	921	270	LBP	134 a
WQ / ADW	91	176	9 , 1	$\frac{1}{65}$	189	751	220	LBP	134 a
WQ / ADW	110	215	11	$\frac{2}{05}$	232	921	270	LBP	134 a
WQ / ADW	128	256	12 , 8	$\frac{2}{3}$	275	1092	320	LBP	134 a C S M F 80
WQ / ADW	142	280	14 , 2	$\frac{2}{6}$	301	1194	350	LBP	134 a C S M F 81
WQ / AD W	153	304	15 , 3	$\frac{2}{8}$	327	1297	380	LBP	134 a C S M F 82

200
/
MODEL 220
/ 50
HZ

MODEL	IN	Displ.	CC R L A	COOLING				W -5 In 7.2+	LBP	134 a
				k	CAL/HR	B	T	U		
OF 605		3 , 4		77		307	90			
OF 700		3 , 9		86		341	100			
OF 789		3 , 9		95		375	110			
OF 1033 A		5 , 3		120		478	140			
OF 1350 A		7		155		614	180			

GVY 35 AA	3 , 4	69	273	80		LBP	134 a	CR MF 2
GVY 40 AA	4	94	372	109		LBP	134 a	CR MF 3
GVY 44 AA	4 , 4	112	444	130		LBP	134 a	CR MF 3
GVY 44 AG	4 , 4			132				
GVY 53 AA	5 , 3	120	478	140		LBP	134 a	CR MF 3
GVY 53 AG	5 , 3	119	471	138				
GVY 57 AA	5 , 7	138	546	160		LBP	134 a	CR MF 4
GVY 57 AG	5 , 7	132	525	154				
GVY 61 AA	6 , 1	146	580	170		LBP	134 a	CR MF 4
GVY 66 AA	6 , 6	163	648	190		LBP	134 a	CR MF 4

	7 , 5	177	703	206	LBP	134 a	CR 4	MF
GVY 75 AG	7 , 5	173	686	201				
GTH 86 AA	8 , 6	206	819	240	LBP	134 a	CR 5	MF
GTH 93 AA	9 , 3	224	887	260	LBP	134 a	CR 5	MF
GTT 66 AA	6 , 6	172	682	200	LBP	134 a	CR 4	MF
GTT 75 AA	7 , 5	181	716	210	LBP	134 a	CR 4	MF
GKD 86 AA	8 , 6	219	870	255	LBP	134 a	CR 6	MF
GKD 93 AA	9 , 3	232	921	270	LBP	134 a	CR 6	MF
MODEL	200 / 220 / 50 HZ							
			COOLING					
			C					
	IN	Displ.CC	R A L	k CAL/HR	B T U	In -23	W -5	In 7.2+
GML 70 A	2 , 8			58	232	68		LBP
GML 90 A	3 , 4			79	314	92		LBP
GML 110 A	4 , 1			97	386	113		LBP
GML 125 A	4 , 1			103	409	120		LBP
GML 140 A	4 , 9			120	478	140		LBP
GML 140 A/I	4 , 9			120	478	140		LBP
GML 160 A	5 , 7			138	546	160		
GML 180 A	6 , 5			155	614	180		LBP
GML 200 A	7			172	682	200		LBP
GML 200 A/I	7			181	716	210		LBP
GTM 26 AA	2 , 6				65			
GTM 75 AA	7 , 5				200			

GTM 93 AA	10		280
GTM 10 AA	10 , 6		300
GTM 12 AA	12		320

GDL160 A	5 , 7	144	570	167	LBP	134 a	CR MF 4
GDL200 A	6 , 5	142	563	165	LBP	134 a	CR MF 5
GXL100 A	4 , 1	91	362	106	LBP	134 a	CR MF 4
GXL125 A	4 , 3	106	420	123	LBP	134 a	CR MF 5
GXL140 A	4 , 6	119	471	138	LBP	134 a	CR MF 5
GXL160 A	5 , 7	138	546	160	LBP	134 a	CR MF 4
GXL 200 A	7	168	665	195	LBP	134 a	CR MF 5
GXL 240 A	8 , 6	206	819	240	LBP	134 a	CR MF 5

MODEL	200 / 220 / 50 HZ		COOLING							
	IN	Displ.CC	R A	L	k CAL/HR	B T U	In -23	W -5	In 7.2+	
GL 60 TP	5				464	1842			540	
GL 80 TP	8				636	2525			740	
GL 90 TP	9 , 3				739	2934		860	HBP	134 a CS MF 50
GL 90 TP/I	9 , 3				739	2934		860	HBP	134 a CS MF 50
GL 10 TP	9 , 3				757	3002		880	HBP	134 a CS MF 50
GL 12 TP	12				972	3855		1130	HBP	134 a CS MF 50
GHP 16 AA	16				1118	4435		1300	HBP	134 a CS MF 100
GHP 18 AA	18				1376	5459		1600	HBP	134 a CS MF 100
GHP 21 AA	21				1634	6483		1900	HBP	134 a CS MF 100
GTM 93 AA	10				241	955		280	HBP	134 a CS MF 50
GTM 10 AA	10 , 6				258	1024		300	HBP	134 a CS MF 50

GTM	12	AA	12	275	1092	320	HBP	134	a	CS	MF
										50	

200
/
MODEL 220
/ 50
HZ

COOLING
C

	IN	Displ.	CC	R	L	k	CAL/HR	B	T	U	In	W	-5	In		
				A							-23			7.2+		
S43C80KA						77		307		90					134	a
S48C95KA						90		358		105					134	a
D66C13RA						125		495		145					134	a
D77C15RA						155		614		180					134	a
D91C18RA						172		682		200					134	a

200
/
MODEL 220
/ 50
HZ

COOLING
C

	IN	Displ.	CC	R	L	k	CAL/HR	B	T	U	In	W	-5	In		
				A							-23			7.2+		
BP1046Z						40		157		46					134	a
BP1058Z						45		177		52					134	a
BP1072Z						57		225		66					134	a
BP1084Z						66		263		77					134	a
BP1111Z						81		321		94					134	a
B1112Z						88		348		102					134	a
B2112Z						88		348		102					134	a
B1116Z						117		464		136					134	a
B2116Z						117		464		136					134	a
B1118Z						131		519		152					134	a
B2118Z						131		519		152					134	a
E1121Z						165		655		192					134	a
BK1086Z						90		358		105					134	a
BK1112Z						96		382		112					134	a
BK1114Z						111		440		129					134	a
BK1116Z						132		525		154					134	a

200
/
MODEL 220
/ 50
HZ

COOLING
C

	IN	Displ.CC	R A	L	k	CAL/HR	B	T	U	In -23	W	-5	In 7.2+
ETR3					52		205		60			134	a
ETR3.5					64		256		75			134	a
ETR4					75		297		87			134	a
ESC5					92		365		107			134	a
ETR5					101		399		117			134	a
ETR5.5					112		444		130			134	a
ESC7					126		502		147			134	a
ESC8					148		587		172			134	a
ESC8.5					160		635		186			134	a
ESC9					176		699		205			134	a
ESC11					212		839		246			134	a



Private Picture Copyright : WWW.MBSM.PRO