

Mbsm.pro, Compressor, Embraco, Aspera, NEK6214Z, HBP, R134a, 220 – 240V/1/50Hz, 1/2 HP, CSIR, HBP, Big ++

Category: compressor

written by Lilianne | 7 February 2022



Private Picture Copyright: WWW.MBSM.PRO

Compressor Embraco Aspera NEK6214Z, HBP – R134a, 220 – 240V/1/50Hz, 1/2 HP, discharge 16.8 cm³, LRA 21.2 A, motor type CSIR, lubricant type POE 22, lubricant charge 350 ml, 1310 W at +5 / +54.4 °, expansion device: capillary or valve, cooling: fan cooling, weight 11.6 kg substitution for T6213Z.

Refrigerant:	R134a
Power range(W):	701 – 1000 W 1 – 1,5 kW
Performance range (C):	-15 C to +10 C
Working area:	HBP
Design type:	Hermetic
Model series:	NEK
Use with:	Expansion/Capillary
Power range(HP):	0-2
Power supply:	230 V
Oil type:	POE22
Engine type:	CSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	13,60 Kg
Dimensions (length × width × height):	24,20 × 17,80 × 20,60 cm
customs tariff number:	84143081
Cooling capacity condition:	T0 -25 C, Tk +55 C

Manufacturer:	Embraco Aspera
Model:	NEK6214Z
Stroke volume (cm ³):	16,8
Performance condition:	+5°C tk +54,4 °C
Power (W):	1310
Cooling capacity (W):	745
Power (HP):	0,5
Max. Starting current (A):	21,2
Engine type:	CSIR
Note:	Fan cooling necessary
Oil quantity (l):	0,35
Compressor type:	Piston
Power range:	-15 C to +10 C
Alternative:	T6213Z



Spécifications Techniques			
Réfrigérant	R-134a	Technologie de compresseur	Hermétique à piston
Application	Moyenne pression - Haute pression	Plage d'application	-15°C à +10°C
Type de tension	Monophasé	Tension	240 / 1 / 50
Cylindrée	16.8cm³	Puissance frigorifique @ -10°C	827W
Intensité maximale	4.3A	Type moteur	CSIR
Détente	Capillaire / Détendeur	Diamètre aspiration ODF	5/16"
Diamètre refoulement ODF	1/4"	Entraxes de fixation	170 x 70mm
Hauteur	206mm	Charge d'huile	0.35l



