

Mbsm.pro, PDF, File, Cubigel Katalog, r134a, Huayi, Electrolux, ZEM

Category: Files

written by Lilianne | 11 February 2022

R134a HMBP HBP 50 Hz										R134a compressors compatible with R12										
MODEL	DISPLACEMENT cm ³	POWER hp	APPLICATION	CPR COOLING	VOLTAGE FREQUENCY	MOTOR	STARTING	EXPANSION	REFRIGERATION CAPACITY °C										WEIGHT Kg	DESIGN
									COP in W/W 1 W = 0.864 kcal/h = 3,415 BTU/h Evaporating Temperature °C											
									Cecomat (W)					Ashrae						
									-25	-15	5	10	15	20	25	30	35	40		
GLY45RAa	4.56	1/6	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	71	139	373	1.85	452	385	2.25	9	Lb			
GLY45RAb	4.56	1/6	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	71	139	373	2.12	452	385	2.45	9	Lb			
GLY60RAa	5.98	1/5	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	106	191	486	2.08	586	500	2.36	9.9	Lc			
GLY60RAb	5.98	1/5	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	106	191	486	2.25	586	500	2.60	9.9	Lc			
GLY80RAa	8.10	1/5	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	159	275	681	2.17	819	700	2.50	10.4	Lc			
GLY80RAb	8.10	1/5	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	159	275	681	2.35	819	700	2.71	10.4	Lc			
GLY90RAa	9.09	1/4	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	169	298	748	2.06	901	770	2.37	10.5	Lc			
GLY90RAb	9.09	1/4	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	169	298	748	2.27	901	770	2.61	10.5	Lc			
GLY99RAa (**)	9.95	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	189	328	814	2.01	972	836	2.31	10.8	Ld			
GLY99RAb (**)	9.95	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	189	328	814	2.18	972	836	2.49	10.8	Ld			
GPY12RAa	12.10	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	228	401	993	2.05	1192	1020	2.35	12.6	Pd			
GPY12RAb	12.10	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	228	401	993	2.24	1192	1020	2.58	12.6	Pd			
GPY14RAa	14.32	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	296	492	1161	1.98	1386	1190	2.27	12.6	Pd			
GPY14RAb	14.32	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	296	492	1161	2.18	1386	1190	2.50	12.6	Pd			
GPY16RAa	16.15	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	315	522	1248	2.20	1490	1351	2.31	12.8	Pd			
GPY16RAb	16.15	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	315	522	1248	2.38	1490	1351	2.50	12.8	Pd			

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_Cubigel-KatalogTélécharger

R134a HMBP HBP 50 Hz										R134a compressors compatible with R12										
MODEL	DISPLACEMENT cm ³	POWER hp	APPLICATION	CPR COOLING	VOLTAGE FREQUENCY	MOTOR	STARTING	EXPANSION	REFRIGERATION CAPACITY °C										WEIGHT Kg	DESIGN
									COP in W/W 1 W = 0.864 kcal/h = 3,415 BTU/h Evaporating Temperature °C											
									Cecomat (W)					Ashrae						
									-25	-15	5	10	15	20	25	30	35	40		
GLY45RAa	4.56	1/6	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	71	139	373	1.85	452	385	2.25	9	Lb			
GLY45RAb	4.56	1/6	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	71	139	373	2.12	452	385	2.45	9	Lb			
GLY60RAa	5.98	1/5	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	106	191	486	2.08	586	500	2.36	9.9	Lc			
GLY60RAb	5.98	1/5	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	106	191	486	2.25	586	500	2.60	9.9	Lc			
GLY80RAa	8.10	1/5	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	159	275	681	2.17	819	700	2.50	10.4	Lc			
GLY80RAb	8.10	1/5	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	159	275	681	2.35	819	700	2.71	10.4	Lc			
GLY90RAa	9.09	1/4	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	169	298	748	2.06	901	770	2.37	10.5	Lc			
GLY90RAb	9.09	1/4	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	169	298	748	2.27	901	770	2.61	10.5	Lc			
GLY99RAa (**)	9.95	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	189	328	814	2.01	972	836	2.31	10.8	Ld			
GLY99RAb (**)	9.95	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	189	328	814	2.18	972	836	2.49	10.8	Ld			
GPY12RAa	12.10	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	228	401	993	2.05	1192	1020	2.35	12.6	Pd			
GPY12RAb	12.10	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	228	401	993	2.24	1192	1020	2.58	12.6	Pd			
GPY14RAa	14.32	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	296	492	1161	1.98	1386	1190	2.27	12.6	Pd			
GPY14RAb	14.32	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	296	492	1161	2.18	1386	1190	2.50	12.6	Pd			
GPY16RAa	16.15	3/8	HMBP	F	220-240V 50Hz -1	CSIR	R	C-V	315	522	1248	2.20	1490	1351	2.31	12.8	Pd			
GPY16RAb	16.15	3/8	HMBP	F	220-240V 50Hz -1	CSR	R	C-V	315	522	1248	2.38	1490	1351	2.50	12.8	Pd			

Private Picture Copyright : WWW.MBSM.PRO