

Mbsm.pro, compressor, MT160HW4D , 13
hp, MT160, Displacement:
271.55cm³/rev

Category: pro

written by Lilianne | 30 August 2022



Danfoss Commercial Compressors

Danfoss

Model no: MT160HW4EVE

Serial no: EF1007049041

MADE IN FRANCE

380-400V 3- 50 Hz
460V 3- 60 Hz

LR 130A 36A MAX

THERMALLY PROTECTED

P.E.D.

Marking	LP side	HP side
PS	18.4 bar	27.8 bar
TS max	50 °C	68 °C
TS min	-35 °C	-35 °C
Volume	31 l	

Lubricant: MINERAL OIL 160 P

CE EAC

Refrigerant: R22(ULrating)-R417A with 160P2

WARNING

CAUTION

Waneurop

Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V, 3PH

Danfoss Commercial Compressors

Danfoss

Model no: MT160HW4EVE



Serial no: EF1007049041



MADE IN FRANCE
 380-400V 3~ 50 Hz UL electrical rating
 460V 3~ 60 Hz
 LR 130A 36A MAX
 THERMALLY PROTECTED
 P.E.D.
 Marking LP side HP side
 PS 18.4 bar 27.8 bar
 TS max 50 °C 68 °C
 TS min -35 °C -35 °C
 Volume 31 l 1.2 l

Lubricant: MINERAL OIL 160 P

CE EAC

Refrigerant: R22(ULrating)-R417A with 160P2

Maneurop
 REFRIGERATING COMPRESSION



WARNING

Installation and servicing shall be performed by trained personnel under strict supervision of those with a working knowledge of current safety practices. Use only authorized Danfoss tools, service manuals and components. Do not use any unauthorized parts or accessories. Do not use any unauthorized parts or accessories. Do not use any unauthorized parts or accessories.



CAUTION

Use only Danfoss tools, approved refrigerants, lubricants and electrical components. Use incorrect refrigerant / lubricant / electrical components could void warranty, cause damage, create a safety hazard. Do not use any unauthorized parts or accessories.

Danfoss Commercial Compressors



Model no: MT160HW4EVE

Serial no: EF1007049041



MADE IN FRANCE
380-400V 3~ 50 Hz
460V 3~ 60 Hz
LR 130A 36A MAX
THERMALLY PROTECTED
P.E.D.
Marking LP side HP side
PS 18.4 bar 27.8 bar
TS max 50 °C 68 °C
TS min -35 °C -35 °C
Volume 3 l 1.2 l

UL electrical ratings



Refrigerant: R22 (UL rating) - R417A with 160PZ

Lubricant: MINERAL OIL 160 P



WARNING

Installation and servicing shall be performed by trained personnel only. Failure to observe these safety warnings could result in personal injury or death.
Always disconnect power to the compressor before servicing. Do not attempt to service or repair the compressor until the power is disconnected.
Always wear safety glasses and safety footwear when servicing the compressor.
Always use proper lifting techniques when lifting or moving the compressor. Do not lift or move the compressor by the top or side rails.
Always use proper lifting techniques when servicing the compressor.
Always use proper lifting techniques when servicing the compressor.



Maneurop

CAUTION

Use only manufacturer's approved refrigerants, lubricants and electrical components. Use of other refrigerant / lubricant / electrical component could cause fire, explosion, electrical shorting.

For details, refer to safety literature, instructions and technical documentation available on Danfoss website at <http://www.danfoss.com>