

AC 220-240V/ 50Hz	MSA141Q-S1A		122	416	1.27	0.67	96	Static	PTC-RSIR
	MSA143Q-S1Z	Refrigerator	112	381	1.34	0.69	83	Static	PTC-RSIR
	SD151Q-L1UB	Compressor	140	478	1.27	0.52	110	Static	RSCR
	SD162Q-L1UA	R134a LBP	170	580	1.36	0.59	125	Static	PTC-RSCR
AC 200-220V/ 50Hz or 220V/ 60Hz	MSA170Q-L1B		201	686	1.56	0.63	129	Static	RSCR
	SD152H-S1UB	Refrigerator	134	457	1.17	0.66	114	Static	RSCR
	SD162H-L1UB	Compressor	170	580	1.22	0.82	139	Static	PTC-RSCR
	MSA170H-L1B	R134a LBP	201	686	1.43	0.87	141	Static	RSCR

R134a LBP

RATED VOLTAGE	MODEL	MOTOR TYPE	VOLTAGE [V-Hz]	ASHRAE							COOLING TYPE	
				COOLING CAPACITY			INPUT	EFFICIENCY				
				Kcal/Hr	Watt	BTU/Hr		W	EFF	COP		EER
AC 127V-60Hz	CD124P-L1Z2	RSIR	127-60	52	60	206	68	0.76	0.89	3.04	ST	
	CD124P-S1ZB	RSIR	127-60	52	60	206	74	0.70	0.82	2.79	ST	
	CD130P-L1Z2	RSIR	127-60	70	81	278	76	0.92	1.07	3.66	ST	
	CD130P-S1ZB	RSIR	127-60	70	81	278	76	0.92	1.07	3.66	ST	
	SD152P-L1W2	CSR	127-60	135	157	536	122	1.11	1.29	4.39	ST	
	MK152P-S1U	RSCR	127-60	148	172	588	108	1.37	1.59	5.44	ST	
	SD162P-L1U2	RSCR	127-60	170	198	675	147	1.16	1.34	4.59	ST	
	MD162P-S1U2	RSCR	127-60	187	217	742	144	1.30	1.51	5.16	ST	
	MSA162P-S1B	RSCR	127-60	187	217	742	147	1.27	1.48	5.05	ST	
	MK162P-S1UA	RSCR	127-60	184	214	730	134	1.37	1.60	5.45	ST	
	MK172P-L2U	RSCR	127-60	224	260	889	159	1.41	1.64	5.59	FC	
	SK182P-L2U	RSCR	127-60	239	278	949	201	1.19	1.38	4.72	FC	
	MK183P-S2U	RSCR	127-60	263	306	1,044	190	1.38	1.61	5.50	FC	
	AC 200-220V-50Hz, 220V-60Hz	CD124H-L1Z2	RSIR	220-50	43	50	171	63	0.68	0.79	2.71	ST
				220-60	52	60	206	64	0.81	0.94	3.23	
CD124H-L1ZA		RSIR	220-50	42	49	167	71	0.59	0.69	2.35	ST	
			220-60	50	58	199	71	0.70	0.82	2.80		
CD130H-L1Z2		RSIR	220-50	58	67	230	73	0.79	0.92	3.15	ST	
			220-60	70	81	278	76	0.92	1.07	3.66		
SD137H-L1ZB		RSIR	220-50	75	87	298	93	0.81	0.94	3.20	ST	
			220-60	93	108	369	98	0.95	1.10	3.77		
SD137H-L1UB		RSCR	220-50	75	87	298	87	0.86	1.00	3.42	ST	
			220-60	93	108	369	92	1.01	1.18	4.01		
			220-50	90	105	357	84	1.07	1.25	4.25		
NC1A37HLB		RSCR	220-60	108	126	429	97	1.11	1.29	4.42	ST	
SD143H-L1UA		RSCR	220-50	98	114	389	109	0.90	1.05	3.57	ST	
			220-60	118	137	468	114	1.04	1.20	4.11		
NC1A43HLB		RSCR	220-50	102	119	405	91	1.12	1.30	4.45	ST	
			220-60	118	137	468	100	1.18	1.37	4.68		
SD152H-S1UB		RSCR	220-50	120	140	476	113	1.06	1.23	4.21	ST	
			220-60	146	170	580	122	1.20	1.39	4.75		
SD162H-L1UB		RSCR	220-50	146	170	580	139	1.05	1.22	4.17	ST	
			220-60	182	212	723	152	1.20	1.39	4.75		
SK170H-L1UB		RSCR	220-50	168	195	667	153	1.10	1.28	4.36	ST	
			220-60	206	240	818	164	1.26	1.46	4.99		
MSA170H-L1B		RSCR	220-50	173	201	687	141	1.23	1.43	4.87	ST	
			220-60	220	256	873	163	1.35	1.57	5.36		
MK172H-L1U		RSCR	220-50	176	205	699	131	1.34	1.56	5.33	ST/OC	
			220-60	224	260	889	159	1.41	1.64	5.59		
MK172H-L1UB		RSCR	220-50	176	205	699	135	1.30	1.52	5.18	ST/OC	

R134a LBP

RATED VOLTAGE	MODEL	MOTOR TYPE	VOLTAGE [V-Hz]	ASHRAE			
				COOLING CAPACITY			INPUT
				Kcal/Hr	Watt	BTU/Hr	
AC 200-220V-50Hz, 220V-60Hz	MK183H-L2UB	RSCR	220-50	203	236	806	154
			220-60	258	300	1,024	179
	SK190H-S2U	RSCR	220-50	227	264	901	233
			220-60	264	307	1,048	229
	SK190H-L2UA	RSCR	220-50	227	264	901	208
			220-60	264	307	1,048	211
AC 220V-60Hz	MK190H-L2U2	RSCR	220-50	225	262	893	168
			220-60	285	331	1,131	200
	CD124B-L1ZA	RSIR	220-60	50	58	199	72
	CD130B-S1ZA	RSIR	220-60	70	81	278	82
	CD130B-S1ZB	RSIR	220-60	70	81	278	82
	NC1A37BLA	RSIR	220-60	108	126	429	103
	MSE148B-L1U	PTC-RSCR	220-60	155	180	615	100
	MD152B-L1UA	RSCR	220-60	148	172	588	122
	MD152B-L1UB	RSCR	220-60	131	152	520	117
	MSE156B-L1U	PTC-RSCR	220-60	188	219	746	121
	MD162B-L1U2	RSCR	220-60	160	186	635	136
	MSE166B-L1U	PTC-RSCR	220-60	225	262	893	145
	SK162B-L1UA	RSCR	220-60	170	198	675	141
	MK162B-L1UB	RSCR	220-60	184	214	730	134
	SK170B-L2W	CSR	220-60	206	240	818	165
MK172B-L2UA	RSCR	220-60	224	260	889	159	
MK172B-L2UB	RSCR	220-60	224	260	889	159	
SK182B-L2W	CSR	220-60	239	278	949	186	
MK183B-L2U	RSCR	220-60	258	300	1,024	179	
SK190B-L2W	CSR	220-60	264	307	1,048	206	
MK190B-S2WA	CSR	220-60	285	331	1,131	200	
DK1A3B-L2WA	CSR	220-60	385	448	1,528	335	
SK1A1B-L2W	CSR	220-60	303	352	1,203	263	
SK1A1B-L2WB	CSR	220-60	330	384	1,310	283	
AC 220-240V-50Hz, 220V-60Hz			220-50	68	79	270	71
	NC1A30GLA	RSIR	220-60	80	93	318	77
	MSS151G-L1U	RSCR	220-50	125	145	496	90
			220-60	152	177	603	107
	MSA151G-L1B	RSCR	220-50	125	145	496	96
			220-60	152	177	603	114
	MSA162G-L1B	RSCR	220-50	151	176	599	119
			220-60	187	217	742	140
	MSS170G-L1U	RSCR	220-50	178	207	707	124
			220-60	222	258	881	151



RATED VOLTAGE	MODEL	MOTOR TYPE	VOLTAGE [V-Hz]	ASHRAE							COOLING TYPE	
				COOLING CAPACITY			POWER INPUT	EFFICIENCY				
				Kcal/Hr	Watt	BTU/Hr	W	EFF	COP	EER		
AC 115V-60Hz	MK183C-S2U	RSCR	115-60	258	300	1024	187	1.38	1.60	5.48	FC	
	SK1A1C-L2W	CSR	115-60	303	352	1203	275	1.10	1.28	4.37	FC	
	SK1A1C-L2WB	CSR	115-60	312	363	1239	290	1.08	1.25	4.27	FC	
AC 115-127V-60Hz	MSS143D-S1U	RSCR	115-60	118	135	481	85	1.38	1.59	5.42	ST	
			127-60	118	135	481	92	1.26	1.47	5.01	ST	
	MSA151D-L1B	RSCR	115-60	152	177	603	113	1.35	1.56	5.34	ST	
			127-60	152	177	603	120	1.27	1.47	5.03	ST	
	MSS162D-S1U	RSCR	115-60	187	217	742	135	1.39	1.61	5.50	ST	
			127-60	187	217	742	142	1.32	1.53	5.23	ST	
	MSA162D-L1B	RSCR	115-60	187	217	742	145	1.29	1.50	5.12	ST	
			127-60	187	217	742	150	1.25	1.45	4.95	ST	
	MK162D-L1U	RSCR	115-60	184	214	730	124	1.48	1.73	5.89	ST	
			127-60	184	214	730	126	1.48	1.70	5.80	ST	
	MK162D-S2UB	RSCR	115-60	184	214	730	135	1.36	1.58	5.41	FC	
			127-60	184	214	730	142	1.30	1.51	5.14	FC	
	MK172D-R2U	RSCR	115-60	224	260	889	149	1.50	1.75	5.97	FC	
			127-60	224	260	889	152	1.47	1.71	5.85	FC	
	MK183D-L2U	RSCR	115-60	258	300	1024	179	1.44	1.68	5.72	FC	
127-60			258	300	1024	182	1.42	1.65	5.63	FC		
MK183D-L2UB	RSCR	115-60	258	300	1024	185	1.39	1.62	5.54	FC		
		127-60	258	300	1024	194	1.33	1.55	5.28	FC		
AC 127V-60Hz	CD124P-L1Z2	RSIR	127-60	52	60	206	68	0.78	0.89	3.04	ST	
	CD124P-S1ZB	RSIR	127-60	52	60	206	74	0.70	0.82	2.79	ST	
	CD130P-L1Z2	RSIR	127-60	70	81	278	76	0.92	1.07	3.88	ST	
	CD130P-S1ZB	RSIR	127-60	70	81	278	92	0.76	0.88	3.02	ST	
	SD152P-L1W2	CSR	127-60	135	157	536	122	1.11	1.29	4.39	ST	
	MK162P-S1U	RSCR	127-60	148	172	588	108	1.37	1.59	5.44	ST	
	SD162P-L1U2	RSCR	127-60	170	198	675	147	1.16	1.34	4.59	ST	
	MD162P-S1U2	RSCR	127-60	187	217	742	144	1.30	1.51	5.16	ST	
	MSA162P-S1B	RSCR	127-60	187	217	742	147	1.27	1.48	5.05	ST	
	MK162P-S1UA	RSCR	127-60	184	214	730	134	1.37	1.60	5.45	ST	
	MK172P-L2U	RSCR	127-60	224	260	889	159	1.41	1.64	5.59	FC	
	SK162P-L2U	RSCR	127-60	239	278	949	201	1.19	1.38	4.72	FC	
	MK183P-S2U	RSCR	127-60	263	306	1044	190	1.38	1.61	5.50	FC	
	AC 200-220V-50Hz, 220V-60Hz	CD124H-L1Z2	RSIR	220-50	43	50	171	63	0.68	0.79	2.71	ST
				220-60	52	60	206	64	0.81	0.94	3.23	ST
CD124H-L1ZA		RSIR	220-50	42	49	167	71	0.59	0.69	2.35	ST	
			220-60	50	58	199	71	0.70	0.82	2.80	ST	
CD130H-L1Z2		RSIR	220-50	58	67	230	73	0.79	0.92	3.15	ST	
			220-60	70	81	278	76	0.92	1.07	3.88	ST	
SD137H-L1ZB		RSIR	220-50	75	87	298	93	0.81	0.94	3.20	ST	
			220-60	93	108	369	98	0.95	1.10	3.77	ST	
SD137H-L1UB		RSCR	220-50	75	87	298	87	0.86	1.00	3.42	ST	
			220-60	93	108	369	92	1.01	1.18	4.01	ST	
SD143H-L1UA		RSCR	220-50	98	114	389	109	0.90	1.05	3.57	ST	
			220-60	118	137	488	114	1.04	1.20	4.11	ST	
SD143H-S1UB	RSCR	220-50	120	140	476	113	1.06	1.23	4.21	ST		

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_SD152H-S1UBTélécharger