

Mbsm.pro, Compressor, PA65H1E,
PA65H1E-4, r290, 1/6 hp++, mhbp, 1/5
hp, MIDEA, freezer, HORIZONTAL, 203
LITRES, MIDEA_HS-268C, HS-268C, 203 L

Category: compressor

written by Lilianne | 4 February 2024



Private Picture Copyright : WWW.MBSM.PRO

DESCRIPTION

- Capacity: 203 Liters
- Shipping name: 1
- Climate class: T
- Adjustable thermostat
- Tension : 230 V
- Frequency: 50 Hz
- Dimensions (L x H x P): 905*608*847 mm
- REFRIGERANT : R290A
- ENERGY COMSUMPTION((KW·H/J) : 3
- COMPRESSOR: PA65H1E□4MF□
- FREEZING CAPACITY (KG/24H): 32KG/24H



Private Picture Copyright : WWW.MBSM.PRO

PRODUCT PERFORMANCE AND PARAMETERS

Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Power frequency	ASHRAE (-23.3 / 54.4 / 32.2 °C)					Certification	Motor Description	Shell height (mm)
						Cooling Capacity			COP				
						W	kcal/h	Btu/h	WW	Btu/Wh			

R290 LBP FIXED SPEED

220V-240V/50Hz													
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Power frequency	ASHRAE (-23.3 / 54.4 / 32.2 °C)					Certification	Motor Description	Shell height (mm)
						W	kcal/h	Btu/h	WW	Btu/Wh			
H	PA50H1E	5.0	ST	RSCR	220V/50Hz	240	206	818	1.55	5.29	-	AI	178
	PA50H1B	5.0	ST	RSCR	220V/50Hz	240	206	818	1.70	5.80	-	Cu	178
	PA59H1B	5.9	FC	RSCR	220V/50Hz	290	249	989	1.70	5.80	-	Cu	178

R290 LBP FIXED SPEED

220V-240V/60Hz													
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Power frequency	ASHRAE (-23.3 / 54.4 / 32.2 °C)					Certification	Motor Description	Shell height (mm)
						W	kcal/h	Btu/h	WW	Btu/Wh			
AL	AL1228-RA	2.8	ST	CSR	220V/60Hz	147	126	501	1.38	4.64	-	Cu	196
	AL1739-RA	3.9	ST	CSR	220V/60Hz	211	181	720	1.41	4.81	-	Cu	196

R290 LBP FIXED SPEED

220V-240V/50-60Hz													
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Power frequency	ASHRAE (-23.3 / 54.4 / 32.2 °C)					Certification	Motor Description	Shell height (mm)
						W	kcal/h	Btu/h	WW	Btu/Wh			
AL	AL2252-SZA	5.2	ST	CSR	220-240V/50Hz	250	215	853	1.52	5.19	-	AI	186
					220-240V/60Hz	287	247	979	1.52	5.19	-	-	-
	AL3058-SZA	6.8	ST	CSR	220-240V/50Hz	320	275	1091	1.48	4.96	-	AI	200
					220-240V/60Hz	376	323	1279	1.50	5.12	-	-	-
AL4089-SZA	8.83	ST	CSR	220-240V/50Hz	400	344	1364	1.45	4.95	-	AI	216	
				220-240V/60Hz	480	413	1637	1.48	5.05	-	-	-	

Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Application	Cooling Capacity												Certification	Motor Description	Shell height (mm)
						Rating point -23.3C/54.4C	Ashrae (W) cooling capacity													
							W	W	W	W	W	W	W	W	W	W	W			

R290 L/MBP Light Commercial

220V-240V/50Hz																						
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Application	Rating point -23.3C/54.4C	Ashrae (W) cooling capacity											Certification	Motor Description	Shell height (mm)		
							W	W	W	W	W	W	W	W	W	W	W				W	
H	PA85H1C	6.5	FC	RSCR	LBP	324	1,02	135	190	233	300	372	463	-	-	-	-	CCC	AI	178		
	PA85H1B	6.5	FC	RSCR	LBP	324	1,70	135	190	233	300	372	463	-	-	-	-	-	Cu	178		
	PA70H1E	7.0	FC	RSCR	LBP	340	1,85	142	199	245	315	391	486	-	-	-	-	-	AI	178		
	SA75H1J	7.5	FC	RSCR	LBP	370	1,30	154	206	266	343	425	529	-	-	-	-	-	-	AI	178	
	PA80H1C	8.0	FC	RSCR	LBP	395	1,53	165	219	284	366	454	564	-	-	-	-	-	CCC/CB	AI	178	
	PA80H1E	9.0	FC	RSCR	LBP	455	1,50	185	247	320	421	523	650	-	-	-	-	-	-	Cu	178	
	PA45H1A	4.5	FC	CSR	LMBP	205	1,50	85	114	147	190	238	293	360	446	539	-	-	-	AI	178	
	PA50H1A	5.0	FC	CSR	LMBP	245	1,50	102	136	176	227	282	350	430	533	645	-	-	-	Cu	178	
	PA59H1A	5.9	FC	CSR	LMBP	295	1,50	110	148	185	255	320	405	480	590	720	-	-	-	CCC/TUV	AI	178
	PA65H1A	6.5	FC	CSR	LMBP	323	1,50	126	163	209	293	370	458	546	693	866	-	-	-	-	AI	178
	PA80H1A	8.0	FC	CSR	MBP	395	1,50	-	-	-	449	544	655	802	901	-	-	-	-	TUV	Cu	178
	PA90H1A	9.0	FC	CSR	MBP	445	1,50	-	-	-	490	614	718	866	1018	-	-	-	-	TUV	Cu	178
	PA99H1A	9.9	FC	CSR	MBP	475	1,50	-	-	-	535	618	753	892	1065	-	-	-	-	TUV	Cu	178

R290 L/MBP Light Commercial

220V-240V / 50/60Hz																				
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Application	Rating point -23.3C/54.4C	Ashrae (W) cooling capacity											Certification	Motor Description	Shell height (mm)
							W	W	W	W	W	W	W	W	W	W	W			
H	PA65H1E-4	6.5	FC	RSCR	LBP	324	1,55	135	180	233	300	372	-	-	-	-	-	-	Cu	178

R290 L/MBP Light Commercial

115V / 60Hz																					
Series	Model	Displace (cm ³)	Coiling Type	Motor Type	Application	Rating point -23.3C/54.4C	Ashrae (W) cooling capacity											Certification	Motor Description	Shell height (mm)	
							W	W	W	W	W	W	W	W	W	W	W				W
EA	EA59H1D	5.9	FC	RSCR	LBP	330	1,80	138	183	237	306	379	471	579	717	868	-	-	-	AI	178
	EA59H1A	5.9	FC	RSCR	LBP	330	1,76	138	183	237	306	379	471	579	717	868	-	-	-	Cu	178
	EA85H1E	6.5	FC	RSCR	LBP	370	1,55	154	206	266	343	425	529	649	804	974	-	-	-	-	AI

Private Picture Copyright : WWW.MBSM.PRO

