

Mbsm.pro, Compressor, ASF852HG, ROHS, 850 w, R134a, 1/4 hp++, 1/3 hp-, Hbp, relative, Aspera NEK6170Z

Category: compressor

written by Lilianne | 11 March 2024



Compressor / Compressor ASF852HG HBP – R134a 208 – 230 V, 1Ph, 50 Hz.

Type of engine: CSIR.

displacement: 8.4 cm³.

Temperature range: HBP.

Suction pipe connection size: 8.10 mm.

Connection size pressure line: 6.10 mm. Weight: 10.4 kg.

Maximum height: 187.0 mm.

Power: 1/4 + hp. Efficiency: 2.07kcal / Wh.

Oil Type: IS022.

Oil quantity: 350ml.

Starting torque: HST.

Compressor type:

Reciprocating piston

Cooling capacity (W):

850

Design:

Hermetic

Dimensions (length × width × height): 24.20 × 17.80 × 20.00 cm

Displacement (cm³):

8,39

Engine type:	CSIR
Info:	Oil prefilled
Manufacturer:	
Max. Starting current (A):	12,4
Model series:	ROHS
Oil quantity (l):	0,35
Oil type:	ISO22, POE22
Power range (W):	852 w
Power range (hp):	0-2
Power supply:	400 V
Rated power (hp):	0.25++/0.3-
Refrigerant:	R134a
Scope of application:	HBP
Start-up torque:	Start-up torque
To be used with:	Capillary/Expansion
Type / Series:	ASF852HG
Voltage:	230V/50Hz

