

**HuaJun , QD30 , Compressor, 90W  
 , R12 , 0.82 LRA , 220V 50Hz  
 , 1/8HP**

written by Lilianne | 21 May 2020

HuaJun , QD30 , Compressor, 90W , R12 , 0.82 LRA , 220V 50H ,  
1/8HP

---

**JX51LCS5-K , Compresseur,  
hermétique Daewoo , 5.12 cc ,  
R12 , 220-240V 60Hz , RSIR ,  
1/6 Hp , 1Phase , L B P ,  
134w**

written by Lilianne | 21 May 2020

JX51LCS5-K , Compresseur, hermétique Daewoo , 5.12 cc , R12 ,  
220-240V 60Hz , RSIR , 1/6 Hp , 1Phase , L B P , 134w

---

**Tecumseh , Compressor Az1355D,**

# **1/6Hp , R12 ,réfrigérateur**

written by Lilianne | 21 May 2020

Tecumseh ,Compressor Az1355D, 1/6Hp , R12 ,réfrigérateur

---

# **NSA43LAEG ,P220MC ,4TM166RFB ,102 Watts ,1/8HP , R12 , 1 Phase**

written by Lilianne | 21 May 2020

NSA43LAEG ,P220MC ,4TM166RFB ,102 Watts ,1/8HP , R12 , 1 Phase

---

# **AES45D , huayi compressor co.ltd , 1/8+Hp(Big , Hbp ,Pression) ,R12**

written by Lilianne | 21 May 2020

AES45D , huayi compressor co.ltd , 1/8+Hp(Big , Hbp ,Pression)  
,R12

---

**LG ,NR52AEG ,1/5Hp , R12 ,  
220v 50Hz , 1 Phase**

written by Lilianne | 21 May 2020

LG ,NR52AEG ,1/5Hp , R12 , 220v 50Hz , 1 Phase

---

**Em40Hnp, Embraco Compressor,  
Aspera ,R134A 240V 50hz , 1/8  
Hp , 1 Phase**

written by Lilianne | 21 May 2020

Em40Hnp, Embraco Compressor, Aspera ,R134A 240V 50hz , 1/8 Hp  
, 1 Phase

---

**Compresseur zel, HML170A ,  
r600a ,LBP, 1/6hp  
,9.5cm<sup>3</sup>,170W**

written by Lilianne | 21 May 2020

Compresseur zel, HML170A , r600a ,LBP, 1/6hp ,9.5cm<sup>3</sup>,170W

---

# **Tecumseh compressor model AE4448YS,refrigeration compressor (AVEC Condensateur), R134a , Lra 19.5A , 220 V 50Hz , 3/8 H ,CSIR , Medium/High Back Pressure**

written by Lilianne | 21 May 2020

Tecumseh compressor model AE4448YS,refrigeration compressor ,  
R134a , Lra 19.5A , 220 V 50Hz , 3/8 H ,CSIR , Medium/High  
Back Pressure

---

## **REFRIGERATION APPLICATION CHART (R12 AND R22)**

written by Lilianne | 21 May 2020

REFRIGERATION APPLICATION CHART (R12 AND R22)

## REFRIGERATION APPLICATION CHART (R-12 AND R-22)\*

H.P.	REF.	NOTE	NORMAL EVAPORTING TEMPERATURE DEGREES F							
			-10 to +5		+5 to +20		+20 to +35		+35 to +50	
1/20	R12	S-F	16 Ft.	TC-26	10 Ft.	TC-26				
1/12	R12	S-F	12 Ft.	TC-26	12 Ft.	TC-31				
1/9	R12	S	12 Ft.	TC-26	12 Ft.	TC-31				
1/9	R12	S	10 Ft.	TC-26	10 Ft.	TC-31				
1/8	R12	S-F	10 Ft.	TC-26	10 Ft.	TC-31				
1/6	R12	S	12 Ft.	TC-31	12 Ft.	TC-36	8 Ft.	TC-36	10 Ft.	TC-42
1/6	R12	F	10 Ft.	TC-31	10 Ft.	TC-36				
1/5	R12	S	10 Ft.	TC-31	10 Ft.	TC-36	7-1/2 Ft.	TC-42	7-1/2 Ft.	TC-49
1/5	R12	F	8 Ft.	TC-31	8 Ft.	TC-36	10 Ft.	TC-42	6 Ft.	TC-42
1/4	R22	S-F	12 Ft.	TC-36	6 Ft.	TC-36	8-1/2 Ft.	TC-42	6 Ft.	TC-49
1/4	R12	F	10 Ft.	TC-36	6 Ft.	TC-36	8 Ft.	TC-42	6 Ft.	TC-49
1/3	R22	F	10 Ft.	TC-36	6 Ft.	TC-36	11 Ft.	TC-49		
1/3	R12	F	12 Ft.	TC-42	6 Ft.	TC-42	9 Ft.	TC-49	6 Ft.	TC-54
1/2	R22	F	6 Ft.	TC-36	9 Ft.	TC-42	7-1/2 Ft.	TC-54	10 Ft.	TC-64
1/2	R12	F	11 Ft.	TC-54	9 Ft.	TC-49				
3/4	R22	F	11 Ft.	TC-54	9 Ft.	TC-54				
3/4	R12	F	7-1/2 Ft.	TC-54	12 Ft.	TC-70	1 Ft.	TC-80		
1	R22	F	10 Ft.	TC-64	12 Ft.	TC-70				
1	R12	F	10 Ft.	TC-70	11 Ft.	TC-54	7-1/2 Ft.	TC-54 (2 pcs)		
1-1/2	R22	F	7-1/2 Ft.	TC-54 (2 pcs)	7-1/2 Ft.	TC-54 (2 pcs)	8 Ft.	TC-64 (2 pcs)		
1-1/2	R12	F			9 Ft.	TC-64 (2 pcs)	10 Ft.	TC-80 (2 pcs)		
2	R22	F			10 Ft.	TC-70 (2 pcs)	9 Ft.	TC-75 (2 pcs)		
2	R12	F	10 Ft.	TC-70 (2 pcs)	9 Ft.	TC-75 (2 pcs)	10 Ft.	TC-85 (2 pcs)		
3	R22	F			10 Ft.	TC-70 (3 pcs)	9 Ft.	TC-75 (3 pcs)		
3	R12	F	10 Ft.	TC-70 (2 pcs)	8 Ft.	TC-64 (4 pcs)	10 Ft.	TC-80 (4 pcs)		
4	R22	F			10 Ft.	TC-70 (4 pcs)	9 Ft.	TC-75 (4 pcs)		
4	R12	F			10 Ft.	TC-70 (5 pcs)	9 Ft.	TC-75 (5 pcs)		
5	R12	F			10 Ft.	TC-80 (5 pcs)	9 Ft.	TC-85 (5 pcs)		

NOTE: Condenser Type: S = Static, F = FAN

\*R-134a - It is suggested to add 10% to length.