

Mbsm.pro, LG, Compressor, BMA098NAMV,
1/4 hp, Series: BMA, BLDC, 9.8 cc,
R600a, 240V 60-225Hz, Inverter, 667
btu, 195 w

Category: compressor

written by Lilianne | 18 September 2022



USE ONLY S
WITH
AV03 - E01


 **LG** P




WARNING: Permanent
will occur if compon
directly connected

BMA098NAMV

240V - 60 - 225Hz LRA2.2 3PH



THERMALLY PROTECTED / PROTECTION THERMIQUE
LG Electronics Inc. MADE IN KOREA



ISEL220144290915

R600

Mbsm.pro, LG, Compressor, BMA098NAMV, 1/4 hp, Series: BMA, BLDC, 9.8 cc, R600a, 240V 60-225Hz, Inverter, 667 btu
#BMA098NAMV

Variable Speed R600a [2 of 4]

Application : LBP

Refrigerant	Series	Model	Motor type	Voltage V	Frequency Hz	Test condition	Speed range RPM	Performance					Dimension Height mm	
								Capacity		EER	COP			
								RPM	Kcal/hr	Btu/Wh	Watts	Btu/Wh		WW
R600a	BMA	BMA098NAMV	BLDC	220-240	50 / 60	System -26°C / 38°C	1,200	3,900	168	667	195	-	-	172
							-4,500	2,400	116	461	135	782	229	
	BMA121NAMV	BLDC	220-240	50 / 60	System -26°C / 38°C	1,200	2,400	149	591	173	771	226	172	
						-4,500	1,800	110	438	128	780	228		
	BMG	BMG089NAMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	191	758	222	624	183	139
							-4,500	3,000	133	529	155	632	185	
		BMG089NCMV	BLDC	100-115	50 / 60	Te/Tc -23.3°C / 38°C	1,020	4,500	202	802	235	700	205	139
							-4,500	1,620	79	314	92	785	230	
		BMG089NHMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	191	758	222	624	183	139
							-4,500	3,000	133	529	155	632	185	
		BMG110NAMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	235	932	262	574	182	139
							-4,500	3,000	175	693	200	642	189	
BMG110NHMV		BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	235	932	262	574	182	139	
						-4,500	3,000	175	693	200	642	189		

Application : LBP

Refrigerant	Series	Model	Motor type	Voltage V	Frequency Hz	Test condition	Speed range RPM	Performance					Dimension Height mm	
								Capacity		EER	COP			
								RPM	Kcal/hr	Btu/Wh	Watts	Btu/Wh		WW
R600a	BMH	BMH089NAMV	BLDC	100-115	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	194	772	226	608	178	139
							-4,500	3,000	142	565	166	669	196	
	BMH089NBMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,200	4,500	239	949	278	608	178	139	
						-4,500	1,800	108	427	125	676	198		
	BMH089NCMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,020	4,500	194	768	225	626	183	139	
						-4,500	3,000	141	558	163	666	195		
	BMH089NHMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,020	4,500	239	949	278	595	174	139	
						-4,500	1,800	108	427	125	674	197		
	BMH110NAMV	BLDC	100-115	50 / 60	ASHRAE -23.3°C / 54.4°C	1,020	4,500	239	949	278	594	174	139	
						-4,500	3,000	177	704	206	641	188		
	BMH110NBMV	BLDC	220-240	50 / 60	ASHRAE -23.3°C / 54.4°C	1,020	4,500	239	949	278	594	174	139	
						-4,500	3,000	177	704	206	642	188		

Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

USE ONLY S
WITH
AV03-E01

 **LG** P



BMA098NAMV

240V ~ 60-225Hz LRA2.2 3PH



THERMALLY PROTECTED / PROTECTION THERMIQUE
LG Electronics Inc. MADE IN KOREA



ISEL220144290915

WARNING: Permanent
will occur if comp
directly connected



R600



Mbsm_dot_pro_private_PDF__BMA098NAMVTélécharger

Mbsm_dot_pro_private_PDF_BMA098NAMVTélécharger