

**Mbsm.pro , Compressor ACC
, Cubigel Huayi, Electrolux
ZEM, GP12TG, HMBP-R134a,
220-230V ,50/60Hz, 3.8 HP**

written by Jamila | 3 October 2018

Mbsm.pro , Compressor ACC ,Cubigel Huayi, Electrolux ZEM,
GP12TG, HMBP-R134a, 220-230V ,50/60Hz, 3.8 HP



MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP , 1PH , 220-240 V 50 Hz

written by Jamila | 3 October 2018

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP ,
1PH , 220-240 V 50 Hz



PictureS Mbsm Dot Pro : www.mbsm.pro

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm³
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette

réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z



ZEM

R 134a



GL

CE



BEAB
Approved

3 25

220-240V

N/A

017



PictureS Mbsm Dot Pro : www.mbsm.pro



Mbsm_dot_pro_private_PDF_GL60AATélécharger
 Mbsm_dot_pro_private_PDF_-GL60AATélécharger



Type: Hermetic piston compressors**Producer: ACC****Series: HMBP**
Model: GL60AA

General data

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [°C]:	43

Compressor's data

Cylinder capacity [cm ³]:	6
Displacement [m ³ /h]:	1
Weight [kg]:	9,1
Oil charge [cm ³]:	265

Oil type:	ISO VG 19 ESTER
-----------	-----------------

Engine's data

Engine type:	RSIR
Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	187-264
Locked rotor current [A]:	9,9
Running winding resistance (25°C) [Ω]:	15,6
Starting winding resistance (25°C) [Ω]:	21,31

Electrical data

Relays:	3003
Shielding element:	MRA38028, T0508, AF18FU
Starting capacitor volume [μF]:	

Connections

	millimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	