

ZMC, zanussi, Made in Egypt, Compressors

written by Lilianne | 8 April 2021

R134a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
▶ <input type="checkbox"/> GL45AA	LBP::R134a	1/8	43	A	96	82	1.06	0.82		
▶ <input type="checkbox"/> GL45AN	LBP::R134a	1/8	50	C	96	81	1.05	0.8		
▶ <input type="checkbox"/> GL60AA	LBP::R134a	1/6	43	A	132	114	1.14	0.89		
▶ <input type="checkbox"/> GL60AF	LBP::R134a	1/6	43	D	132	113	1.07	0.82		
▶ <input type="checkbox"/> GL60AH	LBP::R134a	1/6	43	A	133	114	1.31	1.01		
▶ <input type="checkbox"/> GL60AN	LBP::R134a	1/6	50	C	132	114	1.07	0.83		
▶ <input type="checkbox"/> GL70AA	LBP::R134a	1/5	43	A	149	128	1.18	0.92		
▶ <input type="checkbox"/> GL70AN	LBP::R134a	1/5	50	D	150	129	1.08	0.83		
▶ <input type="checkbox"/> GL70AT	LBP::R134a	1/5	43	E	144	122	1.09	0.84		
▶ <input type="checkbox"/> GL75AA	LBP::R134a	1/5	43	A	155	133	1.18	0.92		
▶ <input type="checkbox"/> GL80AA	LBP::R134a	1/5	43	A	173	148	1.19	0.93		
▶ <input type="checkbox"/> GL80AF	LBP::R134a	1/5	43	D	166	141	1.14	0.88		
▶ <input type="checkbox"/> GL80AH	LBP::R134a	1/5	43	A	175	150	1.35	1.06		
▶ <input type="checkbox"/> GL80AN	LBP::R134a	1/4	43	A	196	168	1.36	1.06		
▶ <input type="checkbox"/> GL90AA	LBP::R134a	1/4	43	A	195	167	1.19	0.93		
▶ <input type="checkbox"/> GL90AH	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> GL90AN	LBP::R134a	1/4	50	D	190	163	1.1	0.85		
▶ <input type="checkbox"/> GL90AT	LBP::R134a	1/4	43	E	190	161	1.19	0.92		
▶ <input type="checkbox"/> GL99AA	LBP::R134a	1/4	43	A	214	182	1.24	0.96		
▶ <input type="checkbox"/> GL99AH	LBP::R134a	1/4	43	A	215	182	1.39	1.08		
▶ <input type="checkbox"/> GL80AD	LBP::R134a	1/5	43	W	0	0	0	0		
▶ <input type="checkbox"/> GL90AD	LBP::R134a	1/4	43	W	0	0	0	0		

R12

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> L45AV	LBP::R12	1/8	43	B	221	192	0.91	0.71		
<input type="checkbox"/> L55AV	LBP::R12	1/6	43	B	115	101	0.99	0.78		
<input type="checkbox"/> L55BV	LBP::R12	1/6	43	B	115	101	0.99	0.78		
<input type="checkbox"/> L76AV	LBP::R12	1/5	43	B	145	127	1.05	0.84		
<input type="checkbox"/> L76BV	LBP::R12	1/5	43	B	145	127	1.05	0.84		
<input type="checkbox"/> L88AV	LBP::R12	1/4	43	B	171	150	1.02	0.81		
<input type="checkbox"/> L88BV	LBP::R12	1/4	43	B	171	150	1.02	0.81		
<input type="checkbox"/> LT45AV	LBP::R12	1/8	50	B	94	83	1.04	0.83		
<input type="checkbox"/> LT55AV	LBP::R12	1/6	50	B	115	102	1.06	0.85		
<input type="checkbox"/> LT55BV	LBP::R12	1/6	50	B	115	102	1.06	0.85		
<input type="checkbox"/> LT76BV	LBP::R12	1/5	50	B	155	137	1.14	0.91		
<input type="checkbox"/> LT88BV	LBP::R12	1/4	50	B	190	169	1.16	0.93		
<input type="checkbox"/> P12BW	LBP::R12	1/3	43	A	221	192	0.91	0.71		

Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_catalogo_cubigel_R134aTélécharger

R600a

Model	Refr.	HP	Ambient Temp C	Rated Voltage	Cooling Capacity		COP without RC		COP with RC	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF	ASHRAE	CECOMAF
					-23.3°C kcal/h	-25°C W	-23.3°C W/W	-25°C W/W	-23.3°C W/W	-25°C W/W
<input type="checkbox"/> HL80AH	LBP::R600a	1/7	43	A	104	89	1.37	1.06		
<input type="checkbox"/> HL90AH	LBP::R600a	1/7	43	A	115	99	1.38	1.08		
<input type="checkbox"/> HL99AH	LBP::R600a	1/6	43	A	120	103	1.34	1.03		

Private Picture Copyright : WWW.MBSM.PRO



ALL COMPRESSOR HERMÉTIC EMBRACO IN ONE FILE

written by Lilianne | 8 April 2021

EMT22HLP	3,00	C	1/12	0,44	S	RSIR	151	69	50	98,00
EMT36HLP	3,97	C	1/10	0,56	S	RSIR	203	94	71	102,00
EMY3111Z	4,85	C	1/8	0,71	S	RSIR	247	117	86	105,00
EMT49HLP	5,56	C	1/6	0,76	S	RSIR	274	131	98	111,00
EMY3115Z	6,76	C	1/6	0,99	S	RSIR	341	158	117	112,00
NEK1116Z	7,37	C	1/5	0,60	S	RSIR	367	172	126	129,00
NEK1118Z	8,39	C	1/4	0,74	S	RSIR	417	195	144	133,00
NE2121Z	9,26	C/V	1/4	1,41	F	CSIR	465	217	163	172,00
NE2130Z	12,11	C/V	1/3	2,07	F	CSIR	613	298	227	186,00
NE2134Z	14,28	C/V	1/3	2,30	F	CSIR	662	313	234	190,00
NEK2140Z	16,80	C/V	1/2	2,35	F	CSIR	801	377	284	207,00

MODELO CM3 EXP C.V INT

(A)

REFR

COMP MOTOR TEMP. DE EVAPORACIÓN PRECIO +5°C 0°C -5°C -10°C

EMT37HDP	3,40	C	1/8	0,85	S	RSIR	343	245	228	181	113,00
EMT45HDR	3,97	C	1/8	0,95	S	CSIR	402	284	229	184	121,00
EMT50HDP	4,50	C	1/6	1,05	S	RSIR	456	374	303	242	120,00
EMT6144Z	5,20	C/V	1/5	1,38	F	RSIR	549	395	367	294	123,00
EMT6160Z	6,76	C/V	1/4	1,74	F	RSIR	696	504	469	377	127,00
EMT6170Z	7,69	C/V	1/4	2,03	F	RSIR	771	559	522	418	134,00
NEU6187Z	10,00	C/V	1/3	2,61	F	RSIR	918	654	600	477	151,00
NEU6210Z	12,12	C/V	1/3	3,15	F	RSIR	1170	955	770	615	163,00
NEU6212Z	14,30	C/V	1/2	3,90	F	RSIR	1365	1114	894	707	174,00
NEU6214Z	16,80	C/V	1/2	4,21	F	RSIR	1569	1292	1047	836	199,00
NT6217Z	20,44	C/V	3/4	4,73	F	RSIR	1795	1256	1173	938	292,00
NT6220Z	22,37	C/V	3/4	5,24	F	RSIR	1897	1554	1260	1010	323,00
NJ6220Z	26,11	C/V	3/4	5,71	F	RSIR	2202	1780	1419	1104	386,00
NJ6220Z	() 26,11	C/V	3/4	5,71	F	RSIR	2202	1780	1419	1104	379,00
NJ6226Z	34,38	C/V	1	5,95	F	CSR	2852	2340	1892	1497	439,00
NJ6226Z	() 34,38	C/V	1	5,95	F	CSR	2852	2340	1892	1497	439,00

410,00

COMPRESORES R404A/ R452A BAJA TEMPERATURA. MONOFÁSICAS 220V

MODELO	CM3	EXP	C.V	INT (A)	REFR COMP	MOTOR	TEMP. DE EVAPORACIÓN			PRECIO
							-10°C	-25°C	-30°C	
EMT2117GK	4,50	C	1/4	1,15	F	CSIR	408	210	164	143,00
EMT2121GK	5,20	C	1/3	1,33	F	CSIR	487	258	204	146,00
EMT2125GK	5,96	C-V	1/3	1,57	F	CSIR	562	301	238	158,00
EMT2130GK	6,76	C-V	1/2	1,70	F	CSIR	605	326	257	165,00
NEU2140GK	8,78	C-V	1/2	2,63	F	CSIR	801	421	326	182,00
NEU2155GK	12,11	C-V	3/4	3,79	F	CSIR	1067	557	432	201,00
NEU2168GJ	14,28	C-V	3/4	3,48	F	CSIR	1213	642	496	240,00
NEU2178GK	16,80	C-V	1	4,27	F	CSIR	1416	753	586	287,00
NT2180GK	20,44	C-V	1	3,12	F	CSIR	1573	814	625	330,00
NT2192GK	22,40	C-V	1	4,92	F	CSIR	1693	865	669	365,00
NT2192GK(*)	22,40	C-V	1	4,92	F	CSIR	1693	865	669	345,00
NT2210GK	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	375,00
NT2210GK(*)	26,20	C-V	1 1/2	6,43	F	CSIR	2041	1052	804	355,00
NT2212GK	27,78	C-V	1 1/2	5,30	F	CSIR	2174	1125	876	380,00
NJ2212GK	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	419,00
NJ2212GK(*)	34,37	C-V	1 1/2	5,80	F	CSIR	2487	1276	961	394,00



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF8compresores_hermeticos_embraco_2019Té
lécharger

**Refrigerator, compressor,
E1134CZA, 1/2 hp, E1130CZA,
E1121CZA, 3/8HP, commercial,
freezer, R134a**

written by Lilianne | 8 April 2021

Refrigerator, compressor, E1134CZA, E1130CZA, E1121CZA, 3/8HP,
commercial, freezer, R134a

COMPRESSOR, MX21TBa, R404A, 1HP, CUBIGEL, HMBP, 220/240V, 50Hz, 20,72 cm³

written by Lilianne | 8 April 2021

Détails techniques

220/240V 50Hz

puissance 1 HP – cylindrée 21,75 cc

gaz R404a/R507 HMBP

...et d'autres dispositifs

MX21TB – ACC – CELLI

MX21TB – CUBIGEL – ELECTROLUX

605093 – GEV – ITV



Brand:	Cubigel
UPC:	3070063
Manufacturer reference:	MX21TBa
Application:	HMBP
Power supply:	220/240V 50Hz
Cooling capacity:	3047 W
Horsepower:	1 Hp
Displacement:	21.7 cm ³
Refrigerant:	R404a/R507
Weight:	17.5 kg
Motor type:	CSR
Type:	Hermetic reciprocating compressor

MBSM.PRO, All Compressor in One File , Pdf and Print

written by Lilianne | 8 April 2021



MBSM.PRO, All Compressor in One File , Pdf and Print

**RÉFRIGÉRATEUR NIKAI,
nrf480fn4, 165W, Compressor,
ATD60L, Wanbao Huaguang
Refrigerator, 1/5Hp, R134A,
120G, 1.25A, 220V/50HZ**

written by Lilianne | 8 April 2021

NIKAI®


REFRIGERATOR MODEL:NRF480FN4

Rated Voltage	220-240V~
Rated Frequency	50Hz
Rated Current	1.25A
Rated Input Power	165W
Defrosting Power	150W
Electricity Consumption	1.385kw.h/24h
Climate Classification	T
Classification of Protection Against Electric Shock	Class I
Lamp Power	≤15W
Foaming Agent	CsH10(CP)
Refrigerant and Inject Amount	R134a/120g
Freeze Capacity	5.0kg/24h
Weight	65kg

MADE IN CHINA صنع في الصين

CB

ELECTRIC DIAGRAM



NIKAI GULF FZCO

PO BOX 9200 DUBAI UAE

نيكاي جلف إف زد سي

صندوق بريد 9200 دبي دولة الإمارات العربية المتحدة

REDMI NOTE 8 PRO
AI QUAD CAMERA



Private Picture Copyright : WWW.MBSM.PRO

RÉFRIGÉRATEUR NIKAI, nrf480fn4, 165W, Compressor, ATD60L, Wanbao Huaguang Refrigerator, 1/6Hp, R134A, 120G, 1.25A, 220V/50HZ