

Mbsm.pro, Compressor, R600a, PZ59E1C, 1/8 Hp, 95 W, Lbp

Category: compressor

written by Lilianne | 31 January 2022



Mbsm.pro, Compressor, R600a, PZ59E1C, 1/8 Hp, 95 W, Lbp

Mbsm.pro, Compressor, Samsung, MSV162AL1J/TS, MSV162, MSV162A-L1B, Compressor Inverter, Block DC, 1200/4000 RPM, 70/244 W, 238/834 BTU, Lnb, 1/3 hp, R134A, Blcd

Category: compressor

written by Lilianne | 31 January 2022



SAMSUNG MSV162A-1J TB2
160-260V-60-200Hz
RoHS Compliance
THERMALLY PROTECTED
4173C3CHA03887
MADE IN KOREA

Mbsm.pro, Compressor, Samsung, MSV162AL1J/TS, MSV162, MSV162A-L1B, Compresseur Inverter, Block DC, 1200/4000 RPM, 70/244 W, 238/834 BTU, Lnb, 1/3 hp, R134A, Blcd

Mbsm.pro, Compressor, Tecumseh, TAH4518A, 1.5 Hp, HBp, R12, 440V 3~ 60Hz 400V 3~ 50Hz, 1684 W, 14048 btu

Category: compressor

written by Lilianne | 31 January 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, Tecumseh, TAH4518A, 1.5 Hp, HBp, R12, 440V 3~ 60Hz 400V 3~ 50Hz, 1684 W, 14048 btu

الطريقة الصحيحة والوحيدة لحساب قدرة تي . . The Only Correct And Reliable Way To Calculate The Capacity Of TEE Compressors.

Category: Arabe,Chaud&Froid

written by Lilianne | 31 January 2022



Picture Private Copyright: WWW.MBSMGROUP.TN

Private Picture Copyright: WWW.MBSM.PRO

تي . . الطريقة الصحيحة والوحيدة لحساب قدرة ضواغط تي . . The Only Correct And Reliable Way To Calculate The Capacity Of TEE Compressors.

Mbsm.pro, Compressor, 4ec-6.2-4os,
6HP, Bitzer Piston Compressor,
4ces-6, Refrigeration Compressor ,
4ec-6.2/4ees-6, Cold Room. R22, R404

Category: compressor

written by Lilianne | 31 January 2022



Typ 4EC-6.2-40S
S.Nr. 1679004388



ER KÜHLMASCHINENBAU GMBH
Made in E.C.

Anspannung	Frequ.	Max. Betr. strom		Anlaufstrom		Fördervol. m³/h	Drehzahl min
		A(Δ)	A(Y)	A(Δ)	A(Y)		
Δ 3Ph- / V Y 3Ph-	Hz	A(Δ)	A(Y)	A(Δ)	A(Y)	22,7	1450
20-240	380-420	50	22,9	13,2	107,7	62,2	1750
265-290	440-480	60	22,9	13,2	107,7	62,2	

IP 65 ND/HD max 19 / 28 bar



Mbsm.pro, Compressor, 4ec-6.2-4os, 6HP, Bitzer Piston Compressor, 4ces-6, Refrigeration Compressor , 4ec-6.2/4ees-6, Cold Room. R22, R404

Mbsm.pro, Compressor, inverter, LG Refrigerator, BMG110NHMV, BMG/BMA LG, Lbp, 1/4 Hp , R600A

Category: compressor

written by Lilianne | 31 January 2022



Mbsm.pro, Compressor, inverter, LG Refrigerator, BMG110NHMV, BMG/BMA LG, Lbp, 1/4 Hp , R600A

Mbsm.pro, Compressor, AJE4511YTZ , R134a, hbp, TAJ4511Y, R-12/R-409A, lbp, 1HP, 3hp, 400V U.H., CAJ4511A, 1ph, R-12, lbp, 220v

Category: compressor

written by Lilianne | 31 January 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, AJE4511YTZ , R134a, TAJ4511Y, R-12/R-409A, 1HP, 3hp, 400V U.H., CAJ4511A, 1ph, R-12, 220v

Mbsm.pro, Compressor, R290, 0.110Kg,

SC15CNX.2, Secop, DANFOSS, SC15CNX,
15,28cm³, LBP, 230V, Hermetic piston
compressors, 5/8 Hp, 104h 8568,
104h8568

Category: compressor

written by Lilianne | 31 January 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, R290, 0.110Kg, SC15CNX, 15,28cm³, LBP, 230V, Hermetic piston compressors, 5/8 Hp, 104h 8568, 104h8568

Mbsm.pro, Daikin, compressor , R22/R407C

Category: compressor

written by Lilianne | 31 January 2022

High Performance Scroll

© 2014 Inverter Standard Compressor (Refrigerant R22/R407C)

Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)
JT90GAJV1L	9.0	12.5	26.1	30.2	3624	12500
JT95BHY1L	9.5	13.2	27.6	31.8	3830	13000
JT125G	12.5	17.2	36.8	42.3	5070	17200
JT125G-YE	12.5	17.2	36.8	42.3	5070	17200

© 2014 Inverter Standard Compressor (Refrigerant R22)

Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)	Performance	
							Efficiency (%)	Power Factor
JT90GAJV1L R22	9.0	12.5	26.1	30.2	3624	12500	92.5	0.95
	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
JT95BHY1L R22	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
	11.0	15.0	32.1	36.6	4448	15100	92.5	0.95
JT125G R22	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95
JT125G-YE R22	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95

Performance at Different Conditions						
Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)
JT90GAJV1L	9.0	12.5	26.1	30.2	3624	12500
JT95BHY1L	9.5	13.2	27.6	31.8	3830	13000
JT125G	12.5	17.2	36.8	42.3	5070	17200
JT125G-YE	12.5	17.2	36.8	42.3	5070	17200

© 2014 Inverter Standard Compressor (Refrigerant R407C)

Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)	Performance	
							Efficiency (%)	Power Factor
JT90GAJV1L R407C	9.0	12.5	26.1	30.2	3624	12500	92.5	0.95
	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
JT95BHY1L R407C	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
	11.0	15.0	32.1	36.6	4448	15100	92.5	0.95
JT125G R407C	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95
JT125G-YE R407C	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95

Performance at Different Conditions						
Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)
JT90GAJV1L	9.0	12.5	26.1	30.2	3624	12500
JT95BHY1L	9.5	13.2	27.6	31.8	3830	13000
JT125G	12.5	17.2	36.8	42.3	5070	17200
JT125G-YE	12.5	17.2	36.8	42.3	5070	17200

© 2014 Inverter Standard Compressor (Refrigerant R22)
 Capacity Range: 9.0~14.0 kW
 Refrigerant R22/R407C/R22
 Use Maximum Refrigerant

Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)	Performance	
							Efficiency (%)	Power Factor
JT90GAJV1L R22	9.0	12.5	26.1	30.2	3624	12500	92.5	0.95
	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
JT95BHY1L R22	9.5	13.2	27.6	31.8	3830	13000	92.5	0.95
	10.0	13.8	29.1	33.4	4036	13700	92.5	0.95
	10.5	14.4	30.6	35.0	4242	14400	92.5	0.95
	11.0	15.0	32.1	36.6	4448	15100	92.5	0.95
JT125G R22	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95
JT125G-YE R22	12.5	17.2	36.8	42.3	5070	17200	92.5	0.95
	13.0	17.8	38.3	43.9	5276	17900	92.5	0.95
	13.5	18.4	39.8	45.5	5482	18600	92.5	0.95
	14.0	19.0	41.3	47.1	5688	19300	92.5	0.95

Performance at Different Conditions						
Model	Capacity (kW)	Capacity (HP)	Capacity (RT)	Capacity (TR)	Capacity (kcal/hr)	Capacity (Btu/hr)
JT90GAJV1L	9.0	12.5	26.1	30.2	3624	12500
JT95BHY1L	9.5	13.2	27.6	31.8	3830	13000
JT125G	12.5	17.2	36.8	42.3	5070	17200
JT125G-YE	12.5	17.2	36.8	42.3	5070	17200

P
E
R
F
O
R
M
A
N
C
E
D
A
T
A

JT90GAJV1L JT95BHY1L JT125GGBBY1L JT125GBBY1L JT125G-YE @ K JT140G-P4Y1 @ K

JT150BCBY1L JT150BK-YE JT160BCBY1L JT170GABY1L JT170FDKYE JT300D-YE JT300D-P1YE
JT300D-YE @ JT315D-Y1L JT335D-Y1L JT100BHVE JT100BHV JT100BCBV1L JT100GABV1L
2YC45BXD 2YC45JXD 2YC45BXD 1GDY23AXD 2YC32VXD JT1FCVDKTYR JT1GCVDKYR 6T55TAC5YE
6T55WAC5YE JT170G-K1YE JT170G-KYE@BA etc. Mainly used for refrigeration
equipment such as air conditioners. Varieties ***, ***, ***, service is
exhausted, welcome to call to discuss!

Daikin Compressor Features: JT170G-K1YE JT170G-KYE@BA

Daikin Compressor Features: Small and light. High reliability and easy to use.

?Due to the small diameter and slenderness of the compressor cylinder, it
provides a good choice for the small and lightweight outdoor unit.

?In order to save the flexibility of space and location design, a new model with
three-legged chassis is added on the basis of the original four-legged
chassis. Give users more choices.

?The number of compressor parts is small and the reliability is high.

?Compressors can withstand the most brutal tests of heat pump systems.

?Only the protection device of the motor in the compressor is built-in, and
other protections are matched by the system. This allows system designers to set
protections in the system as needed, allowing product designers to better
control the compressors used.

JT300DJT160B-NYE JT160B-NFYE New original Daikin marine air conditioner
refrigeration equipment compressor A-Y1L JT335DA-Y1L New original Daikin
compressor R407CJT100BDVTYE JT100FBVD JT100FAVD New original Daikin inverter air
conditioner compressor JT170G-K1YE JT170FDKYE JT170FBKYE New original Daikin air
conditioner compressor Machine JT160BCBY1L JT160GABY1L Original Daikin 5 HP
Central Air Conditioning Compressor VRV3 generation RHXYQ14PY1 inverter
compressor original new JT160GAJY1L Daikin 5 hp central air conditioning
compressor three feet return air pipe upward R22 original 12 hp JT335D-P1YE
JT300D-P1YE Daikin central air conditioning compressor 10 hp JT315D
Original 5 HP JT160GABY1L JT170GABY1L Daikin Air Conditioning Compressor Heat
Pump Straight Tube Daikin Parallel Compressor JT300DA-YE Daikin 10P12 HP Air
Conditioning Compressor R40JT100FBVD JT100BHV JT100G-VDL@S Original Daikin
Inverter Air Conditioning Refrigeration Compressor JT140G-P4Y1@K Brand New
Original 5 Daikin Fixed Frequency Air Conditioning Compressor R410A 3 Foot
Daikin 5P JT160BCBY1L Panasonic C-SB373H8A Air Conditioning Air Energy Heat Pump
Compressor C-SB453



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, compressor, Tecumseh,
SE307-12, 220V, Fla 1.22 A, Lra 7.0
A, R12, 1/5 hp, 687 btu

Category: compressor

written by Lilianne | 31 January 2022

Mbsm.pro, compressor, Tecumseh, SE307-12, 220V, Fla 1.22 A, Lra 7.0 A, R12, 1/5
hp, 687 btu