

Huaguang(Wanbao) Compressor



Huaguang Wanbao Compressor



We are an authorized dealer of Huaguang(Wanbao) compressor for household refrigeration made in China, We supply all kinds of Huaguang(Wanbao) compressor for light commercial market, range from 5/16 – 1HP.

CONTACT US NOW

CONTACT US NOW FOR MORE INFO



- **Huaguang(Wanbao) Compressor**

Huaguang(Wanbao) Compressor started production on July 15, 1987. As one of major refrigerator compressor manufactures in the country, Huaguang(Wanbao) Compressor is specialized in compressor design, production and sale. It's one of the major refrigerator compressor manufactures.

Huaguang(Wanbao) Compressor was certified by ISO9001 quality system in 1995. Got ISO9001:2000 in 2001, Got certificate of QC080000 in 2008. In 2003, "Huaguang" was evaluated as "China's well know brand" by State Quality Inspection Administration. In Sep 2006, "Huaguang" was re-evaluated as "China's well know brand". The compressors got the Certification for CCC, UL, VDE, TUV, CB, etc.

- **Features for Huaguang(Wanbao) Compressor**

1. The smartest
2. Most efficient and cost effective
3. Easy to install, Energy saving, efficiency and silence
4. Designing and delivering intelligent compressor
5. Place of Origin: China (Mainland)
6. Refrigerant: R290/R404A/R134a/R600a
7. Certification: TUV, CCC, UL, VDE, CE, CRAA, TIS, KC, CB, INMETRO

You can **Download Huaguang(Wanbao) Compressor Catalog** to get the all models list.

- The Most Commonly Used Of Huaguang(Wanbao) Compressor Models



R600a Compressors

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity				COP			认证 Certification	最大高度 *A* Max. Height *A*
				ASHRAE -23.3°C		CECOMAF -25°C		ASHRAE -23.3°C		CECOMAF -25°C		
				W	Btu	W	W/W	EER	W/W			
				LBP								
220-240V 50HZ R600a												
T系列 T Series												
ETK80	8.1	ST	RSCR	138	471	103.2	1.55	5.3	1.21	CCC/CB	178	
ETK95	9.6	ST	RSCR	165	563	123.4	1.55	5.3	1.21	CCC/CB/VDE	178	
ETY72	7.2	ST	RSCR	125	427	93.7	1.6	5.5	1.25	CCC/CB/VDE	174	
ETY80	8.1	ST	RSCR	138	471	103.3	1.65	5.6	1.29	CCC	185	
ETY95	9.6	ST	RSCR	165	563	123.5	1.60	5.5	1.25	CCC/CB/VDE	178	
ETZ55	5.6	ST	RSCR	96	328	72.0	1.74	5.9	1.36	CCC	185	
ETZ60	6.0	ST	RSCR	102	348	77.3	1.68	5.7	1.32	CCC/CB/VDE	178	
ETZ66	6.6	ST	RSCR	110	375	83.3	1.68	5.7	1.32	CCC/CB/VDE	185	
ETZ72	7.2	ST	RSCR	125	427	94.7	1.70	5.8	1.33	CCC/CB/VDE	178	
ETZ80	8.1	ST	RSCR	140	478	104.0	1.70	5.8	1.33	CCC/CB/VDE	178	
ETZ86	8.6	ST	RSCR	150	512	113.5	1.70	5.8	1.33	CCC/CB/VDE	185	
ETZ95	9.6	ST	RSCR	165	563	124.0	1.70	5.8	1.33	CCC/CB/VDE	185	
ETZ110	10.7	ST	RSCR	185	631	139.1	1.70	5.8	1.33	CCC/CB/VDE	185	
ETZ120	12.0	ST	RSCR	210	717	157.5	1.70	5.8	1.33	—	185	
ETH50	5.1	ST	RSCR	82	280	62.1	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH55	5.6	ST	RSCR	96	328	72.2	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH60	6.0	ST	RSCR	102	348	77.1	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH66	6.6	ST	RSCR	110	375	83.1	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH72	7.2	ST	RSCR	125	427	94.4	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH80	8.1	ST	RSCR	140	478	105.2	1.76	6.0	1.38	CCC/CB/VDE	185	
ETH95	9.6	ST	RSCR	170	580	127.6	1.78	6.1	1.40	CCC/CB/VDE	185	
ETH110	10.7	ST	RSCR	190	648	142.2	1.78	6.1	1.40	CCC/CB/VDE	185	
ETB50	5.1	ST	RSCR	82	280	61.5	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB55	5.6	ST	RSCR	96	328	72.1	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB60	6.0	ST	RSCR	102	348	76.8	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB66	6.6	ST	RSCR	112	382	84.0	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB72	7.2	ST	RSCR	125	427	94.0	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB80	8.1	ST	RSCR	140	478	105.1	1.83	6.2	1.44	CCC/CB/VDE	185	
ETB95	9.6	ST	RSCR	170	580	128.7	1.83	6.2	1.44	CCC/VDE	185	
ETB110	10.7	ST	RSCR	190	648	142.2	1.83	6.2	1.44	CCC/VDE	185	
ETJ66	6.6	ST	RSCR	115	375	82.7	1.88	6.4	1.47	CCC	185	
ETJ90	9.0	ST	RSCR	155	529	116.3	1.88	6.4	1.47	CCC/VDE	185	
ETJ110	10.7	ST	RSCR	190	648	142.3	1.88	6.4	1.47	CCC/VDE	185	
ETC55	5.6	ST	RSCR	96	328	71.8	1.91	6.5	1.50	CCC	185	
ETC60	6.0	ST	RSCR	102	348	77.1	1.91	6.5	1.50	CCC	185	
ETC72	7.2	ST	RSCR	128	437	96.2	1.91	6.5	1.50	CCC/VDE	185	
ETC86	8.6	ST	RSCR	150	512	113.0	1.91	6.5	1.50	CCC/VDE	185	
ETC95	9.6	ST	RSCR	170	580	128.4	1.91	6.5	1.50	CCC/VDE	185	
ETC55A	5.6	ST	RSCR	96	328	72.5	1.95	6.7	1.53	CCC	185	
ETC60A	6.0	ST	RSCR	105	358	79.4	1.95	6.7	1.53	—	185	

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity				COP			认证 Certification	最大高度 *A* Max. Height *A*
				ASHRAE -23.3°C		CECOMAF -25°C		ASHRAE -23.3°C		CECOMAF -25°C		
				W	Btu	W	W/W	EER	W/W			
				S系列 S Series								
ETC72A	7.2	ST	RSCR	128	437	96.9	1.96	6.7	1.54	CCC	185	
ETX55	5.6	ST	RSCR	96	328	71.9	1.98	6.8	1.56	CCC/VDE	185	
ETX60	6.0	ST	RSCR	102	348	76.3	1.98	6.8	1.56	CCC/CB/VDE	185	
ETX66	6.6	ST	RSCR	115	392	86.0	1.98	6.8	1.56	CCC/CB/VDE	185	
△ETD110K	10.7	ST	RSCR	185	631	139.1	1.45	4.9	1.71	CCC/CB	178	
△ETK80K	8.1	ST	RSCR	138	471	103.8	1.58	5.4	1.24	CB	178	
△ETK95K	9.6	ST	RSCR	165	563	123.4	1.52	5.2	1.18	CCC/CB	182	
△ETY110K	10.7	ST	RSCR	185	631	139.1	1.60	5.5	1.25	CCC/CB	185	
△ETZ95K	9.6	ST	RSCR	165	563	123.4	1.70	5.8	1.33	CCC/CB	182	
ESF60	6.0	ST	RSCR	100	341	75.3	1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESF72	7.2	ST	RSCR	120	409	90.0	1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESF80	8.0	ST	RSCR	140	478	105.5	1.55	5.3	1.21	CCC/CB/VDE	162.5	
ESZ51	5.1	ST	RSCR	85	290	64.0	1.62	5.5	1.27	CCC/CB/VDE	171	

ESZ60	6.0	ST	RSCR	100	341	75.7	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ65	6.5	ST	RSCR	110	375	82.6	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ72	7.2	ST	RSCR	120	409	90.8	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ80	8.0	ST	RSCR	140	478	105.0	1.65	5.6	1.29	CCC/CB/VDE	171
ESH51	5.1	ST	RSCR	88	300	66.1	1.72	5.9	1.34	CCC/CB/VDE	174
ESH60	6.0	ST	RSCR	100	341	75.7	1.72	5.9	1.34	CCC/CB/VDE	174
ESH72	7.2	ST	RSCR	120	409	91.0	1.72	5.9	1.34	CCC/CB/VDE	174
ESH80	8.0	ST	RSCR	140	478	105.7	1.72	5.9	1.34	CCC/CB/VDE	174
△ ES65K	6.5	ST	RSIR	110	375	82.6	1.24	4.2	0.96	CB	162.5
△ ES65AK	6.5	ST	RSIR	110	375	82.6	1.32	4.5	1.03	CB	162.5
△ ESD65AK	6.5	ST	RSCR	110	375	82.6	1.40	4.8	1.10	CB	162.5
△ ESF65K	6.5	ST	RSCR	108	368	81.4	1.58	5.4	1.24	CCC/CB	167
Y 系列 Y Series											
EYK40	4.0	ST	RSCR	62	212	46.9	1.55	5.3	1.21	CCC/CB/VDE	153
EYY50	5.0	ST	RSCR	80	273	60.6	1.62	5.5	1.27	VDE	153
EYY60	6.0	ST	RSCR	96	328	72.4	1.62	5.5	1.27	VDE	153
△ EY60K	6.0	ST	RSIR	96	328	72.0	1.20	4.1	0.98	VDE	148
N 系列 N Series											
ENA130	13.1	ST	RSIR	225	768	168.8	1.35	4.6	1.05	CCC	186
ENK130	13.1	ST	RSCR	225	768	168.8	1.50	5.1	1.17	CCC	186
ENK150	15.1	ST	RSCR	258	880	193.5	1.50	5.1	1.17	CCC	193
ENY120	12.1	ST	RSCR	205	699	153.8	1.62	5.5	1.27	CCC	193
ENY130	13.1	ST	RSCR	225	768	168.8	1.62	5.5	1.27	CCC/VDE	196
ENY150	15.1	ST	RSCR	258	880	193.5	1.62	5.5	1.27	CCC/VDE	196
ENZ130	13.1	ST	RSCR	225	768	168.8	1.70	5.8	1.33	CCC	196
ENB130	13.1	ST	RSCR	225	768	168.8	1.80	6.1	1.41	CCC	196
ENB150	15.1	ST	RSCR	258	880	193.5	1.80	6.1	1.40	CCC	196
△ ENA130K	13.1	ST/OC	RSIR	225	768	168.8	1.30	4.4	1.02	CCC/CB	193
△ ENA150K	15.1	ST/OC	RSCR	258	880	193.5	1.50	5.1	1.17	CCC/CB	193

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity						COP				认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		AHAM	CECOMAF	ASHRAE		AHAM	CECOMAF				
				-23.3°C		-23.3/ 40.5°C	-25°C	-23.3°C		-23.3/ 40.5°C	-25°C				
				W	Btu	W	W	W/W	EER	W/W	W/W				
LBP															
115V 60HZ R600a															
T 系列 T Series															
ETZ50U6	5.0	ST	RSCR	96	328	104.9	71.9	1.70	5.8	2.00	1.33	UL	182		
ETZ60U6	6.0	ST	RSCR	120	409	131.1	89.9	1.70	5.8	2.00	1.33	UL	182		
ETZ72U6	7.2	ST	RSCR	142	485	154.5	107.3	1.70	5.8	2.00	1.33	UL	182		
ETZ80U6	8.0	ST	RSCR	165	563	179.5	124.7	1.70	5.8	2.00	1.33	UL	182		
ETB60U6	6.0	ST	RSCR	120	409	130.6	90.7	1.83	6.2	2.16	1.43	UL	185		
ETB72U6	7.2	ST	RSCR	145	495	157.8	109.6	1.83	6.2	2.16	1.43	UL	185		
ETB80U6	8.1	ST	RSCR	167	570	181.7	126.5	1.83	6.2	2.16	1.43	UL	185		
ETB90U6	9.0	ST	RSCR	190	648	206.7	143.9	1.83	6.2	2.16	1.43	UL	185		
ETB110U6	10.7	ST	RSCR	220	751	239.4	166.7	1.81	6.1	2.14	1.42	UL	185		
S 系列 S Series															
ESD60U6	6.0	ST	RSIR	120	409	/	89.7	1.45	4.9	/	1.13	UL	162.5		
ESD72U6	7.2	ST	RSIR	145	495	/	109.3	1.45	4.9	/	1.13	UL	162.5		
ESD80U6	8.0	ST	RSIR	165	563	/	124.6	1.45	4.9	/	1.13	UL	162.5		
ESY60U6	6.0	ST	RSCR	120	409	/	90.8	1.60	5.5	/	1.25	UL	171		
ESY80U6	8.0	ST	RSCR	165	563	/	124.5	1.60	5.5	/	1.25	UL	171		
Y 系列 Y Series															
EYA40U6	4.0	ST	RSIR	70	239	76.1	52.8	1.40	4.8	1.66	1.09	UL	153		
EYA55U6	5.5	ST	RSIR	105	358	114.2	79.5	1.40	4.8	1.66	1.09	UL	153		
220 ~ 240V 60HZ R600a															
T 系列 T Series															
ETH46X6	4.5	ST	RSCR	85	290	/	64.2	1.76	6.0	/	1.38	VDE/CB	185		
100V 50HZ R600a															
T 系列 T Series															
ETD50F	5.0	ST	RSCR	80	273	/	60.2	1.40	4.8	/	1.09	—	179		
ETD72F	7.2	ST	RSCR	125	427	/	94.3	1.40	4.8	/	1.10	—	179		
ETD80F	8.1	ST	RSCR	145	495	/	108.5	1.40	4.8	/	1.10	—	179		
100V 60HZ R600a															
T 系列 T Series															
ETD50F	5.0	ST	RSCR	95	324	/	71.8	1.50	5.1	/	1.17	—	179		
ETD72F	7.2	ST	RSCR	145	495	/	109.8	1.50	5.1	/	1.18	—	179		
ETD80F	8.1	ST	RSCR	165	563	/	124.0	1.50	5.1	/	1.17	—	179		
127V 60HZ R600a															
T 系列 T Series															
ETH46Y6	4.5	ST	RSCR	85	290	/	63.7	1.76	6.0	/	1.38	VDE/CB	185		

R134a Compressors

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity				COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF		ASHRAE		CECOMAF		
	-23.3°C			-25°C		-23.3°C		-25°C				
	W			Btu	W	W/W	EER	W/W	W/W			
LBP												
220-240V 50HZ R134a												
T系列 T Series												
ATA72X	7.2	ST/OC	RSIR	205	699	155.3	1.35	4.6	1.05	CCC/CB/VDE	185/188	
ATA80X	8.1	ST/OC	RSIR	230	785	174.2	1.35	4.6	1.05	CCC/CB	185/188	
ATK72X	7.2	ST/OC	RSCR	205	699	154.0	1.40	4.8	1.09	CCC/CB/VDE/CE	185/188	
ATK80X	8.1	ST/OC	RSCR	230	785	174.0	1.40	4.8	1.09	CCC/CB	185/188	
▲ ATD50V	5.0	ST	RSIR	140	478	105.2	1.25	4.3	0.98	CCC/CB	182	
ATD66X	6.6	ST/OC	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182	
△ ATA50K	5.0	ST	RSIR	144	491	108.9	1.35	4.6	1.05	CCC/CB	182/185	
△ ATA66K	6.6	ST	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182	
ATA66K(OC)	6.6	OC	RSIR	190	648	143.7	1.35	4.6	1.05	CCC/CB	188	
ATA72K(OC)	7.2	OC	RSIR	205	699	154.0	1.35	4.6	1.05	CCC/CB	188	
ATK55	5.5	ST	RSCR	160	546	121.0	1.35	4.6	1.05	CCC/CB	185	
ATK60	6.0	ST	RSCR	170	580	128.3	1.51	5.2	1.18	CCC/CB/CE	185	
ATK66	6.6	ST	RSCR	192	655	144.0	1.55	5.3	1.21	CCC/CB/CE	185	
ATK72	7.2	ST	RSCR	205	699	154.0	1.50	5.1	1.17	CCC/CB	185	
ATK80	8.1	ST	RSCR	230	785	174.0	1.50	5.1	1.17	CCC/CB	185	
ATZ55	5.5	ST	RSCR	170	580	128.3	1.62	5.5	1.26	CB	185	
S系列 S Series												
ASF43X	4.3	ST	RSCR	117	399	87.7	1.35	4.6	1.05	CCC/CB	162.5	
ASF51X	5.1	ST	RSCR	144	491	108.0	1.35	4.6	1.05	CCC/CB	162.5	
△ ASD43K	4.3	ST	RSIR	117	399	87.8	1.15	3.9	0.88	CCC/CB/VDE	167	
△ ASD53K	5.1	ST	RSIR	144	491	108.1	1.20	4.1	0.94	CCC/CB/VDE	171	
△ ASF43K	4.3	ST	RSCR	117	399	87.4	1.40	4.8	1.10	CB	162.5	
△ ASF53K	5.1	ST	RSCR	144	491	107.8	1.41	4.8	1.10	CB	171	
△ ASF65K	6.5	ST	RSCR	176	601	132.0	1.41	4.8	1.10	CB	171	
Y系列 Y Series												
AYA25X	2.5	ST	RSIR	66	225	49.4	1.10	3.8	0.87	CCC/CB	141	
AYA30X	3.0	ST	RSIR	80	273	59.9	1.10	3.8	0.87	VDE	141	
N系列 N Series												
ANA80	8.0	ST/OC	RSIR	235	802	176.0	1.35	4.6	1.06	CCC/VDE	193	
ANA90	8.8	ST/OC	RSIR	250	853	187.3	1.35	4.6	1.06	CCC/VDE	193	
ANZ80	8.0	ST	RSCR	235	802	176.0	1.62	5.5	1.28	CCC	196	
ANZ90	8.8	ST	RSCR	250	853	187.3	1.62	5.5	1.28	CCC	196	
△ ANA90K	8.8	F/OC	CSIR	250	853	187.3	1.30	4.4	1.02	CB	196	

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity					COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		AHAM	CECOMAF	ASHRAE		AHAM	CECOMAF		
	-23.3°C			-23.3/ 40.5°C	-25°C	-23.3°C		-23.3/ 40.5°C	-25°C				
	W			Btu	W	W/W	EER	W/W	W/W	W/W			
LBP													
115V 60HZ R134a													
T系列 T Series													
ATK60U6	6.0	ST	RSIR	205	699	221.4	153.8	1.45	4.9	1.70	1.13	UL	185
ATH43U6	4.3	ST	RSCR	140	478	151.2	105.0	1.66	5.7	1.95	1.30	UL	185
ATH50U6	5.1	ST	RSCR	170	580	185.5	127.7	1.70	5.8	2.00	1.33	UL	185
ATH60U6	6.0	ST	RSCR	205	699	223.7	153.9	1.70	5.8	2.00	1.33	UL	185
ATH66U6	6.6	ST	RSCR	225	768	245.5	168.7	1.66	5.7	1.95	1.30	UL	185
ATB46U6	4.6	ST	RSCR	150	539	174.0	118.5	1.75	6.1	2.10	1.40	UL	185
ATB50U6	5.1	ST	RSCR	175	614	198.0	135.0	1.75	6.1	2.10	1.40	UL	185
S系列 S Series													
ASF35BU6	3.5	ST	RSCR	125	427	135.0	93.8	1.45	4.9	1.71	1.13	UL	162.5
ASF39U6	3.9	ST	RSCR	130	444	140.4	97.5	1.46	5.0	1.72	1.14	UL	162.5
ASF46BU6	4.6	ST	RSCR	155	539	167.4	116.3	1.45	4.9	1.72	1.13	UL	167

ASF40U6	4.0	ST	RSCR	170	580	183.6	127.5	1.48	5.1	1.75	1.16	UL	167
ASF51U6	5.1	ST	RSCR	170	580	183.6	127.5	1.48	5.1	1.75	1.16	UL	167
ASZ30U6	3.0	ST	RSCR	100	341	108.0	75.0	1.55	5.3	1.83	1.21	UL	171
ASZ43U6	4.3	ST	RSCR	140	478	151.2	105.0	1.55	5.3	1.83	1.21	UL	171
ASZ51U6	5.1	ST	RSCR	170	580	183.6	127.5	1.55	5.3	1.83	1.21	UL	174
Y 系列 Y Series													
AYA25U6	2.5	ST	RSIR	76	259	83.2	57.5	1.25	4.3	1.47	0.98	UL	141
AYK25U6	2.5	ST	RSCR	76	259	82.5	57.2	1.35	4.6	1.59	1.06	UL	141
N 系列 N Series													
ANA90U6	8.8	ST	RSIR	290	989	314.8	217.2	1.35	4.6	1.59	1.05	UL	193
220V 60HZ R134a													
T 系列 T Series													
ATD66X	6.6	ST/OC	RSIR	225	768	/	169.8	1.35	4.6	/	1.06	CCC/CB	182/185
ATK72X	7.2	ST/OC	RSCR	230	785	/	173.6	1.50	5.1	/	1.18	CCC/CB/VDE/CE	185
ATK80X	8.1	ST/OC	RSCR	260	887	/	194.9	1.50	5.1	/	1.17	CCC/CB	185
ATK55X6	5.5	ST	RSCR	190	648	/	142.7	1.55	5.3	/	1.21	CB	182
ATH55X6	5.5	ST	RSCR	190	648	/	143.0	1.65	5.6	/	1.29	CB	185
S 系列 S Series													
ASD65	6.5	ST	RSIR	200	682	/	149.7	1.30	4.4	/	1.02	CCC/CB/VDE	167
ASF43X	4.3	ST	RSCR	140	478	/	106.1	1.40	4.8	/	1.09	CCC/CB	162.5
ASF51X	5.1	ST	RSCR	170	580	/	127.5	1.40	4.8	/	1.09	CCC/CB	162.5
Y 系列 Y Series													
AYA25X	2.5	ST	RSIR	76	259	/	57.5	1.20	4.1	/	0.94	CCC/CB	141
AYA30X	3.0	ST	RSIR	96	328	/	72.4	1.20	4.1	/	0.94	VDE	141
N 系列 N Series													
ANA90X	8.8	F/OC	RSIR	290	989	/	218.7	1.40	4.7	/	1.08	CCC/CB	196
127V 60HZ R134a													
T 系列 T Series													
ATK55Y6	5.5	ST	RSCR	190	648	/	143.5	1.55	5.3	/	1.21	CB	182

Variable Speed Compressors

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	转速 Rotate Speed	制冷量 Cooling Capacity				COP			认证 Certification	最大高度 *A* Max. Height *A*
					ASHRAE		CECOMAF		ASHRAE		CECOMAF		
	cm ³				r/m	-23.3°C	Btu	-25°C	W	W/W	EER		
LBP													
220-240V R600a													
VET系列 VET Series													
VETY50	5.0	ST	PMSM	1200	29	99	27.3	1.50	5.1	1.41	—	147.8	
				1600	40	136	37.6	1.60	5.5	1.50			
				2000	52	177	48.9	1.65	5.6	1.55			
				3000	75	256	70.5	1.65	5.6	1.55			
VETC50	5.0	ST	PMSM	4500	115	392	108.1	1.57	5.4	1.48	—	152.8	
				1200	29	99	27.3	1.85	6.3	1.74			
				1600	40	136	37.6	1.95	6.6	1.83			
				2000	52	177	48.9	1.95	6.6	1.83			
VETB72	7.2	ST	PMSM	3000	75	256	70.5	1.85	6.3	1.74	CCC/ VDE	162.8	
				4500	115	392	108.1	1.7	5.8	1.60			
				1200	46	157	42.9	1.60	5.5	1.51			
				1600	67	229	62.5	1.70	5.8	1.60			
VETB72	7.2	ST	PMSM	2000	86	293	80.2	1.72	5.9	1.62	CCC/ VDE	162.8	
				3000	123	420	114.8	1.65	5.6	1.55			
				4500	190	648	177.3	1.57	5.4	1.48			
				1200	46	157	42.9	1.85	6.3	1.74			
VETB72	7.2	ST	PMSM	1600	67	229	62.5	1.9	6.5	1.79	CCC/ VDE	162.8	
				2000	87	297	81.2	1.9	6.5	1.79			
				3000	125	427	116.6	1.8	6.1	1.70			
				4500	190	648	177.3	1.65	5.6	1.55			
VETZ90	8.8	ST	PMSM	1200	63	215	58.8	1.62	5.5	1.53	CCC/ VDE	162.8	
				1600	85	290	79.3	1.72	5.9	1.62			
				2000	106	362	98.9	1.78	6.1	1.68			
				3000	156	532	145.5	1.72	5.9	1.62			
VETB90	8.8	ST	PMSM	4500	228	778	212.7	1.60	5.5	1.51	CCC/ VDE	162.8	
				1200	65	222	60.6	1.85	6.3	1.74			
				1600	90	307	84.0	1.90	6.5	1.79			
				2000	105	358	98.0	1.90	6.5	1.79			
VETZ110	10.6	ST	PMSM	3000	160	546	149.3	1.80	6.1	1.70	CCC/ VDE	162.8	
				4500	230	785	214.6	1.65	5.6	1.55			
				1200	80	273	74.6	1.62	5.5	1.53			
				1600	105	358	98.0	1.72	5.9	1.62			
VETB110	10.6	ST	PMSM	2000	130	444	121.3	1.78	6.1	1.68	CCC/ VDE	162.8	
				3000	195	665	181.9	1.72	5.9	1.62			
				4500	280	955	261.2	1.60	5.5	1.51			
				1200	80	273	74.6	1.83	6.2	1.72			
VETB110	10.6	ST	PMSM	1600	105	358	98.0	1.88	6.4	1.77	CCC/ VDE	162.8	
				2000	130	444	121.3	1.85	6.3	1.74			
				3000	195	665	181.9	1.80	6.1	1.70			
				4500	280	955	261.2	1.65	5.6	1.55			
VENB130	12.8	ST	PMSM	1200	90	307	84.0	1.7	5.8	1.60	CCC/ VDE	186	
				1600	120	409	112.0	1.78	6.1	1.68			
				2000	155	529	144.6	1.85	6.3	1.74			
				3000	225	768	209.9	1.75	6.0	1.65			
VATZ72	7.2	ST	PMSM	4500	325	1109	303.2	1.6	5.5	1.51	CCC/ VDE	167.8	
				1200	80	273	74.6	1.6	5.5	1.51			
				1600	120	409	112.0	1.73	5.9	1.63			
				2000	155	529	144.6	1.75	6.0	1.65			
220-240V R134a													
VAT系列 VAT Series													
VATZ72	7.2	ST	PMSM	3000	220	751	205.3	1.75	6.0	1.65	CCC/ VDE	167.8	
				4500	325	1109	303.2	1.65	5.6	1.55			
				1200	80	273	74.6	1.6	5.5	1.51			
				1600	120	409	112.0	1.73	5.9	1.63			

R600a Aluminum Compressors

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				-23.3°C		-25°C	-23.3°C		-25°C		
				W	Btu	W	W/W	EER	W/W		
LBP											
220-240V 50HZ R600a											
T系列 T Series											
ETA72	7.2	ST	RSIR	125	427	93.7	1.30	4.4	1.00	CCC	174
ETA80	8.1	ST	RSIR	138	471	103.4	1.35	4.6	1.05	CCC/CB/VDE	178
ETA95	9.6	ST	RSIR	165	563	123.8	1.35	4.6	1.05	CCC/CB/VDE	178
ETA110L	10.7	ST	RSIR	185	631	138.8	1.36	4.6	1.06	CCC	185
ETK72L	7.2	ST	RSIR	125	427	93.7	1.50	5.1	1.17	CCC	170
ETK80L	8.1	ST	RSIR	138	461	103.4	1.50	5.1	1.17	CCC	178
ETK90L	8.8	ST	RSIR	155	529	122.5	1.50	5.1	1.17	CCC/VDE	175
ETK95L	9.6	ST	RSCR	165	563	123.8	1.55	5.3	1.21	CCC/CB/VDE	178
ETK110L	10.7	ST	RSCR	185	631	139.1	1.55	5.3	1.21	CCC/VDE	185
ETK115L	11.4	ST	RSCR	200	682	150.4	1.50	5.1	1.17	CCC/VDE	185
ETY72L	7.2	ST	RSCR	125	427	94.1	1.60	5.5	1.25	CCC	174
ETY80L	8.1	ST	RSCR	138	471	103.8	1.65	5.6	1.29	CCC	185
ETY90L	8.8	ST	RSCR	160	546	122.5	1.62	5.5	1.26	CCC/VDE	175
ETY95L	9.6	ST	RSCR	165	563	123.8	1.60	5.5	1.25	CCC/VDE	185
ETZ60L	6.0	ST	RSCR	102	348	76.8	1.68	5.7	1.32	CCC/VDE	178
ETZ72L	7.2	ST	RSCR	125	427	93.7	1.70	5.8	1.33	CCC/VDE	178
ETZ80L	8.1	ST	RSCR	138	478	105.2	1.70	5.8	1.33	CCC/VDE	185
ETZ95L	9.6	ST	RSCR	165	580	128.7	1.70	5.8	1.33	CCC/VDE	185
ETZ110L	10.7	ST	RSCR	185	631	139.1	1.70	5.8	1.33	CCC/VDE	185
ETH55L	5.6	ST	RSCR	96	328	72.2	1.76	6.0	1.38	CCC/VDE	185
ETH60L	6.0	ST	RSCR	102	348	76.8	1.76	6.0	1.38	CCC/VDE	185
ETH72L	7.2	ST	RSCR	125	427	93.7	1.76	6.0	1.38	—	185
ETH80L	8.1	ST	RSCR	140	478	104.9	1.76	6.0	1.38	CCC	185
ETH95L	9.6	ST	RSCR	165	563	128.7	1.76	6.0	1.38	CCC/VDE	185
ETB55L	5.6	ST	RSCR	96	328	72.1	1.83	6.2	1.44	CCC	185
ETB60L	6.0	ST	RSCR	102	348	76.8	1.83	6.2	1.44	CCC	185
ETB72L	7.2	ST	RSCR	125	427	93.7	1.83	6.2	1.44	CCC	185
ETB80L	8.1	ST	RSCR	140	478	105.2	1.83	6.2	1.44	CCC	185
ETB90L	8.8	ST	RSCR	160	546	122.5	1.83	6.2	1.44	CCC/VDE	185
S系列 S Series											
ESD51A	5.1	ST	RSIR	80	273	60.0	1.45	4.9	1.13	CCC/CB/VDE	167
ESD65A	6.0	ST	RSIR	100	341	75.8	1.45	4.9	1.13	CCC/CB/VDE	167
ESD72A	7.2	ST	RSIR	125	427	90.2	1.30	4.4	1.01	CCC/CB	167
ESD80A	8.0	ST	RSIR	140	478	105.2	1.40	4.8	1.17	CCC/VDE	167
ESF60L	6.0	ST	RSCR	100	341	75.5	1.50	5.1	1.17	CCC/CB/VDE	167
ESZ51L	5.1	ST	RSCR	85	290	64.0	1.62	5.5	1.27	CCC/CB/VDE	171
ESZ60	5.5	ST	RSCR	96	328	72.0	1.65	5.6	1.29	CCC/CB/VDE	171
ESZ72L	7.2	ST	RSCR	125	427	90.6	1.60	5.5	1.25	CCC/CB/VDE	171
Y系列 Y Series											
EY40L	4.0	ST	RSIR	58	198	43.5	1.10	3.8	0.86	CCC/VDE	141
EY50L	5.0	ST	RSIR	80	273	60.0	1.20	4.1	0.94	CCC/VDE	148
EY60L	6.0	ST	RSIR	96	328	72.0	1.10	3.8	0.86	CCC	141
EYA60	6.0	ST	RSIR	96	328	72.0	1.30	4.4	1.01	CCC/VDE	148
EYD40	4.0	ST	RSCR	62	212	46.5	1.40	4.8	1.09	CCC/VDE	153
EYD50	5.0	ST	RSCR	80	273	60.0	1.40	4.8	1.09	CCC/VDE	153
EYD60L	6.0	ST	RSCR	96	328	72.0	1.40	4.8	1.09	CCC/VDE	148
EYK60L	6.0	ST	RSCR	96	328	72.0	1.50	5.1	1.17	CCC	153
EYY60L	6.0	ST	RSCR	96	328	72.0	1.60	5.5	1.25	CCC	153

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				-23.3°C		-25°C	-23.3°C		-25°C		
				W	Btu	W	W/W	EER	W/W		
N 系列 N Series											
ENA150L	15.1	ST	RSIR	255	870	190.9	1.30	4.4	1.00	CCC	196
115V 60HZ R600a											
T 系列 T Series											
ETZ50U6L	5.0	ST	RSCR	96	328	71.9	1.7	5.8	1.33	UL	185
ETZ60U6L	6.0	ST	RSCR	120	409	90.7	1.7	5.8	1.33	UL	185
ETZ72U6L	7.2	ST	RSCR	150	512	113.4	1.7	5.8	1.33	UL	185
ETZ80U6L	8.1	ST	RSCR	165	563	124.7	1.7	5.8	1.33	UL	185
ETB60U6L	6.0	ST	RSCR	120	409	90.7	1.83	6.2	1.44	UL	185
ETB72U6L	7.2	ST	RSCR	150	512	113.4	1.83	6.2	1.44	UL	185
ETB80U6L	8.1	ST	RSCR	165	563	124.7	1.83	6.2	1.44	UL	185
Y 系列 Y Series											
EY40U6L	4.0	ST	RSIR	70	239	52.5	1.20	4.1	0.94	UL	148
EYA40U6L	4.0	ST	RSCR	70	239	52.5	1.35	4.6	1.05	UL	153
EYA55U6L	5.5	ST	RSIR	100	341	75.0	1.35	4.6	1.05	UL	153
S 系列 S Series											
ESD60U6L	6.0	ST	RSIR	120	409	90	1.45	4.9	1.14	UL	167
ESD72U6L	7.2	ST	RSIR	145	495	109	1.45	4.9	1.14	UL	167
ESK35U6L	3.5	ST	RSCR	70	239	53	1.55	5.3	1.21	UL	167
ESK51U6L	5.1	ST	RSCR	100	341	75	1.55	5.3	1.21	UL	167
ESY60U6L	6.0	ST	RSCR	120	409	90	1.60	5.5	1.25	UL	175
ESY72U6	7.2	ST	RSCR	145	495	109	1.60	5.5	1.25	UL	175
ESY80U6L	8.0	ST	RSCR	165	563	124	1.60	5.5	1.25	UL	175

R134a 铝线压缩机 R134a Aluminum Compressors

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"		
				ASHRAE	AHAM	CECOMAF	ASHRAE	AHAM	CECOMAF				
				-23.3°C	-23.3/ 40.5°C	-25°C	-23.3°C	-23.3/ 40.5°C	-25°C				
				W	Btu	W	W	W/W	EER			W/W	W/W
LBP													
220-240V 50HZ R134a													
T 系列 T Series													
ATD50L	5.1	ST	RSIR	144	491	/	108.7	1.25	4.3	/	0.98	CCC/CB	179
ATD60L	6.0	ST	RSIR	170	580	/	127.9	1.25	4.3	/	0.98	CCC/CB	182
ATD55XL	5.6	ST	RSIR	155	529	/	116.6	1.25	4.3	/	0.98	CCC/CB	182
ATD66XL	6.6	ST	RSIR	190	648	/	142.9	1.25	4.3	/	0.98	CCC/CB	182
ATD66XL(OC)	6.6	OC	RSIR	190	648	/	142.9	1.25	4.3	/	0.98	CCC/CB	185
ATK50L	5.1	ST	RSIR	150	512	/	112.5	1.45	4.9	/	1.14	CCC/CB	182
ATK60L	6.0	ST	RSCR	170	580	/	127.2	1.45	4.9	/	1.14	CCC/CB	182
ATK66L	6.6	ST	RSCR	198	675	/	149.8	1.55	5.3	/	1.21	CCC/CB/CE	182
ATZ60L	6.0	ST	RSCR	175	597	/	189.0	1.55	5.3	/	1.21	CCC/CB	185

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"		
				ASHRAE	AHAM	CECOMAF	ASHRAE	AHAM	CECOMAF				
				-23.3°C	-23.3/ 40.5°C	-25°C	-23.3°C	-23.3/ 40.5°C	-25°C				
				W	Btu	W	W	W/W	EER			W/W	W/W
S 系列 S Series													
ASD43K	4.3	ST	RSIR	117	399	/	86.5	1.18	4.0	/	0.92	CCC/VDE	163
ASD53K	5.1	ST	RSIR	144	491	/	108.9	1.20	4.1	/	0.94	CCC/VDE	171
ASF43X	4.3	ST	RSCR	117	399	/	88.5	1.30	4.4	/	1.02	CCC/CB	167
ASF51X	5.1	ST	RSCR	144	491	/	108.9	1.30	4.4	/	1.02	CCC/CB	167
Y 系列 Y Series													
AYT20XL	2.0	ST	RSIR	45	154	/	34.0	0.85	2.9	/	0.70	CCC/CB	141
AYD30L	3.0	ST	RSCR	80	273	/	60.5	1.30	4.4	/	1.02	VDE	153
AYD40L	4.0	ST	RSCR	100	341	/	78.8	1.30	4.4	/	1.02	VDE	153
AYA25XL	2.5	ST	RSIR	64	218	/	49.4	1.10	3.8	/	0.94	CCC/CB	148
AYA30XL	3.0	ST	RSIR	80	273	/	60.1	1.20	4.1	/	0.94	CCC/CB	153
▲ AYT25WL	2.5	ST	RSIR	60	205	/	45.0	1.00	3.4	/	0.78	CCC/CB	153
▲ AYT30WL	3.0	ST	RSIR	80	273	/	60.0	0.90	3.1	/	0.70	CCC/CB	153
N 系列 N Series													
ANA90L	8.8	F	RSIR	250	853	/	187.3	1.35	4.6	/	1.06	CCC	196

ANA120L	12.1	F	CSIR	340	1100	/	234.7	1.30	4.4	/	1.02	CCC	196
ANA80XL	8.0	F	RSIR	230	785	/	172.3	1.35	4.6	/	1.06	CCC	196
115V 60HZ R134a													
T 系列 T Series													
ATZ60U6L	6.0	ST	RSCR	200	682	230.0	150.0	1.64	5.6	1.95	1.28	—	185
ATH43U6L	4.3	ST	RSCR	140	478	151.2	105.0	1.66	5.7	1.96	1.29	—	185
S 系列 S Series													
ASD43U6L	4.3	ST	RSIR	145	478	152.2	106.1	1.32	4.5	1.56	1.02	UL	163
ASD51U6L	4.6	ST	RSIR	160	546	168.0	117.0	1.40	4.8	1.65	1.10	UL	167
ASF30U6L	3.0	ST	RSCR	100	341	108.0	75.0	1.45	4.9	1.71	1.13	UL	167
ASF35BU6	3.5	ST	RSCR	125	427	135.0	93.8	1.45	4.9	1.71	1.13	UL	171
ASF46BU6	4.6	ST	RSCR	155	529	167.4	116.3	1.45	4.9	1.71	1.13	UL	174
ASF51U6L	5.1	ST	RSCR	170	580	183.6	127.5	1.48	5.0	1.75	1.15	UL	174
ASZ30U6L	3.0	ST	RSCR	100	341	108.0	75.0	1.52	5.2	1.79	1.19	UL	174
ASZ35U6L	3.5	ST	RSCR	125	427	135.0	105.0	1.55	5.3	1.83	1.21	UL	174
ASZ43U6L	4.3	ST	RSCR	140	478	151.2	117.6	1.52	5.2	1.79	1.19	—	174
ASZ51U6L	5.1	ST	RSCR	165	563	178.2	123.8	1.55	5.3	1.83	1.21	—	174
Y 系列 Y Series													
AYT20U6L	2.0	ST	RSIR	55	188	60.0	41.4	1.10	3.8	1.30	0.86	UL	148
AYT25U6L	2.5	ST	RSIR	76	259	82.7	57.2	1.00	3.4	1.18	0.78	UL	141
AYT30U6	3.0	ST	RSIR	96	328	104.2	72.3	1.15	3.9	1.36	0.90	UL	148
AYD20U6L	2.0	ST	RSCR	55	188	59.5	41.3	1.25	4.3	1.47	0.98	UL	153
AYA25U6L	2.5	ST	RSIR	76	259	82.9	57.3	1.25	4.3	1.47	0.98	UL	153
AYA30U6	3.0	ST	RSIR	96	328	104.5	72.3	1.25	4.3	1.48	0.98	UL	153
220V 60HZ R134a													
T 系列 T Series													
ATD55XL	5.6	ST	RSIR	180	614	/	135.5	1.35	4.6	/	1.06	CCC/CB	182
ATD66XL	6.6	ST	RSIR	225	768	/	169.4	1.35	4.6	/	1.06	CCC/CB	182
ATD66XL(OC)	6.6	OC	RSIR	225	768	/	169.4	1.35	4.6	/	1.06	CCC/CB	185
S 系列 S Series													
ASF43X	4.3	ST	RSCR	140	478	/	105.8	1.45	4.9	/	1.14	CCC/CB	167
ASF51X	5.1	ST	RSCR	170	580	/	128.4	1.45	4.9	/	1.13	CCC/CB	167
Y 系列 Y Series													
AYT20XL	2.0	ST	RSIR	55	188	/	41.4	1.00	3.4	/	0.78	CCC/CB	153
AYA25XL	2.5	ST	RSIR	76	259	/	57.1	1.20	4.1	/	0.94	CCC	148
AYA30XL	3.0	ST	RSIR	96	328	/	72.3	1.30	4.4	/	1.02	CCC	153
N 系列 N Series													
ANA80XL	8.0	F	RSIR	265	904	/	199.6	1.40	4.8	/	1.10	CCC	196

Small Commercial Compressors

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				-23.3°C		-25°C	-23.3°C		-25°C		
				W	Btu	W	W/W	EER	W/W		
LBP											
220-240V 50HZ R134a											
N 系列 N Series											
ANA120	12.1	F	CSIR	340	1160	256	1.30	4.4	1.01	CCC/VDE	196
ANK110	11.3	F	RSCR	315	1075	237	1.50	5.1	1.17	CCC	196
ANK120	12.1	F	RSCR	340	1160	256	1.50	5.1	1.17	CCC	196
ANZ110	11.3	F	RSCR	315	1075	237.2	1.62	5.5	1.26	CCC	196
220-240V 50HZ R404a											
W 系列 W Series											
GW180	17.6	F	CSR	788	2688	593.4	1.20	4.1	0.94	CCC	218.5
GW210	20.3	F	CSR	934	3187	703.3	1.20	4.1	0.94	—	218.5
*GW230	22.4	F	CSR	1054	3596	793.7	1.20	4.1	0.94	—	218.5
220-240V 60HZ R404a											
W 系列 W Series											
GW180X	17.6	F	CSR	860	2933	646.7	1.20	4.1	0.94	CCC/CB	218.5
GW210X	20.3	F	CSR	1035	3529	778.3	1.20	4.1	0.94	—	218.5
*GW230X	22.4	F	CSR	1210	4128	909.9	1.20	4.1	0.94	—	230.0

型号 Model	气缸容积 Displacement cm ³	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				7.2°C		5°C	7.2°C		5°C		
				W	Btu	W	W/W	EER	W/W		
MBP / HBP											
220-240V 50HZ R134a											
N 系列 N Series											
AN72HX	7.5	F	CSIR	740	2525		2.40	8.2		—	196
AN90HX	8.8	F	RSCR	925	3155		2.80	9.6		CCC	196
AN120H	12.1	F	CSIR	1220	3833		2.30	7.8		CCC	200
W 系列 W Series											
AW180H	17.6	F	CSR	1560	5323		2.20	7.8		—	218.5
AW210H	20.3	F	CSR	1810	6176		2.20	7.9		—	218.5
*AW230H	22.4	F	CSR	2016	6879		2.20	8.0		—	218.5
220-240V 50HZ R404a											
W 系列 W Series											
*GW180HX	17.6	F	CSR	2550	8696		2.25	7.7		CCC/CB	230.0
*GW230HX	22.4	F	CSR	3220	10980		2.25	7.7		—	230.0
220-240V 60HZ R134a											
N 系列 N Series											
AN72HX	7.5	F	CSIR	860	2934		2.40	8.2		—	196
AN90HX	8.8	F	RSCR	1080	3685		2.80	9.6		CCC	196
220-240V 60HZ R404a											
W 系列 W Series											
*GW180HX	17.6	F	CSR	2990	10196		2.25	7.7		CCC/CB	230.0
*GW230HX	22.4	F	CSR	3799	12955		2.25	7.7		—	230.0

R290 Compressors

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
	-23.3°C			-25°C	-23.3°C		-25°C				
	W			Btu	W	W/W	EER	W/W			
LBP											
220-240V 50HZ R290											
FT 系列 FT Series											
FTA55	5.5	ST	RSIR	270	921	202.1	1.40	4.8	1.09	—	172
FTA60	6.0	ST	RSIR	280	955	209.5	1.40	4.8	1.09	—	172
FTK55	5.5	ST	CSIR	270	921	202.1	1.50	5.1	1.17	CCC/VDE	172
FTK60	6.0	ST	CSIR	280	955	209.5	1.50	5.1	1.17	—	172
FTK66	6.6	ST	CSIR	320	1092	239.6	1.50	5.1	1.17	CCC/VDE	172
W 系列 W Series											
*FW210X	20.3	F	CSR	805	2745	605.4	1.15	3.9	0.90	—	218.5

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度 "A" Max. Height "A"
				ASHRAE		—	ASHRAE		—		
	-5°C			—	-5°C		—				
	W			Btu	—	W/W	EER	—			
LBP / MBP											
N 系列 N Series											
FN72M	7.5	F	CSIR	660	2252		1.90	6.5		CCC	196
FN90M	8.8	F	CSIR	780	2660		1.80	6.1		CCC	196

