

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity						COP				认证 Certification	最大高度“A” Max. Height "A"
				ASHRAE		AHAM	CECOMAF	ASHRAE		AHAM	CECOMAF				
				-23.3°C		-23.3/ 40.5°C	-25°C	-23.3°C		-23.3/ 40.5°C	-25°C				
				W	Btu	W	W	W/W	EER	W/W	W/W				

## LBP

## 220-240V 50HZ R134a

## T系列 T Series

ATD50L	5.1	ST	RSIR	144	491	/	108.7	1.25	4.3	/	0.98	CCC/CB	179
ATD60L	6.0	ST	RSIR	170	580	/	127.9	1.25	4.3	/	0.98	CCC/CB	182
ATD55XL	5.6	ST	RSIR	155	529	/	116.6	1.25	4.3	/	0.98	CCC/CB	182
ATD66XL	6.6	ST	RSIR	190	648	/	142.9	1.25	4.3	/	0.98	CCC/CB	182
ATD66XL(OC)	6.6	OC	RSIR	190	648	/	142.9	1.25	4.3	/	0.98	CCC/CB	185
ATK50L	5.1	ST	RSIR	150	512	/	112.5	1.45	4.9	/	1.14	CCC/CB	182
ATK60L	6.0	ST	RSCR	170	580	/	127.2	1.45	4.9	/	1.14	CCC/CB	182
ATK66L	6.6	ST	RSCR	198	675	/	149.8	1.55	5.3	/	1.21	CCC/CB/CE	182
ATZ60L	6.0	ST	RSCR	175	597	/	189.0	1.55	5.3	/	1.21	CCC/CB	185

## S系列 S Series

ASD43K	4.3	ST	RSIR	117	399	/	86.5	1.18	4.0	/	0.92	CCC/VDE	163
ASD53K	5.1	ST	RSIR	144	491	/	108.9	1.20	4.1	/	0.94	CCC/VDE	171
ASF43X	4.3	ST	RSCR	117	399	/	88.5	1.30	4.4	/	1.02	CCC/CB	167
ASF51X	5.1	ST	RSCR	144	491	/	108.9	1.30	4.4	/	1.02	CCC/CB	167

## Y系列 Y Series

AYT20XL	2.0	ST	RSIR	45	154	/	34.0	0.85	2.9	/	0.70	CCC/CB	141
AYD30L	3.0	ST	RSCR	80	273	/	60.5	1.30	4.4	/	1.02	VDE	153
AYD40L	4.0	ST	RSCR	100	341	/	78.8	1.30	4.4	/	1.02	VDE	153
AYA25XL	2.5	ST	RSIR	64	218	/	49.4	1.10	3.8	/	0.94	CCC/CB	148
AYA30XL	3.0	ST	RSIR	80	273	/	60.1	1.20	4.1	/	0.94	CCC/CB	153
▲AYT25WL	2.5	ST	RSIR	60	205	/	45.0	1.00	3.4	/	0.78	CCC/CB	153
▲AYT30WL	3.0	ST	RSIR	80	273	/	60.0	0.90	3.1	/	0.70	CCC/CB	153

## N系列 N Series

ANA90L	8.8	F	RSIR	250	853	/	187.3	1.35	4.6	/	1.06	CCC	196
ANA120L	12.1	F	CSIR	340	1160	/	254.7	1.30	4.4	/	1.02	CCC	196
ANA80XL	8.0	F	RSIR	230	785	/	172.3	1.35	4.6	/	1.06	CCC	196

## 115V 60HZ R134a

## T系列 T Series

ATZ60U6L	6.0	ST	RSCR	200	682	230.0	150.0	1.64	5.6	1.95	1.28	—	185
ATH43U6L	4.3	ST	RSCR	140	478	151.2	105.0	1.66	5.7	1.96	1.29	—	185

## S系列 S Series

ASD43U6L	4.3	ST	RSIR	145	478	152.2	106.1	1.32	4.5	1.56	1.02	UL	163
ASD51U6L	4.6	ST	RSIR	160	546	168.0	117.0	1.40	4.8	1.65	1.10	UL	167
ASF30U6L	3.0	ST	RSCR	100	341	108.0	75.0	1.45	4.9	1.71	1.13	UL	167
ASF35BU6	3.5	ST	RSCR	125	427	135.0	93.8	1.45	4.9	1.71	1.13	UL	171
ASF46BU6	4.6	ST	RSCR	155	529	167.4	116.3	1.45	4.9	1.71	1.13	UL	174
ASF51U6L	5.1	ST	RSCR	170	580	183.6	127.5	1.48	5.0	1.75	1.15	UL	174
ASZ30U6L	3.0	ST	RSCR	100	341	108.0	75.0	1.52	5.2	1.79	1.19	UL	174
ASZ35U6L	3.5	ST	RSCR	125	427	135.0	105.0	1.55	5.3	1.83	1.21	UL	174
ASZ43U6L	4.3	ST	RSCR	140	478	151.2	117.6	1.52	5.2	1.79	1.19	—	174
ASZ51U6L	5.1	ST	RSCR	165	563	178.2	123.8	1.55	5.3	1.83	1.21	—	174

## Y系列 Y Series

AYT20U6L	2.0	ST	RSIR	55	188	60.0	41.4	1.10	3.8	1.30	0.86	UL	148
AYT25U6L	2.5	ST	RSIR	76	259	82.7	57.2	1.00	3.4	1.18	0.78	UL	141
AYT30U6	3.0	ST	RSIR	96	328	104.2	72.3	1.15	3.9	1.36	0.90	UL	148
AYD20U6L	2.0	ST	RSCR	55	188	59.5	41.3	1.25	4.3	1.47	0.98	UL	153
AYA25U6L	2.5	ST	RSIR	76	259	82.9	57.3	1.25	4.3	1.47	0.98	UL	153
AYA30U6	3.0	ST	RSIR	96	328	104.5	72.3	1.25	4.3	1.48	0.98	UL	153

## 220V 60HZ R134a

## T系列 T Series

ATD55XL	5.6	ST	RSIR	180	614	/	135.5	1.35	4.6	/	1.06	CCC/CB	182
ATD66XL	6.6	ST	RSIR	225	768	/	169.4	1.35	4.6	/	1.06	CCC/CB	182
ATD66XL(OC)	6.6	OC	RSIR	225	768	/	169.4	1.35	4.6	/	1.06	CCC/CB	185

## S系列 S Series

ASF43X	4.3	ST	RSCR	140	478	/	105.8	1.45	4.9	/	1.14	CCC/CB	167
ASF51X	5.1	ST	RSCR	170	580	/	128.4	1.45	4.9	/	1.13	CCC/CB	167

## Y系列 Y Series

AYT20XL	2.0	ST	RSIR	55	188	/	41.4	1.00	3.4	/	0.78	CCC/CB	153
AYA25XL	2.5	ST	RSIR	76	259	/	57.1	1.20	4.1	/	0.94	CCC	148
AYA30XL	3.0	ST	RSIR	96	328	/	72.3	1.30	4.4	/	1.02	CCC	153

## N系列 N Series

ANA80XL	8.0	F	RSIR	265	904	/	199.6	1.40	4.8	/	1.10	CCC	196
---------	-----	---	------	-----	-----	---	-------	------	-----	---	------	-----	-----

注：带"▲"的型号适用起动电压范围"150~230V"。

Note: The models with "▲" are available for start voltage "150V~230V".