

Model: AJE2422ZHZ (CAJ2432Z)
Product Description

Type: Reciprocating
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	220V ~ 60HZ	1171	295	343	525	2.23	.56	.65	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 21
Weight Unit of Measure: KG
Displacement (cc): 18.3
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 887

Electrical

Voltage Range (50 Hz): N/A
Voltage Range (60 Hz): 187-242
Locked Rotor Amps (LRA): 31
Rated Load Amps (RLA 50 Hz): 3.3
Rated Load Amps (RLA 60 Hz): 3.3
Max. Continuous Current (MCC in Amps): 6.4
Motor Resistance (Ohm) - Main: 2
Motor Resistance (Ohm) - Start: 8.5
Motor Type: CSR
Overload Type: N/A
Relay Type: N/A

Agency Approval

CE Listed, GOST RUSSIA Listed, UL Recognized