

R290-LMBP 220V~50Hz

220-240V 50Hz (Cubigel品牌)

系列	型号	排气量 cm ³	应用类型	冷却方式	电压/频率	电机类型	启动器类型	节流装置	标准点		ASHRAE工况										高度 mm
									-23.3/54.4		制冷量 (W)										
									制冷量	COP	蒸发温度 (°C)										
											W	W/W	-40	-35	-30	-25	-20	-15	-10	-5	
B	NBC35CA	3.5	LBP	S	220-240V 50Hz	RSIR	P	C	147	1.3	64	84	109	135	170	209	257			161.1	
	NBC35CA	3.5	LBP	S	220-240V 50Hz	RSCR	P	C	147	1.43	64	84	109	135	170	209	257			161.1	
	NBC35CG	3.5	LBP	S	200-220V 50Hz 230V 60Hz	RSIR	P	C	147	1.3	64	84	109	135	170	209	257			161.1	
	NBC41CA	4.1	LBP	S	220-240V 50Hz	RSIR	P	C	180	1.3	79	98	132	165	207	255	314			161.1	
	NBG40CA	4.1	LBP	S	220-240V 50Hz	RSCR	P	C	180	1.43	79	98	132	165	207	255	314			161.1	
	NBG45CA	4.5	LBP	S	220-240V 50Hz	RSCR	P	C	200	1.52	86	113	147	189	238	292	362			161.1	
S	NSG45CA	4.5	LBP	S	220-240V 50Hz	RSCR	P	C	200	1.55	86	113	147	189	238	292	362			165	
U	*NUS40CA	4	LBP	S	220-240V 50Hz	RSCR	P	C	180	1.8	79	98	132	165	207	255	314			173.5	
	NUS70CA	6.7	LBP	S	220-240V 50Hz	RSCR	P	C	325	1.85	135	178	233	300	376	467	565			173.5	
	NUS45NA	4.5	LMBP	S	220-240V 50Hz	RSCR	P	C	210	1.85	86	113	147	189	238	292	362	474	580	176	
	NUS55NA	5.5	LMBP	S	220-240V 50Hz	RSCR	P	C	265	1.85	114	143	192	239	300	370	455	564	671	176	
	NUS60NA	6	LMBP	S	220-240V 50Hz	RSCR	P	C	295	1.85	124	168	218	277	347	434	527	660	785	176	
	NUC45LA	4.5	LBP	S/F	220-240V 50Hz	CSIR	R	C-V	200	1.35	86	113	147	189	238	292	362			173.5	
	NUC45CA	4.5	LBP	S/F	220-240V 50Hz	RSIR	P	C	200	1.35	86	113	147	189	238	292	362			173.5	
	NUC55LA	5.5	LBP	F	220-240V 50Hz	CSIR	R	C-V	258	1.35	114	143	192	239	300	370	455			173.5	
	NUC60LA	6.0	LBP	F	220-240V 50Hz	CSIR	R	C-V	295	1.35	124	168	218	277	347	434	527			173.5	
	NUC70LA	6.7	LBP	F	220-240V 50Hz	CSIR	R	C-V	325	1.35	135	178	233	300	376	467	565			173.5	
	NUH45LA	4.5	LBP	S/F	220-240V 50Hz	CSIR	R	C-V	200	1.45	86	113	147	189	238	292	362			173.5	
	NUH55LA	5.5	LBP	F	220-240V 50Hz	CSIR	R	C-V	260	1.45	114	143	192	239	300	370	455			173.5	
	NUH60LA	6.0	LBP	F	220-240V 50Hz	CSIR	R	C-V	295	1.45	124	168	218	277	347	434	527			173.5	
	NUH70LA	6.7	LBP	F	220-240V 50Hz	CSIR	R	C-V	325	1.45	135	178	233	300	376	467	565			173.5	
	NUH80LA	8.1	LBP	F	220-240V 50Hz	CSIR	R	C-V	400	1.50	167	219	287	369	462	574	695			173.5	
	NUH90LA	8.9	LBP	F	220-240V 50Hz	CSIR	R	C-V	440	1.48	183	241	316	406	508	631	765			173.5	
	NUM55CA	5.5	LBP	S/F	220-240V 50Hz	RSIR	P	C	260	1.45	114	143	192	239	300	370	455			173.5	
			LMBP	S/F	220-240V 50Hz	RSCR	P	C	260	1.55	114	143	192	239	300	370	455	564	671	173.5	
			LBP	S/F	220-240V 50Hz	CSIR	R	C-V	260	1.45	114	143	192	239	300	370	455			173.5	
			LMBP	S/F	220-240V 50Hz	CSR	R	C-V	260	1.55	114	143	192	239	300	370	455	564	671	173.5	
	NUM60CA	6.0	LBP	S/F	220-240V 50Hz	RSIR	P	C	295	1.45	124	168	218	277	347	434	527			173.5	
			LMBP	S/F	220-240V 50Hz	RSCR	P	C	295	1.55	124	168	218	277	347	434	527	660	785	173.5	
			LBP	S/F	220-240V 50Hz	CSIR	R	C-V	295	1.45	124	168	218	277	347	434	527			173.5	
			LMBP	S/F	220-240V 50Hz	CSR	R	C-V	295	1.55	124	168	218	277	347	434	527	660	785	173.5	
	NUM70CA	6.7	LBP	F	220-240V 50Hz	RSIR	P	C	325	1.45	135	178	233	300	376	467	565			173.5	
			LMBP	F	220-240V 50Hz	RSCR	P	C	325	1.55	135	178	233	300	376	467	565	700	830	173.5	
			LBP	F	220-240V 50Hz	CSIR	R	C-V	325	1.45	135	178	233	300	376	467	565			173.5	
			LMBP	F	220-240V 50Hz	CSR	R	C-V	325	1.55	135	178	233	300	376	467	565	700	830	173.5	
	NUM80LA	8.1	LBP	F	220-240V 50Hz	CSIR	R	C-V	400	1.45	166	219	287	369	462	574	695			173.5	
			CSR	R	C-V	400	1.55	167	219	287	369	462	574	695			173.5				
	NUM90LA	8.9	LBP	F	220-240V 50Hz	CSR	R	C-V	440	1.55	183	241	316	406	508	631	765			176	
	NUK55CA	5.5	LBP	S/F	220-240V 50Hz	RSCR	P	C	260	1.65	113	143	192	240	302	375	463			173.5	
	NUK60CA	6.0	LBP	S/F	220-240V 50Hz	RSCR	P	C	295	1.65	124	168	218	277	347	434	527			176	
	NUK70CA	6.7	LBP	S/F	220-240V 50Hz	RSCR	P	C	325	1.65	138	186	241	306	383	474	587			176	
	NUT40NA	4.0	LMBP	S/F	220-240V 50Hz	RSCR	P	C	180	1.72	79	98	132	165	207	255	314	389	462	173.5	
	NUT55NA	5.5	LMBP	S/F	220-240V 50Hz	RSCR	P	C	260	1.72	114	143	192	239	300	370	455	564	671	173.5	
	NUT60NA	6.0	LMBP	S/F	220-240V 50Hz	RSCR	P	C	295	1.72	124	168	218	277	347	434	527	660	785	173.5	
	NUT55CA	5.5	LBP	S/F	220-240V 50Hz	RSCR	P	C	260	1.72	113	143	192	240	302	375	463			173.5	
	NUT60CA	6.0	LBP	S/F	220-240V 50Hz	RSCR	P	C	295	1.76	124	168	218	277	347	434	527			173.5	
	NUT70CA	6.7	LBP	F	220-240V 50Hz	RSCR	P	C	325	1.76	138	186	241	306	383	474	587			173.5	
NUT70NA	6.7	LMBP	F	220-240V 50Hz	RSCR	P	C	325	1.73	138	186	241	306	383	474	587	725	858	180		
NUT90LA	8.9	LBP	F	220-240V 50Hz	CSR	R	C-V	440	1.76	183	241	316	406	508	631	765			176		
NPY12Lab	12.1	LBP	F	220-240V 50Hz	CSR	R	C-V	539	1.49	224	295	387	497	622	773	937			210.5		

P	NPY14Lab	14.32	LBP	F	220-240V 50Hz	CSR	R	C-V	650	1.48	271	357	468	601	753	935	1134			210.5
	NPT16LA	16.15	LBP	F	220-240V 50Hz	CSR	R	C-V	742	1.52	309	407	534	685	858	1065	1293			210.5
	NPT18LA	18.0	LBP	F	220-240V 50Hz	CSR	R	C-V	819	1.46	332	444	584	754	954	1185	1444			210.5