

Compressor, Zanussi, HLY80AA, 1/7Hp, 220-240V 50Hz ~1, R600a, ZEM, Low Back Pressure, RSIR

Category: compressor

written by Lilianne | 26 January 2021



Private Picture Copyright : WWW.MBSM.PRO

Technical Data Sheet

Compressor model HLY80AAa

Voltage 220-240V 50Hz ~1

Refrigerant R600a

APPLICATION COMPRESSOR MOTOR

Application Low Back Pressure Displacement 8,10 cm³ Nominal Power 1/7 hp

Refrigerant R600a Diameter 24,29 mm Voltage/Frequency 220-240V 50Hz
Evaporating Temp. -35,0 °C to -10,0 °C Stroke 17,47 mm Voltage range 187-264 V
Expansion Capillar Net Weight 9,45 Kg Type RSIR
Comp. Cooling Static Oil type ISO VG 10 MINER Phase number 1 PH
Max. ambient temp. 43,0 °C Oil charge 205 cm³ Locked Rotor Amps (LRA) 8,60 A
Max. Cont. Current (MCC) 1,00 A
Main W. resist. at 25°C 22,02 Ω
Start W. resist. at 25°C 22,53 Ω

NOMINAL PERFORMANCE

ASHRAE CECOMAF

Cooling Capacity 113 kCal/h 99 W
COP 1,41 W/W 1,11 W/W
EER 1,22 kCal/Wh 0,96 kCal/Wh
Input Power 93 W 89 W
Current 0,62 A 0,60 A

TEST CYCLE CONDITIONS

ASHRAE CECOMAF

LBP (B) LBP (A)

Evaporating temp. -23,3 °C -25,0 °C
Condensing temp. 55,0 °C 55,0 °C
Liquid temp. 32,0 °C 55,0 °C
Ambient temp. 32,0 °C 32,0 °C
Suction temp. 32,0 °C 32,0 °C
Voltage/Frequency 220 V 50 Hz 220 V 50 Hz

ELECTRICAL COMPONENTS

Relay Option 1

Reference PTC K100

Voltage 200-240 V

Resistance 14.00 Ω

Protector Option 1 Option 2 Option 3 Option 4

Reference MSP318LZ 4TM189NFBYY T0462 AE37FJ

Current 5,90 A 5,50 A 6,20 A 5,90 A

Time check 7,5-14 seg 5-15 seg 7,5-14 seg 7,5-14 seg

Disc temp. (Open/Close) 120,00 / 61,00 °C 120,00 / 61,00 °C 110,00 / 62,00 °C
115,00 / 62,00 °C

Mbsm_dot_pro_private_PDF_HLY80aa_danfoss_HLY80AAa_R600a_220_50Télécharger



Private Picture Copyright : WWW.MBSM.PRO

