Mbsm.pro, Split Units, T3, kt3f-51, kt3f-51w / 18000 btu, kt3f-61w / 22000 btu, kt3f-66w / 24000 btu

Category: air conditioner written by Lilianne | 18 April 2023

Model Model of indoor unit Model of outdoor unit Electric shock protection class Rated volt Rated frequency Test conditions Cooling capacity Cooling power input EER 8.90(B Indoor discharge air-flow Rated power input Rated current input Indoor/Outdoor noise Refrigerant HP. PS LP. PS Indoor max operating pressure exchanger Indoor unit weight	T1; 5100W; 1950W; 9.1A; TU/h)/W;6.8	F-51GW T3F-51G T3F-51W 1 220V~ 60Hz T3 4500W 2250W 10.2A 1(BTU/h)/W ≥800m³/h 2500W 12.9A ~44/54dB(A) R22/1200g 3.0MPa 0.8MPa 13kg
And the second s		13kg
Date of manufacture		
lumber of manufacture		
		Made in Chin
	777	WALL AND CALL DO C

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Split Units, T3, kt3f-51, kt3f-51w / 18000 btu, kt3f-61w / 22000 btu, kt3f-66w / 24000 btu, r22, 1200 g

-		100000000000000000000000000000000000000
1		
Royal	CCool 2	
Model Room Air-co	-3	
THIOUGH OF IRRINGS		
THE COURT OF MALES		F-510W T3F-51G
Land of the service o	×	T3F-51W
Rated volt		1
Rated frequency	_	220V-
Test conditions	Ti.	60Hz
Cooling capacity	5100W	4500W
Cooling power input Cooling current input	1950W+	2250W
	9.1Ai	10.24
	(BTU/h)/W,6.8	1(BTU/hy/W
minori discribige air-flow		≥800m³/h
Rated power input		2500W
Rated current input		12.9A
Indoor/Outdoor noise	37	~44/54dB(A)
Refrigerant		R22/1200g
HP. PS		3.0MPa
LP. PS		0.8MPa
Indoor max operating press	ure of heat	20000
exchanger		0.8MPa
ndoor unit weight	WAR PER	13kg
Date of manufacture		
	MANAGEM N	
lumber of manufacture	TO COMPANY	
DESCRIPTION OF THE PERSON OF T		Made in Chin
ate Picture Copyright: WV	VW.MBS	SM.PRO

Split Units with T3 for Gulf Countries: KT3F(R)-51GW/61GW/66G

Model: KT3F(R)-51GW/61GW/66GW Wall split type,

V/HZ: 220V/60HZ for wall split type;

Cooling Capacity: 18,000 btu / 22,000 btu / 24,000 btu for cooling only / cooling and heating.1) Famous brand compressors in Japan, such as HITACHI, MISTUBISHI, rotary type;

- 2) High degree up to 50 degree high temperature for tropical uses;
- 3) warranty, 5 years for compressors, 3 years for complete units;
- 4) The approvals of ISO9001, SASO. Features:
- 1) Intelligent control and display technology
- 2) Wide voltage design
- 3) Double air guide plate technology
- 4) Memory functions
- 5) Automatic standby mode control
- 6) Fast audio diagnostics in case of failure
- 7) Delayed start and stop

Model/item number: KT3F(R)-51GW/61GW/66GW

