

Compressor, Tee, Turk, mte190yt, 1/4 hp, Double door refrigerator, r134, Lbp, 189 W

Category: compressor

written by Amina | 25 October 2023



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright : WWW.MBSM.PRO

Refrig Applic	Displac cc	Net kg	Oil Cl cc	Coo (°C Max.)	Motor	Voltag V	Freque Hz	Performance Data									
								Ashrae						Cecomaf	Ashrae		Cecomaf
								-35°C	-30°C	-25°C	-23,3°C	-20°C	-15°C	-10°C	-25°C	-23,3°C	-25°C
Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h	Kcal/h	W	W/W	W/W								
STANDARD EFFICIENCY RANGE																	
R134a LBP	AE 123 YD	5.75	9.7	470	O/F*	1	2-3-6	55	80	111	123	150	196	250	105	1.08	0.83
	AE 123 YP	5.75	9.7	470	O/F*	2	2-3									1.08	0.83
	AE 123 YT	5.75	9.7	470	O/F*	3	4									1.22	0.94
	AE 123 YC	5.75	9.7	470	O/F*	4	2									1.08	0.83
	AE 148 YD	6.91	9.9	430	O/F*	1	1-2-3-6	67	96	133	148	179	234	297	126	1.15	0.89
	AE 148 YP	6.91	9.9	430	O/F*	2	2-3									1.15	0.89
	AE 148 YT	6.91	9.9	430	O/F*	3	4-6									1.28	0.99
	AE 148 YC	6.91	9.9	430	O/F*	4	2-3									1.15	0.89
	AE 176 YD	7.94	10.8	450	O/F**	1	1-2-3-6	81	114	158	176	213	276	352	150	1.13	0.87
	AE 176 YP	7.94	10.8	450	O/F**	2	2-3									1.13	0.87
	AE 176 YT	7.94	10.8	450	O/F**	3	4									1.30	1.00
	AE 176 YC	7.94	10.8	450	O/F**	4	1-2-3									1.13	0.87
	AE 196 YD	8.99	10.8	450	O/F**	1	2-3	92	129	178	196	235	306	390	167	1.10	0.85
	AE 196 YP	8.99	10.8	450	O/F**	2	2-3-4									1.10	0.85
	AE 196 YT	8.99	10.8	450	O/F**	3	4									1.30	1.00
	AE 196 YC	8.99	10.8	450	O/F**	4	2-3-6									1.10	0.85
AE 196 YK	8.99	10.8	450	O/F**	5	2-4									1.10	0.85	
AE 230 YC	14.17	11.5	450	F	4	1-2-3	108	152	209	230	276	357	446	196	1.07	0.82	
AE 282 YC	16.13	11.5	450	F	4	2-3	133	186	257	282	338	437	547	240	1.01	0.78	
MEDIUM EFFICIENCY RANGE																	
R134a LBP	TE 150 YP	6.36	10.3	430	S	2	2-3	67	97	134	149	180	235	299	127	1.28	0.99
	TE 150 YT	6.36	10.3	430	S	3	2-3									1.36	1.05
	TE 165 YP	6.91	10.3	430	S	2	2-3	76	107	149	165	200	259	330	140	1.30	1.00
	TE 165 YT	6.91	10.3	430	S	3	2-3									1.38	1.06
	TE 180 YP	7.50	10.9	360	S	2	2-3	83	118	163	181	219	284	362	154	1.32	1.02
	TE 180 YT	7.50	10.9	360	S	3	2-3									1.40	1.08
	TE 195 YP	7.94	11.2	360	S	2	2-3	91	127	176	193	232	301	384	164	1.32	1.02
	TE 195 YT	7.94	11.2	360	S	3	2-3									1.40	1.08
	TE 215 YP	8.99	11.2	360	S	2	2-3	102	143	197	217	260	336	421	184	1.28	0.99
	TE 215 YT	8.99	11.2	360	S	3	2-3									1.36	1.05
HIGH EFFICIENCY RANGE																	
R134a LBP	MTE 160 YP	6.36	10.3	430	S	2	2-3	74	104	144	160	194	251	320	136	1.46	1.12
	MTE 160 YT	6.36	10.3	430	S	3	2-3									1.55	1.19
	MTE 175 YP	6.91	10.3	430	S	2	2-3	80	113	157	174	211	273	348	148	1.46	1.12
	MTE 175 YT	6.91	10.3	430	S	3	2-3									1.55	1.19
	MTE 190 YP	7.50	10.9	360	S	2	2-3	89	125	172	189	227	295	376	161	1.47	1.13
	MTE 190 YT	7.50	10.9	360	S	3	2-3									1.56	1.20
	MTE 205 YP	7.94	11.2	360	S	2	2-3	96	135	187	205	246	318	398	174	1.48	1.14
	MTE 205 YT	7.94	11.2	360	S	3	2-3									1.57	1.21
	MTE 225 YP	8.99	11.2	360	S	2	2-3	106	149	205	225	270	349	437	191	1.46	1.12
	MTE 225 YT	8.99	11.2	360	S	3	2-3									1.55	1.19