

Mbsm.pro, Embraco, Aspera, NT2170U,  
compressor, LBP, R290,, 220 –  
240V/1/50Hz, 1- HP,

Category: compressor

written by Lilianne | 4 May 2023

embraco aspera

NT2170U



THERMALLY PROTECTED		220 - 240V ~ 50Hz
	R 290	
POE. OIL 450CC	1 PH	

MADE IN SLOVAKIA NO START WITHOUT STARTING DEVICE



28A04

KX

M10ZBW8J

Embraco Aspera NT2170U compressor, LBP – R290, 220 – 240V/1/50Hz, 1- HP, 20.44 cc discharge, CSIR type motor, POE 22 type lubricant, 450 ml lubricant charge, 819 W at -23.3 / + 54.4 °C LRA 25 A, expansion device: capillary or valve, cooling: fan cooling, air flow 520 m3/h, weight 17.2 kg

---

Refrigerant:

R290

Power Range (W):

501 – 700W 701 – 1000W

Performance range (C):

-30C to -10C

Work zone:

PSL

Type of design:

Hermetic

Model series:

NT

Use with:

Capillary and VTE

Power Range (HP):

0-2

Power source:

230V

Type of oil:

POE22

Type of engine:

CSIR

Item Condition:

New

Info:

Filled with oil

Shipping weight:

19,20kg

customs tariff number:

84143081

Cooling capacity requirement:

T0 -25 °C, Tk +55 °C

Maker:

Embraco Aspera

Model:

NT2170U

Model Name:

T2170U

Stroke volume (cm3):

20,44

Performance requirement:

-23,3 / +54,4

Power (W):

819

Cooling capacity (W):

620

Power (HP):

1

Max. Starting current (A):

25

Type of engine:

CSIR

Note:

Fan cooling required, airflow 520 m<sup>3</sup>/h

Oil quantity (l):

0,45

Compressor type:

Piston

Power range:

-30C to -10C



Mbsm\_dot\_pro\_private\_PDF\_nt2170