

**HERMETIC , AW5524EK
, Compressor , 20,950 BTU
, 230/1/60 R-22 , : 220-240
V/50 Hz. , 1 Phase ,
1.7458333333 TON**

written by Lilianne | 26 April 2020

Electrical : 220-240 V/50 Hz. 1 Phase

Nominal Performance

Capacity 6,140 / – Watts

20,950 / – BTU/Hr

5,280 / – Kcal/Hr

Power Input 2,089 / – Watts

Locked Rotor Amps 51.30 / – Amps

Max Continuous Current – / – Amps

Rated Load Amps 9.64 / – Amps

COP 2.94 / – Watts / Watts

EER 10.03 / – BTU/W-Hr

Testing Conditions

Condensing Temperature 54.40 °C 129.9 °F

Evaporating Temperature 7.20 / – °C 45.0 / – °F

Liquid Temperature 46.10 °C 115.0 °F

Return Gas Temperature 35.00 °C 95.0 °F

Ambient Temperature 35.00 °C 95.0 °F

Application

Evaporating Temp. Range HBP, A/C @ 0.00 ° C to 13.00 ° C
(32.0° F to 55.4° F)

Heat Pump -23.30 ° C to 13.00 ° C
(-9.9° F to 55.4° F)

Refrigerant R22

Refrigerant Flow Control Capillary Tube

Compressor Cooling Fan

Compressor and Motor data

Compressor Type Reciprocating

Displacement 43.10 cc.

Oil Type Mineral Oil

Oil Charge 964 cc.

Motor Type P.S.C ; 2 Pole 2,850 / – r/m

Voltage Range 198-264/- Volts 50/- Hz.

Winding Resistance at 25 ° C

Start 2.52 Ohms

Run 1.24 Ohms

Weight with Oil 27.72 Kg.

Weight with Oil and Accessories 28.05 Kg.

Electrical Components

Motor Protector

Type Internal Overload

Model Number 4042KGE661-2

Open / Close 125-135 / 50-70 ° C

1st Cycle trip at 25 ° C 50.00 Amps(main) 30.00 Amps(start)

Motor Starter

Type Potential Relay

Model Number 4043KGE681-4(RVA3G6D)

Pick Up (max.) 180.00-195.00 Volts

Drop Out (min.) 40.00-90.00 Volts

Terminal Cover KGM 901-3

Start Capacitor 88-106 µF 330 VAC.

Disch Resistor for Start Cap –

Run Capacitor 45 µF 370/440 VAC.

Mounting Kit

Rubber Grommet 4007KGM905-2


Sleeve Grommet 4023KGM903-2

Washer –

Since we are constantly improving our product , the specification are subject to change without notice.

REV. DATE C / N No.

ECN 01-04-14 ECN 0515/13





DOCUMENTATION PDF

Mbsm_dot_pro_private_pictureAW5524EKTélécharger

**D110C24GAX5 , PANASONIC
,RSIR, Serie D, Reciprocating
,Compressors , 298 w , 1/3 HP
, R134a ,220v 50Hz**

written by Lilianne | 26 April 2020

displacement cm ³	W (cooling)	BTU/HR	K Cal/hr	HP	Model	number
5.1	135	461	116	1/6	D51C10RAW5	1
5.1	135	461	116	1/6	D51C90RAW5	2
5.7	141	481	121	1/6	D57C10RAW5	3
5.7	141	481	121	1/6	D57C13RAX5	4
6.6	160	546	138	1/5	D66C10RAW5	5
6.6	151	515	130	1/5	D66C10RAX5	6
7.7	186	635	160	1/5	D77C10RAW5	7
7.7	186	635	160	1/5	D77C10RAX5	8
9.1	227	774	195	1/4	D91C10RAW5	9
9.1	227	774	195	1/4	D91C10RAX5	10
11.0	298	1017	256	1/3	D51C21RAX5	11
11.0	298	1017	256	1/3	D110C21RA25	12
11.0	298	1017	256	1/3	D110C21RBX5	13
11.0	298	1017	256	1/3	D110C24GAX5	14



Private Picture Copyright : WWW.MBSM.PRO

D110C24GAX5 , PANASONIC ,RSIR, Serie D, Reciprocating ,Compressors , 298 w , 1/3 HP , R134a ,220v 50Hz

**Compresseurs Embraco,
,EMU70HLC , R134a, 220 V,
50Hz, 1/5 HP, 149 watts , 180
mL**

written by Lilianne | 26 April 2020

Compresseurs Embraco, ,EMU70HLC , R134a, 220 V, 50Hz, 1/5 HP,
149 watts , 0.17 kW (0.2214 BHP) ,180 mL

Austria , RECIPROCATING , COMPRESSOR , SECOP , HXD30AA , 0.04 1/25 HP , R600a , 220v 50Hz

written by Lilianne | 26 April 2020

Austria , RECIPROCATING , COMPRESSOR , SECOP , 0.04 HP , HXD30AA ,
1/25 HP , R600a , 220v 50Hz

Tableau de conversion d'unités

written by Lilianne | 26 April 2020





Tableau de conversion d'unités

PREFIXES , CONVERSION , FACTORS

written by Lilianne | 26 April 2020



PREFIXES , CONVERSION , FACTORS

**HUAYI , COMPRESSOR , HYE55YL63
, 1/6 Hp , 129Kcal , R134a ,
220V , LBP**

written by Lilianne | 26 April 2020

HUAYI , COMPRESSOR , HYE55YL63 , 1/6 Hp , 129Kcal , R134a , 220V
, LBP

**Tropical Compressor , TLS5FT
102G4524 , SECOP , R134a ,
1/6 HP , 134 W , LBP , 220/
240 V 50Hz**

written by Lilianne | 26 April 2020

Tropical Compressor , TLS5FT 102G4524 , SECOP , R134a , 1/6 HP
, 134 W , LBP , 220/ 240 V 50Hz

**LOW BACK PRESSURE , HITACHI ,
Compressor FL1257-SR , 1/5HP
, R134a , 135 W , BTU/Hr 512
, Circuit RSIR**

written by Lilianne | 26 April 2020

LOW BACK PRESSURE , HITACHI , Compressor FL1257-SR , 1/5HP ,
R134a , 135 W , BTU/Hr 512 , Circuit RSIR

Notion , Ne jamais utiliser

de , pâte à joints, ni Téflon, ni filasse pour , l'étanchéité des raccords , de Climatisation

written by Lilianne | 26 April 2020

Notion , Ne jamais utiliser de , pâte à joints, ni Téflon, ni
filasse pour , l'étanchéité des raccords , de Climatisation