

R134A, LBP, Motor, Danfu, Compressor , PW2.0VK, 1/15hp

Category: compressor

written by Lilianne | 23 April 2021



PW2.0VKMF   
220-240V~50/60Hz A002364 
SINGLE PHASE R134a
THERMALLY PROTECTED
Sichuan Danfu Environment Technology Co., Ltd.

Private Picture Copyright: WWW.MBSM.PRO

| | | | |
|-------------------------|--------------------|------------------------|--------------------|
| Evaporating Temperature | -23.3°C | Condensing Temperature | |
| 54.4°C | | | |
| Subcooling | | | |
| Temperature | 32.2°C | Suction | Temperature 32.2°C |
| Ambient | Temperature 32.2°C | | |

Features of danfu compressor PW2.0VK:

- 1) Suit all types of water dispenser
- 2) Best cooling function

Specifications

- 1) Running voltage: 220-240V, 50/60HZ
- 2) Capacity: 70W
- 3) Motor Input: 60W
- 4) Current: 0.70A
- 5) Cop: 0.91(W/W)
- 6) Reprigerant: R134a

Outer packing:

1pc/ctn or 120 pcs/pallet

Carton dimensions:20 x13 x 16cm

R134a LMBP Series

| Model | Power(HP) | | Capacity(W) | COP |
|----------------------|-----------|------|-------------|------|
| | 50Hz | 60Hz | 50Hz | 60Hz |
| 220 – 240 V 50/60 Hz | | | | |
| PW1.5VK | 1/20 | | 41 | 49 |
| PW2.0VK | 1/15 | | 52 | 62 |
| PW2.5VK | 1/12 | | 56 | 79 |
| Capillary 0.31 – 2M | | | | |
| PW4.0VK | 1/10 | | 76 | 102 |
| PW4.5VK | 1/6 | | 108 | 110 |
| PW5.5VK | 1/5 | | 126 | |
| 110 – 120 V 60 Hz | | | | |
| PW1.5DV | 1/20 | | | 41 |
| PW2.0DV | 1/15 | | | 52 |
| PW2.5DV | 1/12 | | | 62 |
| PW3.0DV | 1/10 | | | 72 |
| PW3.5VK | 1/10+ | | | 78 |
| PW4.0VK | 1/8 | | | 86 |
| PW4.5VK | 1/6 | | | 108 |

Test Conditions (ASHRAE)

GW: 6.40kgs

Conveyance:


Qty/20' FCL: 6,000pcs

Qty/40' FCL: 13,000pcs

Qty/40' HQ: 16,000pcs



PW2.0VKMF   
 220-240V~50/60Hz A002364 
 SINGLE PHASE R134a
 THERMALLY PROTECTED
 Sichuan Danfu Environment Technology Co., Ltd.

 REDMI NOTE 9 PRO
 AI QUAD CAMERA