

ML90FB , CUBIGEL , R404A / R507, LBP, COMPRESSEUR HERMÉTIQUE , 1/3HP, 230V 50Hz

written by Lilianne | 10 May 2020

ML90FB , CUBIGEL , R404A / R507, LBP, COMPRESSEUR HERMÉTIQUE
, 1/3HP, 230V 50Hz

QD110H , Chest Freezer Compressor , 1/3HP , 220V/50Hz , R134A

written by Lilianne | 10 May 2020

1/3HP Refrigeration Compressor 220V/50Hz R134A

AC Compressor: R134A Hermetic LBP Piston Reciprocating
Compressor

Model: WQ110H

Power Supply: 220-240/50-60V/Hz

Displacement: 11CC

Nominal Power: 1/3HP

Rated Power: 233W

Cooling Capacity: 280W

COP: 1.20W/W

Motor Type: RSIR

Starting relay: Starting Relay/PTC

Starting Capacitor: / μ F

Running Capacitor: / μ F

Cooling Type: F

Application: LBP

Certificate: 3C
1X20'FCL: 1600PCS



PictureS Mbsm Dot Pro : www.mbsm.pro

Application:

LBP: Low back pressure; Refrigerator, Freezer, Wine cooler
MBP: Medium Back Pressure; Air-conditioner, vending machine
HBP: High Back Pressure: Air-conditioner, ice maker

LBP ASHRAE Test Condition:

Evaporation Temperature: -23.3 °C
Condensing Temperature: 54.4 °C
Subcooling Temperature: 32.2 °C
Ambient Temperature: 32.2 °C

MBP ASHRAE Test condition:

Evaporation Temperature: -5 °C
Condensing Temperature: 54.4 °C
Ambient Temperature: 35 °C
Subcooling Temperature: 46.1
Suction Temperature: 35 °C

HBP ASHRAE Test condition:

Evaporation Temperature: 7.2°C
Condensing Temperature: 54.4°C
Ambient Temperature: 35°C
Subcooling Temperature: 46.1°C
Suction Temperature: 35°C

Parameter Variation Range:

Cooling Capacity: $\geq 95\%$
Input Power: $\leq 115\%$
Current: $\leq 110\%$
COP: $\geq 95\%$

Cooling Type:

S: Natural cooling
F1: Fan cooling, 200mm fan diameter, 1.5m/s air speed
F2: Fan cooling, 200mm fan diameter, 3m/s air speed

**Mbsm.pro , Qb91c19gax5 , 1/4
hp, qb110c21rpx5, 1/3 hp,
Panasonic ,Compressor cooling
,1Ph ,220V**

written by Jamila | 10 May 2020



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm.pro , Qb91c19gax5 ,Panasonic ,Compressor cooling , 1/3HP
,236W ,1Ph ,220V