

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Category: Solutions,Tester ok

written by Jamila | 6 October 2018

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co., Ltd,
69 YL ,1/4 Hp ,168Kcal , 220V

Test conditions	According to ASHRAE
Evaporating temperature	-23.3[°C]
Condensing temperature	54.4[°C]
Subcooling temperature	32.2[°C]
Suction temperature	32.2[°C]
Ambient temperature	32.2[°C]
Working condition limit:R134a	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4/0.4Mpa(gauge pressure)187V/98V

Product model:HYE69YL

Cooling capacity:195W

COP[W/W]:1.15

Voltage[V]:220-240~

Frequency(Hz):50



PictureS Mbsm Dot Pro : www.mbsm.pro

Products

- R134a Compressor (LBP)
 - HYE Serie
 - HY Serie
 - HYB Serie
 - HYS Serie
- R600a Compressor (LBP)
 - HYE Serie
 - HY Serie
 - HYB Serie
 - HYS Serie
- R134a Compressor (MBP,HBP)
 - HY Serie
 - HYE Serie

[Newest Catalog Download](#)

Product model:HYE69YL
 Cooling capacity:195W
 COP (W/W) :1.15
 Voltage (V) :220-240~
 Frequency(Hz):50

Test conditions	According to ASHRAE
Evaporating temperature	-23.3°C
Condensing temperature	54.4°C
Subcooling temperature	32.2°C
Suction temperature	32.2°C
Ambient temperature	32.2°C
Working condition limit:R134a	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4/0.4Mpa(gauge pressure)187V/98V

PictureS Mbsm Dot Pro : www.mbsm.pro



AE 1330 Y

1 / 12 HP



AE 1340 Y

1 / 6 HP



AE 1350 Y

1 / 6 HP



AE 1360 Y

1 / 5 HP



AE 1370 Y

1 / 4 HP



AE 1390 Y

1 / 4 HP



HY 81 Y

1 / 4 HP



HYE 55 YL 63

1 / 6 HP



HYE 60 YL 63

1 / 5 HP



HYE 69 YL

1 / 4 HP



HYE 125 MSU

1 / 4 HP





Huayi HYE 69 YL 1/4 Hp 168Kcal R134a 220V

Huayi - Huayi

Huayi HYE 55 YL 63 1/6 Hp 129Kcal R134a 220V

Huayi - Huayi

Huayi HYE 60 YL 63 1/5 Hp 146Kcal R134a 220V

Huayi - Huayi

Huavi HY 81 Y 1/4+ Hp 202Kcal R134a 220V

PictureS Mbsm Dot Pro : www.mbsm.pro



HYE 125 MSU

HYE 69 YL

HYE 60 YL 63

HYE 55 YL 63

HY 81 Y

AE 1390 Y

AE 1370 Y

AE 1360 Y

AE 1350 Y

AE 1340 Y

AE 1330 Y

PictureS Mbsm Dot Pro : www.mbsm.pro






Mbsm.pro , Qb73c15gax5 , R134a , Refrigeration Compressor , 1/4 Hp, Panasonic compressor catalogue, QB series , 1Ph , 220V 50Hz

Category: Solutions, Tester ok
written by Jamila | 6 October 2018



Mbsm.pro , Qb73c15gax5 , R134a , Refrigeration Compressor , 1/4 Hp, Panasonic compressor catalogue, QB series , 1Ph , 220V 50Hz

Rated voltage / Frequency	Model	ASHRAE								Voltage range
		50Hz				60Hz				
		Capacity		COP - WW		Capacity		COP - WW		
		W	kcal/hr	RSIR	RSCR	W	kcal/hr	RSIR	RSCR	
220V 50Hz/60Hz	QB51C99GAX0	128	110	1.14	-	157	135	1.17	-	170V-250V 50Hz 187V-242V 60Hz
	QB57C11GAX0	146	126	1.18	-	175	151	1.22	-	
	QB66C16GAX0	165	142	1.20	-	200	172	1.27	-	
	QB77C18GAX0	202	174	1.21	-	224	193	1.27	-	
	QB91C24GAX0	236	203	1.19	-	255	219	1.22	-	
220V 50Hz	QB66C13GAX5	165	142	1.19	-					170V-250V
	QB73C15GAX5	185	159	1.19	-					
	QB77C16GAX5	202	174	1.22	-					
	QB91C19GAX5	236	203	1.25	-					



Rated voltage / Frequency	Model	ASHRAE								Voltage range
		50Hz				60Hz				
		Capacity		COP - WW		Capacity		COP - WW		
		W	kcal/hr	CSIR	RSCR	W	kcal/hr	CSIR	RSCR	
220V 50z/60Hz	QB110C25CAX0	273	235	1.18	-	279	240	1.19	-	170V-250V 50Hz 198V-242V 60Hz

PictureS Mbsm Dot Pro : www.mbsm.pro



PictureS Mbsm Dot Pro : www.mbsm.pro

Performance DATA

Application & Refrigerant LBP R134a

Voltage	Model	Displacement cm ³	*2) Capacity (W)					*3) C.O.P.		*4) Motor type	Compressor cooling *5)			Net weight kg		Oil charge cm ³	
			Evaporating temperature					NO	YES		ST	OC	FC	ST/FC	OC	ST/FC	OC
			-30°C	-25°C	-23.3°C	-20°C	-15°C										
*6) 100V 50/60Hz	QB57C88RA00	5.65	118	161	178	213	271	1.27	1.33	RSIR/RSCR	O	-	O	9.1	-	250	-
	QB66C12CA00	6.55	119	164	185	219	293	1.19	-	CSIR	-	-	O	8.8	-	250	-
	QB66C13RA00	6.55	133	182	200	239	304	1.28	1.37	RSIR/RSCR	O	-	O	9.4	-	280	-
	QB86C18TA00	8.56	170	226	248	295	376	-	1.35	CSCR	-	-	O	9.9	-	280	-
	QB91C18CA00	9.07	163	226	251	303	394	-	1.21	CSIR	-	-	O	9.6	-	250	-
220V 50Hz	QB66C13GAX5	6.55	108	149	165	200	263	1.23	-	RSIR	O	-	-	9.2	-	250	-
	QB73C15GAX5	7.27	121	167	185	224	294	1.23	-	RSIR	O	O	-	9.7	9.9	250	300
	QB77C16GAX5	7.69	131	182	202	245	319	1.26	-	RSIR	O	O	-	9.8	10.0	250	300
	QB86C18GAX5	8.56	145	200	222	268	347	1.26	-	RSIR	O	O	O	9.9	10.1	250	300
	QB91C19GAX5	9.07	154	213	236	285	372	1.29	-	RSIR	O	O	O	10.2	10.5	250	300
	QB110C25GAX5	10.86	176	246	273	331	432	1.18	-	RSIR	-	O	O	10.4	10.6	250	300
*4) 220-240V 50Hz	QB51C74GAW5	5.10	84	116	128	153	196	1.21	-	RSIR	O	-	-	8.7	-	250	-
	QB57C87GAW5	5.65	97	132	146	175	225	1.23	-	RSIR	O	-	-	8.9	-	250	-
	QB66C97GAW5	6.55	108	149	165	200	263	1.25	-	RSIR	O	O	-	9.2	-	250	-
	QB73C12GAW5	7.27	121	167	185	224	294	1.26	-	RSIR	O	O	-	9.7	-	250	-
	QB77C13GAW5	7.69	131	182	202	245	319	1.27	-	RSIR	O	O	-	9.8	-	250	-
	QB86C13GAW5	8.56	145	200	222	268	347	1.27	-	RSIR	O	O	O	9.9	-	250	-
	QB91C16GAW5	9.07	154	213	236	285	372	1.28	-	RSIR	O	O	O	10.0	-	250	-



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm.pro , Fn77q17g , 1/4Hp , Electrostar , R12 Refrigerator Compressors , 220V/50-60Hz , 1Ph ,for Refrigerator/Freezer

Category: Solutions,Tester ok
written by Jamila | 6 October 2018



PictureS Mbsm Dot Pro : www.mbsm.pro

Mbsm.pro , Fn77q17g , 1/4Hp , Electrostar , R12 Refrigerator Compressors ,
220V/50-60Hz , 1Ph ,for Refrigerator/Freezer



PictureS Mbsm Dot Pro : www.mbsm.pro

- 1) SO60LKAA OR equivalent in 1/10 HP
- 2) FN43Q88G OR equivalent in 1/8 HP
- 3) FN51Q10G OR equivalent in 1/6 HP
- 4) FN57Q12G OR equivalent in 1/5 HP
- 5) FN66Q14G OR equivalent in 1/5 HP Powerful
- 6) **FN77Q17G** OR equivalent in 1/4 HP
- 7) FN91Q20G OR equivalent in 1/4 HP Powerful
- 8) FN110Q24G OR equivalent in 1/3 HP



PictureS Mbsm Dot Pro : www.mbsm.pro

Compressor tests - Calorimeter

Type		FN77Q17G 1)	QA77C17GAX5	QA91C22GAX5
Parameter				
Evaporation temp.	[°C]	LBP -23,3	LBP -25 2) -23,3	LBP -25 -23,3
Refrigerant		R12	R134a	R134a
Q _o				
CECOMAF	[W]		116,7	135
ASHRAE	[W]	191	154,2	187,1
ASHRAE	[kcal/h]	165	132,6	161
P ₁				
CECOMAF	[W]		144,1	166,4
ASHRAE	[W]	180	148,4	171,4
COP				
CECOMAF	[W/W]		0,81	0,81
ASHRAE	[W/W]	1,06	1,04	1,09
Start test				
cold tw = 32 °C		-	o.k	o.k
warm tw = 100 °C		-	o.k	o.k

1) Leaflet data, original compressor


2) average two compressors, measuring



- 1) S060LKAA OR equivalent in 1/10 HP
- 2) FN43Q88G OR equivalent in 1/8 HP
- 3) FN51Q10G OR equivalent in 1/6 HP
- 4) FN57Q12G OR equivalent in 1/5 HP
- 5) FN66Q14G OR equivalent in 1/5 HP Powerful
- 6) FN77Q17G OR equivalent in 1/4 HP
- 7) FN91Q20G OR equivalent in 1/4 HP Powerful
- 8) FN110Q24G OR equivalent in 1/3 HP



MODEL FN77Q17G
220V ~ 50Hz 1PH R-12
THERMALLY PROTECTED
MATSUSHITA ELECTRIC IND. CO., LTD.
SINGAPORE



MODEL FN77Q17G
220 V ~ 50Hz 1PH R-12
THERMALLY PROTECTED
MATSUSHITA ELECTRIC IND. CO., LTD.
SINGAPORE

www.mbsm.pro , compressor, R134a
, ff16hak ,170 watt ,1/4 HP ,1PH

Category: Solutions,Tester ok

written by Jamila | 6 October 2018

www.mbsm.pro , compressor, R134a ,ff16hak ,170 watt ,1/4 HP ,1PH