

**COMPRESSOR, DANFOSS, NL8.4MF,  
R134A, 1/4HP, 8.35CM3,  
Compressor Danfoss Secop  
NL8.4MF, 105G6879, MBP -  
R134a, 220-240V/1/50Hz,  
discharge 8.35 cm3, motor  
type RSIR / CSIR, oil type  
POE, oil charge 320 cm3, 741  
W at +7.2 / +55° C, LRA 11.7  
A, maximum refrigerant charge  
600 g, height: 197 mm, weight  
10.5 kg**

written by Lilianne | 13 December 2021  
230V 50/60HZ

## **FICHE TECHNIQUE COMPRESSEUR DANFOSS NL8.4MF AU R134A 1/4HP 8.35CM3**

Puissance HP	1/4
Tension (V)	230
Fréquence (Hz)	50/60
Marque pie	DANFOSS
Cylindrée	8.35

Référence marque NL8.4MF



Private Picture Copyright : WWW.MBSM.PRO



R134a	refrigerant	605089	رقم القطعة
HP 1/4	power	NL8.4MF	type
RSIR/CSIR	motor system	cm <sup>3</sup> 8.35	cylinder capacity
W 491	power at -5°C	W 390	power at -10°C
W 749	power at +5°C	W 610	power at 0°C
W 235	power at -20°C	W -	power at -25°C
W 912	power at +10°C	W 305	power at -15°C
HMBP	application	ASHRAE	test method
Hz 50	frequency	kg 10.5	weight
mm 197	height	V 220-240	voltage

Private Picture Copyright : WWW.MBSM.PRO

Mbsm\_dot\_pro\_private\_PDF\_NL8.4MFTélécharger

# Cubigel Compressors, Compressor, GQY80AT, 1/4Hp, LBP, R134a, 8.1cmc,165 W, REFRIGERATEUR INDESIT

written by Lilianne | 13 December 2021

Compresor GQY80AT, freon R134a, capacitate 8.1  
cmc, capacitate frigorifica ASHRAE 222 W, capacitate  
frigorifica CECOMAF 165 W, racire statica #GQY80AT

Model: GQY80AT

Freon: R134a

Capacitate: 8.1 cmc

Capacitate frigorifica ASHRAE: 222 W

Capacitate frigorifica CECOMAF: 165 W

35 -30 -25 -10 w COP

• 451.00.3301 GD40AAa / GUY40AA 1/10 S 4.03 34 49 70 0.77 154  
C 200 6.7 RSIR P •

451.00.3202 GD40AA 1/10 S 4.03 34 49 70 0.77 154 C 200 6.7  
RSIR P •

• 451.00.3302 GL45AA / GUY44AA 1/8 S 4.55 37 56 81 0.81 183 C  
265 8.3 RSIR P •

• 451.00.3303 GL60AA / GUY57AA 1/6 S 5.99 50 75 107 0.85 238 C  
265 9.1 RSIR P •

• 451.00.3304 GL75AA / GUY66AA 1/5 S 6.65 57 85 121 0.87 267 C  
345 9.6 RSIR P •

• 451.00.3305 GL80AA / GUY75AA 1/5 S 7.52 68 101 144 0.89 326  
C 345 9.9 RSIR P •

451.00.3104 GL80AAb 1/5 OC 8.10 68 101 144 0.89 326 C-V 345  
9.9 CSIR R •

451.00.3005 GL90AA 1/4 S 9.08 82 119 165 0.90 350 C 345 10.2  
RSIR P •

• 451.00.3306 GL90AAa / GQY80AT 1/4 S 9.08 82 119 165 0.90 350  
C 345 10.2 RSIR P •

451.00.3105 GL90AAb 1/4 OC 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •

- 451.00.3205 GL90AAb 1/4 F 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •
- 451.00.3325 GL90AAa 1/4 OC 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •

451.00.3106 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400 11.5  
RSIR R •

- 451.00.3206 GP12FB 1/3 F 12.00 83 131 190 0.88 424 C 400  
11.5 RSIR R •
- 451.00.3326 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400  
11.5 RSIR R •

451.00.3218 GP14CB 3/8 F 14.17 99 158 228 0.90 509 C 400 11.5  
RSIR R •

451.00.3223 GP16FB 3/8 F 16.15 109 182 266 0.89 585 C-V 530  
12.0 CSIR R •

451.00.3224 GX18FB 3/7 F 18.40 123 199 291 0.91 660 C-V 500  
15.1 CSIR R •

451.00.3225 GX21FB 2/3 F 20.72 151 243 351 0.93 778 C-V 500  
15.5 CSIR R •

451.00.3403 GL45TB 1/6 F 4.50 76 134 342 1.62 412 C-V 300 8.4  
CSIR R •

- 451.00.3503 GL45PB 1/6 F 4.50 76 134 342 1.62 412 C-V 300  
8.4 CSIR R •

451.00.3404 GL60TB 1/5 F 5.67 95 170 437 1.82 527 C-V 300 9.5  
CSIR R •

- 451.00.3504 GL60PB 1/5 F 5.67 95 170 437 1.82 527 C-V 300  
9.5 CSIR R •

451.00.3406 GL80TB 1/5 F 7.57 111 212 554 1.83 667 C-V 300 9.5  
CSIR R •

- 451.00.3505 GL90TB 1/4 F 8.85 142 259 661 1.91 796 C-V 300  
10.8 CSIR R •
- 451.00.3506 GP12TB 3/8 F 12.05 169 338 893 1.80 1077 C-V 350  
11.2 CSIR R •

451.00.3418 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400  
11.5 CSIR R •

- 451.00.3513 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400  
11.5 CSIR R •
- 451.00.3419 GX18TB 1/2 F 18.40 285 539 1390 1.91 1673 C-V 500  
16.0 CSIR R •
- 451.00.3420 GX21TB 5/8 F 20.72 332 603 1550 1.90 1866 C-V 500  
17.0 CSIR R •
- 451.00.3421 GX23TB 5/8 F 23.20 368 677 1730 1.89 2083 C-V 500  
17.0 CSIR R •
- 451.00.3422 GS26TB 3/4 F 25.93 392 771 2071 2.09 1011 C-V  
887 22.7 CSIR R •
- 451.00.3423 GS30TB 7/8 F 29.95 317 785 2452 2.33 3020 C-V 887  
22.7 CSR R •
- 451.00.3424 GS34TB 1 F 34.42 476 1068 2852 2.28 3421 C-V 887  
22.7 CSR R •



**ZEL** **GQY80AT** 0545  
200-220V~50Hz  
R134  
B 706726R

BAJA presión					serie LBP						R-134a					
CÓDIGO REMLE	MODELO	Potencia	Enfri.	Cilindr.	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
* Gases sustitutivos del R-12 y R-134a.					CECOMAF (W)											
o Últimas existencias					-35	-30	-25		-10							
					w	COP										
• 451.00.3301	GD40AAa / GVV40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
o 451.00.3202	GD40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
• 451.00.3302	GL45AA / GVV44AA	1/8	S	4.55	37	56	81	0.81	183	C	265	8.3	RSIR	P	•	
• 451.00.3303	GL60AA / GVV57AA	1/6	S	5.99	50	75	107	0.85	238	C	265	9.1	RSIR	P	•	
• 451.00.3304	GL75AA / GVV66AA	1/5	S	6.65	57	85	121	0.87	267	C	345	9.6	RSIR	P	•	
• 451.00.3305	GL80AA / GVV75AA	1/5	S	7.52	68	101	144	0.89	326	C	345	9.9	RSIR	P	•	
o 451.00.3104	GL80AAb	1/5	OC	8.10	68	101	144	0.89	326	C-V	345	9.9	CSIR	R	•	
o 451.00.3005	GL90AA	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
• 451.00.3306	GL90AAa / GQY80AT	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
o 451.00.3105	GL90AAb	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3205	GL90AAb	1/4	F	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3325	GL90AAa	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
o 451.00.3106	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3206	GP12FB	1/3	F	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3326	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
451.00.3218	GP14CB	3/8	F	14.17	99	158	228	0.90	509	C	400	11.5	RSIR	R	•	
451.00.3223	GP16FB	3/8	F	16.15	109	182	266	0.89	585	C-V	530	12.0	CSIR	R	•	
451.00.3224	GX18FB	3/7	F	18.40	123	199	291	0.91	660	C-V	500	15.1	CSIR	R	•	
451.00.3225	GX21FB	2/3	F	20.72	151	243	351	0.93	778	C-V	500	15.5	CSIR	R	•	

Private Picture Copyright : WWW.MBSM.PRO

ALTA - MEDIA presión					serie HMBP						R-134a					
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
* Gases sustitutivos de R-12 y R-134a.					CECOMAF (W)											
o Últimas existencias					-25	-15	5		10							
					w	COP										
o 451.00.3403	GL45TB	1/6	F	4.50	76	134	342	1.62	412	C-V	300	8.4	CSIR	R	•	
• 451.00.3503	GL45PB	1/6	F	4.50	76	134	342	1.62	412	C-V	300	8.4	CSIR	R	•	
o 451.00.3404	GL60TB	1/5	F	5.67	95	170	437	1.82	527	C-V	300	9.5	CSIR	R	•	
• 451.00.3504	GL60PB	1/5	F	5.67	95	170	437	1.82	527	C-V	300	9.5	CSIR	R	•	
451.00.3406	GL80TB	1/5	F	7.57	111	212	554	1.83	667	C-V	300	9.5	CSIR	R	•	
• 451.00.3505	GL90TB	1/4	F	8.85	142	259	661	1.91	796	C-V	300	10.8	CSIR	R	•	
• 451.00.3506	GP12TB	3/8	F	12.05	169	338	893	1.80	1077	C-V	350	11.2	CSIR	R	•	
o 451.00.3418	GP14TB	3/8	F	14.00	190	373	999	1.77	1208	C-V	400	11.5	CSIR	R	•	
• 451.00.3513	GP14TB	3/8	F	14.00	190	373	999	1.77	1208	C-V	400	11.5	CSIR	R	•	
451.00.3419	GX18TB	1/2	F	18.40	285	539	1390	1.91	1673	C-V	500	16.0	CSIR	R	•	
451.00.3420	GX21TB	5/8	F	20.72	332	603	1550	1.90	1866	C-V	500	17.0	CSIR	R	•	
451.00.3421	GX23TB	5/8	F	23.20	368	677	1730	1.89	2083	C-V	500	17.0	CSIR	R	•	
• 451.00.3422	GS26TB	3/4	F	25.93	392	771	2071	2.09	1011	C-V	887	22.7	CSIR	R	•	
451.00.3423	GS30TB	7/8	F	29.95	317	785	2452	2.33	3020	C-V	887	22.7	CSR	R	•	
• 451.00.3424	GS34TB	1	F	34.42	476	1068	2852	2.28	3421	C-V	887	22.7	CSR	R	•	

Private Picture Copyright : WWW.MBSM.PRO

BAJA presión					serie LBP						R-600a						
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz	
					-35	-30	-25	-23.3	-20	-15	-10						
451.00.0605	HQY55AA	1/9	S	5.46	28	44	62	69	83	105	130	C	210	8.9	RSIR/RSCR	P	•
451.00.0610	HQY70AA	1/8	S	6.64	42	59	80	88	104	131	161	C	210	9.0	RSIR/RSCR	P	•
451.00.0615	HLY99AA	1/6	S	9.93	69	90	119	130	155	198	248	C	345	9.6	RSIR/RSCR	P	•
451.00.0620	HPY12AA	1/5	S	12.10	79	107	143	157	187	239	299	C	300	10.7	RSIR/RSCR	P	•
451.00.0625	HPY14AA	1/5	S	14.31	92	124	165	181	215	274	342	C	300	11.0	RSIR/RSCR	P	•
451.00.0630	HPY16AA	1/4	S	16.14	102	136	180	198	236	302	379	C	300	11.2	RSIR/RSCR	P	•

Private Picture Copyright : WWW.MBSM.PRO



ALTA - MEDIA presión				serie HMBP										R-22				
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watts.								Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
					-20	-15	-10	-5	0	5	7.2	10						
451.00.1404	L45TN	1/5	F	4.50	157	206	265	333	410	496	537	592	C-V	400	9.5	CSIR	P	•
451.00.1405	L57TN	1/4	F	5.67	194	255	327	410	505	610	660	727	C-V	300	9.5	CSIR	R	•
451.00.1428	L76TN	3/8	F	7.57	268	347	441	550	675	814	881	969	C-V	470	10.0	CSIR	R	•
451.00.1408	L88TN	3/8	F	8.85	523	416	527	658	806	973	1052	1159	C-V	400	10.6	CSIR	R	•
451.00.1409	P12TN	1/2	F	12.00	412	537	689	868	1075	1309	1421	1570	C-V	400	12.3	CSR	R	•
451.00.1416	S22TN	7/8	F	21.77	645	890						3000	C-V	887	22.7	CSR	R	•
451.00.1418	S26TN	1 1/4	F	25.93	857	1182	1561	1993	2480	3021	3275	3615	C-V	887	22.7	CSR	R	•

Private Picture Copyright : WWW.MBSM.PRO

ALTA - MEDIA presión				serie HMBP										sustituto del R-404a - R507 (*)				
220-240V 50Hz																		

CÓDIGO REMLE	MODELO	CV	Enfr.	Cil. cm3	Int. A	Conex.		Conex. aspir. Rotalock	Rendimientos (Wattios)*				Aplic.
						ODF	Rotalock		+7,2	-0°C	-5°C	-10°C	
451.00.0299	ML40TB	1/6	F	4.04	2,03	1/4"	-	3/16"	516	387	320	260	C-V
451.00.0300	ML45TB	1/5	F	4.50	2,19	1/4"	-	3/16"	559	432	356	289	C-V
451.00.0305	ML60TB	1/4	F	5.67	2,77	1/4"	-	3/16"	686	525	428	343	C-V
451.00.0310	ML80TB	3/8	F	7.57	3,27	1/4"	-	3/16"	931	720	590	475	C-V
451.00.0315	ML90TB	3/8	F	8.85	3,98	1/4"	-	3/16"	1118	861	705	569	C-V
451.00.0321	MP12RB	1/2	F	12.00	3,80	5/16"	-	1/4"	1765	1379	1142	931	C-V
451.00.0323	MP14RB	1/2	F	14.00	4,86	5/16"	-	1/4"	1765	1379	1142	931	C-V
451.00.0325	MX18TB	7/8	F	18.12	6,50	3/8"	-	1/4"	2275	1719	1379	1078	C-V
451.00.0326	MX21TB	1	F	21,74	6,28	3/8"	-	1/4"	2745	2063	1645	1275	C-V
451.00.0327	MS26TB-V	1 3/8	F	25.95	8,97	5/8"	1" 5/8"R	5/16"	3382	2578	2085	1647	C-V
451.00.0328	MA34TB-V	1 5/8	F	34,42	11,50	5/8"	1" 5/8"R	5/16"	4450	3480	2870	2310	C-V

Private Picture Copyright : WWW.MBSM.PRO





Compresor GQY80AT, freon R134a, capacitate 8.1 cmc, capacitate frigorifica ASHRAE 222 W, capacitate frigorifica CECOMAF 165 W, racire statica #GQY80AT

Model: GQY80AT

Freon: R134a

Capacitate: 8.1 cmc

Capacitate frigorifica ASHRAE: 222 W

Capacitate frigorifica CECOMAF: 165 W

Racire : statica



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_GQY80ATTélécharger

**FR6B, Compressor, 103U2654, FR6B 103U2654, DANFOSS TL, FR and SC Hermetic Compressors, DANFOSS, Kiriazi, 343L, 1/5 Hp, MBP, R12, 280g, équivalence, 1/4Hp, R134A, 190g**

written by Lilianne | 13 December 2021

# Compresseurs hermétiques DANFOSS TL, FR et SC

BOC partie No.	Code Danfoss	Puissance nominale et applic	Refrig.	Capacité nominale (watts)	Réf. BOC	Code Danfoss	Puissance nominale et applic	Réfrigérer	Capacité nominale (watts)
FR6B	103U2654	1/5 MBP	R12	354	TL3F	102G4300	1/10 LBP	R134a	58
FR8.5B	103U2854	1/4 MBP	R12	450	TL4F	102G4400	1/8 LBP	R134a	84
SC10B *	104L2510	1/3 MBP	R12	588	TL55F	102G4520	1/6 LBP	R134a	127
FR11B	103U2154	1/3 MBP	R12	624	TL57F	102G4720	1/5 LBP	R134a	162
SC12B *	104L2670	4/9 MBP	R12	756	NL7F	105G6706	1/4 LBP	R134a	183
SC15B *	104L2830	1/2 MBP (LBP)	R12 (R502)	912 (768)	NL9F **	105G6802	1/4 LBP	R134a	214
SC18B *	1042110	2/3 MBP (LBP)	R12 (R502)	1044 (900)	NL11F **	105G6910	1/4 LBP	R134a	274
SC21B	104L2310	3/4 MBP	R12	1212	SC15F **	104G8500	1/3 LBP	R134a	319
SC10B	104L2510	1/3 LBP	R502	468	SC18F **	104G8800	4/9 LBP	R134a	395
SC12B	104L2670	4/9 LBP	R502	612	TL3G	104G4350	1/8 MBP	R134a	175
SC15C	104L2832	2/3 LBP	R502	768	TL4G	102G4452	1/6 MBP	R134a	215
SC18C	104L2111	3/4 LBP	R502	900	FR6G	103G6660	1/5 MBP	R134a	351
SC10G	104G8000	1/3 MBP	R134a	591	FR8.5G	103G6780	1/4 MBP	R134a	468
SC12G	104G8240	4/9 MBP	R134a	751	FR11G	103G6980	1/3 MBP	R134a	609
SC18G	104G8820	2/3 MBP	R134a	1059	SC15G	104G8520	1/2 MBP	R134a	892
SC21G	104G8140	3/4 MBP	R134a	1256	SC10CL	104L2523	1/3 MBP	R507	450
SC12CL	104L2623	4/9 LBP	R507	624	SC15CL	104L2853	2/3 LBP	R507	758
SC18CL	104L2123	3/4 LBP	R507	893					

## Remarque:

1. Les compresseurs marqués \*\* sont équipés de raccords de refroidisseur d'huile.
2. Les compresseurs marqués \* peuvent être utilisés sur les systèmes R502 avec fonctionnement à tube capillaire dans la gamme LBP.
3. (Systèmes sans dégivrage automatique uniquement).

Capacités nominales basées sur:

LBP = -23,3 ° C température d'évaporation

MBP = -5 ° C température d'évaporation

<b>Relais de remplacement (appareil de démarrage)</b>	
<b>Réf. BOC</b>	<b>Convient au modèle de compresseur</b>

<b>103N0011</b>	TL3A à TL5A, FR7.5A à FR11A
<b>103N0002</b>	SC12A, SC15A





Private Picture Copyright : WWW.MBSM.PRO

FR6B	103 U26 54	1/ 5 M BP	R 1 2	3 5 4	T L 3 F	1 0 2 G 4 3 0 0	1 / 1 0 L B P	R 1 3 4 a	5 8
------	------------------	--------------------	-------------	-------------	------------------	--------------------------------------	---------------------------------	-----------------------	--------



Private Picture Copyright : WWW.MBSM.PRO

Mbsm\_dot\_pro\_private\_PDF\_103U2654Télécharger

---

# Compresseur, BAIXUE, 1/4HP ,MH79R45A, R134a, LBP, 220 240V 50Hz, Certificat:CCC, CE, CB, VDE, 205 W, RSIR

written by Lilianne | 13 December 2021

Lieu d'origine:

Jiangsu, Chine (continentale)

Modalités de paiement:

L / C, T / T

Marque:

BAIXUE

Modèle de produits:

MH79R45A

- Détails des produits
- Profil de la société

## Détails rapides

- Marque:BAIXUE

Numéro de modèle:MH79R45A

Lieu d'origine:Jiangsu, Chine (continentale)

- Type:Pièces de réfrigérateur

VOL./FRE:220 à 240 V / 50 Hz

Capacité (W):205

▪ COP W / W:1,35

Refroidissement:FC

Type de moteur:RSIR

▪ Certificat:CCC, CE, CB, VDE







从原白雪压缩机股份有限公司原产的白雪压缩机V系列

于1982年研制出国内第一台活塞连杆结构的全封闭制冷压缩机。经过不断的技术更新、设备升级，现拥有年产600万台无氟高效全封闭制冷压缩机的生产能力。

白雪压缩机厂严格按照标准要求组织生产经营，1997年获ISO9001质量体系认证证书；1999年获ISO14001环境管理体系认证证书。2008年，公司技术中心被国家发展和改革委员会批准为国家级企业技术中心，现有科技人员381人，直接从事产品研发的员工达264人，下设3个研究所，1个直属开发室和7个附属开发室，1个工艺工业设计室，3个中心（信息中心、质监试验中心、计量中心）和1个理化室，1个专利标准化资料室，1个技术公司。其中，研究所和直属开发室承担公司中长期的产品开发任务，附属开发室主要承担系列产品开发和改型工作。

目前，公司拥有V、S、O、D、K、T六大系列压缩机，2013年公司陆续推出A、M和F三个新压缩机系列。白雪压缩机厂产品已得到了众多知名公司的肯定和广泛使用，其中，小排量微型压缩机质优价廉，特别是最新研发的小排量微型高效压缩机，性能系数居同行领先地位。另外，在V系列压缩机基础上开发的12V、24V直流变速压缩机，在国内处于领先地位。

R600a	FY151R45A	15.1	245	1.5	220-240/50
R134a	FH126C45A	12.6	345	1.3	220-240/50
R134a	FH137C45A	13.7	375	1.3	220-240/50
R134a	FH151S45A	15.1	410	1.2	220-240/50
V系列					
R134a	QDH2500G	2.5	60/70	1	100/50/60, 115/60
R134a	VH23R45A	2.3	55	0.85	220-240/50
R134a	VH23R26D	2.3	65	0.9	220/60
R134a	VH23R16A	2.3	68	1.1	115/60
R134a	VH26R16A	2.8	83	1.1	115/60
R134a	VH23R16G	2.3	68	1.3	115/60
R134a	VH26R16G	2.8	83	1.3	115/60
M系列					
R134a	MH12R45A	7.9	205	1.3	220-240/50
R134a	MH92R45A	9.2	245	1.3	220-240/50
R134a	MH112R45A	11.2	295	1.25	220-240/50
V系列					
R600a	VY33C45D	3.3	55	1.3	220-240/50
R600a	VY33C45G	3.3	55	1.5	220-240/50
R600a	VY35R00A	3.5	50/60	1.12	100/50-60, 115/60
R600a	VY33R16G	3.3	60	1.3	115/60
R600a	VY43R16G	4.3	77	1.3	115/60
K系列					
R600a	KY55R45A	5.5	98	1.35	220-240/50
R600a	KY55C45D	5.5	98	1.45	220-240/50
R600a	KY48C45D	4.8	80	1.55	220-240/50
R600a	KY48C45G	4.8	83	1.75	220-240/50
R600a	KY55C45G	5.5	98	1.8	220-240/50
R600a	KY51R00A	5.1	88/98	1.35	100/50-60, 115/60
R600a	KY51R16G	5.1	98	1.4	115/60





®

MH79R45A



THERMALLY PROTECTED

220-240V ~ 50Hz 1PH

R134a



A001275



 **MH79R45A**    
THERMALLY PROTECTED  
220-240V ~ 50Hz 1PH  
R134A     
  
A001275

2020/12/26 17:16



# **Panasonic, Compressors (Fixed Speed), Q Series, R134a, LBP, QA91C22GAX5, RSIR , 207W ,1/4HP**

written by Lilianne | 13 December 2021

Panasonic, Compressors (Fixed Speed), Q Series, R134a, LBP, QA91C22GAX5, RSIR , 207W ,1/4HP

---

# **www.mbsm.pro, Beko Compressor, MTS170MT, R600A ,Capacity 170 kcal, 1/4HP , 197W , LBP, LRA 12.6 A ,1PH ,BEKO FRIDGE & FREEZER**

written by Lilianne | 13 December 2021

www.mbsm.pro, Beko Compressor, MTS170MT, R600A ,1/4HP , 1PH ,

# **BEKO FRIDGE & FREEZER**

## **More About This Product**

### **Fitting**

This product is manufactured and designed to be compatible or used with appliances of the brand or manufacturer listed above, or for selected commercial/domestic applications.

### **Other Information**

None, at present.

### **Product Classification**

This is a genuine original product made and supplied by the original equipment manufacturer (OEM). In order to maintain a valid warranty it is recommended to always use genuine original products. Genuine original products are specifically manufactured to increase the performance, functionality and life-span of your machine.

### **Manufacturer Information**

We stock and supply a range of Beko, Blomberg, Flavel, Leisure Arcelik Group products.

Beko has become one of the fastest growing brands in the UK offering today an extensive product range including refrigeration, laundry, dishwashers and television. Second largest brand in Turkey, its home market, Beko continues to develop the mission and the reputation to serve customers with innovative products that genuinely surprise them, like the New Xpress Washing machine. Beko has been operating in the UK & Ireland since 1990 and is the UK's Best-selling Large Home Appliance brand. Designed to make your life easier thanks to super-fast programmes and energy saving technology – Beko delivers exceptional value for money, providing smart,

innovative and energy efficient home appliances. Beko has achieved an average of 9 out of 10 review score from thousands of customer reviews for its range of American style fridge freezers, Built In Ovens and washing machines.

## **Consumables**

### **Bulk Ordering**

This product may be offered in bulk quantities, please refer to the box or pallet quantity in the specification box above. There may be a bulk discount available. In order to benefit from any discount available, add the box or pallet quantity (or multiples thereof) to your basket and the price will be updated automatically.

### **Related Items & Substitutes**

Where available we may have an alternative or substitute product, or other items we think you may be interested in. Please see below.

### **Still Having Trouble?**

If the information provided on this page still isn't sufficient for you to be certain it's what you require, please contact us for further assistance.





Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Mbsm\_dot\_pro\_private\_PDF\_ntu170mt-1Télécharger

---

**QB73C12GAW5, 185W, 1/4Hp ,  
RSIR, Q Series PANASONIC  
(Reciprocating Fixed Speed),  
R134a, LBP**

written by Lilianne | 13 December 2021

QB73C12GAW5, 185W, 1/4Hp , RSIR, Q Series PANASONIC  
(Reciprocating Fixed Speed), R134a, LBP

---

**Ideal Zanussi Comfort  
refrigerator , 340 L , 17  
Feet , Compresseur Cubigel  
,Compresseur ,GL90AA ,R-134a  
,1/4HP ,230V,non frost**

written by Lilianne | 13 December 2021



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Ideal Zanussi Comfort refrigerator , 340 L , 17 Feet ,  
Compresseur Cubigel ,Compresseur ,GL90AA ,R-134a ,1/4HP  
,230V,non frost

---

**COMPRESSEUR , Turkish  
Electric, NTU 170 MT,  
220-240V 50Hz, R600A ,POUR  
REFRIGERATEUR ,BEKO ,1/4HP ,  
LBP , LRA 12.4A ,197W,  
capacity 170KCal**

written by Lilianne | 13 December 2021

COMPRESSEUR , Turkish Electric, NTU 170 MT, 220-240V 50Hz,  
R600A ,POUR REFRIGERATEUR ,BEKO ,1/4HP , LBP , LRA 12.4A  
,197W, capacity 170KCal

---

**Compresseur Embraco ,Aspera,  
nbm1118y, nby1118y ,coolant  
,R600a ,NBY1118Y ,220-240V  
50Hz, LBP ,fully hermetic,  
10,8kg ,1/4HP**

written by Lilianne | 13 December 2021

ompresseur Embraco ,Aspera, nbm1118y, nby1118y ,coolant ,R600a  
,NBY1118Y ,220-240V 50Hz, LBP ,fully hermetic, 10,8kg  
,1/4HP,nbt1118y