

**Compressor, Zanussi, HLY80AA,  
1/7Hp, 220-240V 50Hz ~1,  
R600a, ZEM, Low Back  
Pressure, RSIR**

written by Lilianne | 26 January 2021



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

Technical Data Sheet  
Compressor model HLY80AAa  
Voltage 220-240V 50Hz ~1  
Refrigerant R600a

## APPLICATION COMPRESSOR MOTOR

Application Low Back Pressure Displacement 8,10 cm<sup>3</sup> Nominal Power 1/7 hp

Refrigerant R600a Diameter 24,29 mm Voltage/Frequency 220-240V 50Hz

Evaporating Temp. -35,0 °C to -10,0 °C Stroke 17,47 mm Voltage range 187-264 V

Expansion Capillar Net Weight 9,45 Kg Type RSIR

Comp. Cooling Static Oil type ISO VG 10 MINER Phase number 1 PH

Max. ambient temp. 43,0 °C Oil charge 205 cm<sup>3</sup> Locked Rotor Amps (LRA) 8,60 A

Max. Cont. Current (MCC) 1,00 A

Main W. resist. at 25°C 22,02 Ω

Start W. resist. at 25°C 22,53 Ω

## NOMINAL PERFORMANCE

### ASHRAE CECOMAF

Cooling Capacity 113 kCal/h 99 W

COP 1,41 W/W 1,11 W/W

EER 1,22 kCal/Wh 0,96 kCal/Wh

Input Power 93 W 89 W

Current 0,62 A 0,60 A

## TEST CYCLE CONDITIONS

### ASHRAE CECOMAF

LBP (B) LBP (A)

Evaporating temp. -23,3 °C -25,0 °C

Condensing temp. 55,0 °C 55,0 °C

Liquid temp. 32,0 °C 55,0 °C

Ambient temp. 32,0 °C 32,0 °C

Suction temp. 32,0 °C 32,0 °C

Voltage/Frequency 220 V 50 Hz 220 V 50 Hz

## ELECTRICAL COMPONENTS

Relay Option 1

Reference PTC K100

Voltage 200-240 V

Resistance 14.00 Ω

Protector Option 1 Option 2 Option 3 Option 4  
Reference MSP318LZ 4TM189NFBYY T0462 AE37FJ  
Current 5,90 A 5,50 A 6,20 A 5,90 A  
Time check 7,5-14 seg 5-15 seg 7,5-14 seg 7,5-14 seg  
Disc temp. (Open/Close) 120,00 / 61,00 °C 120,00 / 61,00 °C  
110,00 / 62,00 °C 115,00 / 62,00 °C

Mbsm\_dot\_pro\_private\_PDF\_HLY80aa\_danfoss\_HLY80AAa\_R600a\_220\_50  
Télécharger





Private Picture Copyright : WWW.MBSM.PRO

smart



---

# Compresseur, réfrigérateur, JIAXIPERA, 115W, 1/7HP, R600a, JM1110Y, RSIR, 220-240~/50

written by Lilianne | 26 January 2021



Private Picture Copyright: [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

压缩机型号	排量	电机型式	电压/频率	W	BTU/h	Kcal	W	W/W	BTU/Wh	W/W	总电容量 ( $\mu$ F)	
	(cm <sup>3</sup> )											
JM1080Y	6,0	RSIR	220-240 ~ / 50	100	341	86	75	1,45	4,95	1.13	/	CCC / VDE
<i>JM1080Y</i>	<i>6,0</i>	<i>RSIR</i>	<i>220-240 ~ / 50</i>	<i>100</i>	<i>341</i>	<i>86</i>	<i>75</i>	<i>1,45</i>	<i>4,95</i>	<i>1.13</i>	<i>/</i>	<i>VDE, CCC</i>
JM1110Y	7,0	RSIR	220-240 ~ / 50	118	403	101	89	1,45	4,95	1.13	/	CCC / VDE
<i>JM1110Y</i>	<i>7,1</i>	<i>RSCR</i>	<i>220-240 ~ / 50</i>	<i>118</i>	<i>403</i>	<i>101</i>	<i>89</i>	<i>1,42</i>	<i>4,85</i>	<i>1.11</i>	<i>/</i>	<i>VDE, CCC</i>
JK1080Y	6,0	RSCR	220-240 ~ / 50	100	341	86	75	1,55	5,29	1,21	4.0	CCC / VDE
<i>JK1080Y</i>	<i>6,0</i>	<i>RSCR</i>	<i>220-240 ~ / 50</i>	<i>100</i>	<i>341</i>	<i>86</i>	<i>75</i>	<i>1,55</i>	<i>5,29</i>	<i>1,21</i>	<i>3.0</i>	<i>VDE, CCC</i>
JK1110Y	7,0	RSCR	220-240 ~ / 50	118	403	101	89	1,55	5,29	1,21	4.0	CCC / VDE
JT1080Y	6,0	RSCR	220-240 ~ / 50	100	341	86	75	1,65	5,63	1,29	2,5	CCC / VDE
JT1110Y	7,0	RSCR	220-240 ~ / 50	118	403	101	89	1,65	5,63	1,29	2,5	CCC / VDE
JH1080Y	6,0	RSCR	220-240 ~ / 50	100	341	86	75	1,75	5,97	1,37	2,5	CCC / VDE
JH1111Y	7.4	RSCR	220-240 ~ / 50	128	437	110	96	1,75	5,97	1,37	3.0	CCC / VDE

Private Picture Copyright : WWW.MBSM.PRO

# Specifications

## Description

### Detailed Product Description

- 1.Low levels of noise and vibration
- 2.Standard,medium,high and very high levels of efficiency

Compressor Model	Displ. (cm <sup>3</sup> )	Cooling Type	Motor Type	Vol./Fre. (V~/Hz)	Capacity (W)		COP (W/W)	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF
					(-23.3°C)	(-25°C)	(-23.3°C)	(-25°C)
JM1080Y	6.02	ST	RSIR	220-240~/50	100	75	1.45	1.13
JM1110Y	7.04	ST	RSIR	220-240~/50	115	86	1.25	0.98
JM1111Y	7.70	ST	RSIR	220-240~/50	125	94	1.30	1.01
JK1080Y	6.02	ST	RSCR	220-240~/50	100	75	1.55	1.21
JT1080Y	6.02	ST	RSCR	220-240~/50	95	71	1.65	1.29

## Description

### Detailed Product Description

- 1.Low levels of noise and vibration
- 2.Standard,medium,high and very high levels of efficiency

Compressor Model	Displ. (cm3)	Cooling Type	Motor Type	Vol./Fre. (V~/Hz)	Capacity (W)		COP (W/W)	
					ASHRAE	CECOMAF	ASHRAE	CECOMAF
					(-23.3°C)	(-25°C)	(-23.3°C)	(-25°C)
JM1080Y	6.02	ST	RSIR	220-240~/50	100	75	1.45	1.13
JM1110Y	7.04	ST	RSIR	220-240~/50	115	86	1.25	0.98
JM1111Y	7.70	ST	RSIR	220-240~/50	125	94	1.30	1.01
JK1080Y	6.02	ST	RSCR	220-240~/50	100	75	1.55	1.21
JT1080Y	6.02	ST	RSCR	220-240~/50	95	71	1.65	1.29



Private Picture Copyright : WWW.MBSM.PRO

# COMPRESSEUR, Dongbei, (Donper) ,LBP , S série, S43CZ , 1/7Hp, R134a, RSIR

written by Lilianne | 26 January 2021

COMPRESSEUR, Dongbei, (Donper) ,LBP , S série, S43CZ , 1/7Hp,  
R134a, RSIR