

**Compressor, NL7.3FT, SECOP,
105G6726, DANFOSS, 6726,
105G, 105 G 6726, 105G 6726,
1/5 HP, 180W, LBP, Zanussi,
Kiriazi Electric Company, TGV
335L, NO FROST, TSV 320L, FC
83L , R134A, 125G, 220-240V
50Hz, CSIR**

written by Lilianne | 16 February 2021

R134a is a low pressure refrigerant, very efficient for high temperature applications.

This makes it ideal in air conditioning applications that may leak refrigerant like car air conditioning.

Now it is being phased out because of its high global warming potential and replaced by R134

R404a is a high pressure refrigerant ideal for applications in low and medium temperature.

You want low pressure refrigerants in household applications like refrigerators that may be inside kitchens with (possible) high ambient temperature, so you make sure nothing will blow up. For the same reason you want R134a in your car air conditioning.

R404a instead has pressures slightly above atmospheric in low temperature applications where R134a would have negative pressures and its heat transmission coefficients would be much lower.

Type de gaz	App	HP	Watt	Modèle	TL
R134A	LBP	1/6	134	TLY5.1FK	
R134A	LBP	1/4	183	TLES7FT.4	
R134A	LBP	1/5	156	NL6FT.2	NL
R134A	LBP	1/5	185	NL7.3FT (RSIR)	
R134A	LBP	+ 1/4	219	NL9FT.2 (RSIR)	
R134A	LBP	1/4	185	NL7.3FT (CSIR)	
R134A	LBP	+ 1/4	219	NL9FT.2 (CSIR)	
R134A	LBP	1/3	284	NL10FT	
R134A	MBP	1/3	621	NL11MF	
R404A	LBP	1/3	433	NL7CLX	
R404A	LBP	1/3	471	NL8.4CLX	
R134A	LBP	1/4	187	NLY6F	
R134A	LBP	+ 4 / (1)	213	NLY7F	
R134A	LBP	1/3	237	NLY9FK	
R600A	LBP	+ 1/4	227	NLE13KTK.2	
R600A	LBP	1/3	253	NLE15KTK.2	
R600A	LBP	+ 1/4	225	NLX13KK.3	
R600A	LBP	1/3	254	NLX15KK.3	

R134A	LBP / MBP / HBP	1/3	264	SC12G	SC
R134A	LBP / MBP / HBP	1/2	392	SC18G	
R134A	LBP / MBP / HBP	3/4	456	SC21G	
R134A	MBP	3/4	1073	SC21MFX	
R134A	LBP	3/4	567	SC21FTX	
R404A	LBP	1	1033	ST21CL	
R404A	LBP	1	986	SC18CLX.2	
R404A	MBP	1/2	359/650	SC15MLX	
R404A	MBP	7/8	762/1584	SC18MLX	

KIRIAZI



CE



ELECTRIC
COMPANY

®

Product

No Frost Refrigerator

Class

T

Model

E 335N/3

Current / Amp.

1.1/~

Rated Voltage

220-240V/50HZ

Refrigerant

R 134a

125g

Rated input of lamp

1 x 25 W

Total Gross Volume

335 L

Ins : Basic

Type II

IPX4

Total Storge Volume

320 L

Freezing Capacity

4 kg/24hr

Freezer Capacity

83L

ES 6000 / 2008
ES 3793 / 2006

Tow Door Ref.

Serial Number

Made in Egypt



REDMI NOTE 8
AI QUAD CAMERA

Private Picture Copyright : WWW.MBSM.PRO



Mbsm_dot_pro_private_PDF_NL7.3FTTélécharger



COMPRESSEUR, DANFOSS, SECOP, NL7.3MF, 105G6772 195B0370, 105G, 6773, R134a, 1 / 4L Hp, cylindrée 7.27 cc, displacement 7.27 cc, MBP

written by Lilianne | 16 February 2021

mbsm.pro, COMPRESSEUR, DANFOSS, SECOP, NL7.3MF, 105G6772
195B0370, 105G, 6773, R134a, 1 / 4L Hp++big, cylindrée 7.27
cc, displacement 7.27 cc, MBP

Détails techniques

220/230V 50/60Hz

puissance 1/4L HP – cylindrée 7,27 cc

gaz R134a MBP

DANFOSS 105G6772

FRIULINOX

FriulinoxArmoireréfrigérée AF12-14, AF12-14 VTR, AF12-14 VTRP,
AF14, AF6-1, AF6-7, AF6-7 VTR, AF7, AF7 VTR, AF7-14, AG60
GOLD, AG60 H20, AG60 SILVER, AG60 SILVERP, AG60P, AL-EN SUPER,
AL-EN1, AL-EN1 SUPER, AL-EN1P, AL-EN2, AL-EN2 SUPER, AL-ENP,
AP12-14, AP14, AP6, AP6-12, AP6-7, AP7, AP7-14, AR12-14,
AR12-14 VTR, AR14, AR6-12, AR6-12 VTR, AR6-7, AR6-7 VTR, AR7,
AR7-14, AR7-14 VTR, AR-EN GOLD, AR-EN SILVER, AR-EN1, AR-EN1

GOLD, AR-EN1 VTR, AR-EN2, AR-ENP, ARF142, ARP142, ARP-EN1, ARP-EN2, EN GOLD, EN P, EN SILVER, EN1, EN1 GOLD, EN1 H2O, EN1 H2O SILVER, EN1 SILVER, EN1 VTR, EN2, EN2 H2O

FriulinoxCellulede refroidissement ARP122

FriulinoxVitrineréfrigérée AFP122, AFP142, ARF122

INFRICO

InfricoArmoireréfrigérée AN-502-MX

InfricoComptoirneutre réfrigérée ME-1000-BAND, ME-1000-II, MP-1740-CN

InfricoTableréfrigérée BMPP-1500-EN, BMPPF-1500-II, EB-1500-II, ME-1000-PIZZA

...et d'autres dispositifs



Private Picture Copyright: WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_nl7.3mf-1Télécharger