


Mbsm.pro, Danfoss, Reciprocating, compressor, NLX11KK.2, 105H6971, NLX11KK.2 105H6971, 1/4 hp++, 1/3 hp-, r600a

written by mahdi miled | 10 November 2022



			-35	-30	-20	-15	-10	-5	0	5	[W]	[W/W]	[W/W]	[W]	[kcal/h]	[W/W]	[kcal/Wh]			
Energy-optimized	1.	PLE35K	101H0360			38	52	68	87	109		27		0.68	38	33				
		TLES4KK.3	102H4438	19	29	57	75	96				42	0.90		57	49	1.18			
		TLES4.8KK.3	102H4538	28	40	73	94	119				55	1.00		74	65	1.30			
	2.	TLES5.7KK.3	102H4638	36	50	89	114	144				68	1.02		91	79	1.32			
		TLES6.5KK.3	102H4738	45	61	105	134	168				81	1.02		108	94	1.31			
		TLES7.5KK.3	102H4838	53	71	122	155	194				94	1.02	1.07	126	108	1.32	1.14		
	3.	TLES8.7KK.3	102H4938	62	83	143	181	228				110	1.03	1.08	147	126	1.33	1.14		
		TLES10KK.3	102H4038									130	1.04		172	148	1.35	1.15		
		NLE8.8KK.4	105H6800	63	84	141	179	223				110	1.18	1.22	147	127	1.51	1.30		
	4.	NLE10KK.4	105H6867	74	98	164	207	257				128	1.19	1.23	170	151	1.51	1.30		
		NLE11KK.4	105H6952	82	109	184	232	290				143	1.19	1.22	191	165	1.52	1.31		
		NLE13KK.4	105H6959	99	131	217	274	340				170	1.18	1.23	226	194	1.50	1.29		
	High Energy-optimized	1.	NLE15KK.4	105H6968	110	146	243	307	382				190	1.20	1.25	253	213	1.53	1.32	
			2.	TLY4 KK.3	102H4442	19	29	57	74	95				42	0.96	0.99	57	49	1.26	1.08
				TLY4.8KK.3	102H4542	28	40	73	94	119				55	1.04	1.06	74	65	1.35	1.16
TLY5.7KK.3		102H4642		36	51	89	114	144				68	1.03	1.06	91	79	1.33	1.15		
3.		TLY6.5KK.3	102H4742	46	62	106	135	170				82	1.10	1.14	110	94	1.42	1.22		
		TLY7.5KK.3	102H4842	53	71	122	155	194				94	1.09	1.14	126	108	1.41	1.22		
		TLY8.7KK.3	102H4942	65	86	144	182	227				112	1.12	1.16	149	126	1.44	1.24		
3.		TLX4KK.3	102H4447	21	32	59	76	95				45		1.15***	60	52				
		TLX4.8KK.3	102H4547	36	52	90	116	146				57		1.24***	76	65				
		TLX5.7KK.3	102H4647	37	52	91	115	143				70		1.28***	93	80				
3.		TLX6.5KK.3	102H4747	46	63	106	133	165				83		1.30***	110	95				
		TLX7.5KK.3	102H4847	55	75	125	157	195				98		1.32***	130	112				
		TLX8.7KK.3	102H4947	65	88	146	184	227				115		1.31***	152	131				
1.		NLX8.8KK	105H6874	60	83	144	182	227				111		1.35	148	127				
		NLX10KK	105H6871	74	100	169	215	269				131		1.36	174	150				
	NLX11KK	105H6984	84	112	189	240	300				147		1.36	195	168					
	NLX13KK	105H6983	98	133	223	282	350				174		1.36	231	199					
	NLX15KK	105H6981	110	147	249	317	397				193		1.34	257	221					
	NLX8.0KK.2	105H6010	52	73	130	167	210				99		1.47***	133	115					
	NLX8.8KK.2	105H6011	62	85	147	187	234				113		1.49***	151	130					
2.	NLX10KK.2	105H6101	75	101	171	217	271				133		1.49***	178	153					
	NLX11KK.2	105H6971	86	115	192	242	301				150		1.49***	200	172					

Private Picture Copyright : WWW.MBSM.PRO

Description

Product details

Gross weight	12.47 kg
Net weight	12.47 kg
Gross weight	12.47 kg

Net weight	12.47 kg
-------------------	----------

Application energy level	High Energy-optimized
Applications	LBP
Auxiliary winding resistance (start winding) for single-phase compressors alt [Ohm]	31.8 Ohm
Base plate type	EU small
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Black
Compressor power supply [V/Ph/Hz]	220-240/1/50
Configuration code	Single
Cut in current LST [A]	6.4 A
Description	NLX11KK.2
Discharge connection angle [°]	21 °
Discharge connection comments	Al-cap
Discharge connection diameter [mm]	5 mm
Discharge connection material	Cu-plated steel
Economizer	No
Free gas volume [cm3]	2360 cm3
Frequency [Hz]	50
Height from baseplate [mm]	197 mm
High value of nominal voltage at 50Hz [V]	240 V
High value of voltage range at 50Hz [V]	255 V
Length [mm]	252 mm
Liquid injection	No

Low value of nominal voltage at 50Hz [V]	220 V
Low value of voltage range at 50Hz [V]	187 V
LRA LST [A]	3.5 A
Main winding resistance for single-phase compressors [Ohm]	18.5 Ohm
Model number	NLX11KK.2
Motor type	RSCR
No. of phases (compressor)	1
Oil quantity [cm³]	270 cm ³
Oil type	POE
Packing format	Industrial pack
Packing quantity	80
Process connection angle [°]	25 °
Process connection comments	Al-cap
Process connection diameter [mm]	6.2 mm
Process connection material	Cu-plated steel
Refrigerant	R600a
Refrigerant charge [kg] [Max]	0.15 kg
RLA	0.70 A
Rotational speed at 50Hz [rpm]	3000 rpm
Run capacitor capacitance	2 µF
Segment usage	Refrigeration LT
Speed Platform	Fixed-speed
Suction connection angle [°]	2 °
Suction connection comments	Al-cap
Suction connection diameter [mm]	6.2 mm
Suction connection material	Cu-plated steel
Swept volume [cm³]	11.15 cm ³

Technology	Reciprocating
Total height [mm]	203 mm
Type	NL
Type designation	Compressor
Voltage 50Hz [V]	220 V
Voltage 50Hz [V] [Max]	240 V
Width [mm]	166 mm
Winding temperature short term [°C] [Max]	110 °C
Winding temperature stat [°C] [Max]	95 °C
Application energy level	High Energy-optimized
Applications	LBP
Auxiliary winding resistance (start winding) for single-phase compressors alt [Ohm]	31.8 Ohm
Base plate type	EU small
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Colour	Black
Compressor power supply [V/Ph/Hz]	220-240/1/50
Configuration code	Single
Cut in current LST [A]	6.4 A
Description	NLX11KK.2
Discharge connection angle [°]	21 °
Discharge connection comments	Al-cap
Discharge connection diameter [mm]	5 mm
Discharge connection material	Cu-plated steel
Economizer	No
Free gas volume [cm3]	2360 cm3
Frequency [Hz]	50

Height from baseplate [mm]	197 mm
High value of nominal voltage at 50Hz [V]	240 V
High value of voltage range at 50Hz [V]	255 V
Length [mm]	252 mm
Liquid injection	No
Low value of nominal voltage at 50Hz [V]	220 V
Low value of voltage range at 50Hz [V]	187 V
LRA LST [A]	3.5 A
Main winding resistance for single-phase compressors [Ohm]	18.5 Ohm
Model number	NLX11KK.2
Motor type	RSCR
No. of phases (compressor)	1
Oil quantity [cm³]	270 cm ³
Oil type	P0E
Packing format	Industrial pack
Packing quantity	80
Process connection angle [°]	25 °
Process connection comments	Al-cap
Process connection diameter [mm]	6.2 mm
Process connection material	Cu-plated steel
Refrigerant	R600a
Refrigerant charge [kg] [Max]	0.15 kg
RLA	0.70 A
Rotational speed at 50Hz [rpm]	3000 rpm
Run capacitor capacitance	2 µF

Segment usage	Refrigeration LT
Speed Platform	Fixed-speed
Suction connection angle [Â°]	2 Â°
Suction connection comments	Al-cap
Suction connection diameter [mm]	6.2 mm
Suction connection material	Cu-plated steel
Swept volume [cm3]	11.15 cm3
Technology	Reciprocating
Total height [mm]	203 mm
Type	NL
Type designation	Compressor
Voltage 50Hz [V]	220 V
Voltage 50Hz [V] [Max]	240 V
Width [mm]	166 mm
Winding temperature short term [Â°C] [Max]	110 Â°C
Winding temperature stat [Â°C] [Max]	95 Â°C

Refrigerant: R600a, Segment usage: Refrigeration LT, Compressor power supply [V/Ph/Hz]: 220-240/1/50Mbsm_dot_pro_private_PDF_nlx11kk.2

			-35	-30	-20	-15	-10	-5	0	5	(W)	(W/W)	(W)	(W/W)	(W/W)	(W/W)
	PLE35K	102H40360									27	0.68	36	33		
	TL5400K.3	102H44330	19	29	57	75	96				42	0.90	57	69	1.18	
	TL5400K.3	102H44330	28	40	73	94	119				55	1.00	74	65	1.30	
	TL5400K.3	102H44330	36	50	89	114	144				68	1.02	91	79	1.52	
	TL5400K.3	102H44330	45	61	105	134	168				81	1.02	108	94	1.81	
	TL5400K.3	102H44330	53	71	122	155	194				94	1.02	126	108	2.02	1.14
	TL5400K.3	102H44330	62	83	143	181	228				110	1.03	147	126	2.33	1.14
	TL5400K.3	102H44330									130	1.04	172	148	2.55	1.15
	TL5400K.4	102H44330	62	84	140	179	223				110	1.18	147	127	2.51	1.20
	TL5400K.4	102H44330	74	99	164	207	257				128	1.19	170	151	2.51	1.30
	TL5400K.4	102H44330	82	108	184	232	290				143	1.19	181	165	2.52	1.31
	TL5400K.4	102H44330	99	137	217	274	340				170	1.18	226	194	2.50	1.29
	TL5400K.4	102H44330	110	146	243	307	382				190	1.20	251	219	2.53	1.32
	TL5400K.3	102H44342	19	29	57	74	95				42	0.96	57	69	1.26	1.08
	TL5400K.3	102H44342	28	40	73	94	119				55	1.04	74	65	1.35	1.16
	TL5400K.3	102H44342	36	51	89	114	144				68	1.03	91	79	1.53	1.15
	TL5400K.3	102H44342	46	62	106	135	170				82	1.10	110	94	1.62	1.22
	TL5400K.3	102H44342	53	71	122	155	194				94	1.09	126	108	1.81	1.22
	TL5400K.3	102H44342	65	86	144	182	227				112	1.12	149	126	1.84	1.24
	TL5400K.3	102H44347	21	32	59	76	95				45	1.10***	60	52		
	TL5400K.3	102H44347	36	52	90	116	146				57	1.20***	76	65		
	TL5400K.3	102H44347	37	52	91	115	143				70	1.20***	83	80		
	TL5400K.3	102H44347	46	63	106	133	165				83	1.20***	110	95		
	TL5400K.3	102H44347	55	75	125	157	195				98	1.20***	130	112		
	TL5400K.3	102H44347	65	88	146	184	227				115	1.20***	152	131		
	TL5400K.4	102H44374	60	83	144	182	227				111	1.25	140	127		
	TL5400K.4	102H44371	74	100	169	215	269				131	1.26	174	150		
	TL5400K.4	102H44384	84	112	189	240	300				147	1.26	195	168		
	TL5400K.4	102H44385	98	133	223	282	350				174	1.26	231	199		
	TL5400K.4	102H44381	110	147	249	317	397				193	1.24	257	221		
	TL5400K.2	102H44303	32	43	73	93	117				49	1.40***	63	51		
	TL5400K.2	102H44301	62	85	147	187	234				113	1.40***	151	130		
	TL5400K.2	102H44301	75	101	171	217	271				133	1.40***	176	153		
	TL5400K.2	102H44301	86	115	192	242	301				150	1.40***	200	172		