

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, 1bp, 750 btu, r134a

written by Lilianne | 30 May 2022

R	Series	Model	Capacity (kg/24h)	Capacity (lb/24h)	Power (W)	Power (hp)	Current (A)	Voltage (V)	ISO	CCC/VDE	Performance			
											160°C	170°C		
R 134a	EMZ	EMZ 66 CLP	220-240/50	10.61	190	163.4	1.74	1.50	4	ISO 5	CCC/VDE	171	6.73	
		EMX	EMX 32 CLC	220-240/50	5.96	102	87.7	1.78	1.53	2.5	ISO 5	CCC	166	6.54
			EMX 40 CLC	220-240/50	7.24	128	110.1	1.80	1.55	4	ISO 5	CCC	166	6.54
	EMB	EMB 32 CLC	220-240/50	5.96	103	88.6	1.88	1.62	2.5	ISO 5	CCC	166	6.54	
		EMB 40 CLC	220-240/50	7.24	128	110.1	1.92	1.65	4	ISO 5	CCC/VDE	171	6.73	
		EMB 46 CLC	220-240/50	7.96	142	122.1	1.90	1.63	4	ISO 5	CCC/VDE	171	6.73	
		EMB 55 CLC	220-240/50	9.05	163	140.2	1.88	1.62	4	ISO 5	CCC/VDE	171	6.73	
		EMB 66 CLC	220-240/50	10.61	190	163.4	1.87	1.61	4	ISO 5	CCC/VDE	171	6.73	
		EMT	EMT 45 HLP	220-240/50	4.85	145	124.7	1.40	1.20		ISO 7	CCC/VDE	158	6.22
	EMU		EMU 45 HLP	220-240/50	4.85	145	124.7	1.50	1.29		ISO 7	CCC/VDE	158	6.22
			EMU 55 HLP	220-240/50	5.20	161	138.5	1.50	1.29		ISO 7	CCC/VDE	166	6.54
			EMU 65 HLP	220-240/50	5.96	185	159.1	1.47	1.26		ISO 7	CCC/VDE	166	6.54
			EMU 45 HLP	200-230/50	4.85	145	124.7	1.45	1.25		ISO 22	CCC/VDE	158	6.22
			EMU 55 HLP	200-230/50	5.20	161	138.5	1.45	1.25		ISO 22	CCC/VDE	166	6.54
			EMU 65 HLP	200-230/50	5.96	185	159.1	1.45	1.25		ISO 22	CCC/VDE	166	6.54
	EMU 55 HLP		115-127/60	4.15	148	127.3	1.46	1.26		ISO 7	UL	158	6.22	
	EMY		EMY 55 HLC	220-240/50	5.20	161	138.5	1.60	1.38	4	ISO 7	CCC/VDE	166	6.54
			EMY 65 HLC	220-240/50	5.96	185	159.1	1.60	1.38	4	ISO 7	CCC/VDE	166	6.54
EMY 75 HLC			220-240/50	7.00	215	184.9	1.60	1.38	4	ISO 7	CCC/VDE	171	6.73	
EMY 50 HLP			115-127/60	4.15	140	120.4	1.60	1.38	12	ISO 7	UL	158	6.22	
EMY 55 HLP		115-127/60	4.50	160	137.6	1.60	1.38	12	ISO 7	UL	158	6.22		
EMY 60 HLP		115-127/60	4.85	180	154.8	1.60	1.38	12	ISO 7	UL	166	6.54		
EMH	EMH 60 HER	115-127/60	5.19	189	162.5	1.47	1.26		ISO 7	CCC	166	6.54		
	R 290	EMT 2121 U	220-240/50	5.57	256	220.0	1.42	1.22	48	ISO 22	CCC/VDE	166	6.54	
EMT 2125 U		220-240/50	5.96	301	259.0	1.48	1.28	58	ISO 22	CCC/VDE	166	6.54		

测试条件: 蒸发-23.3°C (-10°F) 冷凝54.4°C (130°F) 吸气/环境32.2°C (90°F) 液体32.2°C (90°F)
 Test Conditions: Evaporating: -23.3°C (-10°F) | Condensing: 54.4°C (130°F) | Gas and Ambient: 32.2°C (90°F) | Liquid: 32.2°C (90°F)

Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, compressor, EM Series, Embraco, EMY75HLC, 211 w, 1/4 hp, 1bp, 750 btu, r134a