

**Mbsm.pro, Compressor,
hpk190A, 1/4 hp++, 1/3 hp-,
R600, HMBP, 220/240V, 50Hz,
12.11 cc , unionaire, UR-350,
340 L, R600a/48g, 0.87 A**

written by Lilianne | 8 October 2023



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compressor, hpk190A, 1/4 hp++, 1/3 hp-, R600, HMBP,
220/240V, 50Hz, 12.11 cc , unionaire, UR-350, 340 L,
R600a/48g, 0.87 A

Bsa357cv-r1an Small compressor replaced by qx36h

written by Lilianne | 8 October 2023



Mbsm.pro, Compressor, bsa357cv-r1an, Highly, Hitachi, R134a, Rotary Compressor, for Air Condition, 220/240V, 1245BTU, run capacitor 5 mF/38, replaced by qx36h

**Mbsm.pro, Compressor, ZEL,
GML160G, 1/6 hp, 129 w, LBP,
R134a, 220-240V, KONOR
CATALOG**

written by Lilianne | 8 October 2023



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, ZEL, GML160G, 1/6 hp, 129 w, LBP, R134a, 220-240V, KONOR CATALOG

Mbsm.pro, Compressor, 105g 6728, NL7FT, 1/4hp, 105g6728, Danfoss, R134A, 220-240V, 1bp

written by Lilianne | 8 October 2023



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Compressor, 105g 6728, NL7FT, 1/4hp, 105g6728,
Danfoss, R134A, 220-240V

Compressor, ACC, Cubigel, GL60AN, R134a, 220-240V, HMBP, 1/6HP

written by Lilianne | 8 October 2023

Type: Hermetic piston compressors Producer: ACC Series: HMBP

Model: GL60AN

General data

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [°C]:	50

Compressor's data

Cylinder capacity [cm ³]:	6
Displacement [m ³ /h]:	1
Weight [kg]:	9,9
Oil charge [cm ³]:	345
Oil type:	ISO VG 19 ESTER

Engine's data

Engine type:	RSIR
Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	170-264
Locked rotor current [A]:	14,6
Running winding resistance (25°C) [Ω]:	9,33
Starting winding resistance (25°C) [Ω]:	10,81

Electrical data

Relays:	3003
Shielding element:	MRA38085, T0515, AF11BJ
Starting capacitor volume [μ F]:	

Connections

	millimeters	inches	
Suction tube:	6,5		
Service tube:	6,5		
Discharge tube:	4,9		



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_GL60ANTélécharger

Congélateur, glacière, 180 à 280 litres, Compresseur LG MA57, 130 W, 1/6Hp, LBP, R134, 220-240V

written by Lilianne | 8 October 2023

Application Réfrigérateur FF	MA57LBJG, MA57LHJG
Capacité	280 litres
Application Congélateur profond	MA57LBJG, MA57LHJG
Capacité	250 litres
Déplacement	5,7
Capacité de refroidissement	138 (kcal / h), 160 W, 548 (Btu / h), 0,215 HP
La puissance d'entrée	130 W
COP W / W	1.2
EER Btu / Wh	4,21
Type de moteur	RSIR-PTC
Dispositif de démarrage (PTC)	QP2-33MC1
Protecteur de moteur (OLP)	4TM232TFB
(Condensateur) Runnig / surtension	4uF / 400
(HUILE) Viscosité cst / Qté (cc)	22/220
Type de refroidissement	ST
Hauteur du compresseur	177 mm
Poids net	9,1 kg.

NS30LBJG	LBP	220	50	RSIR	P470MC	4TM213SFB			22	180	ST
NS36LBJG				RSIR	P470MC	4TM213SFB			22	180	ST
MA53LAJG				RSIR	P330MC	4TM222VFB			dix	220	ST
MA57LAJG		RSIR	P470MC	4TM213SFB			dix	220	ST		
NS24LADG		220	60	RSIR	P220MC	4TM101RFB			22	180	ST
NS36LADG				RSIR	P220MC	4TM174TFB			22	180	ST
NS36LADG				RSCR	P220MD	4TM174TFB		4/400	22	180	ST
MA53LADG				RSIR	P330MC	4TM232NFB			dix	220	ST
MA53LADM				RSCR	P330MD	4TM232NFB		5/400	dix	220	ST
MA57LADM				RSCR	P330MD	4TM213SFB		5/400	dix	220	ST
NS24LABG		220	50-60	RSIR	P330MC	4TM149NFB			22	180	ST
NS30LABG				RSIR	P220MC	4TM158RFB			22	180	ST
NS36LABG				RSIR	P220MC	4TM174TFB			22	180	ST
MA53LABM				RSCR	P330MD	4TM232NFB		5/400	dix	220	ST
MA57LABM				RSCR	P330MD	4TM213SFB		5/400	dix	220	ST
NS24LAEG		220-240	50	RSIR	P220MC	4TM117SFB			22	180	ST
NS24LBEG				RSIR	P330MC	4TM117SFB			22	180	ST
NS30LAEG				RSIR	P330MC	4TM149NFB			22	180	ST
MSA30LAEG				RSIR	P330MC	4TM149NFB			22	180	ST
NS36LAEG				RSIR	P220MC	4TM149NFB			22	180	ST
MSA43LBEG				RSIR	P330MC	4TM166RFB			22	180	ST
MSA43LAEM				RSCR	P330MD	4TM205RFB		4/400	22	180	ST
MA53LAEC				RSIR	P330MC	4TM158RFB			dix	220	ST
MA53LAEM				RSCR	P330MD	4TM232TFB		5/400	dix	220	ST
MSB53LAJG				RSIR	P330MC	4TM213SFB			dix	180	ST
MA57LAEG				RSIR	P330MC	4TM158RFB			dix	220	ST
MA57LAEM				RSCR	P330MD	4TM205RFB		5/400	dix	220	ST
MA57LBEG				RSIR	P330MC	4TM149NFB			dix	200	ST
MC57LAEM				RSCR	P330MD	4TM166RFB		4/400	sept	200	ST
MSB57LAEG				RSIR	P330MC	4TM166RFB			dix	180	ST
MSB57LAEM				RSCR	P330MC	4TM166RFB		4/400	dix	180	ST
MA62LCEG				RSIR	P330MC	4TM232VFB			dix	220	ST
MA62LCEM				RSCR	P330MD	4TM205RFB		5/400	dix	220	ST
MA62LDEG				RSIR	P330MC	4TM232VFB			dix	220	ST
MA69LDEG				RSIR	P330MC	4TM232VFB			dix	220	ST
MA69LCEG				RSIR	P330MC	4TM232VFB			dix	220	ST
MA69LCEM				RSCR	P330MD	4TM232NFB		4/400	dix	220	ST
MA98LAEM				RSCR	P470MD	4TM265RFB		4/400	dix	220	ST
MC98LAEM				RSCR	P470MD	4TM265RFB		5/400	dix	220	ST
MQ98LAEM				RSCR	P470MB	4TM265RFB		5/400	dix	220	ST
MA108LAEH				RSE	P470MB	4TM276VFB	30/300	5/400	dix	220	ST



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_LG_Refrigerator_Compressor_CatalogueT
élécharger

**ASPERA, COMPRESSEUR, 1 /
3HP++ (Big), NE6181E, CSIR,
HMBP, R22, 220-240V**

written by Lilianne | 8 October 2023



Private Picture Copyright : WWW.MBSM.PRO

NE6181E 1 / 3HP / R22

- **Détails techniques**
puissance 1/3 CV, cylindrée 7,28 cm³
220 / 240V 50Hz
- LIGNE LIQUIDE (DIAMÈTRE) : 1/4
- LIGNE D'ASPIRATION (DIAMÈTRE) : 5/16
- BRÈVE DESCRIPTION



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_NE6181ETélécharger

**1/5HP, Refrigerator, Samsung,
Compressor, R134A, 220-240V,
SD162Q-L1UA, PTC-RSCR, 6.16CC**

written by Lilianne | 8 October 2023



Picture Copyright: WWW.MBSM.PRO

Model No.: SD162Q-L1UA

Test condition: ASHARE

Evaporating Temperature: -23.3° C

Condensing Temperature: 54.4° C

Displacement: 6.16CC/ Rev

Oil: 180CC

Motor type: PTC-RSCR

Nominal voltage range: 187V~276V at 50Hz

Characteristics:

1. Strong load capacity
2. High efficiency & reliability
3. Reliable starting performance
4. Low noise

v id="StyleTableProd">

[Mbsm_dot_pro_private_PDF_qdoc.tips_catalogo-compresores-samsungpdfTélécharger](#)



RATED VOLTAGE	MODEL	VOLTAGE VOLT-HZ	MOTOR TYPE	DISPL (cc)	HEIGHT (mm)	ASHRAE						COOLING TYPE		
						COOLING CAPACITY -23.3 °C			POWER INPUT		EFFICIENCY (-23.3 °C)			
						Kcal/Hr	Watt	BTU/Hr	W	Kcal/Hr	COP		EER	
AC 110V/50-60HZ	CD124E-L1Z2	100-50	RSIR	2.40	157	43	50	171	68	0.63	0.74	2.51	ST	
	100-60	52				60	206	68	0.76	0.89	3.04			
	100-50	58				67	230	76	0.76	0.89	3.03			
	CD130E-L1Z2	100-60	RSIR	2.93	157	70	81	278	79	0.89	1.03	3.52	ST	
	100-50	72				84	286	91	0.79	0.92	3.14			
	100-60	87				101	345	99	0.88	1.02	3.49			
	SD137E-L1U2	100-50	RSCR	3.71	166	117	136	464	111	1.05	1.23	4.18	ST	
	100-60	135				157	536	121	1.12	1.30	4.43			
	100-50	144				168	572	141	1.02	1.19	4.06			
	SD152E-L1W2	100-50	CSR	6.16	175	170	198	676	147	1.16	1.35	4.60	ST	
	100-60	80				93	317	85	0.94	1.09	3.73			
	100-50	96				111	380	90	0.97	1.12	3.84			
	DD137-L1U2	100-60	RSCR	3.71	166	118	137	468	103	1.15	1.33	4.55	ST	
	100-50	143				166	568	118	1.21	1.41	4.81			
	100-60	143				166	568	116	1.23	1.43	4.89			
	MD162E-L1U2	100-50	RSCR	6.16	175	182	212	723	141	1.29	1.50	5.12	ST	
	100-60	168				195	667	149	1.13	1.31	4.48			
	100-50	206				240	818	170	1.21	1.41	4.81			
	SK170E-L2W	100-60	CSR	8.19	189	203	236	806	188	1.08	1.26	4.29	FC	
	100-50	239				278	950	196	1.22	1.42	4.85			
100-60	203	236				806	161	1.26	1.47	5.01				
DK182E-L2U	100-60	RSCR	8.19	189	256	298	1016	191	1.34	1.56	5.32	FC		
100-50	230				267	913	180	1.28	1.49	5.07				
100-60	280				326	1112	209	1.34	1.56	5.32				
DK190E-L2U	100-50	RSCR	9.07	189	181	210	719	140	1.29	1.50	5.13	FC		
100-60	225				263	897	162	1.40	1.62	5.54				
100-50	280				326	1112	209	1.34	1.56	5.32				
MK172E-L2U	100-60	RSCR	7.21	189	225	263	897	162	1.40	1.62	5.54	ST		
100-50	280				326	1112	209	1.34	1.56	5.32				
100-60	225				263	897	162	1.40	1.62	5.54				

Samsung compressors are imported in Europe by: Procold S.r.l. - Italy
www.samsung-compressors.com www.procold.it

Private Picture Copyright : WWW.MBSM.PRO

1/5HP Refrigerator Compressor R134A 220-240V



Price : **US \$ 28/ Piece**
Payment Terms : **L/C, T/T, Western Union**
Trade Terms : **FOB**
Production Capacity : **6, 000, 000PCS/ Year**
Packing Details : **by Pallet**
Refrigerant Gas : **R134A**
Main Markets : **Global**
Place of Origin : **china**
Category : **Refrigerators**



Private Picture Copyright : WWW.MBSM.PRO



Compresseur, SC15B, R-12, 3/8HP, 230V , 104L , 2830 ,220-240V ,50HZ ,1PH, LBP/HBP ,Compressor DANFOSS

written by Lilianne | 8 October 2023

Compresseur SC15B R-12 3/8HP 230V , 104L , 2830 ,220-240V
,50HZ ,1PH, LBP/HBP ,Compressor DANFOSS

Mini Frigidaire ,compresseur Americold RG209-12 , 1/4 Hp , 0.95 FLA & 9.5 LRA , 210 w ,220-240V ,50-60HZ ,R134a

written by Lilianne | 8 October 2023

Mini Frigidaire ,compresseur Americold RG209-12 , 1/6 Hp ,
0.95 FLA & 9.5 LRA , 220-240V ,50-60HZ ,R134a