

**NL8.4FT ,Tropical , 1/4 Hp  
Compressor R134a 220-240V  
50Hz ,HERMETIC ,143 W -25/+55  
°C , LBP, 105g6866, 105g6865**

written by Lilianne | 21 April 2020

NL8.4FT ,Tropical , 1/4 Hp Compressor R134a 220-240V 50Hz  
,HERMETIC ,143 W -25/+55 °C , LBP

---

**Mbsm.pro , Compressors ZMC,  
EGL90AA, R-134a ,1/4 HP LBP,  
220 – 240 V**

written by Lilianne | 21 April 2020

Mbsm.pro , Compressors ZMC, EGL90AA, R-134a ,1/4 HP LBP, 220 –  
240 V

## **BRAND**

• – ZMC

## **TECHNICAL SPECIFICATIONS :**

– MODEL: EGL 90 AA

– POWER: 1/4 Hp

- VOLTAGE: **220 – 240 V**
- WATT: **227.00 W**
- REFRIGERANT GAS: **R 134**
- K.CAL: **195.00 Cal.**

**Features** : The compressors form the basis of the refrigerant system and function to compress the gas from the evaporation to the condensation pressure.

## **USAGE PLACES :**

It is used in Refrigerator devices belonging to all brands and models.

## **INSTRUCTIONS FOR USE:**

**Zmc EGL90AA**;It is recommended to be used by a specialist authorized or authorized service.



Picture5 Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm\_dot\_pro\_private\_PDF\_catalogo\_cubigel\_R134aTélécharger  
Mbsm\_dot\_pro\_private\_PDF\_cubigel-katalogTélécharger

---

**MBSM.PRO , Compressor,  
Electrolux-Zem GL60AA R134A  
,1/6 HP , 1PH , 220-240 V 50  
Hz**

written by Jamila | 21 April 2020

MBSM.PRO , Compressor, Electrolux-Zem GL60AA R134A ,1/6 HP ,  
1PH , 220-240 V 50 Hz



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

- Puissance en cheval 1/6 CV
- Cylindrée 5.99 cm<sup>3</sup>
- 220-240 V 50 Hz
- Gaz R134a LBP
- Température d'utilisation max. 32°C
- Avec boîtier et système de démarrage

La photo montre l'aspect du compresseur, pas son étiquette réelle

Codes fabricants

- ACC-GL60AA
- ACC-GL60AB
- ACC-GL60AH
- CUBIGEL-GL60AA
- CUBIGEL-GL60AB
- CUBIGEL-GL60AH
- MONDIAL ELITE-4106004
- MONDIAL ELITE-1147031
- Embraco Aspera- B1112Z





PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)



PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

Mbsm\_dot\_pro\_private\_PDF\_GL60AATélécharger  
Mbsm\_dot\_pro\_private\_PDF\_-GL60AATélécharger



**Type:** Hermetic piston compressors **Producer:** ACC **Series:** HMBP  
**Model:** GL60AA  
**General data**

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [°C]:	43

### Compressor's data

Cylinder capacity [cm <sup>3</sup> ]:	6
Displacement [m <sup>3</sup> /h]:	1
Weight [kg]:	9,1
Oil charge [cm <sup>3</sup> ]:	265
Oil type:	ISO VG 19 ESTER

### Engine's data

Engine type:	RSIR
Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	187-264
Locked rotor current [A]:	9,9
Running winding resistance (25°C) [Ω]:	15,6
Starting winding resistance (25°C) [Ω]:	21,31

### Electrical data

Relays:	3003
Shielding element:	MRA38028, T0508, AF18FU
Starting capacitor volume [μF]:	

### Connections

	millimeters	inches
Suction tube:	6,5	
Service tube:	6,5	

Discharge tube:	4,9		
-----------------	-----	--	--