

**MBSM.pro, Compressor, 13HP,
Danfoss, Performer, Scroll
Compressor, Sm160, Sm161t4vc,
Refrigeration Chiller, 3 ph,
380 v, 38BB 055 – 240,
38bb-250 9e/k, 38BB 250, 250
= 250000 kBtu/hr, 30 Ton,
r22, 19 Kg, suction 1-1/8"–2,
refoulement 5/8"–2**

written by Lilianne | 19 April 2022



Model no: SM161T4VC



Serial no: GD2503110072



Danfoss
MADE IN CHINA

M	380-400 V 3 ~ 50 Hz	UL electrical
	460 V 3 ~ 60 Hz	MAX OPER. 31 A
	LR 145 A	Thermally protected system
	P.E.D.	LP side HP side
Marking	25 bar	27.8 bar
PS	63 °C	150 °C
TS max	-35 °C	-35 °C
TS min	-35 °C	2.0 L
Volume	17.8 L	Lubricant: MINERAL OIL 1500

CE US EAC
0062



Refrigerant: R22 (UL rating) - R417A with 160SZ
PROTECTED BY DOMESTIC AND FOREIGN PATENTS

WARNING

Installation and servicing should be performed by trained personnel only. Failure to observe these safety warnings could result in serious injury or death.

ELECTRIC SHOCK HAZARD: Turn off power before servicing. Disconnect all connections.

Keep terminal cover in place and securely fastened whenever power is applied to the compressor. Use the equipment only as provided by the manufacturer.

HIGH PRESSURE: System contains refrigerant and oil under pressure. Release pressure from both the high and low side before servicing. Never release refrigerant.

FLAME HAZARD: Use flammable solvents for cleaning. Do not use open flame or other heat source.

MAX

Private Picture Copyright: WWW.MBSM.PRO

MBSM.pro, Compressor, 13HP, Danfoss, Performer, Scroll Compressor, Sm160, Sm161t4vc, Refrigeration Chiller, 3 ph, 380 v, 38BB 055 – 240, 38bb-250 9e/k, 38BB 250, 250 = 250000 kBtu/hr, 30 Ton, r22, 19 Kg, suction 1-1/8”-2, refoulement

5/8"-2