

# mbsm.pro , CUBIGEL Compressor GX21TB, 220-240 VOLTS, 5/8 HP , R134a

written by Jamila | 14 September 2018



**GX21TB VE01**  
220-240V 50Hz ~1

## COMPRESSOR

Displacement (cm <sup>3</sup> )	20.72
Diameter (mm)	34.93
Stroke (mm)	21.62
Net Weight (Kg)	17
Oil type	ISO VG 46 ESTER
Oil charge (cm <sup>3</sup> )	500

## MOTOR

Approximate Power (CV)	5/8
Voltage/Frequency (V/Hz)	220V 50Hz
Voltage range (V)	187-264
Code	82,197
Type	CSIR
Phase number	1 PH
Locked rotor current (A)	26.0
Main W. resist. at 25°C (Ω)	2.45
Start W. resist. at 25°C (Ω)	25.9

## ELECTRICAL COMPONENTS

Relay	9660 A 180	MTRP 16
Pick-Up (A)	16.70	16.70
Drop-Out (A)	14.00	14.00
Protector	MRA38128	T0535/G.
Current (A)	17.0	17.0
Time check (seg)	7.5-14	7.5-14
Disc temp. (Open/Close) (°C)	105.0 / 52.0	105.0 / 52.0

## APPLICATION

Application	High/Mid. back pressure
Refrigerant	R134a
Evaporating (°C)	-25 to 10
Expansion	Capillar/Valve
Comp. cooling	Fan cooled
Max. ambient temp. (°C)	43

## NOMINAL PERFORMANCE

	CYCLE C	CYCLE D
Cooling capacity (W)	1550	1855
Input power (W)	818	850
EER (kcal/Wh)	1.62	1.87
COP (W/W)	1.89	2.18
Current (A)	5.16	5.29

## TEST CONDITIONS

Evaporating temp. (°C)	5.0	7.2
Condensing temp. (°C)	55.0	55.0
Liq.t. entering expan. (°C)	55.0	46.0
Ambient t. and return (°C)	32.0	35.0
Tens/Freq (V/Hz)	220V 50Hz	220V 50Hz

PictureS Mbsm Dot Pro : [www.mbsm.pro](http://www.mbsm.pro)

mbsm.pro , CUBIGEL Compressor GX21TB, 220-240 VOLTS, 5/8 HP ,  
R134a

**www.mbsm.pro, cOMPRESsOR A/A**  
**, R22 , 124MBTU, 220V/380v,**

# 3HP, H25G124DBDE, BRISTOL

written by Jamila | 14 September 2018



[www.mbsm.pro](http://www.mbsm.pro), COMPRESSOR A/A ,124MBTU, 220V/380v, 3HP,  
H25G124DBDE, BRISTOL