

Mbsm.pro, Compresseur, Secop, GTK70AT, 204W, R134, LBP, 1/4 HP, RSIR, 699 BTU

Category: pro

written by Lilianne | 18 September 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Compresseur, Secop, GTK70AT, 204W, R134, LBP, 1/4 HP, RSIR, 699 BTU

Mbsm.pro, COMPRESSEUR, CUBIGEL, L45TN, R22, HMBP, 1/5HP, 220/240V 50HZ, ORIGINE 4.56CM3

Category: Archivation,compressor
written by Lilianne | 18 September 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, COMPRESSEUR, CUBIGEL, L45TN, R22, HMBP, 1/5HP, 220/240V 50HZ, ORIGINE
4.56CM3

Mbsm.pro, TECUMSEH, Compressor,

Condensing, Units, AHC4540EFZ,
FH4540F, FH4524F, FH4528F, FH4531F,
FH4540F, R22, 3-1/2 HP, hbp, CSR,
220V ~ 50HZ

Category: compressor

written by Lilianne | 18 September 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, TECUMSEH, Compressor, Condensing, Units, AHC4540EFZ, FH4540F, FH4524F, FH4528F, FH4531F, FH4540F, R22, 3-1/2 HP

Mbsm.pro, Panasonic, rotary,
compressor, rotary compressor, R22,
220-240V 50HZ, 2jd550D3AA03, 2JD550D,
35.000 BTU, Rla 5.65 A, Lra 21.0 A,
4.375 Hp, 2.91 Ton

Category: compressor

written by Lilianne | 18 September 2022

Mbsm.pro, Panasonic, rotary, compressor, rotary compressor, R22, 220-240V 50HZ,
2jd550D3AA03, 2JD550D, 35.000 BTU, Rla 14.7, Lra 68.0, 4.375 Hp, 2.91 Ton

Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V, 3PH

Category: compressor

written by Lilianne | 18 September 2022



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, Danfoss, Compressor, MT100HS4D, 8.3HP, R22, 380V, 3PH

Mbsm.pro, Compressor, Embraco, Aspera, EMY26CLC, LBP, R600a, 220 – 240V/1/50Hz, 1/12 HP, RSIR, LRA 7.8 A, 83 Wat

Category: compressor

written by Lilianne | 18 September 2022



Private Picture Copyright: WWW.MBSM.PRO

Compressor, Embraco, Aspera, EMY26CLC, LBP, R600a, 220 – 240V/1/50Hz, 1/12 HP, RSIR, LRA 7.8 A, 83 Wat

Mbsm.pro, Compressor, Hermetic, Tecumseh, AEZ9440T, R22, 1/3 hp++, MHBP

Category: compressor

written by Lilianne | 18 September 2022

Basic Info.

Model NO.AEZ9440TLubrication StyleLubricatedCooling SystemAir CoolingCylinder ArrangementBalanced Opposed ArrangementCylinder PositionHorizontalStructure TypeClosed TypeCompress LevelSingle-StageRefrigerant TypeFreonTypeReciprocatingPerformanceLow NoiseDrive ModeElectricPower SourceAC PowerConfigurationStationaryMaterialCopperPiston TypeClosedTrademarkTecumseh HermetiqueTransport PackagePalletSpecificationCE / RoHsOriginChinaHS Code8414301900

Product Description

Tecumseh Hermetique R134a / R404a/ R22 reciprocating compressor

Hermetique R22
HBP

For Air
Conditioning
Applications.

Features:

Anti Vibration
mounts supplied

Charged with
mineral oil and
dry nitrogen

Crankcase
heater on TAG
models

Fan cooling
required on all
models

Specifications:

Capacity Rating
Basis: 35°C
Ambient, 11K
Return Gas
Superheat,
54.5°C
Condensing,
46.2°C Liquid
entering
Expansion
Valve.

Current FLA are
given at
nominal
voltage, rated
conditions and
7.2°C
Evaporating
Temperature.

Motor Types:

PSC = Permanent
Split
Capacitor, 1
Phase, 50 Hz.
220-240 Volt

3Ø: 3 Phase, 50
Hz, 400 Volt

Expansion
Device:

C = Capillary
Tube

C/V = Capillary
Tube or
Expansion Valve

R22 Hermetic

Model No.	Nominal HP	Displ. cm ³ /rev	Motor Type	Nominal Current FLA	Exp. Device	Oil Charge cm ³	Connections: inches		
cm ³	Discharge Proc.								
AE 5465E	1/2	12.05	PSC	3.2	C	450	3/8 Tube	1/4 Tube	3/8 Tube
AJ 5510F	3/4	18.6	PSC	5.2	C	887	3/8 Tube	1/4 Tube	1/4 Tube
AJ 5512E	1	21.75	PSC	5.9	C	887	3/8 Tube	1/4 Tube	1/4 Tube

AJ 5513E	1	24.2	PSC	6	C	887	3/8 Tube	1/4 Tube	1/4 Tube
AJ 5515E	1 1/4	25.95	PSC	7.2	C	887	1/2 Tube	5/16 Tube	1/4 Tube
AJ 5518E	1 1/2	32.7	PSC	9.3	C	887	1/2 Tube	5/16 Tube	1/4 Tube
AJ 5519E	1 1/2	34.45	PSC	9.96	C	887	1/2 Tube	5/16 Tube	1/4 Tube
FH 5522E	1 3/4	39.95	PSC	9	C	1330	5/8 Tube	3/8 Tube	5/16 Tube
TFH 5522E	1 3/4	39.95	3Ø	3.8	C/V	1330	5/8 Tube	3/8 Tube	5/16 Tube
FH 5524E	2	43.5	PSC	10	C	1330	5/8 Tube	3/8 Tube	5/16 Tube
TFH 5524E	2	43.5	3Ø	4	C/V	1330	5/8 Tube	3/8 Tube	5/16 Tube
FH 5527E	2 1/4	49.1	PSC	12	C	1330	5/8 Tube	3/8 Tube	5/16 Tube
TFH 5527E	2 1/4	49.1	3Ø	4.2	C/V	1330	5/8 Tube	3/8 Tube	5/16 Tube
FH 5531E	2 1/2	56.65	PSC	14.1	C	1330	3/4 Tube	3/8 Tube	5/16 Tube
TFH 5531E	2 1/2	56.65	3Ø	8	C/V	1330	3/4 Tube	3/8 Tube	5/16 Tube
FH5540E	3	74.25	PSC	18.6	C	1330	3/4 Tube	3/8 Tube	5/16 Tube
TFH 5540E	3	74.25	3Ø	6	C/V	1330	3/4 Tube	3/8 Tube	5/16 Tube
TFH 5540E	3	74.25	3Ø	6	C/V	1330	78	1/2 Valve	5/16 Tube
TAG 5546E	3 3/4	90.2	3Ø	6.6	C/V	1960	7/8 Tube	1/2 Tube	3/8 Tube
TAG 5553E	4	100.7	3Ø	7.4	C/V	1960	7/8 Tube	1/2 Tube	3/8 Tube
TAG 5561E	5	112.5	3Ø	9	C/V	1960	7/8 Tube	1/2 Tube	3/8 Tube
TAG 5568E	6	124.4	3Ø	9.6	C/V	1960	7/8 Tube	1/2 Tube	3/8 Tube
TAG 5573E	6 1/2	134.8	3Ø	11	C/V	1960	7/8 Tube	1/2 Tube	3/8 Tube

Hermetique R22
M/HBP
For Medium /
High
Temperature
Applications
Features:
Anti-Vibration
mounts supplied
Charged with
mineral oil and
dry nitrogen
Rotalock
suction valve
on CAJ/TAJ
models
Crankcase
heater on
FH/TFH and TAG
models
Oil sight glass
on FH/TFH and
TAG models

Fan cooling
required on all
models

All models suit
capillary tube
or expansion
valve operation

Rotalock
suction and
discharge
valves on
FH/TFH and TAG
models

Specifications:

Capacity Rating

Basis: 35°C

Ambient, 11K

Return Gas

Superheat,
54.5°C

Condensing,
46°C Liquid

entering

Expansion

Valve.

Current FLA are
given at
nominal
voltage, rated
conditions and
7.2°C

evaporating
temperature.

Motor Types:

CSIR: Capacitor
start,

Induction run }
1 Phase, 50 Hz,
220-240 Volt

CSR: Capacitor
start and run

3Ø: 3 Phase, 50
Hz, 400 Volt

Conversion:

Watts x 3.412 =

BTU/Hr BTU/Hr x

0.293 = Watts

R22 Hermetic

Model No.	Nominal HP	Displ. cm ³ /rev	Motor Type	Nominal Oil Current Charge FLA	cm ³	Connections: inches	
	Suction	Discharge					
AEZ 4425E	1/5	4.5	CSIR	1.75	450	1/4 Tube	3/16 Tube
AEZ 4430E	1/4	5.7	CSIR	2.2	450	1/4 Tube	3/16 Tube
AEZ 4440E	1/3	7.55	CSIR	2.6	450	1/4 Tube	3/16 Tube
AEZ 9440T	1/3	7.55	CSR	2.03	450	3/8 Tube	1/4 Tube
CAE 4450E	3/8	9.4	CSIR	3.3	450	3/8 Tube	1/4 Tube
CAE 9450T	3/8	9.5	CSR	2.6	450	3/8 Tube	1/4 Tube
CAE 9460T	1/2	11.3	CSR	3.2	450	3/8 Tube	1/4 Tube
CAJ 9408T	5/8	15.2	CSR	3.68	887	1/2 Valve	5/16 Tube
CAJ 9510T	1	18.3	CSR	4.8	887	5/8 Valve	5/16 Tube
CAJ 9513T	1 1/8	24.2	CSR	5.9	887	5/8 Valve	5/16 Tube
CAJ 4517E	1 1/4	25.95	CSR	6.1	887	5/8 Valve	3/8 Tube
TAJ 4517T	1 1/2	25.95	3Ø	2.5	887	5/8 Valve	3/8 Tube
TAJ 4519T	1 1/2	34.45	3Ø	3.5	887	5/8 Valve	1/2 Valve
FH 4524F	2	43.5	CSR	9.55	1480	5/8 Valve	1/2 Valve

TFH 4524F	2	4.35	30	3.9	1480	7/8 Valve	1/2 Valve
FH 4531F	2 1/2	56.65	CSR	12.6	1480	7/8 Valve	1/2 Valve
TFH4531F	2 1/2	56.65	30	4.75	1480	7/8 Valve	1/2 Valve
TFH 4540F	3	74.25	30	6.08	1480	7/8 Valve	1/2 Valve
TAG 4546T	4	90.2	30	6.6	1960	7/8 Valve	5/8 Valve
TAG 4553T	4 1/2	100.7	30	7.4	1960	7/8 Valve	5/8 Valve
TAG 4561T	5	112.5	30	9	1960	1 7/8 Valve	5/8 Valve
TAG 4568T	6	124.4	30	9.6	1960	1 7/8 Valve	5/8 Valve
TAG 4573T	6 1/2	134.8	30	11	1960	1 7/8 Valve	5/8 Valve

Tecumseh
Hermetique
R134a

The world
renowned
L'Unite
Hermetique
compressors are
manufactured by
Tecumseh.

Features:

Charged with
polyolester oil
and dry
nitrogen

Crankcase
heater on
FH/TFH and TAG
models

Oil sight glass
on FH/TFH and
TAG models

Rotalock valves
are included
for all valve
connection
compressors

Anti-vibration
mounts supplied

Single Phase –
Medium High SST

Model No.	Nominal HP	Displacement: cm ³ /rev	Cooling	Oil Charge: ml
CAJ4476Y	5/8	21.75	Fan	887
CAJ4492Y	3/9	25.95	Fan	887
CAJ4511Y	1	32.7	Fan	887
FH4518Y	1 1/2	53.2	Fan	1480
FH4525Y	2	74.25	Fan	1480

Three Phase –
Medium High SST

Model No.	Nominal HP	Displacement: cm ³ /rev	Cooling	Oil Charge: ml
TAJ4511Y	1	32.7	Fan	887
TFH4518Y	1 1/2	53.2	Fan	1480
TFH4525Y	2	74.25	Fan	1480
TAG4528Y	2 1/2	90.2	Fan	1960
TAG4534Y	2 3/4	100.7	Fan	1960
TAG4537Y	3	112.5	Fan	1960
TAG4543Y	3 1/2	124.4	Fan	1960

Superceded
Models

Model No.	Nominal HP	Displacement: cm3/rev	Cooling	Oil Charge: ml
AEZ4425Y	1/5	7.55	Fan	450
AEZ4430Y	1/4	8.85	Fan	450
CAE4440Y	3/8	12.05	Fan	450
CAE4448Y	1/3	14.15	Fan	450
CAJ4452Y	1/3	15.2	Fan	887
CAE4456Y	1/2	16	Fan	450
CAJ4461Y	1/2	18.3	Fan	887

Tecumseh
Hermetique
R404A

The world
renowned
L'Unite
Hermetique
compressors are
manufactured by
Tecumseh.

Features:

Charged with
polyolester oil
and dry
nitrogen

Crankcase
heater on
FH/TFH and TAG
models

Oil sight glass
on FH/TFH and
TAG models

Rotalock valves
are included
for all valve
connection
compressors

Anti-vibration
mounts supplied

Specifications:

Capacity Rating
Basis: 35°C
Ambient, 11K
Return Gas
Superheat,
54.5°C
Condensing,
46°C Liquid
entering
Expansion
Valve.

Current FLA are
given at
nominal
voltage, rated
conditions and
7.2°C

Evaporating
Temperature.

Motor Types:

CSIR: Capacitor
Start,
Induction Run 1
Phase, 50 Hz,
220-240 Volt

CSR: Capacitor
Start and Run
3Ø: 3 Phase, 50
Hz, 400 Volt

All models are
also suitable
for operation
with R507

Single Phase –
Medium High SST

Model No.	Nominal HP	Displacement: cm ³ /rev	Cooling	Oil Charge: ml
CAJ9480Z	5/8	15.2	Fan	887
CAJ9510Z	1	18.3	Fan	887
CAJ9513Z	1 1/8	24.2	Fan	887
CAJ4517Z	1 1/4	25.95	Fan	887
CAJ4519Z	1 1/2	34.45	Fan	887
FH4522Z	1 3/4	39.95	Fan	1480
FH4524Z	2	43.5	Fan	1480
FH4531Z	2 1/2	56.65	Fan	1480
FH4540Z	3	74.25	Fan	1480

Three Phase –
Medium High SST

Model No.	Nominal HP	Displacement: cm ³ /rev	Cooling	Oil Charge: ml
TAJ9480Z	5/8	15.2	Fan	887
TAJ9510Z	1	18.3	Fan	887
TAJ9513Z	1 1/8	24.2	Fan	887
TAJ4517Z	1 1/4	25.95	Fan	887
TAJ4519Z	1 1/2	34.45	Fan	887
TFH4522Z	1 3/4	39.95	Fan	1480
TFH4524Z	2	43.5	Fan	1480
TFH4531Z	2 1/2	56.65	Fan	1480
TFH4540Z	3	74.25	Fan	1480
TAG4546Z	4	90.2	Fan	1960
TAG4553Z	4 1/2	100.7	Fan	1960
TAG4561Z	5	112.5	Fan	1960
TAG4568Z	6	124.4	Fan	1960
TAG4573Z	6 1/2	134.8	Fan	1960

Single Phase –
Low SST

Model No.	Nominal HP	Displacement: cm ³ /rev	Cooling	Oil Charge: ml
CAE2417Z	1/3	11.3	Fan	450
CAE2420Z	1/2	12.54	Fan	450
CAE2424Z	5/8	15	Fan	450
CAJ2428Z	1/2	15.2	Fan	887
CAJ2432Z	5/8	18.3	Fan	887
CAJ2446Z	3/4	26.15	Fan	887
CAJ2464Z	1 1/2	34.45	Fan	887
FH2480Z	2	53.2	Fan	1625

FH2511Z 2 1/2 74.25 Fan 1625

Three Phase –
Low SST

Model No.	Nominal HP	Displacement: cm3/rev	Cooling	Oil Charge: ml
TAJ2464Z	1 1/2	34.45	Fan	887
TFH2480Z	2	53.2	Fan	1625
TFH2511Z	2 1/2	74.25	Fan	1625
TAG2516Z	4	112.5	Fan	1960
TAG2522Z	5 1/2	134.8	Fan	1960

Three Phase –
Parallel
Applications

Model No.	Nominal HP	Displacement: cm3/rev	Application: SST	Cooling	Oil Charge: ml
TAGP4546Z	4	90.2	Medium	Fan	1960
TAGP4553Z	4 1/2	100.7	Medium	Fan	1960
TAGP4561Z	5	112.5	Medium	Fan	1960
TAGP4568Z	6	124.4	Medium	Fan	1960
TAGP4573Z	6 1/2	134.8	Medium	Fan	1960
TAGP2516Z	4	112.5	Low	Fan	1960
TAGP2522Z	5 1/2	134.8	Low	Fan	1960



MEDIUM/HIGH BAK PRESSURE COMPRESSORS

Type	COMPRESSOR MODELS	Nominal Power (H.P.)	Refrigerant		REFRIGERATION CAPACITY AT 50HZ Rafed 54.5°C Cond Temp (Watts)						VOLTAGE
			Displacement (cm ³)	Oil charge (cm ³)	Evaporating Temperature						
					-25°C	-15°C	-10°C	0°C	+7.2°C	+15°C	
AEZ4425E	1/5	R22	4.50	250	138	192	256	413	553	728	220-240V/1/50Hz
AEZ4430E	1/4	R22	5.70	250	192	255	336	538	718	945	220-240V/1/50Hz
AEZ3440E	1/3	R22	7.55	350	308	362	464	733	980	1298	220-240V/1/50Hz
AEZ4440E	1/3	R22	7.55	350	308	362	464	733	980	1298	220-240V/1/50Hz
AEZ9440T	1/3	R22	7.55	350	222	362	464	733	975	1302	220-240V/1/50Hz
CAE4450E	3/7	R22	9.40	350	355	426	554	896	1212	1623	220-240V/1/50Hz
CAE9450T	3/7	R22	9.40	350	256	426	554	896	1212	1623	220-240V/1/50Hz
CAE9460T	1/2	R22	11.30	350	324	553	715	1134	1514	2000	220-240V/1/50Hz
CAJ9480T TAJ9480T	5/8	R22	15.20	887	461	786	1011	1586	2103	2761	220-240V/1/50Hz 400V/3/50Hz
CAJ9510T TAJ9510T	1	R22	18.30	887	545	956	1229	1909	2510	3266	220-240V/1/50Hz 400V/3/50Hz
CAJ9513T TAJ9513T	1-1/8	R22	24.20	887	526	1074	1451	2411	3272	4366	220-240V/1/50Hz 400V/3/50Hz
CAJ4517E TAJ4517T	1-1/4	R22	25.95	887	771	1233	1673	2727	3629	4743	220-240V/1/50Hz 400V/3/50Hz





Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_AEZ9440TTélécharger

Mbsm.pro, Motor, compressor, type, RSIR, RSCR, CSIR, CSCR, PSC

Category: compressor

written by Lilianne | 18 September 2022

(1) RSIR

Resistance start induction run

(2) RSCR

Resistance start capacitor run

(3) CSIR

Capacitor start induction run

(4) CSCR/CSR

Capacitor start capacitor run

(5) PSC

Permanent split capacitor

(1) RSIR

Resistance start induction run

(2) RSCR

Resistance start capacitor run

(3) CSIR

Capacitor start induction run

(4) CSCR/CSR

Capacitor start capacitor run


(5) PSC

Permanent split capacitor

Private Picture Copyright : WWW.MBSM.PRO

Private Picture Copyright : WWW.MBSM.PRO

Compressor Windings



Private Picture Copyright: WWW.MBSM.PRO




(1) RSIR
Resistance start induction run

Private Picture Copyright: WWW.MBSM.PRO

RSIR



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO


(2) RSCR Resistance start capacitor run

Private Picture Copyright : WWW.MBSM.PRO

RSCR



Private Picture Copyright : WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO


(3) CSIR Capacitor start induction run

Private Picture Copyright: WWW.MBSM.PRO

CSIR



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO




(4) CSCR/CSR Capacitor start capacitor run

Private Picture Copyright: WWW.MBSM.PRO

CSCR/CSR



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO


(5) PSC Permanent split capacitor

Private Picture Copyright: WWW.MBSM.PRO

PSC



Private Picture Copyright: WWW.MBSM.PRO



Private Picture Copyright: WWW.MBSM.PRO

Mbsm.pro, COMPRESSOR, ZEL, Zanussi, refrigerator, CUBIGEL/ ACC , HML140A, HDL140A, LBP, R600A, 220-240V, 1 /8hp, 140w

Category: compressor

written by Lilianne | 18 September 2022



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, COMPRESSOR, ZEL, Zanussi, refrigerator, CUBIGEL/ ACC , HML140A, HDL140A, LBP, R600A, 220-240V, 1 /8hp, 140w

Mbsm.pro, Compressor, JIAXIPERA,
ND1080Y, 1/8HP, ND1090Y, 1/8+HP,
ND1110Y, 1/7HP, ND1111Y, 1/6-HP,
ND1112Y, 1/6+HP, NX1080Y, 1/8HP,
NX1090Y, 1/8+HP, NX1110Y, 1/7HP,
NX1111Y, 1/6HP, NX1112Y, 1/6+HP,
NX1113Y, 1/5HP, NX1114Y, 1/5+HP,
NX1116Y, 1/4HP, NX1117Y, 1/4HP,
NX1119Y, 1/4+HP, NX1120Y, 1/4+HP,
TB1080Y, 1/8HP, TB1090Y, 1/8+HP,

TB1110Y, 1/7HP, TB1111Y, 1/6HP,
TB1112Y, 1/6+HP, TB1113Y, 1/5HP,
TB1114Y, 1/5+HP, TX1080Y, 1/8HP,
TX1090Y, 1/8+HP, TX1110Y, 1/7HP,
TX1111Y, 1/6HP, TX1112Y, 1/6+HP,
TX1113Y, 1/5HP, TX1114Y, 1/5+HP,
VNX1111Y, 1/6HP, VNX1113Y, 1/5HP,
VNX1116Y, 1/4HP, ZBX1117CY, 1/4HP,
ZBX1119CY, 1/4+HP, ZBX1121CY, 1/4+HP

Category: compressor

written by Lilianne | 18 September 2022

Mbsm.pro, Compressor, JIAXIPERA, ND1080Y, 1/8HP, ND1090Y, 1/8+HP, ND1110Y, 1/7HP, ND1111Y, 1/6-HP, ND1112Y, 1/6+HP, NX1080Y, 1/8HP, NX1090Y, 1/8+HP, NX1110Y, 1/7HP, NX1111Y, 1/6HP, NX1112Y, 1/6+HP, NX1113Y, 1/5HP, NX1114Y, 1/5+HP, NX1116Y, 1/4HP, NX1117Y, 1/4HP, NX1119Y, 1/4+HP, NX1120Y, 1/4+HP, TB1080Y, 1/8HP, TB1090Y, 1/8+HP, TB1110Y, 1/7HP, TB1111Y, 1/6HP, TB1112Y, 1/6+HP, TB1113Y, 1/5HP, TB1114Y, 1/5+HP, TX1080Y, 1/8HP, TX1090Y, 1/8+HP, TX1110Y, 1/7HP, TX1111Y, 1/6HP, TX1112Y, 1/6+HP, TX1113Y, 1/5HP, TX1114Y, 1/5+HP, VNX1111Y, 1/6HP, VNX1113Y, 1/5HP, VNX1116Y, 1/4HP, ZBX1117CY, 1/4HP, ZBX1119CY, 1/4+HP, ZBX1121CY, 1/4+HP



Private Picture Copyright : WWW.MBSM.PRO



TB 1080 Y

1 / 8 HP

TB 1090 Y

1 / 8 + HP

TB 1110 Y

1 / 7 HP



TB 1111 Y

1 / 6 HP



TB 1112 Y

1 / 6 + HP



TB 1113 Y

1 / 5 HP



TB 1114 Y

1 / 5 + HP



TX 1080 Y

1 / 8 HP



TX 1090 Y

1 / 8 + HP



NX 1110 Y

1 / 7 HP

NX 1111 Y

1 / 6 HP

NX 1112 Y

1 / 6 + HP



NX 1113 Y

1 / 5 HP

NX 1114 Y

1 / 5 + HP

NX 1116 Y

1 / 4 HP



NX 1117 Y

1 / 4 HP

NX 1119 Y

1 / 4 + HP

NX 1120 Y

1 / 4 + HP

MH 1110 Y

1 / 6 - HP

ND 1070 Y

1 / 9 HP

ND 1080 Y

1 / 8 HP



ND 1090 Y

1 / 8 + HP



ND 1110 Y

1 / 7 HP



ND 1111 Y

1 / 6 - HP



ND 1112 Y

1 / 6 + HP



NX 1080 Y

1 / 8 HP



NX 1090 Y

1 / 8 + HP



JK 1080 Y

1 / 8 + HP



JK 1090 FY

1 / 6 - HP



JK 1110 Y

1 / 7 HP



JK 1111 HY

1 / 6 - HP



MH 1050 Y

1 / 12 HP



MH 1090 Y

1 / 8 + HP