

# Compressor, TEE, TURK ELEKTRIK , R600a, MTS200MT, MTS170MT, MTS185MT

written by Lilianne | 12 April 2021



Compressor, TEE, TURK ELEKTRIK , R600a, MTS200MT, MTS170MT, MTS185MT

---

## LG rotary, compressor, model,

# **QJS222PMA, 12700BTU 5.6Amps, EER = 10.7, air conditioner**

written by Lilianne | 12 April 2021

LG rotary, compressor, model, QJS222PMA, 12700BTU 5.6Amps, EER = 10.7, air conditioner

---

**no frost, egl99aa zmc  
refrigerator, DF40, silver,  
ideal, zanussi, IDEAL  
ZANUSSI, EGL99AA ZMC, DF 40  
Elgance, Compressor, ACC  
Cubigel, Huayi, Electrolux,  
ZEM GL99AA, GL99AA, LBP ,  
R134a, 220-240V/1/50Hz, 1/4  
HP, discharge 9.93 cm<sup>3</sup>, motor  
type RSIR, LRA 14.4A**

written by Lilianne | 12 April 2021



Mbsm\_dot\_pro\_private\_PDF\_GL99AA-compresseur-acc-cubigell-gl99aaTélécharger

Mbsm\_dot\_pro\_private\_PDF\_GL99AATélécharger

Compressor ACC Cubigel Huayi Electrolux ZEM GL99AA, LBP – R134a, 220-240V/1/50Hz, 1/4 HP, discharge 9.93 cm<sup>3</sup>, motor type RSIR, LRA 14.4A, expansion device: capillary, cooling: static, weight 11 kg , the statutory warranty period shall apply (24 months), Delivery time Info: with “immediately available” and “scarce stock”, usually delivery within 2 days. For “currently not available” delivery time usually 2 weeks or delivery time in urgent cases contact us.

Refrigerant:	R134a
Power range(W):	101 – 200 W
Performance range (C):	-35 C to -10 C
Connecting size:	4,9 mm
Suction:	6,5 mm
Working area:	LBP
Design type:	Hermetic
Model series:	GL
Use with:	Capillary
Power range(HP):	0-2
Power supply:	230 V
Oil type:	ISO VG 22 Ester
Engine type:	RSIR
Article condition:	New
Info:	Oil filled
Shipping weight:	13,00 Kg
Dimensions ( length × width × height ):	23,10 × 16,20 × 18,60 cm

Cooling capacity condition:	T0 -25 C, Tk +55 C
Manufacturer:	ACC Cubigel Huayi Electrolux ZEM
Model:	GL99AA
Stroke volume (cm <sup>3</sup> ):	9,93
Cooling capacity (W):	174
Power (HP):	0,25
Max. Starting current (A):	14,4
Max. Operating current (A):	1,31
Engine type:	RSIR
COP:	0,92
Note:	Static cooling
Conveying and suction volume (m <sup>3</sup> ):	1,72
Oil quantity (l):	0,295
Compressor type:	Piston
Cooling:	Static
RPM:	2900
Power range:	-35 C to -10 C
Alternative:	HLY90AA, NL11F
Pressure line (mm):	4,9
Suction line (mm):	6,5

ZMC

C

GL99AA 0326

220-240V~50Hz



CE

R 134 a

MADE IN EGYPT



482

3975 6

**GL99AAa VE09**  
**220-240V 50Hz ~1**

**COMPRESSOR**

Displacement (cm <sup>3</sup> )	9.95
Diameter (mm)	25.4
Stroke (mm)	19.62
Net Weight (Kg)	9.6
Oil type	ISO VG 22 ESTER
Oil charge (cm <sup>3</sup> )	295

**MOTOR**

Approximate Power (CV)	1/4
Voltage/Frequency (V/Hz)	220V 50Hz
Voltage range (V)	187-264
Code	-
Type	RSIR
Phase number	1 PH
Locked rotor current (A)	14.0
Main W. resist. at 25°C (Ω)	9.96
Start W. resist. at 25°C (Ω)	20.39

**APPLICATION**

Application	Low back pressure
Refrigerant	R134a
Evaporating (°C)	-35 to -10
Expansion	Capillar
Comp. cooling	Static
Max. ambient temp. (°C)	43

**NOMINAL PERFORMANCE**

	CYCLE A	CYCLE B
Cooling capacity (W)	175	238
Input power (W)	189	200
EER (kcal/Wh)	0.79	1.02
COP (W/W)	0.92	1.19
Current (A)	1.31	1.34

**TEST CONDITIONS**

Evaporating temp. (°C)	-25.0	-23.3
Condensing temp. (°C)	55.0	55.0
Liq.t. entering expan. (°C)	55.0	32.0
Ambient t. and return (°C)	32.0	32.0
Tens/Freq (V/Hz)	220V 50Hz	220V 50Hz

**ELECTRICAL COMPONENTS**

Relay	PTC 3003 - K100
Nominal voltage (V)	200 - 240
Resistance μ	14.00
Protector	MRP336JZ      T0377      AE11FU



- ✘
- ✘
- ✘
- ✘
- ✘
- ✘
- ✘
- ✘



---

**Tecumseh, Copeland,  
Compressor, Cross, Reference,**

# **P12FW, Compressor, R-12, 1/3HP, 230V, HMBP, ACC-ELECTROLUX, CUBIGEL/HUAYI**

written by Lilianne | 12 April 2021

Tecumseh, Copeland, Compressor, Cross, Reference, P12FW, Compressor, R-12, 1/3HP, 230V, HMBP, ACC-ELECTROLUX, CUBIGEL/HUAYI

---

# **Specification for r-22 Compressor, Ph Rotary Models Specification, PH41VPJT, 2 Ton, Mitsubishi Rotary Compressor, 24000BTu**

written by Lilianne | 12 April 2021

## **Product Specification**

Horse Power	2 Ton
Brand	Mitsubishi
Compressor Technology	Rotary Compressor
Rental Available	No
Spares Available	No
Is It Portable	Yes



Installation/After Sales Service Available	No
Cylinder	1
Warranty	1 Year
Phase	Single
Weight	28 Kg
No. Of Cylinder	1
Cylinder Type	Round
Voltage	220 V
Material	Copper
Accessories	No
Application	AC
Color	Black



Mbsm\_dot\_pro\_private\_PDF\_Rotary-CatalogueTélécharger

Mbsm\_dot\_pro\_private\_PDF\_SCI\_Rotary\_Compressor-PHTélécharger

# Refrigerator, compressor, E1134CZA, 1/2 hp, E1130CZA, E1121CZA, 3/8HP, commercial, freezer, R134a

written by Lilianne | 12 April 2021

Refrigerator, compressor, E1134CZA, E1130CZA, E1121CZA, 3/8HP,  
commercial, freezer, R134a

---

**RÉFRIGÉRATEUR NIKAI,  
nrf480fn4, 165W, Compressor,  
ATD60L, Wanbao Huaguang  
Refrigerator, 1/5Hp, R134A,  
120G, 1.25A, 220V/50HZ**

written by Lilianne | 12 April 2021



RÉFRIGÉRATEUR NIKAI, nrf480fn4, 165W, Compressor, ATD60L,  
Wanbao Huaguang Refrigerator, 1/6Hp, R134A, 120G, 1.25A,  
220V/50HZ

---

**Compressor, 1/3HP, FR10S,  
103U2930, SECOP, 103U, 2930,  
Compressor Danfoss, R12,  
220-240V, 50Hz**

written by Lilianne | 12 April 2021

▪ DESCRIPTION

# DESCRIPTION



Mbsm\_dot\_pro\_private\_PDF\_103u2930-compressorTélécharger

Mbsm\_dot\_pro\_private\_PDF\_103u2930Télécharger

Sr	Material	Material Description	Capacity	Cons. Watts -25
		<b>R134a</b>		
1	103G6660	Danfoss Compressor FR 6G	1/6 HP	119 W
2	103G6680	Danfoss compressor FR 7.5G	1/5 HP	138 W
3	103G6780	Danfoss compressor FR 8.5G	1/4 HP	164 W
4	103G6880	Danfoss compressor FR 10G	1/3 HP	194 W
		<b>R12a</b>		
5	103G2630	Danfoss compressor FR 6S	1/6 HP	119 W
6	103U2730	Danfoss compressor FR 7.5S	1/5 HP	138 W
7	103U2830	Danfoss compressor FR 8.5S	1/4 HP	164 W
8	103U2930	Danfoss compressor FR 10S	1/3 HP	194 W
		<b>R134a</b>		
9	104G8240	Danfoss compressor SC 12G	3/8 HP	298 W
10	104G8520	Danfoss compressor SC 15G	1/2 HP	356 W
11	104G8820	Danfoss compressor SC 18G	5/8 HP	615 W
12	104G8140	Danfoss compressor SC 21G	7/8 HP	702 W
		<b>R404a / R507a</b>		
13	104L2523	Danfoss Compressor SC 10CL	1/3 HP	352 W
14	104L2623	Danfoss Compressor SC 12CL	3/8 HP	445 W
15	104L2853	Danfoss Compressor SC 15CL	1/2 HP	560 W
16	104L2123	Danfoss Compressor SC 18CL	5/8 HP	615 W

17	104L2322	Danfoss Compressor SC 21CL	7/8 HP	702 W
----	----------	----------------------------	--------	-------

# COMPRESSOR, DONPER, NE6213CK, 1/2hp, R404a

written by Lilianne | 12 April 2021

Ne6213Ck Compressor R404A Med Temp 12 Disp 1080W @ -5 1/2Hp  
240V 50Hz



Mbsm\_dot\_pro\_private\_PDF\_ne6213ck-compressorTélécharger

# Compressor, QD110, 3/10 HP, LBP, R12/R406, 276w, R12, R406

written by Lilianne | 12 April 2021

Quantité(Pièce)	1 – 30	31 – 70	71 – 150	>150
Durée estimée (jours)	5	10	15	À négocier

Tension: 220 V-240 V

50 HZ

Compresseur LBP R12/R406

Modèle	Valage	Fréquence	Déplacement	Capacité	Puissance d'entrée	Type de moteur	De charge d'huile	Type de refroidissement	Poids
	(V)	(Hz)	(CC)	(W)	(W)		(CC)		(Kg)
QD30	220-240	50	3.0	62	81	RSIR	180	ST	6.3
QD36	220-240	50	3.6	75	93	RSIR	180	ST	6.4
QD55	220-240	50	5.5	133	110	RSIR	240	ST	8.4
QD65	220-240	50	6.5	155	130	RSIR	240	ST	8.4
QD75	220-240	50	7.5	176	146	RSIR	240	ST	8.6
QD85	220-240	50	8.5	202	168	RSIR	240	ST	8.9
QD110	220-240	50	11.0	276	236	RSIR	240	ST	9.9
QD125	220-240	50	12.5	305	254	RSCR	280	ST	11.2



Mbsm\_dot\_pro\_private\_PDF\_QD110-1Télécharger

