

**Mbsm.pro, Hermetic, Copeland,  
Compressors, CRHQ-0275-PFV,  
crhq0275pfv, crhq-0275-  
pfv-501, crhq0275-pfv-501,  
crhq0275-pfv, 4 Hp, r22,  
33800 btu**

written by Lilianne | 9 October 2022



Mbsm.pro, Hermetic, Copeland, Compressors, CRHQ-0275-PFV,  
crhq0275pfv, crhq-0275-pfv-501, crhq0275-pfv-501, crhq0275-  
pfv, 4 Hp, r22, 33800 btu

---

**Mbsm.pro, Copeland,  
Reciprocating, Hermetic,  
Compressors, CRNQ-0500-TFD, 5  
hp, R22, HCFC, R-22, 50 Hz, 3  
– Phase, 380/420 V , CR QR  
Series**

written by Lilianne | 9 October 2022



Mbsm.pro, Copeland, Reciprocating, Hermetic, Compressors,  
CRNQ-0500-TFD, 5 hp, R22, HCFC, R-22, 50 Hz, 3 – Phase,

**Mbsm.pro, compressors, L88AV,  
1/4 hp++, 1/3 hp-, R12, HMBP  
, rcir**

written by Lilianne | 9 October 2022



Mbsm.pro, compressors, L88AV, 1/4 hp++, 1/3 hp-, R12, HMBP ,  
rcir

---

**Mbsm.pro, Bristol,  
Compressor, H24B22QABJC,  
21800 btu/h, H24BQ SERIES,  
6397 W, 230 v, 1 Phase, Ira  
52 A, Compressors, Chillers &  
Condensers, high temperature,  
R22, basic model, model B,**

**PSC capacitor, line break  
internal, capillarie, 0.64/80  
cm, 0.70/100 cm**

written by Lilianne | 9 October 2022



Mbsm.pro, Bristol, Compressor, H24B22QABJC, 21800 btu/h, H24BQ SERIES, 6397 W, 230 v, 1 Phase, lra 52 A, Compressors, Chillers & Condensers, high temperature, R22, basic model, model B, PSC capacitor, line break internal, capillarie, 0.64/80 cm, 0.70/100 cm

---

**Mbsm.pro, Scroll, Danfoss, HRP051T4LP6, compressors, Hermetic, 49.15 kBtu/h, R22, R407C, 4 1/4Hp, 3Ph, POE, Lra 60A**

written by Lilianne | 9 October 2022

bsm.pro, Scroll, Danfoss, HRP051T4LP6, compressors, Hermetic, 49.15 kBtu/h, R22, R407C, 4 1/4Hp, 3Ph, POE, Lra 60A

---

**Catalogue, DANFOSS, All Compressor, PDF Catalogs, Documentation**

written by Lilianne | 9 October 2022

Catalogue, DANFOSS, All Compressor, PDF Catalogs, Documentation

Mbsm\_dot\_pro\_private\_PDF\_DANFOSS-FRCC.PK\_.046.A1.02Télécharger  
Mbsm\_dot\_pro\_private\_PDF\_Danfoss\_scroll\_compressors\_HXX\_R410AT  
élécharger

Mbsm\_dot\_pro\_private\_PDF\_DANFOSS-1Télécharger

Mbsm\_dot\_pro\_private\_PDF\_DANFOSSTélécharger



---

# Whirlpool, Aspera, NE2125E, LBP, capacitive, start inductive run, hermetic compressor, R22, 1/4Hp++ or 1/3Hp-

written by Lilianne | 9 October 2022

ompressor Aspera NE2125E, LBP – R22, 220-240V / 1 / 50Hz,  
stroke volume 8.78 cm<sup>3</sup>, LRA 11.0A, motor type CSIR, capillary  
tube / expansion valve operation, oil AB 46.Cooling  
capacity measured for condensation temperature of: 45 ° C,  
Measurement conditions: ASHRAE

Unfortunately the compressor is no longer available.

If you would like an offer for an identical alternative,  
please email us or give us a short call, we will prepare an  
offer for you.Cooling capacity (W) at To

- 10 ° C	- 15 ° C	- 20 ° C	- 25 ° C	- 30 ° C
651	517	401	304	226



- ✘
- ✘
- ✘
- ✘
- ✘



Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)

- ✘

Mbsm\_dot\_pro\_private\_PDF\_ne2125e-Embraco\_VerdichterTélécharger

<b>Shipping Class</b>	Default
<b>Scope Of Application</b>	LBP
<b>Delivery Time</b>	2-3 Weeks

<b>Stock Availability</b>	In Stock
<b>Type</b>	Reciprocating Piston
<b>Condensation Temperature</b>	45 ° C
<b>Manufacturer</b>	Aspera
<b>Manufacturer No.</b>	NE2125E
<b>Power In Hp</b>	1/4 +
<b>Starting Torque</b>	HST
<b>Stroke Volume In Cm3</b>	8.78
<b>Measurement Conditions</b>	Ashrae
<b>Refrigerant</b>	R22
<b>Oil Type</b>	ISO46
<b>Series</b>	NE
<b>Condensing Units Compressors</b>	Compressor
<b>Tension</b>	220-240V
<b>Weight In Kg</b>	10.4

---

# Compressor, ACC, Cubigel, GL60AN, R134a, 220-240V, HMBP, 1/6HP

written by Lilianne | 9 October 2022

Type: Hermetic piston compressors Producer: ACC Series: HMBP

Model: GL60AN

General data

Refrigerant:	R134a
Discharge element:	C



Cooling:	S	
Maximum ambient temperature [°C]:	50	

### Compressor's data

Cylinder capacity [cm <sup>3</sup> ]:	6	
Displacement [m <sup>3</sup> /h]:	1	
Weight [kg]:	9,9	
Oil charge [cm <sup>3</sup> ]:	345	
Oil type:	ISO VG 19 ESTER	

### Engine's data

Engine type:	RSIR	
Power [KM]:	1/6	
Starting element:	LST	
Power supply:	220V 50Hz	
Voltage range:	170-264	
Locked rotor current [A]:	14,6	
Running winding resistance (25°C) [Ω]:	9,33	
Starting winding resistance (25°C) [Ω]:	10,81	

### Electrical data

Relays:	3003	
Shielding element:	MRA38085, T0515, AF11BJ	
Starting capacitor volume [μF]:		

### Connections

	millimeters	inches
Suction tube:	6,5	
Service tube:	6,5	
Discharge tube:	4,9	



# Danfoss, Compressor, 5 Hp, R22, Démontage, ouverture, DESTRUCTION

written by Lilianne | 9 October 2022



---

**Mbsm.pro, PDF, GL80AF , ZEM,  
EGL80AF, Compressors , GD40AF  
1/9 , GL45AF 1/8 , GL60AF,  
GL70AF , GL70ANa 1/5**

# , GL70AND, GL80AF 1/5

written by Lilianne | 9 October 2022



Mbsm\_dot\_pro\_private\_PDF\_GLy80aaTélécharger

Mbsm\_dot\_pro\_private\_PDF\_GLy80aa-compresseur-acc-cubigellTélécharger

Mbsm\_dot\_pro\_private\_PDF\_GLy80aa-1Télécharger

