





Mbsm.pro, Compressor, Panasonic, Gp21tb, Gp21fb, 5/8 hp, 415 kcal, 351 w (cap/cool), ELECTROLUX, HERMETIC, R134a, LBP, 220-240/1/50

written by Lilianne | 10 February 2024

ELECTROLUX HERMETIC COMPRESSORS - R134a LBP
VOLTAGE 220-240/1/50

Code	Model	Nom. hp	Displacem. cc	Expansion	Ashrae -23,3C° kcal/h	Cecomaf -25C° W
CMP100AC	GD24AA	1/20	2,44	C	41	34
CMP101AC	GD30AA	1/12	3,08	C	62	52
CMP102AC	GD36AA	1/12	3,62	C	72	61
CMP103AC	GD40AA	1/10	4,03	C	82	70
CMP104AC	AS45AA	1/8	4,56	C/V	112	82
CMP105AC	AS60AA	1/6	5,99	C/V	154	114
CMP106AC	AS75AA	1/5	6,64	C/V	176	129
CMP107AC	AS80AA	1/5	7,39	C/V	198	145
CMP108AC	GL45AA	1/8	4,55	C	96	81
CMP109AC	GL50AA	1/7	5,12	C	107	91
CMP110AC	GL60AA	1/6	5,99	C	126	107
CMP111AC	GL70AA	1/5	6,65	C	142	121
CMP112AC	GL75AA	1/5	7,39	C	155	132
CMP113AC	GL80AA	1/5	8,10	C	170	144
CMP114AC	GL90AA	1/5	9,08	C	193	165
CMP115AC	GL99AA	1/4	9,93	C	205	175
CMP116AC	GP12FB	1/3	12,00	C/V	225	190
CMP117AC	GP14FB	3/8	14,00	C/V	270	228
CMP118AC	GP16FB	3/8	16,14	C/V	315	266
CMP119AC	GP18FB	3/7	18,40	C/V	345	291
CMP120AC	GP21FB	2/3	20,72	C/V	415	351
CMP121AC	GVY35AA	1/10	3,36	C/V	84	62
CMP122AC	GVY40AA	1/9	3,87	C/V	107	79
CMP123AC	GVY44AA	1/8	4,38	C/V	122	91
CMP124AC	GVY57AA	1/7	5,73	C/V	150	109
CMP125AC	GVY66AA	1/5	7,00	C/V	181	132
CMP126AC	GVY75AA	1/5	7,52	C/V	205	150
CMP127AC	GQY35AA	1/10	3,66	C/V	91	67
CMP128AC	GQY40AA	1/9	4,01	C/V	104	76
CMP129AC	GQY45AA	1/8	4,56	C/V	121	90

Mbsm.pro, Compressor, Panasonic, Gp21tp, 5/8 hp, 415 kcal, 351 w (cap/cool), ELECTROLUX, HERMETIC, COMPRESSORS, R134a, LBP, 220-240/1/50

**Mbsm.pro, compressor, Sanyo,
Rotary, Split system air
conditioner, Compressors, C-
R221H5S, S6231526791, 24000
btu, R22, 3 hp, 2 ton**

written by Lilianne | 10 February 2024

SANYO



MODEL C-R221H5S

CODE 80687145



CHINA RESOURCES SANYO (SHENYANG) COMPRESSOR CO., LTD.
沈阳三洋压缩机有限公司

WARNING-SERVICEMAN

- 1. FIELD SERVICE LEAK TEST PRESSURE MUST NOT EXCEED 40PSI (2.7MPa)
 - 2. THIS COMPRESSOR MUST BE GROUNDED.
 - 3. DO NOT OPERATE WITHOUT PROTECTIVE COVER OVER TERMINALS
- DISCONNECT ALL POWER BEFORE REMOVING THE PROTECTIVE COVER

CAUTION

COMPRESSOR HOUSING MAY REACH 150°C WITH THERMAL PROTECTION
APPROVED BY SANYO AND TESTED IN ACCORDANCE WITH EN 1254

Mbsm.pro, compressor, Sanyo, Rotary, Split system air conditioner, Compressors, C-R221H5S, S6231526791, 24000 btu,

R22, 3 hp, 2 ton

**Mbsm.pro, compressors,
DZ120V1A, DZ120V1V, DZ120V1B,
inverter, blcd, from 1320 to
4320 rpm, from 82 to 265 w
input, cooling 293 btu to 904
, 1/3 hp, r600a, lbp**

written by Lilianne | 10 February 2024



Mbsm.pro, compressors, DZ120V1A, DZ120V1V, DZ120V1B, inverter, blcd, from 1320 to 4320 rpm, from 82 to 265 w input, cooling 293 btu to 904 , 1/3 hp, r600a, lbp

**Commercial refrigerator,
compressors, GLY16RG, 3/8
hp++, R134a, HMBP, 1492W,
r134, Compressor ACC,**

Cubigel, Huayi, Electrolux, ZEM

written by Amina | 10 February 2024



Commercial refrigerator, compressors, GLY16RG, 3/8 hp++, R134a, HMBP, 1492W, r134, Compressor ACC, Cubigel, Huayi, Electrolux, ZEM

**Mbsm.pro, Compressors,
Danfoss, R134a, FR11G, 1/4
hp++, 1/3 hp-, HBP, 103g6980,
103g 6980, 103 g 6980,
195B0028, 103G6980**

written by Lilianne | 10 February 2024



Mbsm.pro, Compressors, Danfoss, R134a, FR11G, 1/4 hp++, 1/3 hp-, HBP, 103g6980, 103g 6980, 103 g 6980, 195B0028, 103G6980

**Mbsm.pro, Danfoss, Scroll,
Compressors, HRH, HLH, HLJ,
R410A, 6hp, HLJ072T5LP6,
HLJ075T5LP6, HLJ083T5LP6, 3**

ph, 380 v

written by Lilianne | 10 February 2024



Norme d'approbation	CE -UL
Résistance de l'enroulement auxiliaire (enroulement de démarrage) pour les compresseurs monophasés [Ohm]	1,02 ohm
Technique de la marque	Compresseur scroll
Contrôle de capacité	Vitesse fixe
Capacité du condensateur A	55 µF
Capacité du condensateur B	88-108 µF
Couleur	Noir
Alimentation du compresseur [V/Ph/Hz]	220-240/1/50
Code de configuration	Seul
Type de connexion	Brasé
La description	HLJ083T5
Diamètre [mm]	184 millimètres
Hauteur de raccordement de refoulement [mm]	422 millimètres
Taille du tuyau de raccordement de décharge [po]	1/2 po
Taille de la connexion de décharge [po]	1/2 po
Numéro de dessin	0XR6002B-2
Économiseur	Non
Norme de montage	FDAL
Fréquence [Hz]	50
Orifice manomètre HP	Aucun
Orifice de jauge LP	Aucun

Égalisation gaz	Aucun
Montage sur verre	Aucun
Pression max côté haut (Ps)	46,1 bars
Valeur haute de la tension nominale à 50Hz [V]	230V
Valeur haute de la tension nominale à 60Hz [V]	0V
Valeur élevée de la plage de tension à 50 Hz [V]	253V
Valeur élevée de la plage de tension à 60 Hz [V]	0V
Classe de protection IP	IP22
Longueur [mm]	239 millimètres
Pression max côté bas (Ps)	31,1 bars
Basse valeur de la tension nominale à 50Hz [V]	230V
Basse valeur de la tension nominale à 60Hz [V]	0V
Valeur basse de la plage de tension à 50 Hz [V]	207V
Valeur basse de la plage de tension à 60 Hz [V]	0V
LRA	130 A
Résistance de l'enroulement principal pour les compresseurs monophasés [0hm]	0,39 ohm
CMC	50 A
Numéro de modèle	HLJ083T5LP6
Protection moteur	Protecteur de surcharge interne
Puissance frigorifique nominale à 50Hz	17,3kW

Puissance calorifique nominale à 50Hz	11,3kW
Charge d'huile [L]	1,57L
Vidange d'huile	Aucun
Égalisation d'huile	Aucun
Référence huile	320HV
Type d'huile	PVE
Forme d'emballage	Paquet individuel/palette
Quantité d'emballage	16
Phase	1
Connexions électriques	Bêche
Réfrigérant	R410A
Charge de réfrigérant [kg] [Max]	5,44 kilogrammes
Modèle de relais	3ARR3*25AS*
Soupape de décharge	Oui
RLA	32 A
Vitesse de rotation à 50 Hz [tr/min]	2900 tr/min
Vitesse de rotation à 60 Hz [tr/min]	0 tr/min
Utilisation des segments	Climatisation
Instructions expédiées	Instructions d'installation
Montage livré	Kit de montage avec œillets et manchons
Pétrole expédié	Charge d'huile initiale
Hauteur du raccord d'aspiration [mm]	280 millimètres
Taille du tuyau de raccordement d'aspiration [po]	7/8 po

Taille du raccord d'aspiration [in]	7/8 po
Volume balayé [cm³]	78,08 cm ³
Technologie	Faire défiler
Hauteur totale [mm]	455 millimètres
Taper	HLJ
Désignation de type	Compresseur
Viscosité [cP]	68 cP
Tension du condensateur A [V]	440V
Tension du condensateur B [V]	330V
Largeur [mm]	239 millimètres

Danfoss Scroll Compressors HRH, HLH, HLJ




MODEL DANFOSS	CODE DANFOSS M-PACK	REFRI-GERANT	VOLTAGE	Cond. t° +45°C and Nominal capacity at 50Hz	POWER INPUT (Kw)	Swept Volume DISPL. sm ³ /r	Displ. m ³ /h
				R410 EVAPORATING TEMPERATURE °C (BTU/HR) 7,2°C 50Hz			
HRH031U4LP6	120U1191	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	29484	2,67	29,8	5,19
HRH031U5LP6	120U1166	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	29484			
HRH032U4LP6	120U1196	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	29942	2,75	30,6	5,33
HRH032U5LP6	120U1171	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	29942			
HRH036U4LP6	120U1201	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	34493	3,13	34,7	6,04
HRH036U5LP6	120U1176	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	34493			

HRH038U4LP6	120U1206	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	36353	3,35	36,5	6,36
HRH038U5LP6	120U1181	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	36353			
HRH040U4LP6	120U1211	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	39789	3,58		-
HRH040U5LP6	120U1186	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	39789			
HRH041U4LP6	120U1356	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	39077			
HRH044U4LP6	120U1361	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	42309	3,92	42,6	7,41
HRH049U4LP6	120U1366	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	47079	4,04	47,4	8,24
HRH051U4LP6	120U1371	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	50057	4,21	49,3	8,58
HRH051U5LP6	120U1326	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	50057			
HRH054U4LP6	120U1376	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	52103	4,41	52,1	9,07
HRH054U5LP6	120U1331	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	52103			
HRH056U4LP6	120U1381	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	53997	4,58	54,1	9,42
HRH056U5LP6	120U1336	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	53997			
HLH061T4LC6	120U2052	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	57408	4,89	57,8	10,10
HLH068T4LC6	120U1391	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	65244	5,26	64,4	11,21
HLH068T5LP6	120U1341	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	65244			
HLJ072T4LC6	120U1396	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	68892			
HLJ072T5LP6	120U1346	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	68028	6,09		-
HLJ083T4LC6	120U1401	R410A	380-400V/3~/50Hz & 460V/3~/60Hz	79393			
HLJ083T5LP6	120U1351	R410A	220-240V/1~/50Hz & 265V/1~/60Hz	77059	7,02		-

**Mbsm.pro, LBP, S series,
compressors, HuaJun, QD65,
1/6 hp++, 1/5 hp-, R134a**

written by mahdi miled | 10 February 2024

OK
93 25-10-2020

 **QD65** RoHS
220-240V ~ 50Hz
R134a  
← SUCTION TUBE 2020040065
NingBo Anuodan Machinery Co.,LTD

Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, LBP, S series, compressors, HuaJun, QD65, 1/6 hp++, 1/5 hp-, R134a

**Mbsm.pro, AJA4461AXA,
Tecumseh, Compressors,
AJ311AT-141-J7, 115V, 1/2HP,
R12, high temperature, 6100
BTU,**

written by Jamila | 10 February 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, AJA4461AXA, Tecumseh, Compressors, AJ311AT-141-J7,
115V, 1/2HP, R12, high temperature, 6100 BTU,

Mbsm.pro, Danfoss, compressors, R134a, medium, temperature, HMBP

written by Jamila | 10 February 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, Danfoss, compressors, R134a, medium, temperature, HMBP

Mbsm.pro, compressor, Panasonic, 1/3 hp, Lbp, E Series, R134a, ETI57C13DCH, ENI68C13DCH, Reciprocating, Compressors, Variable Speed, inverter, BLCD, from 63 to 240 w, 240v+-, from 60 to 268 hz, from 25 rps to 72 rps

written by Jamila | 10 February 2024



Private Picture Copyright : WWW.MBSM.PRO

Mbsm.pro, compressor, Panasonic, Lbp, E Series, R134a,

ETI57C13DCH, ENI68C13DCH, Reciprocating, Compressors, Variable Speed, inverter, from 63 to 240 w, 240v+-, from 60 to 268 hz, from 25 rps to 72 rps