


# Mbsm.pro, Refregirator, UR-10/BCD-480, 420 L, Compressor, GUY75AA, LBP, R134a, 145 G, 1/4 hp, 1.30 A

written by Lilianne | 28 February 2024



Mbsm.pro, Refregirator, UR-10/BCD-480, 420 L, Compressor, GUY75AA, LBP, R134a, 145 G, 1/4 hp, 1.30 A

Mbsm.pro, Codes and

# capacities of ZEL all compressors, pistons, motors, and refrigeration and air conditioning motors

written by Lilianne | 28 February 2024

Model	输入功率 (Input Power)	制冷量 (Cooling Capacity)
GML200A	.152W	.200W
GML180A	.144W	.187W
GML160G	.129W	.168W
GML140A	.108W	.140W
GML110A	.90W	.112W

WOMA 旺码  
广州旺码制冷设备有限公司  
Email: davidhu815@gmail.com

C 63010440

ZEL GML200A 17-41  
220-240V 50Hz  
R134a SUCTION >  
8 379 0004810 2

Private Picture Copyright : WWW.MBSM.PRO

GVY61AA, GVY75AA, GVY75AG, GTH86AA, GTH93AA, GTT66AA, GTT75AA, GKD86AA, GKD93AA, GXL140F, GXL200F, MODEL, GML70A, GML90A, GML110A, GML125A, GML140A, GML140A/I, GML160A, GML180A, GML200A, GML200A/I, GTM26AA, GTM75AA, GDL160A, GDL200A, GXL100A, GXL125A, GXL140A, GXL160A, GXL200A, GXL240A, GL60TP, GL80TP, GL90TP, GL90TP/I, GL10TP, GL12TP, GHP16AA, GHP18AA, GHP21AA, MODEL, HML100A, HML125A, HML140A, HML155A, HML170A, HML190A, HML200A, HDL100A, HDL125A, HDL140A, HDL155A, HDL170A, HDL200A, HXL100A, HXL125A, HXL140A, HXL155A, HXL170A, HXL190A, HPL100A, HPL125A, HPL140A, HML125A(T), HML140A(T),

HML170A(T), HMK12AA , , MODEL , HDL125F, HDL140F, HDL160F, HDL180F, HDL190F, HXL140F, HXL160F, HXL190F , HML125G , HML140G , HML170G , HDL140G , HDL170G , HXL155G , HXL185G , , MODEL , GML70A, GML80A, GML90A, GML110A, GML125A, GML140A, GML180A, GML200A(M), GML200A, GDL140A, GDL160A, GDL200A(M), GDL200A, GXL125A, GXL140A, GXL160A, GXL200A , , MODEL , GML70G , GML80G , GML90G , GML125G , GML140G , GML160G , GXL125G , GXL140G , GXL160G , GML110A(T), GML140A(T), GML200A(T) , MODEL , HDZ100A(M), HDZ100A, HDZ125A, HDZ140A, HDZ155A, HDZ170A, HXZ100A, HXZ125A, HXZ140A, HXZ155A, HXZ170A, HPZ100A, HPZ125A, HPZ140A, HPZ155A, HPZ170A, HDZ100F, HDZ125F, HDZ140F, HDZ160F, HDZ190F , , MODEL , HMM70A, HMM80A, HMM90A, HMM100A, HDM80A, HDM90A, HDM100A, HDM110A , , MODEL , GL90TB, GL90TB(B), GL10TB, GL12TB , GL60TG , GL90TG , GTM93AA, GTM10AA, GTM12AA , GTM93AG , GMM70A, GMM80A, GMM90A, GMM110A , , MODEL , NLT44AA, NLT53AA, NLT57AA, NLT61AA, NLT66AA, NLT75AA, NLT80AA, NLT86AA, NLT93AA, NLT44AA(I), NLT53AA(I), NLT57AA(I), NLT61AA(I), NLT66AA(I), NLT75AA(I), NLT80AA(I), NLL160A, NLL200A, NLL200A(I), NMT53AA, NMT57AA, NMT66AA, NMT75AA , , MODEL , HTT11AA, HPKD190A, HPKX190A, HTH14AA, HTH14AA(I), HKD14AA, HYV67AA.02, HTK12AA.02 , HPKD180G , HPKD200G , , MODEL , GVY57AA, GVY61AA, GVY66AA, GVY75AA, GTH86AA, GTH93AA, GTM93AA, GTT66AA, GTT75AA, GKD86AA, GKD86AA(I), GKD93AA , GVY53AG , GVY57AG , GVY75AG , GKD86AG , GKD93AG

---

**Cubigel Compressors,  
Compressor, GQY80AT, 1/4Hp,**

# LBP, R134a, 8.1cmc, 165 W, REFRIGERATEUR INDESIT

written by Lilianne | 28 February 2024

Compresor GQY80AT, freon R134a, capacitate 8.1  
cmc, capacitate frigorifica ASHRAE 222 W, capacitate  
frigorifica CECOMAF 165 W, racire statica #GQY80AT

Model: GQY80AT

Freon: R134a

Capacitate: 8.1 cmc

Capacitate frigorifica ASHRAE: 222 W

Capacitate frigorifica CECOMAF: 165 W

35 -30 -25 -10 w COP

• 451.00.3301 GD40AAa / GVY40AA 1/10 S 4.03 34 49 70 0.77 154  
C 200 6.7 RSIR P •

451.00.3202 GD40AA 1/10 S 4.03 34 49 70 0.77 154 C 200 6.7  
RSIR P •

• 451.00.3302 GL45AA / GVY44AA 1/8 S 4.55 37 56 81 0.81 183 C  
265 8.3 RSIR P •

• 451.00.3303 GL60AA / GVY57AA 1/6 S 5.99 50 75 107 0.85 238 C  
265 9.1 RSIR P •

• 451.00.3304 GL75AA / GVY66AA 1/5 S 6.65 57 85 121 0.87 267 C  
345 9.6 RSIR P •

• 451.00.3305 GL80AA / GVY75AA 1/5 S 7.52 68 101 144 0.89 326  
C 345 9.9 RSIR P •

451.00.3104 GL80AAb 1/5 OC 8.10 68 101 144 0.89 326 C-V 345  
9.9 CSIR R •

451.00.3005 GL90AA 1/4 S 9.08 82 119 165 0.90 350 C 345 10.2  
RSIR P •

• 451.00.3306 GL90AAa / GQY80AT 1/4 S 9.08 82 119 165 0.90 350  
C 345 10.2 RSIR P •

451.00.3105 GL90AAb 1/4 OC 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •

• 451.00.3205 GL90AAb 1/4 F 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •

- 451.00.3325 GL90AAa 1/4 OC 9.08 82 119 165 0.90 350 C-V 345  
10.2 CSIR R •
- 451.00.3106 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400 11.5  
RSIR R •
- 451.00.3206 GP12FB 1/3 F 12.00 83 131 190 0.88 424 C 400  
11.5 RSIR R •
- 451.00.3326 GP12BB 1/3 OC 12.00 83 131 190 0.88 424 C 400  
11.5 RSIR R •
- 451.00.3218 GP14CB 3/8 F 14.17 99 158 228 0.90 509 C 400 11.5  
RSIR R •
- 451.00.3223 GP16FB 3/8 F 16.15 109 182 266 0.89 585 C-V 530  
12.0 CSIR R •
- 451.00.3224 GX18FB 3/7 F 18.40 123 199 291 0.91 660 C-V 500  
15.1 CSIR R •
- 451.00.3225 GX21FB 2/3 F 20.72 151 243 351 0.93 778 C-V 500  
15.5 CSIR R •
  
- 451.00.3403 GL45TB 1/6 F 4.50 76 134 342 1.62 412 C-V 300 8.4  
CSIR R •
- 451.00.3503 GL45PB 1/6 F 4.50 76 134 342 1.62 412 C-V 300  
8.4 CSIR R •
- 451.00.3404 GL60TB 1/5 F 5.67 95 170 437 1.82 527 C-V 300 9.5  
CSIR R •
- 451.00.3504 GL60PB 1/5 F 5.67 95 170 437 1.82 527 C-V 300  
9.5 CSIR R •
- 451.00.3406 GL80TB 1/5 F 7.57 111 212 554 1.83 667 C-V 300 9.5  
CSIR R •
- 451.00.3505 GL90TB 1/4 F 8.85 142 259 661 1.91 796 C-V 300  
10.8 CSIR R •
- 451.00.3506 GP12TB 3/8 F 12.05 169 338 893 1.80 1077 C-V 350  
11.2 CSIR R •
- 451.00.3418 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400  
11.5 CSIR R •
- 451.00.3513 GP14TB 3/8 F 14.00 190 373 999 1.77 1208 C-V 400  
11.5 CSIR R •
- 451.00.3419 GX18TB 1/2 F 18.40 285 539 1390 1.91 1673 C-V 500  
16.0 CSIR R •

451.00.3420 GX21TB 5/8 F 20.72 332 603 1550 1.90 1866 C-V 500  
17.0 CSIR R •  
451.00.3421 GX23TB 5/8 F 23.20 368 677 1730 1.89 2083 C-V 500  
17.0 CSIR R •  
• 451.00.3422 GS26TB 3/4 F 25.93 392 771 2071 2.09 1011 C-V  
887 22.7 CSIR R •  
451.00.3423 GS30TB 7/8 F 29.95 317 785 2452 2.33 3020 C-V 887  
22.7 CSR R •  
• 451.00.3424 GS34TB 1 F 34.42 476 1068 2852 2.28 3421 C-V 887  
22.7 CSR R •



BAJA presión					serie LBP							R-134a				
CÓDIGO REMLE	MODELO	Potencia	Enfri.	Cilindr.	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
* Gases sustitutivos del R-12 y R-134a.					CECOMAF (W)											
o Últimas existencias					-35	-30	-25		-10							
					w	COP										
• 451.00.3301	GD40AAa / GVV40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
o 451.00.3202	GD40AA	1/10	S	4.03	34	49	70	0.77	154	C	200	6.7	RSIR	P	•	
• 451.00.3302	GL45AA / GVV44AA	1/8	S	4.55	37	56	81	0.81	183	C	265	8.3	RSIR	P	•	
• 451.00.3303	GL60AA / GVV57AA	1/6	S	5.99	50	75	107	0.85	238	C	265	9.1	RSIR	P	•	
• 451.00.3304	GL75AA / GVV66AA	1/5	S	6.65	57	85	121	0.87	267	C	345	9.6	RSIR	P	•	
• 451.00.3305	GL80AA / GVV75AA	1/5	S	7.52	68	101	144	0.89	326	C	345	9.9	RSIR	P	•	
o 451.00.3104	GL80AAb	1/5	OC	8.10	68	101	144	0.89	326	C-V	345	9.9	CSIR	R	•	
o 451.00.3005	GL90AA	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
• 451.00.3306	GL90AAa / GQY80AT	1/4	S	9.08	82	119	165	0.90	350	C	345	10.2	RSIR	P	•	
o 451.00.3105	GL90AAb	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3205	GL90AAb	1/4	F	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
• 451.00.3325	GL90AAa	1/4	OC	9.08	82	119	165	0.90	350	C-V	345	10.2	CSIR	R	•	
o 451.00.3106	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3206	GP12FB	1/3	F	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
• 451.00.3326	GP12BB	1/3	OC	12.00	83	131	190	0.88	424	C	400	11.5	RSIR	R	•	
451.00.3218	GP14CB	3/8	F	14.17	99	158	228	0.90	509	C	400	11.5	RSIR	R	•	
451.00.3223	GP16FB	3/8	F	16.15	109	182	266	0.89	585	C-V	530	12.0	CSIR	R	•	
451.00.3224	GX18FB	3/7	F	18.40	123	199	291	0.91	660	C-V	500	15.1	CSIR	R	•	
451.00.3225	GX21FB	2/3	F	20.72	151	243	351	0.93	778	C-V	500	15.5	CSIR	R	•	

Private Picture Copyright : WWW.MBSM.PRO

ALTA - MEDIA presión					serie HMBP							R-134a				
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
* Gases sustitutivos de R-12 y R-134a.					CECOMAF (W)											
o Últimas existencias					-25	-15	5		10							
					w	COP										
o 451.00.3403	GL45TB	1/6	F	4.50	76	134	342	1.62	412	C-V	300	8.4	CSIR	R	•	
• 451.00.3503	GL45PB	1/6	F	4.50	76	134	342	1.62	412	C-V	300	8.4	CSIR	R	•	
o 451.00.3404	GL60TB	1/5	F	5.67	95	170	437	1.82	527	C-V	300	9.5	CSIR	R	•	
• 451.00.3504	GL60PB	1/5	F	5.67	95	170	437	1.82	527	C-V	300	9.5	CSIR	R	•	
451.00.3406	GL80TB	1/5	F	7.57	111	212	554	1.83	667	C-V	300	9.5	CSIR	R	•	
• 451.00.3505	GL90TB	1/4	F	8.85	142	259	661	1.91	796	C-V	300	10.8	CSIR	R	•	
• 451.00.3506	GP12TB	3/8	F	12.05	169	338	893	1.80	1077	C-V	350	11.2	CSIR	R	•	
o 451.00.3418	GP14TB	3/8	F	14.00	190	373	999	1.77	1208	C-V	400	11.5	CSIR	R	•	
• 451.00.3513	GP14TB	3/8	F	14.00	190	373	999	1.77	1208	C-V	400	11.5	CSIR	R	•	
451.00.3419	GX18TB	1/2	F	18.40	285	539	1390	1.91	1673	C-V	500	16.0	CSIR	R	•	
451.00.3420	GX21TB	5/8	F	20.72	332	603	1550	1.90	1866	C-V	500	17.0	CSIR	R	•	
451.00.3421	GX23TB	5/8	F	23.20	368	677	1730	1.89	2083	C-V	500	17.0	CSIR	R	•	
• 451.00.3422	GS26TB	3/4	F	25.93	392	771	2071	2.09	1011	C-V	887	22.7	CSIR	R	•	
451.00.3423	GS30TB	7/8	F	29.95	317	785	2452	2.33	3020	C-V	887	22.7	CSR	R	•	
• 451.00.3424	GS34TB	1	F	34.42	476	1068	2852	2.28	3421	C-V	887	22.7	CSR	R	•	

Private Picture Copyright : WWW.MBSM.PRO

BAJA presión					serie LBP							R-600a					
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watios.						Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz	
					-35	-30	-25	-23.3	-20	-15	-10						
451.00.0605	HQY55AA	1/9	S	5.46	28	44	62	69	83	105	130	C	210	8.9	RSIR/RSCR	P	•
451.00.0610	HQY70AA	1/8	S	6.64	42	59	80	88	104	131	161	C	210	9.0	RSIR/RSCR	P	•
451.00.0615	HLY99AA	1/6	S	9.93	69	90	119	130	155	198	248	C	345	9.6	RSIR/RSCR	P	•
451.00.0620	HPY12AA	1/5	S	12.10	79	107	143	157	187	239	299	C	300	10.7	RSIR/RSCR	P	•
451.00.0625	HPY14AA	1/5	S	14.31	92	124	165	181	215	274	342	C	300	11.0	RSIR/RSCR	P	•
451.00.0630	HPY16AA	1/4	S	16.14	102	136	180	198	236	302	379	C	300	11.2	RSIR/RSCR	P	•

Private Picture Copyright : WWW.MBSM.PRO

ALTA - MEDIA presión				serie HMBP										R-22				
CÓDIGO REMLE	MODELO	Potencia	Enfriamiento	Cilindrada	Producción Frigorífica en Watios.								Expansión	Aceite cm3	Peso Kg.	Motor	Arranque	220-240V/50Hz
					-20	-15	-10	-5	0	5	7.2	10						
451.00.1404	L45TN	1/5	F	4.50	157	206	265	333	410	496	537	592	C-V	400	9.5	CSIR	P	•
451.00.1405	L57TN	1/4	F	5.67	194	255	327	410	505	610	660	727	C-V	300	9.5	CSIR	R	•
451.00.1428	L76TN	3/8	F	7.57	268	347	441	550	675	814	881	969	C-V	470	10.0	CSIR	R	•
451.00.1408	L88TN	3/8	F	8.85	523	416	527	658	806	973	1052	1159	C-V	400	10.6	CSIR	R	•
451.00.1409	P12TN	1/2	F	12.00	412	537	689	868	1075	1309	1421	1570	C-V	400	12.3	CSR	R	•
451.00.1416	S22TN	7/8	F	21.77	645	890						3000	C-V	887	22.7	CSR	R	•
451.00.1418	S26TN	1 1/4	F	25.93	857	1182	1561	1993	2480	3021	3275	3615	C-V	887	22.7	CSR	R	•

Private Picture Copyright : WWW.MBSM.PRO



Mbsm\_dot\_pro\_private\_PDF\_GQY80ATTélécharger

**www.mbsm.pro**, ZEL  
**, COMPRESSEUR , R134a , 1/4 HP**  
**, GUY75AA**

written by Lilianne | 28 February 2024

Compresseur frigorifique

Puissance en cheval 1/4 CV

Alimentation 220-240 V 50 Hz

Gaz R134a



# **mbsm.pro, COMPRESSEUR, GUY75AA , R134 , 1/5 HP**

written by Jamila | 28 February 2024



Compressors of the hermetic type from the manufacturer ACC Cubigel Huayi Electrolux ZEM can be found in our online shop category compressors.