

# Compressor, r600a, 1/5HP, LBP, 149W, htk12aa, Electrolux, Brandt, 220-240V 50Hz, Run Capacitor: 4.0 µF ( 5.0 µF as alternative ) , Motor type RSCR/RSIR

written by Lilianne | 2 December 2021

compressor/compressor ACC – Electrolux HTK12AA, LBP – R600a, Power consumption 1/5HP++, 220-240V/1/50Hz, Motor type RSIR, Injection: Capillary operation, Displacement 11.1 cm<sup>3</sup>, Oil type mineral oil, Oil quantity 170 cm<sup>3</sup>, Power 116 W at -25 / +55°C, Power consumption 149 W, Current 0.77, Weight 8.6Cooling capacity

| -10 °C                          | -15 °C | -20 °C | -25 °C | -30 °C     | -35 °C |
|---------------------------------|--------|--------|--------|------------|--------|
| 300                             | 240    | 188    | 144    | 107        | 78     |
| <b>Shipping Class</b>           |        |        |        | Standard   |        |
| <b>Scope Of Application</b>     |        |        |        | LBP        |        |
| <b>Lieferzeit</b>               |        |        |        | 2-3 Wochen |        |
| <b>Type Of Construction</b>     |        |        |        | Piston     |        |
| <b>Condensation Temperature</b> |        |        |        | 55°C       |        |
| <b>Maker</b>                    |        |        |        | ACC        |        |
| <b>Manufacturer No.</b>         |        |        |        | HPY12AA    |        |
| <b>Displacement In Cm3</b>      |        |        |        | 11.1       |        |
| <b>Measuring Requirements</b>   |        |        |        | Ashrae     |        |
| <b>Refrigerants</b>             |        |        |        | R600a      |        |
| <b>Series</b>                   |        |        |        | HPY        |        |

|                                     |             |
|-------------------------------------|-------------|
| <b>Condensing Units Compressors</b> | Compressors |
| <b>Suspense</b>                     | 220-240V    |
| <b>Weight In Kg</b>                 | 12.7        |

1. Be the first to review this product

Mbsm\_dot\_pro\_private\_PDF\_HTK12AA-1-1Télécharger

Mbsm\_dot\_pro\_private\_PDF\_HTK12aa-1Télécharger



## Verdichter - Cubigel

R-600a, LBP



Hermetische Verdichter für Kapillarrohrbetrieb.  
Hochleistungs-Verdichter mit Betriebskondensatoren.  
LBP Temperaturbereich -30 °C bis -10 °C.  
Netzspannung 220 - 240 V / 50 Hz.

| Artikelnr.    | Typ       | Leistung (PS) | Kälteleistung [W] T <sub>o</sub> -25 °C, T <sub>k</sub> +45 °C |     |
|---------------|-----------|---------------|----------------------------------------------------------------|-----|
|               |           |               |                                                                | -25 |
| 47-32 HQY45AA | HQY 45 AA | 1/12          |                                                                | 52  |
| 47-32 HQY55AA | HQY 55 AA | 1/9           |                                                                | 62  |
| 47-32 HQY70AA | HQY 70 AA | 1/8           |                                                                | 80  |
| 47-32 HQY80AA | HQY 80 AA | 1/7           |                                                                | 99  |
| 47-32 HQY90AA | HQY 90 AA | 1/7           |                                                                | 109 |
| 47-32 HQY99AA | HQY 99 AA | 1/6           |                                                                | 119 |
| 47-32 HPY12AA | HPY 12 AA | 1/5           |                                                                | 144 |
| 47-32 HPY14AA | HPY 14 AA | 1/5           |                                                                | 166 |
| 47-32 HPY16AA | HPY 16 AA | 1/4           |                                                                | 181 |

**Gesamtkatalog jetzt anfordern unter [info@kaeltepartner.net](mailto:info@kaeltepartner.net)!**

 **Hinweis: Bilder Können vom Produkt abweichen**

Private Picture Copyright : [WWW.MBSM.PRO](http://WWW.MBSM.PRO)