

Compressor, ACC, Cubigel, GL60AN, R134a, 220-240V, HMBP, 1/6HP

written by Lilianne | 18 March 2021

Type: Hermetic piston compressors Producer: ACC Series: HMBP

Model: GL60AN

General data

Refrigerant:	R134a
Discharge element:	C
Cooling:	S
Maximum ambient temperature [°C]:	50

Compressor's data

Cylinder capacity [cm ³]:	6
Displacement [m ³ /h]:	1
Weight [kg]:	9,9
Oil charge [cm ³]:	345
Oil type:	ISO VG 19 ESTER

Engine's data

Engine type:	RSIR
Power [KM]:	1/6
Starting element:	LST
Power supply:	220V 50Hz
Voltage range:	170-264
Locked rotor current [A]:	14,6
Running winding resistance (25°C) [Ω]:	9,33
Starting winding resistance (25°C) [Ω]:	10,81

Electrical data

Relays:	3003
Shielding element:	MRA38085, T0515, AF11BJ
Starting capacitor volume [μ F]:	

Connections

	millimeters	inches	
Suction tube:	6,5		
Service tube:	6,5		
Discharge tube:	4,9		



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_GL60ANTélécharger

**Compressor ,ACC Cubigel
,Huayi Electrolux ,ZEM GL80AA
/ GVY75AA, LBP – R134a, 220 –
240V/1/50Hz, 1/4 HP,
discharge 7.52 cm³, motor
type RSIR / RSCR, oil type
ester, oil charge 180 cm³,
150 W at -25 / +55 °, input
power, current 146 W, 1.16 A,
expansion device: capillary,
cooling: static, weight 8.6
kg**

written by Lilianne | 18 March 2021

Compressor ,ACC Cubigel ,Huayi Electrolux ,ZEM GL80AA /
GVY75AA, LBP – R134a, 220 – 240V/1/50Hz, 1/5 HP, discharge
7.52 cm³, motor type RSIR / RSCR, oil type ester, oil charge
180 cm³, 150 W at -25 / +55 °, input power, current 146 W,
1.16 A, expansion device: capillary, cooling: static, weight
8.6 kg