

Compressor, Embraco, EMX20CLC, High-quality, compressor Aspera, EMX20CLC, LBP R600a, 220-240V 50Hz, 3.97 cm³, 1/12HP

written by Lilianne | 15 December 2021

GENERAL DATA

Application: LBP

Refrigerant: R600a

Evaporating Temperature Range: -35°C to -10°C

Compressor Cooling: Static

Type: Hermetic reciprocating

Technology Type: On-Off

Expansion Device: Capillary Tube

Packing Quantity: 100

Displacement: 3.97 cm³

Horse power: 1/12 hp

Approvals:

MECHANICAL DATA

Bore: 19 mm

Stroke: 14 mm

Oil Charge: 180ml

Oil Type Configuration: ALQUILB

Oil Type Viscosity: IS05

Weight: 7.88 kg

ELECTRICAL DATA

Motor Type: RSCR

Starting Torque: LST



Voltage working range at 50 Hz: 198-242 V

Voltage working range at 60 Hz: 198-242 V

Maximum Motor Temperature: 130 °C

Start Winding Resistance: 22.1 Ω (\pm 10%) at 25°C

Run Winding Resistance: 50.65 Ω (\pm 10%) at 25°C

Model EMX20CLC Code 513309529...S		embraco POWER IN. CHANGE ON.
220V 60 1~		GENERAL DATA Application: LBP Refrigerant: R600a Evaporating Temperature Range: -35°C to -10°C Compressor Cooling: Static Type: Hermetic reciprocating Technology Type: On-Off Expansion Device: Capillary Tube Packing Quantity: 100 Displacement: 3.97 cm ³ Horse power: 1/12 hp Approvals:
		
MECHANICAL DATA Bore: 19 mm Stroke: 14 mm Oil Charge: 180ml Oil Type Configuration: ALQUILB Oil Type Viscosity: ISOS Weight: 7.88 kg	ELECTRICAL DATA Motor Type: RSCR Starting Torque: LST Voltage working range at 50 Hz: 198-242 V Voltage working range at 60 Hz: 198-242 V Maximum Motor Temperature: 130 °C Start Winding Resistance: 22.1 Ω (\pm 10%) at 25°C Run Winding Resistance: 50.65 Ω (\pm 10%) at 25°C	
Private Picture Copyright : WWW.MBSM.PRO		



Private Picture Copyright : WWW.MBSM.PRO

Mbsm_dot_pro_private_PDF_EMX20CLC_techTélécharger