

Resin Pack ,Brushless ,Dc motor , Gangdong ,Welling Motor Manufacturing ,CO.,LTD. ,DC280v ,20w , 0.10a ECL ,8P 1300r/min

written by Lilianne | 8 January 2019

Resin Pack ,Brushless ,Dc motor , Gangdong ,Welling Motor Manufacturing ,CO.,LTD. ,DC280v ,20w , 0.10a ECL ,8P 1300r/min

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co. , Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

written by Jamila | 8 January 2019

MBSM.PRO , HYE69YL ,Compressor (LBP) , China R134a ,Huayi Compressor Co. , Ltd, 69 YL ,1/4 Hp ,168Kcal , 220V

Test conditions	According to ASHRAE
Evaporating temperature	-23.3□
Condensing temperature	54.4□

Subcooling temperature	32.2□
Suction temperature	32.2□
Ambient temperature	32.2□
Working condition limit:R134a	
Max ambient temperature	43[□]
Evaporation temperature range	-35~-15[□]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0[Mpa](gauge pressure)
Max allowable housing temperature	95[□]
Max discharge temperature	125[□]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4/0.4Mpa(gauge pressure)187V/98V

Product model:HYE69YL

Cooling capacity:195W

COP□W/W□:1.15

Voltage□V□:220-240~

Frequency(Hz):50



PictureS Mbsm Dot Pro : www.mbsm.pro

Products

- R134a Compressor (LBP)
 - HYE Serie
 - HY Serie
 - HYB Serie
 - HYS Serie
- R600a Compressor (LBP)
 - HYE Serie
 - HY Serie
 - HYB Serie
 - HYS Serie
- R134a Compressor (MBP,HBP)
 - HY Serie
 - HYE Serie

[Newest Catalog Download](#)

Product model: HYE69YL
 Cooling capacity: 195W
 COP (W/W) : 1.15
 Voltage (V) : 220-240~
 Frequency(Hz): 50

Test conditions	According to ASHRAE
Evaporating temperature	-23.3°C
Condensing temperature	54.4°C
Subcooling temperature	32.2°C
Suction temperature	32.2°C
Ambient temperature	32.2°C
Working condition limit: R134a	
Max ambient temperature	43[°C]
Evaporation temperature range	-35~-15[°C]
Working voltage range.	187~254/98~127[V]
Max discharge pressure	2.0 [Mpa](gauge pressure)
Max allowable housing temperature	95[°C]
Max discharge temperature	125[°C]
Max pressure housing endured	2.7[Mpa](gauge pressure)
Low voltage start	0.4~0.4Mpa(gauge pressure)187V/98V

PictureS Mbsm Dot Pro : www.mbsm.pro





AE 1330 Y

1 / 12 HP



AE 1340 Y

1 / 6 HP



AE 1350 Y

1 / 6 HP



AE 1360 Y

1 / 5 HP



AE 1370 Y

1 / 4 HP



AE 1390 Y

1 / 4 HP





HY 81 Y

1 / 4 HP



HYE 55 YL 63

1 / 6 HP



HYE 60 YL 63

1 / 5 HP



HYE 69 YL

1 / 4 HP



HYE 125 MSU

1 / 4 HP



Huayi HYE 69 YL 1/4 Hp 168Kcal R134a 220V

Huayi - Huayi

Huayi HYE 55 YL 63 1/6 Hp 129Kcal R134a 220V

Huayi - Huayi

Huayi HYE 60 YL 63 1/5 Hp 146Kcal R134a 220V

Huayi - Huayi

Huavi HY 81 Y 1/4+ Hb 202Kcal R134a 220V

PictureS Mbsm Dot Pro : www.mbsm.pro

HYE 125 MSU

HYE 69 YL

HYE 60 YL 63

HYE 55 YL 63

HY 81 Y

AE 1390 Y

AE 1370 Y

AE 1360 Y

AE 1350 Y

AE 1340 Y

AE 1330 Y

PictureS Mbsm Dot Pro : www.mbsm.pro





Features 1/4 HP

Energy Efficient

Wide Voltage Range

Low Noise & Low Vibration

High Overload Capacity

Designed for High Ambient conditions

