

**Compressor, CR32KQ-PFV,
CR32K6-PFV-875, Copeland,
américain, 3 CV, 2.5 3 Ton,
208 230 Volt A/C, 1 PH,
32,000 BTU, R22, R407C,
Hermetic (Reciprocating)
Compressor Replacement**

written by Lilianne | 2 May 2021



Private Picture Copyright: WWW.MBSM.PRO

Compressor, CR32KQ-PFV, CR32K6-PFV-875, Copeland, américain, 3 CV, 2.5 3 Ton, 208 230 Volt A/C, 1 PH, 32,000 BTU, R22, R407C, Hermetic (Reciprocating) Compressor Replacement

**Compressor, NPT12FSC,
CUBIGEL, R290, 12,10ccm, LBP,
3/8HP, 220 V 50/60 Hz**

written by Lilianne | 2 May 2021



Private Picture Copyright : WWW.MBSM.PRO

Compressor, NPT12FSC, CUBIGEL, R290, 12,10ccm, LBP, 3/8HP, 220 V 50/60 Hz

R134A, LBP, Motor, Danfu, Compressor, PW2.0VK, 1/15hp

written by Lilianne | 2 May 2021



REDMI NOTE 9 PRO
AI QUAD CAMERA

Private Picture Copyright: WWW.MBSM.PRO

R134A, LBP, Motor, Danfu, Compressor , PW2.0VK, 1/15hp

**LG, Refrigerator, Compressor,
FC75LBNA, TCA35271202,
Inverter, AR125VC, R134A,
1/3hp, 0-220V 53HZ**

written by Lilianne | 2 May 2021



LG, Refrigerator, Compressor, FC75LBNA, TCA35271202, Inverter,
AR125VC, R134A, 1/3hp, 0-220V 53HZ

**Kulthorn, Kirby, Compressor,
AE2425ZK, ae 2425zk-sr, R404,
1/2HP, Hermetic piston
compressor, AE2425ZK-SR,
Application: low temperature,
Displacement: 14.14 cm³,
Cooling capacity: 613 W, 220
V / 50 Hz / 1 phase.**

written by Lilianne | 2 May 2021

16L3

KULTHORN
AE 2425ZK-SR 03D
220 - 240 V ~ 50Hz R404A/R507
RLA 2.71 LRA 16.3 CE

KK
KULTHORN KIRBY
MADE IN THAILAND

03D17L13023143

Q-MARK

RoHS TIS.812-2548

Private Picture Copyright : WWW.MBSM.PRO

Kulthorn, Kirby, Compressor, AE2425ZK, ae 2425zk-sr, R404, 1/2HP, Hermetic piston compressor, AE2425ZK-SR, Application: low temperature, Displacement: 14.14 cm³, Cooling capacity: 613 W, 220 V / 50 Hz / 1 phase.

**Compressor, Aspera, Embraco,
EMT60HLP, R134a, 1/5 CV, 220
à 240 V 50 Hz, Cylindrée =
6.76 CM3, LBP, RSIR**

written by Lilianne | 2 May 2021

ZK105

 **Embraco ECU60HLP**

	Thermally Protected		220-240V ~
	12.0LRA	280 ml oil	
	R134a	1PH	50Hz



Compressor, Aspera, Embraco, EMT60HLP, R134a, 1/5 CV, 220 à 240 V 50 Hz, Cylindrée = 6.76 CM3, LBP, RSIR

**Medium and High Back Pressure
Compressors, M/HBP, RSIR,
TECUMSEH, 1/5++ HP, R134a,
160g, TWB1374YGS, TW146GY,
220v/50-60, kiriazi defrost,
340L, k350, k350/1, Embraco,
ff17.5hak, tw146-gy-486,
twb1374ygs**

written by Lilianne | 2 May 2021

Medium and High Back Pressure Compressors, M/HBP, RSIR, TECUMSEH, 1/5++ HP, R134a, 160g, TWB1374YGS, TW146GY, 220v/50-60, kiriazi defrost, 340L, k350, k350/1, Embraco, ff17.5hak, tw146-gy-486, twb1374ygs

LG rotary, compressor, model,

QJS222PMA, 12700BTU 5.6Amps, EER = 10.7, air conditioner

written by Lilianne | 2 May 2021

LG rotary, compressor, model, QJS222PMA, 12700BTU 5.6Amps, EER = 10.7, air conditioner

Pressure and boiling Temperature list, standing, Refrigerant, suction, discharge

written by Lilianne | 2 May 2021

Some Refrigerant Standing, Suction, Discharge Pressure & Boiling Temperature List.

Refrigerant Name	Standing Pressure	Suction Pressure	Discharge Pressure	Boiling Temp
R-22	150-155 psi	60-70 psi	250-300 psi	-40.8 C
R-410a	225-230 psi	120-130 psi	450-500 psi	-51.4 C
R-134a	85-95 psi	12-15 psi		-26.2 C
R-600a	40-50 psi	Below 0-1 psi		-11.7 C
R-32	240-245 psi	110-115 psi		-52.0 C
R-290	125-130 psi	65-70 psi	275-300 psi	-42.1 C
R-407c	180-185 psi	75-80 psi	275-300 psi	-45.0 C
R-404a	180-185 psi	80-90 psi		-46.2 C
R-417	140 psi	65 psi	261 psi	



Private Picture Copyright : WWW.MBSM.PRO

Pressure and boiling Temperature list, standing, Refrigerant, suction, discharge

**Compressor Embraco Aspera
NEK6210GK, MBP – R404A, R507,
220 – 240V/1/50Hz, 1/2 HP,
discharge 8.77 cm³, motor
type CSIR, lubricant type POE
22, lubricant charge 350
ml.1318 W at +7.2 / +54.4 °,
expansion device: capillary
or valve, cooling: fan
cooling, weight 11 kg**

written by Lilianne | 2 May 2021

Compressor ASPERA NEK6210GK | NEK 6210 GK

Compressor Embraco Aspera NEK6210GK, MBP – R404A, R507, 220 – 240V/1/50Hz, 1/2 HP, discharge 8.77 cm³, motor type CSIR, lubricant type POE 22, lubricant charge 350 ml.1318 W at +7.2 / +54.4 °, expansion device: capillary or valve, cooling: fan cooling, weight 11 kg

Refrigerant	R404A/R507
Working range[stC] MBP	-20 do +10
Nominal capacity [W] (evaporating temperature +7,2C, Condensing temperatur +54,4C)	1303
Power supply	220-240V 50Hz

Engine type	CSIR
Displacement [cm ³]	8,77
Weight [kg]	11

Evaporating temperature +55 C

Evaporating Temperature	Cooling Capacity +/-5%	Power Consumption +/-5%	Current Consumption +/-5%	Gas Flow Rate +/-5%	Efficiency +/-7%			
						(kg/h)	(kcal/Wh)	(W/W)
°C	(kcal/h)	(W)	(Btu/h)	(W)	(A)	(kg/h)	(kcal/Wh)	(W/W)
-20	384	447	1.525	365	2,36	11,99	1,05	1,22
-15	467	544	1.855	419	2,58	14,69	1,12	1,30
-10	574	668	2.278	470	2,79	18,18	1,22	1,42
-5	704	819	2.795	519	3,00	22,51	1,36	1,58
0	858	998	3.405	565	3,20	27,73	1,52	1,77
5	1.036	1.204	4.109	609	3,40	33,90	1,70	1,98
10	1.237	1.438	4.907	650	3,59	41,06	1,90	2,21

Substitutes for this compressor are: Electrolux ML90TB , L'Unite Hermetique/Tecumseh AE4450Z

Refrigerant:	R404A, R507
--------------	-------------

Embraco aspera

NEK6210GK



THERMALLY PROTECTED

220 - 240V - 50Hz

R 404A

POE: OIL 350°C

1 PH

SUCTION

MADE IN SLOVAKIA NO START WITHOUT STARTING DEVICE



958CA51

LX

N10ZGP43

Mbsm_dot_pro_private_PDF_NEK6210GKTélécharger